

## N-channel 800 V, 1.50 $\Omega$ typ., 4 A MDmesh™ K5 Power MOSFET in a TO-220FP package

Datasheet - production data





Figure 1: Internal schematic diagram



### Features

| Order code | V <sub>DS</sub> | R <sub>DS(on)</sub> max. | I <sub>D</sub> |
|------------|-----------------|--------------------------|----------------|
| STF5N80K5  | 800 V           | 1.75 $\Omega$            | 4 A            |

- Industry's lowest R<sub>DS(on)</sub> X area
- Industry's best FoM (figure of merit)
- Ultra-low gate charge
- 100% avalanche tested
- Zener-protected

### Applications

- Switching applications

### Description

This very high voltage N-channel Power MOSFET is designed using MDmesh™ K5 technology based on an innovative proprietary vertical structure. The result is a dramatic reduction in on-resistance and ultra-low gate charge for applications requiring superior power density and high efficiency.

Table 1: Device summary

| Order code | Marking | Package  | Packing |
|------------|---------|----------|---------|
| STF5N80K5  | 5N80K5  | TO-220FP | Tube    |

---

## Contents

|          |                                              |           |
|----------|----------------------------------------------|-----------|
| <b>1</b> | <b>Electrical ratings .....</b>              | <b>3</b>  |
| <b>2</b> | <b>Electrical characteristics .....</b>      | <b>4</b>  |
|          | 2.1 Electrical characteristics (curves)..... | 6         |
| <b>3</b> | <b>Test circuits .....</b>                   | <b>8</b>  |
| <b>4</b> | <b>Package information .....</b>             | <b>9</b>  |
|          | 4.1 TO-220FP package information .....       | 10        |
| <b>5</b> | <b>Revision history .....</b>                | <b>12</b> |

# 1 Electrical ratings

Table 2: Absolute maximum ratings

| Symbol        | Parameter                                                                                                                           | Value       | Unit               |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------|-------------|--------------------|
| $V_{GS}$      | Gate-source voltage                                                                                                                 | $\pm 30$    | V                  |
| $I_D$         | Drain current (continuous) at $T_C = 25\text{ }^{\circ}\text{C}$                                                                    | 4           | A                  |
| $I_D$         | Drain current (continuous) at $T_C = 100\text{ }^{\circ}\text{C}$                                                                   | 2.3         | A                  |
| $I_D^{(1)}$   | Drain current (pulsed)                                                                                                              | 16          | A                  |
| $P_{TOT}$     | Total dissipation at $T_C = 25\text{ }^{\circ}\text{C}$                                                                             | 20          | W                  |
| $dv/dt^{(2)}$ | Peak diode recovery voltage slope                                                                                                   | 4.5         | V/ns               |
| $dv/dt^{(3)}$ | MOSFET $dv/dt$ ruggedness                                                                                                           | 50          |                    |
| $V_{ISO}$     | Insulation withstand voltage (RMS) from all three leads to external heat sink ( $t=1\text{ s}$ ; $T_C=25\text{ }^{\circ}\text{C}$ ) | 2500        | V                  |
| $T_j$         | Operating junction temperature range                                                                                                | - 55 to 150 | $^{\circ}\text{C}$ |
| $T_{stg}$     | Storage temperature range                                                                                                           |             |                    |

**Notes:**

(1)Pulse width limited by safe operating area

(2) $I_{SD} \leq 4\text{ A}$ ,  $di/dt = 100\text{ A}/\mu\text{s}$ ;  $V_{DS\text{ peak}} < V_{(BR)DSS}$ ,  $V_{DD} = 640\text{ V}$ (3) $V_{DS} \leq 640\text{ V}$ 

Table 3: Thermal data

| Symbol         | Parameter                           | Value | Unit                        |
|----------------|-------------------------------------|-------|-----------------------------|
| $R_{thj-case}$ | Thermal resistance junction-case    | 6.25  | $^{\circ}\text{C}/\text{W}$ |
| $R_{thj-amb}$  | Thermal resistance junction-ambient | 62.5  | $^{\circ}\text{C}/\text{W}$ |

Table 4: Avalanche characteristics

| Symbol   | Parameter                                                                                                              | Value | Unit |
|----------|------------------------------------------------------------------------------------------------------------------------|-------|------|
| $I_{AR}$ | Avalanche current, repetitive or not repetitive (pulse width limited by $T_{jmax}$ )                                   | 1.2   | A    |
| $E_{AS}$ | Single pulse avalanche energy (starting $T_j = 25\text{ }^{\circ}\text{C}$ , $I_D = I_{AR}$ , $V_{DD} = 50\text{ V}$ ) | 165   | mJ   |

## 2 Electrical characteristics

$T_C = 25\text{ }^{\circ}\text{C}$  unless otherwise specified

**Table 5: On/off-state**

| Symbol        | Parameter                         | Test conditions                                                                                       | Min. | Typ. | Max.     | Unit          |
|---------------|-----------------------------------|-------------------------------------------------------------------------------------------------------|------|------|----------|---------------|
| $V_{(BR)DSS}$ | Drain-source breakdown voltage    | $V_{GS} = 0\text{ V}$ , $I_D = 1\text{ mA}$                                                           | 800  |      |          | V             |
| $I_{DSS}$     | Zero gate voltage drain current   | $V_{GS} = 0\text{ V}$ , $V_{DS} = 800\text{ V}$                                                       |      |      | 1        | $\mu\text{A}$ |
|               |                                   | $V_{GS} = 0\text{ V}$ , $V_{DS} = 800\text{ V}$<br>$T_C = 125\text{ }^{\circ}\text{C}$ <sup>(1)</sup> |      |      | 50       | $\mu\text{A}$ |
| $I_{GSS}$     | Gate body leakage current         | $V_{DS} = 0\text{ V}$ , $V_{GS} = \pm 20\text{ V}$                                                    |      |      | $\pm 10$ | $\mu\text{A}$ |
| $V_{GS(th)}$  | Gate threshold voltage            | $V_{DD} = V_{GS}$ , $I_D = 100\text{ }\mu\text{A}$                                                    | 3    | 4    | 5        | V             |
| $R_{DS(on)}$  | Static drain-source on-resistance | $V_{GS} = 10\text{ V}$ , $I_D = 2\text{ A}$                                                           |      | 1.50 | 1.75     | $\Omega$      |

**Notes:**

<sup>(1)</sup>Defined by design, not subject to production test

**Table 6: Dynamic**

| Symbol                     | Parameter                             | Test conditions                                                                                                                                  | Min. | Typ. | Max. | Unit     |
|----------------------------|---------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|------|------|------|----------|
| $C_{iss}$                  | Input capacitance                     | $V_{DS} = 100\text{ V}$ , $f = 1\text{ MHz}$ ,<br>$V_{GS} = 0\text{ V}$                                                                          | -    | 177  | -    | pF       |
| $C_{oss}$                  | Output capacitance                    |                                                                                                                                                  | -    | 15   | -    | pF       |
| $C_{rss}$                  | Reverse transfer capacitance          |                                                                                                                                                  | -    | 0.3  | -    | pF       |
| $C_{o(tr)}$ <sup>(1)</sup> | Equivalent capacitance time related   | $V_{DS} = 0\text{ to }640\text{ V}$ , $V_{GS} = 0\text{ V}$                                                                                      | -    | 33   | -    | pf       |
| $C_{o(er)}$ <sup>(2)</sup> | Equivalent capacitance energy related |                                                                                                                                                  | -    | 12   | -    | pf       |
| $R_g$                      | Intrinsic gate resistance             | $f = 1\text{ MHz}$ , $I_D = 0\text{ A}$                                                                                                          | -    | 16   | -    | $\Omega$ |
| $Q_g$                      | Total gate charge                     | $V_{DD} = 640\text{ V}$ , $I_D = 4\text{ A}$<br>$V_{GS} = 10\text{ V}$<br>see <a href="#">Figure 15: "Test circuit for blue charge behavior"</a> | -    | 5    | -    | nC       |
| $Q_{gs}$                   | Gate-source charge                    |                                                                                                                                                  | -    | 1.7  | -    | nC       |
| $Q_{gd}$                   | Gate-drain charge                     |                                                                                                                                                  | -    | 2.9  | -    | nC       |

**Notes:**

<sup>(1)</sup> $C_{o(tr)}$  is a constant capacitance value that gives the same charging time as  $C_{oss}$  while  $V_{DS}$  is rising from 0 to 80%  $V_{DSS}$ .

<sup>(2)</sup> $C_{o(er)}$  is a constant capacitance value that gives the same stored energy as  $C_{oss}$  while  $V_{DS}$  is rising from 0 to 80%  $V_{DSS}$ .

Table 7: Switching times

| Symbol       | Parameter           | Test conditions                                                                                                                                                                                                                           | Min. | Typ. | Max. | Unit |
|--------------|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|------|------|------|
| $t_{d(on)}$  | Turn-on delay time  | $V_{DD} = 400\text{ V}$ , $I_D = 2\text{ A}$ , $R_G = 4.7\ \Omega$<br>$V_{GS} = 10\text{ V}$<br>see <a href="#">Figure 14: "Test circuit for resistive load switching times"</a> and <a href="#">Figure 19: "Switching time waveform"</a> | -    | 12.7 | -    | ns   |
| $t_r$        | Rise time           |                                                                                                                                                                                                                                           | -    | 11.7 | -    | ns   |
| $t_{d(off)}$ | Turn-off delay time |                                                                                                                                                                                                                                           | -    | 23   | -    | ns   |
| $t_f$        | Fall time           |                                                                                                                                                                                                                                           | -    | 14.8 | -    | ns   |

Table 8: Source-drain diode

| Symbol          | Parameter                     | Test conditions                                                                                                                                                                                                                   | Min. | Typ. | Max. | Unit          |
|-----------------|-------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|------|------|---------------|
| $I_{SD}$        | Source-drain current          |                                                                                                                                                                                                                                   | -    |      | 4    | A             |
| $I_{SDM}^{(1)}$ | Source-drain current (pulsed) |                                                                                                                                                                                                                                   | -    |      | 16   | A             |
| $V_{SD}^{(2)}$  | Forward on voltage            | $I_{SD} = 4\text{ A}$ , $V_{GS} = 0\text{ V}$                                                                                                                                                                                     | -    |      | 1.6  | V             |
| $t_{rr}$        | Reverse recovery time         | $I_{SD} = 4\text{ A}$ , $di/dt = 100\text{ A}/\mu\text{s}$ ,<br>$V_{DD} = 60\text{ V}$<br>see <a href="#">Figure 16: "Test circuit for inductive load switching and diode recovery times"</a>                                     | -    | 265  |      | ns            |
| $Q_{rr}$        | Reverse recovery charge       |                                                                                                                                                                                                                                   | -    | 1.59 |      | $\mu\text{C}$ |
| $I_{RRM}$       | Reverse recovery current      |                                                                                                                                                                                                                                   | -    | 12   |      | A             |
| $t_{rr}$        | Reverse recovery time         | $I_{SD} = 4\text{ A}$ , $di/dt = 100\text{ A}/\mu\text{s}$ ,<br>$V_{DD} = 60\text{ V}$ , $T_J = 150\text{ }^\circ\text{C}$<br>see <a href="#">Figure 16: "Test circuit for inductive load switching and diode recovery times"</a> | -    | 386  |      | ns            |
| $Q_{rr}$        | Reverse recovery charge       |                                                                                                                                                                                                                                   | -    | 2.18 |      | $\mu\text{C}$ |
| $I_{RRM}$       | Reverse recovery current      |                                                                                                                                                                                                                                   | -    | 11.3 |      | A             |

**Notes:**

(1)Pulse width limited by safe operating area

(2)Pulsed: pulse duration = 300  $\mu\text{s}$ , duty cycle 1.5%

Table 9: Gate-source Zener diode

| Symbol        | Parameter                     | Test conditions                                 | Min. | Typ. | Max. | Unit |
|---------------|-------------------------------|-------------------------------------------------|------|------|------|------|
| $V_{(BR)GSO}$ | Gate-source breakdown voltage | $I_{GS} = \pm 1\text{ mA}$ , $I_D = 0\text{ A}$ | 30   | -    | -    | V    |

The built-in back-to-back Zener diodes are specifically designed to enhance the ESD performance of the device. The Zener voltage facilitates efficient and cost-effective device integrity protection, thus eliminating the need for additional external componentry.

## 2.1 Electrical characteristics (curves)






Figure 8: Capacitance variations




Figure 9: Normalized gate threshold voltage vs temperature




Figure 10: Normalized on-resistance vs temperature




Figure 11: Normalized V(BR)DSS vs temperature




Figure 12: Maximum avalanche energy vs starting T\_J






Figure 13: Source-drain diode forward characteristics




### 3 Test circuits

**Figure 14: Test circuit for resistive load switching times**




AM01468v1

**Figure 15: Test circuit for gate charge behavior**




AM01469v10

**Figure 16: Test circuit for inductive load switching and diode recovery times**




AM01470v1

**Figure 17: Unclamped inductive load test circuit**




AM01471v1

**Figure 18: Unclamped inductive waveform**



AM01472v1

**Figure 19: Switching time waveform**



AM01473v1




## 4 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: **[www.st.com](http://www.st.com)**. ECOPACK® is an ST trademark.

## 4.1 TO-220FP package information

Figure 20: TO-220FP package outline



7012510\_Rev\_K\_B

Table 10: TO-220FP package mechanical data

| Dim. | mm   |      |      |
|------|------|------|------|
|      | Min. | Typ. | Max. |
| A    | 4.4  |      | 4.6  |
| B    | 2.5  |      | 2.7  |
| D    | 2.5  |      | 2.75 |
| E    | 0.45 |      | 0.7  |
| F    | 0.75 |      | 1    |
| F1   | 1.15 |      | 1.70 |
| F2   | 1.15 |      | 1.70 |
| G    | 4.95 |      | 5.2  |
| G1   | 2.4  |      | 2.7  |
| H    | 10   |      | 10.4 |
| L2   |      | 16   |      |
| L3   | 28.6 |      | 30.6 |
| L4   | 9.8  |      | 10.6 |
| L5   | 2.9  |      | 3.6  |
| L6   | 15.9 |      | 16.4 |
| L7   | 9    |      | 9.3  |
| Dia  | 3    |      | 3.2  |

## 5 Revision history

**Table 11: Document revision history**

| Date        | Revision | Changes                                                                                                                                                                                                                                                                                                                                 |
|-------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 16-Oct-2015 | 1        | First release.                                                                                                                                                                                                                                                                                                                          |
| 06-Nov-2015 | 2        | Updated title in cover page.                                                                                                                                                                                                                                                                                                            |
| 09-May-2016 | 3        | Modified: title<br><i>Table 2: "Absolute maximum ratings", Table 3: "Thermal data", Table 5: "On/off-state", Table 6: "Dynamic", Table 7: "Switching times", Table 8: "Source-drain diode"</i><br>Added: <i>Section 3.1: "Electrical characteristics (curves)"</i><br>Modified: <i>Section 4: "Test circuits"</i><br>Minor text changes |

**IMPORTANT NOTICE – PLEASE READ CAREFULLY**

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2016 STMicroelectronics – All rights reserved

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9