

3



5	6	7	8
---	---	---	---

	1	2	3	4	5	6	7	8																																																																												
	<table><tr><td>PRODUCT NUMBER</td><td colspan="7"></td></tr><tr><td>10127400-05HI410LF</td><td colspan="7"></td></tr></table>								PRODUCT NUMBER								10127400-05HI410LF																																																																			
PRODUCT NUMBER																																																																																				
10127400-05HI410LF																																																																																				
A	NOTES: ①. "FCI", PART NUMBER AND DATE CODE TO BE MARKED ON THIS SURFACE. THE P/N CAN BE OMITTED IF THERE IS NOT ENOUGH SPACE ON THIS SURFACE. 2. MATERIALS: HOUSING: GLASS FILLED WITH HIGH TEMP POLYAMIDE, BLACK, UL94V-0. POWER CONTACTS: COPPER ALLOY. SIGNAL CONTACTS: COPPER ALLOY. HOLD DOWN: COPPER ALLOY. 3. PLATING SPECIFICATION: POWER CONTACT: CONTACT AREA: Gold-flash OVER 2.54um [100μ"] Silver OVER 1.27um [50μ"] Ni + Lubricant. Lubricant application at the end of the Plating Line.⚠ TAIL AREA: Sn OVER Ni SIGNAL CONTACT: CONTACT AREA: 0.76um [30μ"] GXT OVER 1.27um [50μ"] Ni TAIL AREA: Sn OVER Ni ④. DENOTES CONNECTOR KEEP OUT ZONE. ⑤. DATUM AND BASIC DIMENSION ARE ESTABLISHED BY CUSTOMER. ⑥. ALL HOLE DIAMETERS ARE FINISHED HOLE SIZES. ⑦. 1.150±0.025mm DRILLED HOLE PLATED WITH 7.62μm MIN Sn OVER 25.4μm-76.2μm Cu PLATING TO ACHIEVE A 1.02±0.07mm FINISHED HOLE. 8. PRODUCT SPECIFICATION: FCI GS-12-1176. APPLICATION SPECIFICATION: FCI GS-20-0389. PRODUCT PACKAGE SPECIFICATION: FCI GS-14-2354. ⑨. THE VOID CORING BETWEEN POWER MODULES, SIGNAL MODULES AND END MODULES ARE OPTIONAL AND THE SHAPE MAY BE DIFFERENT TO OPTIMIZE THE MOLDING PROCESS. THE VOID CORING WILL NOT EFFECT THE PRODUCT FUNCTION. 10. A ⚠ SYMBOL WILL BE NEXT TO ANY DIMENSION, VIEW, OR NOTE WHICH HAS BEEN MODIFIED WITH THE CURRENT DRAWING REVISION.								A																																																																											
B									B																																																																											
C									C																																																																											
D									D																																																																											
E									E																																																																											
F	<table><tr><td>spec ref</td><td colspan="3">-</td><td>dr</td><td>Kaka Zhang</td><td>2015/11/24</td><td rowspan="4"></td><td>projection</td><td rowspan="4">MM</td><td>size</td><td>A2</td><td>scale</td><td>2:1</td></tr><tr><td>tolerance std</td><td colspan="3">-</td><td>eng</td><td>Kaka Zhang</td><td>2017/06/05</td><td>ecn no</td><td>ELX-DG-27148-1</td></tr><tr><td>ASME Y14.5</td><td colspan="3">TOLERANCES UNLESS OTHERWISE SPECIFIED</td><td>chr</td><td>Fancy Zhang</td><td>2017/06/06</td><td>rel level</td><td>Released</td></tr><tr><td></td><td colspan="3"></td><td>appr</td><td>Pei-Ming Zheng</td><td>2017/09/01</td><td>product family</td><td>PwrBlade ULTRA</td></tr><tr><td>surface</td><td rowspan="3"></td><td>linear</td><td>0.X</td><td>±0.50</td><td rowspan="3"></td><td colspan="4">title</td><td rowspan="3">drawing no</td><td colspan="2">3LP+4HP+2IS+4HP+3LP, PRESS-FIT</td><td rowspan="3">rev</td><td rowspan="3">B</td></tr><tr><td></td><td></td><td>0.XX</td><td>±0.25</td><td colspan="4">R/A RECEPTACLE, PwrBlade ULTRA</td></tr><tr><td>ASME Y14.5</td><td>angular</td><td>0°</td><td>±2°</td><td colspan="4">cat. no.</td><td>-</td><td>Product - Customer Special Drw</td><td>sheet 3 of 3</td></tr></table>								spec ref	-			dr	Kaka Zhang	2015/11/24		projection	MM	size	A2	scale	2:1	tolerance std	-			eng	Kaka Zhang	2017/06/05	ecn no	ELX-DG-27148-1	ASME Y14.5	TOLERANCES UNLESS OTHERWISE SPECIFIED			chr	Fancy Zhang	2017/06/06	rel level	Released					appr	Pei-Ming Zheng	2017/09/01	product family	PwrBlade ULTRA	surface		linear	0.X	±0.50		title				drawing no	3LP+4HP+2IS+4HP+3LP, PRESS-FIT		rev	B			0.XX	±0.25	R/A RECEPTACLE, PwrBlade ULTRA				ASME Y14.5	angular	0°	±2°	cat. no.				-	Product - Customer Special Drw	sheet 3 of 3	F
spec ref	-			dr	Kaka Zhang	2015/11/24		projection	MM	size	A2	scale	2:1																																																																							
tolerance std	-			eng	Kaka Zhang	2017/06/05		ecn no		ELX-DG-27148-1																																																																										
ASME Y14.5	TOLERANCES UNLESS OTHERWISE SPECIFIED			chr	Fancy Zhang	2017/06/06		rel level		Released																																																																										
				appr	Pei-Ming Zheng	2017/09/01		product family		PwrBlade ULTRA																																																																										
surface		linear	0.X	±0.50		title				drawing no	3LP+4HP+2IS+4HP+3LP, PRESS-FIT		rev	B																																																																						
			0.XX	±0.25		R/A RECEPTACLE, PwrBlade ULTRA																																																																														
ASME Y14.5		angular	0°	±2°		cat. no.					-	Product - Customer Special Drw			sheet 3 of 3																																																																					
	1	2	3	4	5	6	7	8																																																																												

Amphenol FCI

© 2016 APCI

Creo File - REV E - 2016-02-12

Amphenol
FCI

© 2016 APCI

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9