

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT

ALL RIGHTS RESERVED.

LOC

DIST

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD

D

C

B

A


REPLACED BY OCEAN STYLE APPLICATOR PART NUMBER

FOR REPLACEMENT PARTS FOR APPLICATOR REFER TO ADDITIONAL PAGE(S). SPARE PARTS KIT (IF LISTED) WILL REMAIN AVAILABLE.

THE REPLACEMENT OCEAN STYLE APPLICATOR HAS THE SAME TERMINATOR/PRESS INTERFACE AS APPLICATOR

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:



TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	±
1 PLC	±
2 PLC	±
3 PLC	±
4 PLC	±
ANGLES	±

MATERIAL

FINISH

DWN

CHK

APVD

PRODUCT SPEC

APPLICATION SPEC

WEIGHT

TE Connectivity

NAME

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A3

C-

SCALE

SHEET OF

REV

1470-19 (3/11)


Pro/ENGINEER DRAWING

—	1	1	1	1	1	1	5-547505-2	SPRING, COMP. (INS. DEP.)	77
—	1	1	1	1	1	1	854769-3	HOLDER, INSULATION	74
—	1	1	1	1	1	1	1490525-3	DEPRESSOR, WIRE	73
—	1	1	1	1	1	1	1528082	PRINT, APPLICATOR LOG SHEET	72
—	1	1	1	1	1	1	1338705-3	DOCUMENTATION PACKAGE	71
—	3	3	3	3	3	3	2-23147-2	SPRING, DEPRESSOR	70
—	1	1	1	1	1	1	1490524-1	SPACER, DEPRESSOR	69
—	1	1	1	1	1	1	461264-5	PLATE, IDENTIFICATION	67
—	2	2	2	2	2	2	21017-2	SCR,DRIVE(#2x.19)JD PLATE	66
—	1	1	1	1	1	1	1424350-1	HOLDER, PIN, WIRED	65
—	1	1	1	1	1	1	3-18031-0	SCR,SKT SET(M6X6)RAM	63
									62
—	2	2	2	2	2	2	2-18032-5	SCR,SKT SET(M5X20)DRAG	61
—	1	1	1	1	1	1	18024-7	SCR,BHC(M4X10)ANVIL	60
—	1	1	1	1	1	1	5-18022-2	SCR,HEX(M4X8)FEED FINGER	59
—	1	1	1	1	1	1	21028-2	PIN, SLOTTED SPRING	58
									57
—	1	1	1	1	1	1	1338685-1	PAWL, FEED	56
									55
—	4	4	4	4	4	4	18024-8	SCR,BHC(M4x12)SHEAR HOLDER	54
									53
—	1	1	1	1	1	1	18030-1	NUT,HEX(M3)HOLD DOWN	52
—	1	1	1	1	1	1	811242-5	BUMPER, HOLDDOWN	51
—	1	1	1	1	1	1	690753-2	SPACER, TONKER	50
—	1	1	1	1	1	1	18024-3	SCR,BHC(M3X10)CAM	49
—	—	1	—	—	1	—	1338675-1	CAM, PRE FEED 30 & 40 mm ST	48
—	1	—	1	1	—	1	1338676-1	CAM, POST FEED 30 & 40 mm ST	47
—	1	1	1	1	1	1	1320999-3	APPLICATOR BASIC SUBASSY	46
—	1	1	1	1	1	1	690191-1	PLUG, NYLON	45
—	1	1	1	1	1	1	1338660-1	RAM	44
									43
									42
—	1	1	1	1	1	1	2-18024-6	SCR,BHC(M8X25)RAM	41
									40
—	1	1	1	1	1	1	690125-1	SHIM SUBASS'Y	39
—	1	1	1	1	1	1	469367-1	SPACER, FINE ADJUST	38
—	1	1	1	1	1	1	879103-2	FINE ADJUST HEAD SUBASSY	37
									36
									35
—	1	1	1	1	1	1	1320934-3	SUPPORT, TERMINAL	34
—	2	2	2	2	2	2	1-18024-0	SCR,BHC(M4X20)STRIP GUIDE	33
—	1	1	1	1	1	1	18027-2	WASHER, FLAT(M4)	32
—	3	3	3	3	3	3	1-18023-2	SCR,SKT CAP(M4X12)MOUNT BLOCK	31
—	1	1	1	1	1	1	1320908-2	SPACER, STRIP GUIDE	30
—	1	1	1	1	1	1	1633073-1	STRIP GUIDE PLATE ASSY	29
—	1	1	1	1	1	1	1-455888-6	SPACER, FRONT SHEAR DEP	28
—	2	2	2	2	2	2	1-22284-0	SPRING, DRAG	27
—	1	1	1	1	1	1	356835-1	LEVER, DRAG RELEASE	26
—	1	1	1	1	1	1	240792-1	DRAG, TERMINAL	25
—	1	1	1	1	1	1	1320928-1	PLATE, STRIP GUIDE	24
—	1	1	1	1	1	1	980371-4	SCR,SHC SHLD	23
—	1	—	1	1	—	1	690472-2	STRIPPER	22
—	1	1	1	1	1	1	1-18023-1	SCR,SHC(M4X10)STRIPPER	21
—	4	4	4	4	4	4	18025-2	WASHER,LOCK(M4)STRIPPER	20
—	—	1	—	—	1	—	690472-1	STRIPPER	19
									18
—	1	—	—	1	—	—	1338684-1	HOLDER, SHEAR, FRONT (NO-CUT)	17
									16
									15
									14
									13
—	1	1	1	1	1	1	3-22280-3	SPRING, SHEAR	12
—	1	1	1	1	1	1	356885-4	STOP, SHEAR	11
—	—	1	1	—	1	1	1320921-1	HOLDER, SHEAR, FRONT (CUT)	10
—	1	1	1	1	1	1	462006-1	SHEAR, FLOAT (FRONT)	9
1	2	2	2	1	1	1	1333205-7	ANVIL	8
									7
									6
—	1	1	1	1	1	1	854772-6	DEPRESSOR, SHEAR (FRONT)	5
—	1	1	1	1	1	1	238011-4	SPACER, BLOCK CRIMPER	4
1	2	2	2	1	1	1	679440-3	CRIMPER, INSULATION	3
									2
1	2	2	2	1	1	1	1-456406-8	CRIMPER, WIRE	1

[illegible]


 1. RECOMMENDED SPARE PARTS.


2. GREASE RAM, CAM, CAM FOLLOWER AND FEED ROD LIGHTLY.
3. LUBRICATE DAILY PER THE APPLICATOR INSTRUCTION SHEET SUPPLIED WITH THE APPLICATOR.



POST FEED 40 mm STROKE	POST FEED 30 mm STROKE	PRE FEED 30 mm STROKE	PRE FEED 40 mm STROKE

* **WARNING:**
ON INSTALLATION, SET WIRE DISC TO LARGEST WIRE SIZE
SETTING. USE OF SETTINGS BELOW MIN REQ'D CRIMP
HEIGHT SETTING WILL CAUSE DAMAGE TO CRIMP TOOLING.



THIS DRAWING IS A CONTROLLED DOCUMENT.		DWG NO. 12F0602 L1 FLOTHOUSE CHK:	 Tyco Electronics Corporation Harrisburg, PA 17105-3608	
DIMENSIONS: INCHES		TO TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 .010 ± 1 .015 ± 2 .010 ± 3 .015 ± 4 .010 ± ANGLES ±	12F0602 NAME SIDE FD HD-I FINE ADJ APPL	
		P L C ± 1 P L C ± 2 P L C ± 3 P L C ± 4 P L C ± ANGLES ±	PRODUCT SPEC APPLICATION SPEC	
MATERIAL FINISH		WEIGHT	SIZE A1	GAGE CODE 00779
		CUSTOMER DRAWING	DRAWING NO. C=1528082	RESTRICTED TO
			SCALE 1 OF 1	REV F

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9