






DIMENSIONING AND TOLERANCING PER ASME Y14.5M (ISO STANDARDS)
THIS DRAWING IS A CONTROLLED DOCUMENT.

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TE CONNECTIVITY. IT IS TO BE USED ONLY FOR THE PURPOSES AND APPLICATIONS SPECIFIED IN THE DRAWING AND NOT BE REPRODUCED, COPIED, EITHER IN WHOLE OR IN PART, OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, WITHOUT AUTHORIZATION FROM TE CONNECTIVITY.

TOOL NUMBER 	WIRE SIZE mm ² [AWG]	INSULATION DIAMETER mm [in.]	INSULATION ADJUSTER 	FLIP LOCATOR 	STRIP LENGTH mm [in.]	CRIMP HEIGHT mm [in.]	CONTACT PART NUMBERS 		CONTACT DESCRIPTION	APPLIC. SPECIFIC.
							LOOSE PIECE 	STRIP FORM 		
91509-1 91509-3	0.32-0.89 [22-18]	2.29-3.30 [.090-.130]	YES	NO	4.75 ± 0.38 [.187 ± .015]	1.27 ± 0.05 [.050 ± .002]	42566-[] 60196-3 62228-1 42638-2	42452-[] 60196-[] 62026-1 42373-[]	187 FASTON Contacts	114-2036 and 114-35000
	1.25-1.42 [16]					1.52 ± 0.08 [.060 ± .003]				
91511-1 91511-3	0.20-0.38 [24-22]	1.02-1.52 [.040-.060]	NO	NO	4.75 ± 0.38 [.187 ± .015]	0.76 ± 0.05 [.030 ± .002]	-	42067-[] 42415-[]	110 FASTON Contacts	114-2036 and 114-35000
	0.32-0.96 [22-18]	1.52-2.54 [.060-.100]				1.14 ± 0.05 [.045 ± .002]	42922-[]	42635-[]		
91514-1 91514-3	0.32-0.96 [22-18]	1.52-2.54 [.060-.100]	YES	NO	6.35 ± 0.38 [.250 ± .015]	1.40 ± 0.10 [.055 ± .004]	41969-[] 42731-[] 60878-2 61316-1 170187-[]	41772-[] 42640-[] 60294-2 170183-[]	250 FASTON contacts	114-2036 and 114-35000
		2.29-3.30 [.090-.130]								
91581-1 91581-3	0.50-0.85 [20-18]	2.03-3.05 [.080-.120]	NO	NO	4.5 ± 0.38 [.177 ± .015]	0.97-1.10 [.038-.043]	170042-[] 172799-[]	170015-[] 170033-[]	110 FASTON Contacts	114-2036 and 114-35000
						1.42-1.55 [.056-.061]	170041-[]	170014-[]		
91593-1 91593-3	0.51-0.89 [20-18]	1.90-3.00 [.075-.118]	YES	NO	4.50 ± 0.50 [.177 ± .020]	1.10-1.24 [.043-.049]	170331-[]	170325-[]	187 POSITIVE LOCK FASTON Contacts	114-5041
	1.25-1.38 [16]	2.40-3.40 [.094-.134]				1.35-1.54 [.053-.061]				
2031929-1 2031929-3	0.32-0.96 [22-18]	1.52-2.54 [.060-.100]	NO	NO	4.75 ± 0.38 [.187 ± .015]	1.14 ± 0.05 [.045 ± .002]	42470-[]	42068-[]	110 FASTON Contacts	114-2036 and 114-35000
2063247-1 2063247-3	0.31-0.56 (22-20)	2.03-2.65 (.080-.104)	YES	NO	4.78 ± 0.38 (.188 ± .015)	1.37 ± 0.05 (.054 ± .002)	-	42490-[]	187 FASTON Contacts	114-2036
	0.76-0.89 (18)	2.13-3.05 (.084-.120)				1.57 ± 0.05 (.062 ± .002)				
2063846-1 2063846-3	0.20-0.38 [24-22]	1.02-1.52 [.040-.060]	NO	NO	4.75 ± 0.38 [.187 ± .015]	0.76 ± 0.05 [.030 ± .002]	-	42067-[] 42415-[]	110 FASTON Contacts	114-2036 and 114-35000
	0.32-0.96 [22-18]	1.52-2.54 [.060-.100]				1.14 ± 0.05 [.045 ± .002]	42470-[]	42068-[]		


-  LIST OF APPLIED CONTACT PART NUMBERS MAY NOT BE COMPLETE AND IS SUBJECT TO CHANGE. FOR CURRENT INFORMATION ON TERMINAL PART NUMBERS, CONTACT THE TOOLING ASSISTANCE CENTER : 1-800-722-1111.
2. AMP, CERTI-CRIMP, and FASTON ARE TRADEMARKS.
-  -1 IS A CERTICRIMP II HAND TOOL ASSEMBLY.
-3 IS A CERTICRIMP II HEAD SUB-ASSEMBLY.
4. THE HAND TOOL INSTRUCTION SHEET, ALSO KNOWN AS AN "IS", FOR MOST CERTI-CRIMP II TOOLS USE IS 408-8547. IF THE TOOL HAS A FLIP LOCATOR USE IS 408-10414.

CERTI-CRIMP II DATA SHEET

DWG: M. YOUNGER 21FEB2012		MATERIAL: -	HEAT TREAT: -
CHK: B.A.WOLFE 22FEB2012		 TE Connectivity	
APVD: B.A. WOLFE 22FEB2012			
NAME: B.A. WOLFE			
CERTI-CRIMP II TOOL DATA SHEET FASTON & POSITIVE LOCK CONTACT FAMILY			
SCALE: -	SIZE: A1	DRAWING NO: 1583005	SHEET 1 OF 2






D3	REVISED - NEW FORMAT	2-2012	MY	BAW
P	LTR	REVISION RECORD	DATE	DWN

APVD	DATE	BY	DATE

DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED:	
	0 PLC ± -	1 PLC ± -	2 PLC ± -
	3 PLC ± -	4 PLC ± -	
ANGLES: -		SURFACE TEXTURE: 	

LOC A
DIST 00

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TFCO. IT IS TO BE KEPT CONFIDENTIAL AND PROPRIETARY AND NOT TO BE DISCLOSED TO ANY OTHER PERSON OR ENTITY WITHOUT THE WRITTEN AUTHORIZATION OF TFCO. ANY VIOLATION OF THIS POLICY WILL BE CAUSE FOR IMMEDIATE DISCIPLINE, UP TO AND INCLUDING TERMINATION. THIS DRAWING IS A CONTROLLED DOCUMENT. 1583005

TOOL NUMBER 	WIRE SIZE mm ² [AWG]	INSULATION DIAMETER mm [in.]	INSULATION ADJUSTER 	FLIP LOCATOR 	STRIP LENGTH mm [in.]	CRIMP HEIGHT mm [in.]	CONTACT PART NUMBERS 		CONTACT DESCRIPTION	APPLIC. SPECIF.
							LOOSE PIECE 	STRIP FORM 		
2063848-1	0.20-0.35 [24-22]	1.50-2.55 [.059-.100]	NO	NO	3.50 ± 0.50 [.138 ± .020]	0.89-0.99 [.035-.039]	170203-2	-	187 FASTON contacts	114-5013
2063848-3	0.50-0.56 [20]	1.95-2.60 [.077-.102]				1.00-1.10 [.039-.043]				
2063760-1	0.20-0.35 [24-22]	1.50-1.90 [.059-.075]	NO	NO	4.5 ± 0.5 [.177 ± .020]	0.90-1.05 [.035-.041]	170330-()	170324-()	.187 SERIES POSITIVE LOCK RECEPTACLE	114-5041
2063760-3	0.50-0.53 [20]	2.00-2.70 [.079-.106]				1.00-1.13 [.039-.047]				

-  LIST OF APPLIED CONTACT PART NUMBERS MAY NOT BE COMPLETE AND IS SUBJECT TO CHANGE. FOR CURRENT INFORMATION ON TERMINAL PART NUMBERS, CONTACT THE TOOLING ASSISTANCE CENTER : 1-800-722-1111.
2. AMP, CERTI-CRIMP, and FASTON ARE TRADEMARKS.
-  -1 IS A CERTICRIMP II HAND TOOL ASSEMBLY.
-3 IS A CERTICRIMP II HEAD SUB-ASSEMBLY.
4. THE HAND TOOL INSTRUCTION SHEET, ALSO KNOWN AS AN "IS", FOR MOST CERTI-CRIMP II TOOLS USE IS 408-8547. IF THE TOOL HAS A FLIP LOCATOR USE IS 408-10414.

CERTI-CRIMP II DATA SHEET

DWN	M. YOUNGER	21FEB2012	MATERIAL	-	HEAT TREAT	-					
CHK	B.A.WOLFE	22FEB2012	 TE Connectivity								
APVD	B.A. WOLFE	22FEB2012									
NAME											
CERTI-CRIMP II TOOL DATA SHEET FASTON & POSITIVE LOCK CONTACT FAMILY											
SCALE	-	SIZE	A1	DRAWING NO	1583005	SHEET	2	of	2	REV	D3

LOC
A
DIST
00

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9