

PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION

**Part Number:** [0736440206](#)  
**Status:** **Active**  
**Overview:** [hdm](#)  
**Description:** 2.00mm (.079") Pitch HDM® Board-to-Board Backplane Header, Vertical, SMC, Press-Fit, Guide Post Location B, Polarizing Key Position D, 72 Circuits

**Documents:**  
[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

**Agency Certification**

|     |         |
|-----|---------|
| CSA | LR19980 |
| UL  | E29179  |

**General**

|                |                       |
|----------------|-----------------------|
| Product Family | Backplane Connectors  |
| Series         | <a href="#">73644</a> |
| Application    | Backplane             |
| Comments       | Standard Press-Fit    |
| Component Type | PCB Header            |
| Overview       | <a href="#">hdm</a>   |
| Product Name   | HDM®                  |
| Style          | N/A                   |

**Physical**

|                                |                                  |
|--------------------------------|----------------------------------|
| Circuits (Loaded)              | 72                               |
| Circuits (maximum)             | 72                               |
| Color - Resin                  | Black, Natural                   |
| Durability (mating cycles max) | 250                              |
| First Mate / Last Break        | No                               |
| Flammability                   | 94V-0                            |
| Guide to Mating Part           | Yes                              |
| Keying to Mating Part          | Yes                              |
| Material - Metal               | Phosphor Bronze, Stainless Steel |
| Material - Plating Mating      | Gold                             |
| Material - Plating Termination | Gold                             |
| Material - Resin               | High Temperature Thermoplastic   |
| Number of Columns              | 12                               |
| Number of Pairs                | Open Pin Field                   |
| Number of Rows                 | 6                                |
| Orientation                    | Vertical                         |
| PC Tail Length (in)            | 0.138 In                         |
| PC Tail Length (mm)            | 3.50 mm                          |
| PCB Locator                    | No                               |
| PCB Retention                  | Yes                              |
| PCB Thickness Recommended (in) | 0.098 In                         |
| PCB Thickness Recommended (mm) | 2.50 mm                          |
| Packaging Type                 | Tube                             |
| Pitch - Mating Interface (in)  | 0.079 In                         |
| Pitch - Mating Interface (mm)  | 2.00 mm                          |
| Pitch - Term. Interface (in)   | 0.079 In                         |
| Pitch - Term. Interface (mm)   | 2.00 mm                          |
| Plating min: Mating (µin)      | 30                               |
| Plating min: Mating (µm)       | 0.75                             |
| Plating min: Termination (µin) | 2                                |
| Plating min: Termination (µm)  | 0.05                             |
| Polarized to PCB               | No                               |



Series

image - Reference only

**EU RoHS**

**ELV and RoHS  
Compliant**  
**REACH SVHC  
Not Reviewed**  
**Halogen-Free  
Status**

**China RoHS**



**Need more information on product environmental compliance?**  
  
Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
For a multiple part number RoHS Certificate of Compliance, [click here](#)  
  
Please visit the [Contact Us](#) section for any non-product compliance questions.

**Search Parts in this Series**  
[73644Series](#)

**Mates With**  
[73632](#) HDM PLUS® Board-to-Board Daughtercard Receptacle. [73780](#) HDM® Board-to-Board Daughtercard Receptacle

| Application Tooling   FAQ                                                                                                                                                       |                            |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|
| Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document. |                            |
| Global                                                                                                                                                                          |                            |
| Description                                                                                                                                                                     | Product #                  |
| Flat Rock Tooling for Pneumatic Press                                                                                                                                           | <a href="#">0622013700</a> |
| HDM® Backplane Insertion Signal Contact Tool                                                                                                                                    | <a href="#">0621001400</a> |
| Extraction Tool                                                                                                                                                                 | <a href="#">0621001000</a> |

|                                |                              |
|--------------------------------|------------------------------|
| Stackable                      | No                           |
| Surface Mount Compatible (SMC) | Yes                          |
| Temperature Range - Operating  | -55°C to +105°C              |
| Termination Interface: Style   | Through Hole - Compliant Pin |

**Electrical**

|                               |          |
|-------------------------------|----------|
| Current - Maximum per Contact | 1A       |
| Data Rate                     | 1.0 Gbps |
| Real Signals (per 25mm)       | 75       |
| Shielded                      | No       |
| Voltage - Maximum             | 250V AC  |

**Material Info**

**Reference - Drawing Numbers**

|                         |                |
|-------------------------|----------------|
| Packaging Specification | PK-70873-0818  |
| Sales Drawing           | SDA-73644-**** |

HDM and High Density Metric are trademarks of Amphenol Corporation

This document was generated on 05/14/2010

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**

# NOTES:

1. MATERIALS: HOUSING - LIQUID CRYSTAL POLYMER (LCP), GLASS-FILLED, UL94V-0, COLOR: BLACK, TERMINAL - PHOSPHOR BRONZE.
2. FINISHES: SELECTIVE GOLD (Au) IN CONTACT AREA, 0.00076mm MINIMUM THICKNESS; NICKEL (Ni) AND GOLD FLASH OVERALL SELECTIVE GOLD (Au) IN CONTACT AREA, 0.00076mm MIN. THICKNESS; SELECTIVE TIN/LEAD (Sb/Pb) IN TAIL AREA; NICKEL (Ni) OVERALL.
3. THIS PART CONFORMS TO MOLEX PRODUCT SPECIFICATION PS-73670-9999.
4. FOR MIXED CONTACT MATING LENGTHS, CONSULT FACTORY FOR AVAILABILITY.
5. DIMENSIONS ARE IN MILLIMETERS.
6. FOR SPECIFIC MATERIAL NUMBERS, REFER TO SHEET 2.
7. PACKAGE PER PK-70873-0818.
8. PARTS MARKED WITH PART NUMBER AND DATE CODE, ON EITHER SIDE, APPROXIMATELY WHERE SHOWN.



PCB LAYOUT: COMPONENT SIDE  
RECOMMENDED PCB THICKNESS: 2.50 MIN

|      |     |
|------|-----|
| 2    | D   |
| 1    | J   |
| MFG. | SH. |
| REV. |     |

SEE NOTE 8

|      |                                                |      |                                                 |
|------|------------------------------------------------|------|-------------------------------------------------|
|      |                                                | I    | REVISED<br>ECR UDT2000-0348<br>BINGHAM 99/10/12 |
|      |                                                | H    | REVISED<br>ECR UDT1999-0662<br>BINGHAM 99/05/18 |
| J    | REVISED<br>ECR UCP2003-2260<br>THOMAS 03/04/25 | G    | REVISED<br>ECR UDT1999-0476<br>BINGHAM 98/12/21 |
| LTR. | REVISIONS                                      | LTR. | REVISIONS                                       |

| DIMENSIONS SHOWN (METRIC) INCH                           |       |              |        |
|----------------------------------------------------------|-------|--------------|--------|
| UNLESS OTHERWISE SPECIFIED<br>TOLERANCES: ANGULAR ± 1/2° |       |              |        |
|                                                          |       | INCH         | METRIC |
| 3 PLACE                                                  | ± N/A | ---          |        |
| 2 PLACE                                                  | ± N/A | ± 0.05       |        |
| 1 PLACE                                                  | ---   | ± 0.10       |        |
| DRAFT WHERE APPLICABLE MUST<br>REMAIN WITHIN DIMENSIONS  |       |              |        |
| DRWG.<br>BY                                              | JRR   | CHK'D.<br>BY | SMR    |
| APP'D.<br>BY                                             | CAB   | SCALE        | 2 : 1  |

|                                                                                                                               |  |                                                                                                                           |  |                           |            |
|-------------------------------------------------------------------------------------------------------------------------------|--|---------------------------------------------------------------------------------------------------------------------------|--|---------------------------|------------|
|  = 0                                     |  |  = 0                                 |  | REVISE ONLY ON CAD SYSTEM |            |
| TITLE                                                                                                                         |  |                                                                                                                           |  |                           |            |
| SALES ASSY, HDM BACKPLANE<br>MODULE, POLAR/GUIDE OPTION                                                                       |  |                                                                                                                           |  |                           |            |
|  MOLEX INCORPORATED<br>LISLE, ILL. 60532 |  | SHEET NO.<br>1 OF 2                                                                                                       |  | DATE<br>96/12/18          |            |
| PART NO.                                                                                                                      |  | DRWG. NO.                                                                                                                 |  |                           |            |
| SEE CHART                                                                                                                     |  | SDA-73644-*****                                                                                                           |  |                           |            |
| FILE NAME<br>S73644X1                                                                                                         |  | THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO<br>MOLEX INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION. |  |                           | DIV.<br>DA |
| SIZE<br>B                                                                                                                     |  |                                                                                                                           |  |                           |            |



## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9