



PCI-7230/7233/7234, LPCI/LPCle/cPCI-7230

32-CH Isolated DIO Cards

PCI EXPRESS® **PCI CompactPCI**



PCI-7230



PCI-7233



LPCI-7230



LPCle-7230



cPCI-7230

Features

- Supports a 32-bit 5 V PCI bus (PCI-7230/7233/7234/7234P)
- Supports a 32-bit 3.3 V or 5 V PCI bus (LPCI-7230)
- x1 lane PCI Express Interface (LPCle-7230)
- 3U Eurocard form factor, CompactPCI compliant (PICMG 2.0 R2.1) (cPCI-7230)
- 16-CH isolated digital inputs & 16-CH isolated digital outputs (PCI-7230/LPCI-7230/LPCle-7230/cPCI-7230)
- 32-CH isolated digital inputs (PCI-7233)
- 32-CH isolated digital outputs (PCI-7234/7234P)
- 5000 V_{RMS} optical isolation (PCI-7230 & PCI-7233/cPCI-7230)
- 2500 V_{RMS} optical isolation (PCI-7234/7234P/LPCI-7230/LPCle-7230)
- Sink current up to 500 mA on single isolated output
- Two external interrupt sources (PCI-7230/LPCI-7230/LPCle-7230/cPCI-7230)
- Change-of-state interrupt sources (PCI-7233)
- Compact, low-profile PCI/PCI Express® size PCB (LPCI-7230/LPCle-7230)

Operating Systems

- Windows 7/Vista/XP/2000/2003 Server
- Linux

Recommended Software

- AD-Logger
- VB.NET/VC.NET/VB/VC++/BCB/Delphi
- DAQBench

Driver Support

- DAQPilot for LabVIEW™
- DAQ-MTLB for MATLAB®
- PCIS-DASK for Windows
- PCIS-DASK/X for Linux

Introduction

ADLINK's PCI/LPCI/LPCle/cPCI-723X series are 32-CH isolated input and/or output cards which provide a 2,500 V optical isolation protection. The wide input range of the PCI/cPCI/LPCI/LPCle-7230 and PCI-7233 makes it easy to sense the status of external devices. The non-polarity characteristic is suitable for a wide variety of industry applications. The PCI/cPCI/LPCI/LPCle-7230 and PCI-7234 devices also feature a wide output range from 5 to 35 V, which is suitable for relay driving and industrial automation applications. The PCI-7234P provides current-source output capability. The PCI/cPCI/LPCI/LPCle-7230 and PCI-7233 also provide two interrupt sources on digital input channels. The PCI-7233 also features a change-of-state (COS) function that generates an interrupt when any digital input changes its state.

Specifications

Isolated Digital Input

- Number of channels
 - 16 (PCI-7230/LPCI-7230/LPCle-7230/cPCI-7230)
 - 32 (PCI-7233)
- Maximum input range
 - 24 V, non-polarity
 - PCI-7230/PCI-7233/LPCI-7230/LPCle-7230
- Digital logic levels
 - 0-24 V, non-polarity
 - Input high voltage: 5-24 V
 - Input low voltage: 0-1.5 V
- Input resistance: 1.2 k @ 0.5 W
- Isolation voltage
 - 2500 V_{RMS} (LPCI-7230/LPCle-7230)
 - 5000 V_{RMS} (PCI-7230/PCI-7233/cPCI-7230)
- Interrupt sources
 - Digital input channel 0 and 1 (PCI-7230/LPCI-7230/LPCI-7230/cPCI-7230)
 - Change-of-state (PCI-7233)
- Data transfers: programmed I/O

Isolated Digital Output

- Number of channels
 - 16 (PCI-7230/LPCI-7230/LPCle-7230/cPCI-7230)
 - 32 (PCI-7234)
- Output type: Darlington transistor

- Sink current
 - 500 mA for one channel @ 100% duty (PCI-7230/LPCI-7230/LPCle-7230)
 - 370 mA for all channels @ 10% duty (PCI-7230/LPCI-7230/LPCle-7230)
 - 130 mA for all channels @ 50% duty (PCI-7230/LPCI-7230/LPCle-7230)
 - 500 mA for single channel @ 100% duty (PCI-7234)
 - 500 mA for all channels @ 20% duty (PCI-7234)
- Source current
 - 500 mA for one channel @ 100% duty cycle (PCI-7234P)
 - 260 mA for all channels @ 10% duty cycle (PCI-7234P)
- Power dissipation
 - Max. 1.47 W per chip (8 DO channels) (PCI-7230/PCI-7234P/LPCI-7230/LPCle-7230)
 - Max. 2.25 W per chip (8 DO channels) (PCI-7234)
- Supply voltage: 5-35 V_{DC}
- Isolation voltage: 2500 V_{RMS}
- Data transfers: programmed I/O

General Specifications

- I/O connector
 - PCI-7230/7233/7234/7234P
 - 37-pin D-sub female
 - PCI-7230/LPCI-7230/cPCI-7230
 - One 50-pin SCSI-II female

- Operating temperature: 0°C to 60°C
- Storage temperature: -20°C to 80°C
- Relative humidity: 5% to 95%, non-condensing
- Power requirements

Device	Power Consumption
PCI-7230	+5 V @ 150 mA typical (needs external DC power)
PCI-7233	+5 V @ 300 mA typical
PCI-7234	+5 V @ 180 mA typical (with internal DC-DC power)
PCI-7234P	+5 V @ 150 mA typical
LPCI-7230	+3.3 V @ 279 mA
LPCL-7230	+1.2 V @ 133 mA
cPCI-7230	+5 V @ 270 mA typical

- Dimensions (not including connectors)
 - 153 mm X 107 mm (PCI-7230)
 - 158 mm X 107 mm (PCI-7233)
 - 175 mm X 107 mm (PCI-7234 & PCI-7234P)
 - 120 mm X 65 mm (LPCI-7230)
 - 119.9 mm(L) x 68.9 mm(H) (LPCL-7230)
 - 160 mm x 100 mm (cPCI-7230)

Terminal Boards & Cables

PCI-7230/7233/7234/7234P:

DIN-37D-01

Terminal Board with One 37-pin D-sub Connector and DIN-Rail Mounting (Cables are not included.)

ACL-9137-01

General-Purpose Terminal Board with One 37-pin D-sub Male Connector

ACL-10137-1MM

37-pin D-sub male/male cable, 1 M

LPCL-7230/LPCL-7230/cPCI-7230:

DIN-50S-01

Terminal Board with One 50-pin SCSI-II Connector and DIN-Rail Mounting (Cables are not included.)

ACL-10250-1

50-pin SCSI-II cable (mating with AMP-787082-5), 1 M

* For more information on mating cables, please refer to P2-61/62.

Ordering Information

- PCI-7230**
16-CH Isolated DI & 16-CH Isolated DO Card
- PCI-7233**
32-CH Isolated DI Card with inversed input logic
- PCI-7234**
32-CH Isolated DO Card
- PCI-7234P**
32-CH Isolated DO Card with Source Current Transistor
- LPCI-7230**
16-CH Isolated DI & 16-CH Isolated DO Low-Profile PCI Card
- LPCL-7230**
16-CH Isolated DI & 16-CH Isolated DO Low-Profile PCI Express® Card
- cPCI-7230**
16-CH Isolated DI & 16-CH Isolated DO Module

Pin Assignment

PCI-7230

IDI_0	1	20	IDI_1
IDI_2	2	21	IDI_3
IDI_4	3	22	IDI_5
IDI_6	4	23	IDI_7
IDI_8	5	24	IDI_9
IDI_10	6	25	IDI_11
IDI_12	7	26	IDI_13
IDI_14	8	27	IDI_15
EICOM	9	28	EOGND
EOGND	10	29	EOGND
IDO_0	11	30	IDO_1
IDO_2	12	31	IDO_3
IDO_4	13	32	IDO_5
IDO_6	14	33	IDO_7
IDO_8	15	34	IDO_9
IDO_10	16	35	IDO_11
IDO_12	17	36	IDO_13
IDO_14	18	37	IDO_15
VDD	19		

PCI-7234

IDO_0	1	20	IDO_1
IDO_2	2	21	IDO_3
IDO_4	3	22	IDO_5
IDO_6	4	23	IDO_7
IGND	5	24	IDO_8
IDO_9	6	25	IDO_10
IDO_11	7	26	IDO_12
IDO_13	8	27	IDO_14
IDO_15	9	28	IGND
IDO_16	10	29	IDO_17
IDO_18	11	30	IDO_19
IDO_20	12	31	IDO_21
IDO_22	13	32	IDO_23
IGND	14	33	IDO_24
IDO_25	15	34	IDO_26
IDO_27	16	35	IDO_28
IDO_29	17	36	IDO_30
IDO_31	18	37	IGND
VDD	19		

PCI-7233

IDI_0	1	20	IDI_1
IDI_2	2	21	IDI_3
IDI_4	3	22	IDI_5
IDI_6	4	23	IDI_7
IGND	5	24	IDI_8
IDI_9	6	25	IDI_10
IDI_11	7	26	IDI_12
IDI_13	8	27	IDI_14
IDI_15	9	28	IGND
IDI_16	10	29	IDI_17
IDI_18	11	30	IDI_19
IDI_20	12	31	IDI_21
IDI_22	13	32	IDI_23
IGND	14	33	IDI_24
IDI_25	15	34	IDI_26
IDI_27	16	35	IDI_28
IDI_29	17	36	IDI_30
IDI_31	18	37	IGND
IGND	19		

PCI-7234P

IDO_0	1	20	IDO_1
IDO_2	2	21	IDO_3
IDO_4	3	22	IDO_5
IDO_6	4	23	IDO_7
VDD	5	24	IDO_8
IDO_9	6	25	IDO_10
IDO_11	7	26	IDO_12
IDO_13	8	27	IDO_14
IDO_15	9	28	VDD
IDO_16	10	29	IDO_17
IDO_18	11	30	IDO_19
IDO_20	12	31	IDO_21
IDO_22	13	32	IDO_23
VDD	14	33	IDO_24
IDO_25	15	34	IDO_26
IDO_27	16	35	IDO_28
IDO_29	17	36	IDO_30
IDO_31	18	37	VDD
IGND	19		

LPCL-7230/LPCL-7230

VDD	1	26	VDD
EICOM	2	27	+5V
EICOM	3	28	EICOM
EICOM	4	29	EICOM
IDO_7	5	30	IDO_14
IDO_6	6	31	IDO_15
IDO_5	7	32	IDO_12
IDO_4	8	33	IDO_13
IDO_3	9	34	IDO_10
IDO_2	10	35	IDO_11
IDO_1	11	36	IDO_8
IDO_0	12	37	IDO_9
IDI_3H	13	38	IDI_7H
IDI_3L	14	39	IDI_7L
IDI_2H	15	40	IDI_6H
IDI_2L	16	41	IDI_6L
IDI_1H	17	42	IDI_5H
IDI_1L	18	43	IDI_5L
IDI_0H	19	44	IDI_4H
IDI_0L	20	45	IDI_4L
IDI_11	21	46	IDI_15
IDI_10	22	47	IDI_14
IDI_9	23	48	IDI_13
IDI_8	24	49	IDI_12
EOGND	25	50	EOGND

cPCI-7230

VDD	1	26	VDD
EOGND	2	27	EOGND
EOGND	3	28	EOGND
EOGND	4	29	EOGND
IDO_7	5	30	IDO_14
IDO_6	6	31	IDO_15
IDO_5	7	32	IDO_12
IDO_4	8	33	IDO_13
IDO_3	9	34	IDO_10
IDO_2	10	35	IDO_11
IDO_1	11	36	IDO_8
IDO_0	12	37	IDO_9
IDI_3H	13	38	IDI_7L
IDI_3L	14	39	IDI_7H
IDI_2H	15	40	IDI_6L
IDI_2L	16	41	IDI_6H
IDI_1H	17	42	IDI_5L
IDI_1L	18	43	IDI_5H
IDI_0H	19	44	IDI_4L
IDI_0L	20	45	IDI_4H
IDI_11	21	46	IDI_15
IDI_10	22	47	IDI_14
IDI_9	23	48	IDI_13
IDI_8	24	49	IDI_12
EICOM	25	50	EICOM

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9