

# Dual common source MOSFET Power Module

$V_{DSS}$ = 200V
$R_{DSon}$ = 5mΩ typ @ Tj = 25°C
$I_D$ = 317A @ Tc = 25°C




**Application**

- AC Switches
- Switched Mode Power Supplies
- Uninterruptible Power Supplies

**Features**

- Power MOS 7® MOSFETs
  - Low $R_{DSon}$
  - Low input and Miller capacitance
  - Low gate charge
  - Avalanche energy rated
  - Very rugged
- Kelvin source for easy drive
- Very low stray inductance
  - Symmetrical design
  - M5 power connectors
- High level of integration

**Benefits**

- Outstanding performance at high frequency operation
- Direct mounting to heatsink (isolated package)
- Low junction to case thermal resistance
- Low profile
- RoHS Compliant

## Absolute maximum ratings

| *Symbol* | *Parameter* | | *Max ratings* | *Unit* |
|---|---|---|---|---|
| $V_{DSS}$ | Drain - Source Breakdown Voltage | | 200 | V |
| $I_D$ | Continuous Drain Current | $T_c$ = 25°C | 317 | A |
| | | $T_c$ = 80°C | 237 | |
| $I_{DM}$ | Pulsed Drain current | | 1268 | |
| $V_{GS}$ | Gate - Source Voltage | | ±30 | V |
| $R_{DSon}$ | Drain - Source ON Resistance | | 6 | mΩ |
| $P_D$ | Maximum Power Dissipation | $T_c$ = 25°C | 1136 | W |
| $I_{AR}$ | Avalanche current (repetitive and non repetitive) | | 89 | A |
| $E_{AR}$ | Repetitive Avalanche Energy | | 50 | mJ |
| $E_{AS}$ | Single Pulse Avalanche Energy | | 2500 | |

CAUTION: These Devices are sensitive to Electrostatic Discharge. Proper Handing Procedures Should Be Followed. See application note APT0502 on www.microsemi.com

**All ratings @ $T_j$ = 25°C unless otherwise specified**

## Electrical Characteristics

| Symbol | Characteristic | Test Conditions | | Min | Typ | Max | Unit |
|---|---|---|---|---|---|---|---|
| $I_{DSS}$ | Zero Gate Voltage Drain Current | $V_{GS}$ = 0V, $V_{DS}$ = 200V | $T_j$ = 25°C | | | 400 | µA |
| | | $V_{GS}$ = 0V, $V_{DS}$ = 160V | $T_j$ = 125°C | | | 2000 | |
| $R_{DS(on)}$ | Drain – Source on Resistance | $V_{GS}$ = 10V, $I_D$ = 158.5A | | | 5 | 6 | mΩ |
| $V_{GS(th)}$ | Gate Threshold Voltage | $V_{GS}$ = $V_{DS}$, $I_D$ = 10mA | | 3 | | 5 | V |
| $I_{GSS}$ | Gate – Source Leakage Current | $V_{GS}$ = ±30 V, $V_{DS}$ = 0V | | | | ±200 | nA |

## Dynamic Characteristics

| Symbol | Characteristic | Test Conditions | Min | Typ | Max | Unit |
|---|---|---|---|---|---|---|
| $C_{iss}$ | Input Capacitance | $V_{GS}$ = 0V<br>$V_{DS}$ = 25V<br>f = 1MHz | | 27.4 | | nF |
| $C_{oss}$ | Output Capacitance | | | 8.72 | | |
| $C_{rss}$ | Reverse Transfer Capacitance | | | 0.38 | | |
| $Q_g$ | Total gate Charge | $V_{GS}$ = 10V<br>$V_{Bus}$ = 100V<br>$I_D$ = 300A | | 448 | | nC |
| $Q_{gs}$ | Gate – Source Charge | | | 172 | | |
| $Q_{gd}$ | Gate – Drain Charge | | | 188 | | |
| $T_{d(on)}$ | Turn-on Delay Time | **Inductive switching @ 125°C**<br>$V_{GS}$ = 15V<br>$V_{Bus}$ = 133V<br>$I_D$ = 300A<br>$R_G$ = 1.2Ω | | 28 | | ns |
| $T_r$ | Rise Time | | | 56 | | |
| $T_{d(off)}$ | Turn-off Delay Time | | | 81 | | |
| $T_f$ | Fall Time | | | 99 | | |
| $E_{on}$ | Turn-on Switching Energy | **Inductive switching @ 25°C**<br>$V_{GS}$ = 15V, $V_{Bus}$ = 133V<br>$I_D$ = 300A, $R_G$ = 1.2Ω | | 1852 | | µJ |
| $E_{off}$ | Turn-off Switching Energy | | | 1820 | | |
| $E_{on}$ | Turn-on Switching Energy | **Inductive switching @ 125°C**<br>$V_{GS}$ = 15V, $V_{Bus}$ = 133V<br>$I_D$ = 300A, $R_G$ = 1.2Ω | | 2432 | | µJ |
| $E_{off}$ | Turn-off Switching Energy | | | 2124 | | |

## Source - Drain diode ratings and characteristics


| Symbol | Characteristic | Test Conditions | | Min | Typ | Max | Unit |
|---|---|---|---|---|---|---|---|
| $I_S$ | Continuous Source current (Body diode) | | Tc = 25°C | | | 317 | A |
| | | | Tc = 80°C | | | 237 | |
| $V_{SD}$ | Diode Forward Voltage | $V_{GS}$ = 0V, $I_S$ = - 300A | | | | 1.3 | V |
| dv/dt | Peak Diode Recovery ❶ | | | | | 5 | V/ns |
| $t_{rr}$ | Reverse Recovery Time | $I_S$ = -300A, $V_R$ = 100V<br>$di_S/dt$ = 400A/µs | | | 284 | | ns |
| $Q_{rr}$ | Reverse Recovery Charge | | | | 12.24 | | µC |

❶ dv/dt numbers reflect the limitations of the circuit rather than the device itself.
$I_S \le$ - 300A  di/dt ≤ 700A/µs  $V_R \le V_{DSS}$  $T_j \le$ 150°C

## Thermal and package characteristics


| *Symbol* | *Characteristic* | | | *Min* | *Typ* | *Max* | *Unit* |
|---|---|---|---|---|---|---|---|
| $R_{thJC}$ | Junction to Case Thermal Resistance | | | | | 0.11 | °C/W |
| $V_{ISOL}$ | RMS Isolation Voltage, any terminal to case t =1 min, I isol<1mA, 50/60Hz | | | 2500 | | | V |
| $T_J$ | Operating junction temperature range | | | -40 | | 150 | °C |
| $T_{STG}$ | Storage Temperature Range | | | -40 | | 125 | |
| $T_C$ | Operating Case Temperature | | | -40 | | 100 | |
| Torque | Mounting torque | To heatsink | M6 | 3 | | 5 | N.m |
| | | For terminals | M5 | 2 | | 3.5 | |
| Wt | Package Weight | | | | | 280 | g |


## SP6 Package outline (dimensions in mm)






See application note APT0601 - Mounting Instructions for SP6 Power Modules on www.microsemi.com


## Typical Performance Curve












**Breakdown Voltage vs Temperature**





**ON resistance vs Temperature**





**Threshold Voltage vs Temperature**





**Maximum Safe Operating Area**





**Capacitance vs Drain to Source Voltage**





**Gate Charge vs Gate to Source Voltage**




**Delay Times vs Current**





**Rise and Fall times vs Current**





**Switching Energy vs Current**





**Switching Energy vs Gate Resistance**




**Operating Frequency vs Drain Current**




**Source to Drain Diode Forward Voltage**




**Microsemi reserves the right to change, without notice, the specifications and information contained herein**

Microsemi's products are covered by one or more of U.S patents 4,895,810 5,045,903 5,089,434 5,182,234 5,019,522 5,262,336 6,503,786 5,256,583 4,748,103 5,283,202 5,231,474 5,434,095 5,528,058 and foreign patents. U.S and Foreign patents pending. All Rights Reserved.

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

**Данный компонент на территории Российской Федерации**

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

**Офис по работе с юридическими лицами:**

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9