



Low-Voltage Dual SPST Analog Switch

FEATURES

- Low Voltage Operation (1.8 V to 5.5 V)
- Low On-Resistance - $r_{DS(on)}$: 1.2 Ω
- Fast Switching - 14 ns
- Low Charge Injection - Q_{INJ} : 1 pC
- Low Power Consumption
- TTL/CMOS Compatible
- MSOP-8 Package

BENEFITS

- Reduced Power Consumption
- Simple Logic Interface
- High Accuracy
- Reduce Board Space

APPLICATIONS

- Cellular Phones
- Communication Systems
- Portable Test Equipment
- Battery Operated Systems
- Sample and Hold Circuits




DESCRIPTION

The DG2003/2004/2005 are dual single-pole/single-throw monolithic CMOS analog switch designed for high performance switching of analog signals. Combining low power, fast switching, low on-resistance ($r_{DS(on)}$: 1.2 Ω) and small physical size (MSOP-8), the DG2003/2004/2005 are ideal for portable and battery powered applications requiring high performance and efficient use of board space.

The DG2003/2004/2005 are built on Vishay Siliconix's low voltage J12 process. An epitaxial layer prevents latchup.

Each switch conducts equally well in both directions when on, and blocks up to the power supply level when off.

FUNCTIONAL BLOCK DIAGRAM AND PIN CONFIGURATION

**TRUTH TABLE - DG2003**

Logic	NO
0	Off
1	On

TRUTH TABLE - DG2004

Logic	NC
0	On
1	Off

TRUTH TABLE - DG2005

Logic	NO ₁	NC ₂
0	Off	On
1	On	Off

ORDERING INFORMATION

Temp Range	Package	Part Number
-40 to 85°C	MSOP-8	DG2003DQ
		DG2004DQ
		DG2005DQ

ABSOLUTE MAXIMUM RATINGS

Reference to GND

V+	-0.3 to +6 V
IN, COM, NC, NO ^a	-0.3 to (V+ + 0.3 V)
Continuous Current (Any terminal)	±50 mA
Peak Current (Pulsed at 1 ms, 10% duty cycle)	±200 mA
Storage Temperature (D Suffix)	-65 to 150°C

Power Dissipation (Packages)^b

MSOP-8 ^c	320 mW
---------------------	--------

Notes:

- Signals on NC, NO, or COM or IN exceeding V+ will be clamped by internal diodes. Limit forward diode current to maximum current ratings.
- All leads welded or soldered to PC Board.
- Derate 6.5 mW/°C above 25°C

SPECIFICATIONS (V+ = 2.0 V)							
Parameter	Symbol	Test Conditions Otherwise Unless Specified V+ = 2.0 V, ±10%, VIN = 0.4 or 1.6 V ^e	Temp ^a	Limits −40 to 85°C			Unit
				Min ^b	Typ ^c	Max ^b	
Analog Switch							
Analog Signal Range ^d	VNO, VNC, VCOM		Full	0		V+	V
On-Resistance	rON	V+ = 2.0 V, VCOM = 1.0 V, INO, INC = 1 mA	Room Full ^d		7.0 12.5	10.0 16.0	Ω
rON Flatness ^d	rON Flatness	V+ = 2.0 V, VCOM = 0 to V+, INO, INC = 1 mA	Room		5		
Switch Off Leakage Current ^f	INO(off), INC(off)	V+ = 2.2 V VNO, VNC = 0.5 V/1.5 V, VCOM = 1.5 V/0.5 V	Room Full ^d	−500 −4.0		500 4.0	pA nA
	ICOM(off)		Room Full ^d	−500 −4.0		500 4.0	pA nA
Channel-On Leakage Current ^f	ICOM(on)	V+ = 2.2 V, VNO, VNC = VCOM = 0.5 V/1.5 V	Room Full ^d	−500 −4.0		500 4.0	pA nA
Digital Control							
Input High Voltage	VINH		Full	1.6			V
Input Low Voltage	VINL		Full			0.4	
Input Capacitance ^d	Cin		Full		5		pF
Input Current	INL or IINH	VIN = 0 or V+	Full	−1		1	μA
Dynamic Characteristics							
Turn-On Time	tON	VNO or VNC = 1.5 V, RL = 300 Ω, CL = 35 pF Figures 1 and 2	Room Full ^d		30	47 48	ns
Turn-Off Time	tOFF		Room Full ^d		22	37 48	
Charge Injection ^d	QINJ	CL = 1 nF, VGEN = 0 V, RGEN = 0 Ω, Figure 3	Room		2		pC
Off-Isolation ^d	OIRR	RL = 50 Ω, CL = 5 pF, f = 1 MHz	Room		−61		dB
Crosstalk ^d	XTALK		Room		−67		
NO, NC Off Capacitance ^d	CNO(off), CNC(off)	VIN = 0 or V+, f = 1 MHz	Room		53		pF
Channel-On Capacitance ^d	CON		Room		110		
Power Supply							
Power Supply Range	V+			1.8		2.2	V
Power Supply Current ^d	I+	VIN = 0 or V+			0.02	1.0	μA
Power Consumption	PC					2.2	μW









SPECIFICATIONS (V+ = 3.0 V)

Parameter	Symbol	Test Conditions Otherwise Unless Specified V+ = 3 V, ± 10%, VIN = 0.4 or 2.0 V ^e	Temp ^a	Limits –40 to 85°C			Unit
				Min ^b	Typ ^c	Max ^b	
Analog Switch							
Analog Signal Range ^d	VNO, VNC, VCOM		Full	0		V+	V
On-Resistance	rON	V+ = 2.7 V, VCOM = 1.5 V, INO, INC = 10 mA	Room Full		2.2 2.4	3.5 3.7	Ω
rON Flatness ^d	rON Flatness	V+ = 2.7 V, VCOM = 0 to V+, INO, INC = 10 mA	Room		0.5		
Switch Off Leakage Current ^f	INO(off), INC(off)	V+ = 3.3 V VNO, VNC = 1 V/3 V, VCOM = 3 V/1 V	Room Full	–500 –6.0		500 6.0	pA nA
	ICOM(off)		Room Full	–500 –6.0		500 6.0	pA nA
Channel-On Leakage Current ^f	ICOM(on)	V+ = 3.3 V, VNO, VNC = VCOM = 1 V/3 V	Room Full	–500 –6.0		500 6.0	pA nA
Digital Control							
Input High Voltage	VINH		Full	2			V
Input Low Voltage	VINL		Full			0.4	
Input Capacitance ^d	Cin		Full		5		pF
Input Current	IINL or IINH	VIN = 0 or V+	Full	–1		1	μA
Dynamic Characteristics							
Turn-On Time ^d	tON	VNO or VNC = 2.0 V, RL = 300 Ω, CL = 35 pF Figure 1 and 2	Room Full		19	35 36	ns
Turn-Off Time ^d	tOFF		Room Full		17	31 34	
Charge Injection ^d	QINJ	CL = 1 nF, VGEN = 0 V, RGEN = 0 Ω, Figure 3	Room		1		pC
Off-Isolation ^d	OIRR	RL = 50 Ω, CL = 5 pF, f = 1 MHz	Room		–61		dB
Crosstalk ^d	XTALK		Room		–67		
NO, NC Off Capacitance ^d	CNO(off), CNC(off)	VIN = 0 or V+, f = 1 MHz	Room		53		pF
Channel-On Capacitance ^d	CON		Room		110		
Power Supply							
Power Supply Range	V+			2.7		3.3	V
Power Supply Current	I+	VIN = 0 or V+			0.02	1.0	μA
Power Consumption	PC					3.3	μW

SPECIFICATIONS (V+ = 5.0 V)							
Parameter	Symbol	Test Conditions Otherwise Unless Specified V+ = 5 V, ± 10%, VIN = 0.8 or 2.4 V ^e	Temp ^a	Limits –40 to 85°C			Unit
				Min ^b	Typ ^c	Max ^b	
Analog Switch							
Analog Signal Range ^d	VNO, VNC, VCOM		Full	0		V+	V
On-Resistance	rON	V+ = 4.5 V, VCOM = 3 V, INO, INC = 10 mA	Room Full		1.2 1.6	2.5 2.7	Ω
rON Flatness ^d	rON Flatness	V+ = 4.5 V, VCOM = 0 to V+, INO, INC = 10 mA	Room		0.2		
Switch Off Leakage Current	INO(off), INC(off)	V+ = 5.5 V VNO, VNC = 1 V/4.5 V, VCOM = 4.5 V/1 V	Room Full	–1.0 –8.0		1.0 8.0	nA
	ICOM(off)		Room Full	–1.0 –8.0		1.0 8.0	
Channel-On Leakage Current	ICOM(on)	V+ = 5.5 V, V+ = 5.5 V VNO, VNC = VCOM = 1 V/4.5 V	Room Full	–1.0 –8.0		1.0 8.0	
Digital Control							
Input High Voltage	VINH		Full	2.4			V
Input Low Voltage	VINL		Full			0.8	
Input Capacitance	Cin		Full		5		pF
Input Current	IINL or IINH	VIN = 0 or V+	Full	–1		1	μA
Dynamic Characteristics							
Turn-On Time ^d	tON	VNO or VNC = 3 V, RL = 300 Ω, CL = 35 pF Figure 1 and 2	Room Full		13	28 31	ns
Turn-Off Time ^d	tOFF		Room Full		19	22 31	
Charge Injection ^d	QINJ	CL = 1 nF, VGEN = 0 V, RGEN = 0 Ω, Figure 3	Room		1		pC
Off-Isolation ^d	OIRR	RL = 50 Ω, CL = 5 pF, f = 1 MHz	Room		–61		dB
Crosstalk ^d	XTALK		Room		–67		
Source-Off Capacitance ^d	CNO(off), CNC(off)	VIN = 0 or V+, f = 1 MHz	Room		51		pF
Channel-On Capacitance ^d	CON		Room		110		
Power Supply							
Power Supply Range	V+			4.5		5.5	V
Power Supply Current	I+	VIN = 0 or V+			0.02	1.0	μA
Power Consumption	PC						5.5


Notes:

- Room = 25°C, Full = as determined by the operating suffix.
- The algebraic convention whereby the most negative value is a minimum and the most positive a maximum, is used in this data sheet.
- Typical values are for design aid only, not guaranteed nor subject to production testing.
- Guarantee by design, nor subjected to production test.
- V_{IN} = input voltage to perform proper function.
- Guaranteed by 5-V leakage testing, not production tested.


**TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)**

TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)


Switching Time vs. Temperature and Supply Voltage




Insertion Loss, Off-Isolation, Crosstalk vs. Frequency



Switching Threshold vs. Supply Voltage



Charge Injection vs. Analog Voltage



TEST CIRCUITS




FIGURE 1. Switching Time




FIGURE 2. Charge Injection




FIGURE 3. Off-Isolation




FIGURE 4. Channel Off/On Capacitance



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9