

# C3D20065D

## Silicon Carbide Schottky Diode

### Z-REC<sup>®</sup> RECTIFIER

|                               |   |         |
|-------------------------------|---|---------|
| $V_{RRM}$                     | = | 650 V   |
| $I_F (T_c=135^\circ\text{C})$ | = | 28 A**  |
| $Q_c$                         | = | 50 nC** |

#### Features

- 650-Volt Schottky Rectifier
- Zero Reverse Recovery Current
- Zero Forward Recovery Voltage
- High-Frequency Operation
- Temperature-Independent Switching Behavior
- Extremely Fast Switching
- Positive Temperature Coefficient on  $V_F$


#### Benefits

- Replace Bipolar with Unipolar Rectifiers
- Essentially No Switching Losses
- Higher Efficiency
- Reduction of Heat Sink Requirements
- Parallel Devices Without Thermal Runaway


#### Applications

- Switch Mode Power Supplies
- Solar Inverters
- Power Factor Correction
  - Typical PFC  $P_{out}$  : 2000W-4000W
- Motor Drives
  - Typical Power : 5HP-10HP

#### Package



TO-247-3



| Part Number | Package  | Marking  |
|-------------|----------|----------|
| C3D20065D   | TO-247-3 | C3D20065 |

#### Maximum Ratings ( $T_c = 25^\circ\text{C}$ unless otherwise specified)

| Symbol         | Parameter                                                  | Value                     | Unit             | Test Conditions                                                                                                                 | Note |
|----------------|------------------------------------------------------------|---------------------------|------------------|---------------------------------------------------------------------------------------------------------------------------------|------|
| $V_{RRM}$      | Repetitive Peak Reverse Voltage                            | 650                       | V                |                                                                                                                                 |      |
| $V_{RSM}$      | Surge Peak Reverse Voltage                                 | 650                       | V                |                                                                                                                                 |      |
| $V_{DC}$       | DC Blocking Voltage                                        | 650                       | V                |                                                                                                                                 |      |
| $I_F$          | Continuous Forward Current (Per Leg/Device)                | 29.5/59<br>14/28<br>10/20 | A                | $T_c=25^\circ\text{C}$<br>$T_c=135^\circ\text{C}$<br>$T_c=152^\circ\text{C}$                                                    |      |
| $I_{FRM}$      | Repetitive Peak Forward Surge Current (Per Leg/Device)     | 67/134<br>44/88           | A                | $T_c=25^\circ\text{C}$ , $t_p=10$ ms, Half Sine Wave, $D=0.3$<br>$T_c=110^\circ\text{C}$ , $t_p=10$ ms, Half Sine Wave, $D=0.3$ |      |
| $I_{FSM}$      | Non-Repetitive Peak Forward Surge Current (Per Leg/Device) | 90/157<br>71/115          | A                | $T_c=25^\circ\text{C}$ , $t_p=10$ ms, Half Sine Wave, $D=0.3$<br>$T_c=110^\circ\text{C}$ , $t_p=10$ ms, Half Sine Wave, $D=0.3$ |      |
| $I_{FSM}$      | Non-Repetitive Peak Forward Surge Current (Per Leg/Device) | 250/500                   | A                | $T_c=25^\circ\text{C}$ , $t_p=10$ $\mu$ s, Pulse                                                                                |      |
| $P_{tot}$      | Power Dissipation (Per Leg)                                | 136.3<br>59               | W                | $T_c=25^\circ\text{C}$<br>$T_c=125^\circ\text{C}$                                                                               |      |
| $T_J, T_{stg}$ | Operating Junction and Storage Temperature                 | -55 to<br>+175            | $^\circ\text{C}$ |                                                                                                                                 |      |
|                | TO-247 Mounting Torque                                     | 1<br>8.8                  | Nm<br>lbf-in     | M3 Screw<br>6-32 Screw                                                                                                          |      |

\* Per Leg, \*\* Per Device

## Electrical Characteristics (Per Leg)

| Symbol | Parameter               | Typ.            | Max.       | Unit          | Test Conditions                                                                                                                                                                                                    | Note |
|--------|-------------------------|-----------------|------------|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| $V_F$  | Forward Voltage         | 1.5<br>2.0      | 1.8<br>2.4 | V             | $I_F = 10\text{ A}$ $T_J = 25^\circ\text{C}$<br>$I_F = 10\text{ A}$ $T_J = 175^\circ\text{C}$                                                                                                                      |      |
| $I_R$  | Reverse Current         | 12<br>24        | 60<br>220  | $\mu\text{A}$ | $V_R = 650\text{ V}$ $T_J = 25^\circ\text{C}$<br>$V_R = 650\text{ V}$ $T_J = 175^\circ\text{C}$                                                                                                                    |      |
| $Q_C$  | Total Capacitive Charge | 25              |            | nC            | $V_R = 650\text{ V}$ , $I_F = 10\text{ A}$<br>$di/dt = 500\text{ A}/\mu\text{s}$<br>$T_J = 25^\circ\text{C}$                                                                                                       |      |
| C      | Total Capacitance       | 480<br>50<br>42 |            | pF            | $V_R = 0\text{ V}$ , $T_J = 25^\circ\text{C}$ , $f = 1\text{ MHz}$<br>$V_R = 200\text{ V}$ , $T_J = 25^\circ\text{C}$ , $f = 1\text{ MHz}$<br>$V_R = 400\text{ V}$ , $T_J = 25^\circ\text{C}$ , $f = 1\text{ MHz}$ |      |

Note:

1. This is a majority carrier diode, so there is no reverse recovery charge.

## Thermal Characteristics

| Symbol          | Parameter                                | Typ.           | Unit                      |
|-----------------|------------------------------------------|----------------|---------------------------|
| $R_{\theta JC}$ | Thermal Resistance from Junction to Case | 1.1**<br>0.55* | $^\circ\text{C}/\text{W}$ |

\*\* Per Leg, \* Both Legs

## Typical Performance (Per Leg)




Figure 1. Forward Characteristics




Figure 2. Reverse Characteristics

## Typical Performance (Per Leg)




Figure 3. Current Derating




Figure 4. Capacitance vs. Reverse Voltage




Figure 5. Transient Thermal Impedance

# Typical Performance (Per Leg)





Figure 6. Power Derating

## Diode Model (Per Leg)



$$V_{f_T} = V_T + I_f \cdot R_T$$


$$V_T = 0.98 + (T_j \cdot -1.6 \cdot 10^{-3})$$

$$R_T = 0.04 + (T_j \cdot 0.522 \cdot 10^{-3})$$

**Note:**  $T_j$  = Diode Junction Temperature In Degrees Celsius, valid from 25°C to 175°C


## Package Dimensions

Package TO-247-3



| POS | Inches   |      | Millimeters |        |
|-----|----------|------|-------------|--------|
|     | Min      | Max  | Min         | Max    |
| A   | .605     | .635 | 15.367      | 16.130 |
| B   | .800     | .831 | 20.320      | 21.10  |
| C   | .780     | .800 | 19.810      | 20.320 |
| D   | .095     | .133 | 2.413       | 3.380  |
| E   | .046     | .052 | 1.168       | 1.321  |
| F   | .060     | .095 | 1.524       | 2.410  |
| G   | .215 TYP |      | 5.460 TYP   |        |
| H   | .175     | .205 | 4.450       | 5.210  |
| J   | .075     | .085 | 1.910       | 2.160  |
| K   | 6°       | 21°  | 6°          | 21°    |
| L   | 4°       | 6°   | 4°          | 6°     |
| M   | 2°       | 4°   | 2°          | 4°     |
| N   | 2°       | 4°   | 2°          | 4°     |
| P   | .090     | .100 | 2.286       | 2.540  |
| Q   | .020     | .030 | .508        | .762   |
| R   | 9°       | 11°  | 9°          | 11°    |
| S   | 9°       | 11°  | 9°          | 11°    |
| T   | 2°       | 8°   | 2°          | 8°     |
| U   | 2°       | 8°   | 2°          | 8°     |
| V   | .137     | .144 | 3.487       | 3.658  |
| W   | .210     | .248 | 5.334       | 6.300  |
| X   | .502     | .557 | 12.751      | 14.150 |
| Y   | .637     | .695 | 16.180      | 17.653 |
| Z   | .038     | .052 | 0.964       | 1.321  |
| AA  | .110     | .140 | 2.794       | 3.556  |
| BB  | .030     | .046 | 0.766       | 1.168  |
| CC  | .161     | .176 | 4.100       | 4.472  |

## Recommended Solder Pad Layout



| Part Number | Package  | Marking  |
|-------------|----------|----------|
| C3D20065D   | TO-247-3 | C3D20065 |

**Note:** Recommended soldering profiles can be found in the applications note here: [http://www.cree.com/power\\_app\\_notes/soldering](http://www.cree.com/power_app_notes/soldering)





## Notes

---

- **RoHS Compliance**

The levels of RoHS restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted application, in accordance with EU Directive 2011/65/EC (RoHS2), as implemented January 2, 2013. RoHS Declarations for this product can be obtained from your Cree representative or from the Product Documentation sections of [www.cree.com](http://www.cree.com).

- **REACH Compliance**

REACH substances of high concern (SVHCs) information is available for this product. Since the European Chemical Agency (ECHA) has published notice of their intent to frequently revise the SVHC listing for the foreseeable future, please contact a Cree representative to insure you get the most up-to-date REACH SVHC Declaration. REACH banned substance information (REACH Article 67) is also available upon request.

- This product has not been designed or tested for use in, and is not intended for use in, applications implanted into the human body nor in applications in which failure of the product could lead to death, personal injury or property damage, including but not limited to equipment used in the operation of nuclear facilities, life-support machines, cardiac defibrillators or similar emergency medical equipment, aircraft navigation or communication or control systems, or air traffic control systems.

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9