

3M™ Pak 50 Boardmount Plug

.050" Through-Hole, Straight and Right Angle, with Ret. Clips, Flng. Option

P50 Series



- Contact design features two contact points and straight beam construction for connector reliability and low insertion force
- Retention clip secures connector for wave soldering eliminating additional hardware expenses
- Horizontal, parallel or vertical mating available
- Insulator design prevents mis-insertion errors and contact damage
- Available with and without flanges
- RoHS Compliant. See the Regulatory Information Appendix (RIA) in the "RoHS Compliance" section of www.3Mconnector.com for compliance information (RIA E1 and C1 apply)

Date Modified: February 10, 2010

TS-2046-B
Sheet 1 of 6

Physical

Insulator:

Material: Glass Filled Nylon

Flammability: UL 94V-0

Color: Black

Contact Material: Phosphor Bronze

Plating:

Underplating: Nickel

Wiping Area: 10 μ" [0.25 μm] Gold

Solder Tails: Gold Flash

Retaining Clips: Tin-Copper

Mating Compatibility: TS-2047

Electrical

Current Rating: 0.5 A

Insulation Resistance: $> 1 \times 10^9 \Omega$ at 500 V_{DC}

Withstanding Voltage: 500 V_{rms} at Sea Level

Environmental

Temperature Rating: -55°C to +85°C

Process Rating: 260°C Wave Solder Compatible

UL File No.: E68080

3M™ Pak 50 Boardmount Plug

.050" Through-Hole, Straight and Right Angle, with Ret. Clips, Flng. Option

P50 Series




Product Table / Dimensions for Straight with Flanges, with or without Retention Clips

| Contact Quantity | A | B | C | D |
|------------------|------------------|------------------|------------------|------------------|
| 20 | 25.43 [1.001] | 20.32 [0.800] | 15.83 [0.623] | 11.43 [0.450] |
| 26 | 29.24 [1.151] | 24.13 [0.950] | 19.64 [0.773] | 15.24 [0.600] |
| 30 | 31.78 [1.251] | 26.67 [1.050] | 22.18 [0.873] | 17.78 [0.700] |
| 32 | 33.05 [1.301] | 27.94 [1.100] | 23.45 [0.923] | 19.05 [0.750] |
| 34 | 34.32 [1.351] | 29.21 [1.150] | 24.72 [0.973] | 20.32 [0.800] |
| 40 | 38.13 [1.501] | 33.02 [1.300] | 28.53 [1.123] | 24.13 [0.950] |

| Contact Quantity | A | B | C | D |
|------------------|------------------|------------------|------------------|------------------|
| 50 | 44.48 [1.751] | 39.37 [1.550] | 34.88 [1.373] | 30.48 [1.200] |
| 52 | 45.75 [1.801] | 40.64 [1.600] | 36.15 [1.423] | 31.75 [1.250] |
| 60 | 50.83 [2.001] | 45.72 [1.800] | 41.23 [1.623] | 36.83 [1.450] |
| 68 | 55.91 [2.201] | 50.80 [2.000] | 46.31 [1.823] | 41.91 [1.650] |
| 80 | 63.53 [2.501] | 58.42 [2.300] | 53.93 [2.123] | 49.53 [1.950] |
| 100 | 76.23 [3.001] | 71.12 [2.800] | 66.63 [2.623] | 62.23 [2.450] |

With Retention Clips

Without Retention Clips



X-X' Cross Section



Shown with Retention Clips

TS-2046-B
Sheet 2 of 5

3M™ Pak 50 Boardmount Plug

.050" Through-Hole, Straight and Right Angle, with Ret. Clips, Flng. Option

P50 Series



Product Table / Dimensions for Straight without Flanges

| Contact Quantity | A | B | C |
|------------------|------------------|------------------|------------------|
| 20 | 17.83 [0.702] | 15.83 [0.623] | 11.43 [0.450] |
| 26 | 21.64 [0.852] | 19.64 [0.773] | 15.24 [0.600] |
| 30 | 24.18 [0.952] | 22.18 [0.873] | 17.78 [0.700] |
| 32 | 25.45 [1.002] | 23.45 [0.923] | 19.05 [0.750] |
| 34 | 26.72 [1.052] | 24.72 [0.973] | 20.32 [0.800] |
| 40 | 30.53 [1.202] | 28.53 [1.123] | 24.13 [0.950] |

| Contact Quantity | A | B | C |
|------------------|------------------|------------------|------------------|
| 50 | 36.88 [1.452] | 34.88 [1.373] | 30.48 [1.200] |
| 52 | 38.15 [1.502] | 36.15 [1.423] | 31.75 [1.250] |
| 60 | 43.23 [1.702] | 41.23 [1.623] | 36.83 [1.450] |
| 68 | 48.31 [1.902] | 46.31 [1.823] | 41.91 [1.650] |
| 80 | 55.93 [2.202] | 53.93 [2.123] | 49.53 [1.950] |
| 100 | 68.63 [2.702] | 66.63 [2.623] | 62.23 [2.450] |



X-X' Cross Section



Ordering Information

P5X - XXXP - XXX - EA

Mounting Options:

- 0 = With Flanges
- 1 = Without Flanges, offered without retention clips only

Contact Quantity:
See Table

Solder Tail and Clip Options:

- S1 = Straight without Retention Clips
- SR1 = Right Angle without Retention Clips
- R1 = Straight with Retention Clips
- RR1 = Right Angle with Retention Clips

TS-2046-B
Sheet 3 of 5

3M™ Pak 50 Boardmount Plug

.050" Through-Hole, Straight and Right Angle, with Ret. Clips, Flng. Option

P50 Series

Product Table / Dimensions for Right Angle with Flanges, with or without Retention Clips

| Contact Quantity | A | B | C | D |
|------------------|------------------|------------------|------------------|------------------|
| 20 | 25.43 [1.001] | 20.32 [0.800] | 15.83 [0.623] | 11.43 [0.450] |
| 26 | 29.24 [1.151] | 24.13 [0.950] | 19.64 [0.773] | 15.24 [0.600] |
| 30 | 31.78 [1.251] | 26.67 [1.050] | 22.18 [0.873] | 17.78 [0.700] |
| 32 | 33.05 [1.301] | 27.94 [1.100] | 23.45 [0.923] | 19.05 [0.750] |
| 34 | 34.32 [1.351] | 29.21 [1.150] | 24.72 [0.973] | 20.32 [0.800] |
| 40 | 38.13 [1.501] | 33.02 [1.300] | 28.53 [1.123] | 24.13 [0.950] |


| Contact Quantity | A | B | C | D |
|------------------|------------------|------------------|------------------|------------------|
| 50 | 44.48 [1.751] | 39.37 [1.550] | 34.88 [1.373] | 30.48 [1.200] |
| 52 | 45.75 [1.801] | 40.64 [1.600] | 36.15 [1.423] | 31.75 [1.250] |
| 60 | 50.83 [2.001] | 45.72 [1.800] | 41.23 [1.623] | 36.83 [1.450] |
| 68 | 55.91 [2.201] | 50.80 [2.000] | 46.31 [1.823] | 41.91 [1.650] |
| 80 | 63.53 [2.501] | 58.42 [2.300] | 53.93 [2.123] | 49.53 [1.950] |
| 100 | 76.23 [3.001] | 71.12 [2.800] | 66.63 [2.623] | 62.23 [2.450] |

With Retention Clips

Without Retention Clips



X-X' Cross Section



3M™ Pak 50 Boardmount Plug


.050" Through-Hole, Straight and Right Angle, with Ret. Clips, Flng. Option

P50 Series

Product Table / Dimensions for Right Angle without Flanges

| Contact Quantity | A | B | C |
|------------------|------------------|------------------|------------------|
| 20 | 17.83 [0.702] | 15.83 [0.623] | 11.43 [0.450] |
| 26 | 21.64 [0.852] | 19.64 [0.773] | 15.24 [0.600] |
| 30 | 24.18 [0.952] | 22.18 [0.873] | 17.78 [0.700] |
| 32 | 25.45 [1.002] | 23.45 [0.923] | 19.05 [0.750] |
| 34 | 26.72 [1.052] | 24.72 [0.973] | 20.32 [0.800] |
| 40 | 30.53 [1.202] | 28.53 [1.123] | 24.13 [0.950] |

| Contact Quantity | A | B | C |
|------------------|------------------|------------------|------------------|
| 50 | 36.88 [1.452] | 34.88 [1.373] | 30.48 [1.200] |
| 52 | 38.15 [1.502] | 36.15 [1.423] | 31.75 [1.250] |
| 60 | 43.23 [1.702] | 41.23 [1.623] | 36.83 [1.450] |
| 68 | 48.31 [1.902] | 46.31 [1.823] | 41.91 [1.650] |
| 80 | 55.93 [2.202] | 53.93 [2.123] | 49.53 [1.950] |
| 100 | 68.63 [2.702] | 66.63 [2.623] | 62.23 [2.450] |



TS-2046-B
Sheet 5 of 5

3M™ Pak 50 Boardmount Plug

.050" Through-Hole, Straight and Right Angle, with Ret. Clips, Flng. Option

P50 Series

Printed Circuit Board Layout (Component Side View)

STRAIGHT WITH FLANGES (with and without Retention Clips)



STRAIGHT WITHOUT FLANGES





▼=Polarity identification
Recommended PCB Thickness $t = 1.6 \pm 0.19 (0.063 \pm 0.007)$
"n" is number of contacts.

RIGHT ANGLE WITH FLANGES (with and without Retention Clips)



RIGHT ANGLE WITHOUT FLANGES



TS-2046-B
Sheet 6 of 5

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for a period of one (1) year from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.**

**3M Electronics Solutions Division**

6801 River Place Blvd.
Austin, TX 78726-9000
U.S.A.
1-800-225-5373
www.3Mconnector.com

Please recycle. Printed in USA.
© 3M 2010. All rights reserved.
RIA-2217B-E

3M is a trademark of 3M Company.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9