



Product: [1511C](#) 



Audio Snake Cable, #24-6pr, TC, Individ. Shielded, CM

Product Description

Audio Snake Cable, CM-Rated, 6-24 AWG tinned copper pairs, polyolefin insulation, individually shielded with Beldfoil® bonded to numbered/color-coded PVC jackets so both strip simultaneously, overall Beldfoil® shield, drain, flexible PVC jacket

Technical Specifications

Physical Characteristics (Overall)

Conductor

| AWG | Stranding | Material | Nominal Diameter | No. of Pairs |
|-----|-----------|--------------------|------------------|--------------|
| 24 | 7x32 | TC - Tinned Copper | 0.024 in | 6 |

| | |
|------------------------|----|
| Conductor Count: | 12 |
| Total Number of Pairs: | 6 |

Insulation

| Material | Nominal Diameter | Nominal Wall Thickness |
|--------------------|------------------|------------------------|
| PP - Polypropylene | 0.04 in | 0.008 in |

Color Chart

| Number | Color |
|--------|--------|
| 1 | Brown |
| 2 | Red |
| 3 | Orange |
| 4 | Yellow |
| 5 | Green |
| 6 | Blue |

Inner Shield Material

| Type | Material | Material Trade Name | Coverage [%] | Drainwire Material | Drainwire Diameter | Drainwire AWG | Drainwire Construction n x D |
|------|-------------|---------------------|--------------|--------------------|--------------------|---------------|------------------------------|
| Tape | Alum / Poly | Beldfoil® | 100 % | TC - Tinned Copper | 0.024 in | 24 | 7x32 |

Inner Jacket Material

| Material | Nominal Diameter | Nominal Wall Thickness |
|--------------------------|------------------|------------------------|
| PVC - Polyvinyl Chloride | 0.113 in | 0.015 in |

Outer Shield Material

| Type | Material | Material Trade Name | Coverage [%] | Drainwire Material | Drainwire Diameter | Drainwire AWG | Drainwire Construction n x D |
|------|-------------|---------------------|--------------|--------------------|--------------------|---------------|------------------------------|
| Tape | Alum / Poly | Beldfoil® | 100 % | TC - Tinned Copper | 0.046 in | 18 | 7x26 |

Outer Jacket Material

| Material | Nominal Diameter | Nominal Wall Thickness | Ripcord |
|--------------------------|------------------|------------------------|---------|
| PVC - Polyvinyl Chloride | 0.418 in | 0.037 in | Yes |

Electrical Characteristics

Conductor DCR

| Individual Pair Nominal Shield DCR | Nominal Conductor DCR | Nominal Conductor DCR Conductor Resistance |
|------------------------------------|-----------------------|--|
| 15.9 Ohm/1000ft | 23.3 Ohm/1000ft | 23.3 Ohm/1000ft |

Capacitance

| Nom. Capacitance Conductor to Conductor | Nom. Capacitance Conductor to Other Conductor to Shield |
|---|---|
| 31 pF/ft | 58 pF/ft |

Inductance

| Nominal Inductance |
|--------------------|
| 0.18 μ H/ft |

Impedance

| Nominal Characteristic Impedance |
|----------------------------------|
| 50 Ohm |

Delay

| Nominal Velocity of Propagation (VP) [%] |
|--|
| 66 % |

Current

| Max. Recommended Current [A] |
|--------------------------------|
| 1.05 Amps per conductor @ 25°C |

Voltage

| UL Voltage Rating |
|-------------------|
| 300 V RMS |

Temperature Range

| | |
|-----------------------|----------------|
| Operating Temp Range: | -35°C To +75°C |
|-----------------------|----------------|

Mechanical Characteristics

| | |
|----------------------------------|---------------|
| Bulk Cable Weight: | 94 lbs/1000ft |
| Max Recommended Pulling Tension: | 122 lbs |
| Min Bend Radius/Minor Axis: | 4.25 in |

Standards

| | |
|--------------------------|----|
| NEC/(UL) Specification: | CM |
| CEC/C(UL) Specification: | CM |

Applicable Environmental and Other Programs

| | |
|---------------------------------------|-------------------------------|
| Environmental Space: | Indoor (Not Riser or Plenum) |
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2003/11/EC (BFR): | Yes |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| EU Directive 2012/19/EU (WEEE): | Yes |
| EU Directive 2015/863/EU: | Yes |
| EU Directive Compliance: | EU Directive 2003/11/EC (BFR) |
| EU CE Mark: | No |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2004-01-01 |
| MII Order #39 (China RoHS): | Yes |

Suitability

| | |
|-----------------------|-----|
| Suitability - Indoor: | Yes |
|-----------------------|-----|

Flammability, LS0H, Toxicity Testing

| | |
|--------------------|-----------|
| UL voltage rating: | 300 V RMS |
|--------------------|-----------|

Plenum/Non-Plenum

| | |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

Part Number

Variants

| Item # | Color | Putup Type | Length | UPC |
|---------------|--------------|------------|----------|--------------|
| 1511C B59500 | Black, Matte | Reel | 500 ft | 612825116813 |
| 1511C B591000 | Black, Matte | Reel | 1,000 ft | 612825116806 |
| 1511C B595000 | Black, Matte | Reel | 5,000 ft | 612825431275 |

Footnote: C - CRATE REEL PUT-UP.

History

Update and Revision: Revision Number: 0.263 Revision Date: 04-28-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9