

Features:

- Low optical insertion loss
- Cost-effective WDM technology
- Terminates 1310 and four or eight CWDM wavelengths
- LC connectors (SC version available)
- Color coded for easy installation
- Reliable passive WDM technology
- Ring or point-to-point applications
- Low-profile modular design
- Fits in 1RU 19" rack mount chassis
- RoHS compliant

1310/CWDM MUX/DEMUX (type II) Plug-in Module



1310/CWDM plug-in module is a passive optical multiplexer/demultiplexer designed to add CWDM wavelengths to an existing 1310nm backbone ring. The module multiplexes and demultiplexes a single 1310nm wavelength and four or eight additional CWDM wavelengths in a two-fiber ring network.

This MUX/DEMUX module plugs into one half of a 1RU, 19" rack mount chassis for simple installation and modularity. This Chassis based system offers network equipment manufacturers a more scalable and higher-density solution to add CWDM capability to their existing and new networks with simple pluggable interface.

Finisar's CWDM product delivers dramatic cost savings to network equipment manufacturers, enabling them to develop metro access systems that are lower in cost, easier to provision and simpler to operate.

1310/CWDM MUX/DEMUX (Type II) Plug-in Module

Specifications

Mechanical

Dimensions:

8.3" x 1.7" x 10.4",
210mm x 43mm x 264mm,
plug-in for 1RU rack-mount

Connectors:

- Network side: LC/PC or LC/APC
- Equipment side: LC/PC or LC/APC

Optical

Wavelengths Ports:

MUX/DEMUX-1310/CWDM-4 Plug-in

- 1310nm
- 1471nm
- 1511nm
- 1551nm
- 1591nm

MUX/DEMUX-1310/CWDM-8 Plug-in

- 1310nm
- 1471nm • 1491nm
- 1511nm • 1531nm
- 1551nm • 1571nm
- 1591nm • 1611nm

Directivity:

≥ 55dB

Return Loss:

≥ 45dB

PDL:

≤ 0.15dB

PMD:

≤ 0.2ps

Environmental:

- Operating 0 to 70°C
- Relative humidity: 10 to 85%, non-condensing
- Storage - 40 to 85°C

1310/CWDM MUX/DEMUX (type II) Plug-in Module Parameter Specifications

FWSF-M/D-1310/CWDM-4


Channel	Passband	Max Insertion Loss (dB)		Min Isolation (dB)	
		Mux	Demux	Mux	Demux
1310 channel	1260nm-1360nm	1.1	1.1	30	45
CWDM channels	CWL+/-6.5nm	2.4	2.7	30	45

FWSF-M/D-1310/CWDM-8


Channel	Passband	Max Insertion Loss (dB)		Min Isolation (dB)	
		Mux	Demux	Mux	Demux
1310 channel	1260nm-1360nm	1.1	1.1	30	45
CWDM channels	CWL+/-6.5nm	3.2	3.5	30	45

Note: Connector loss included

Front Panel



Dimensions (Unit: inch)



Ordering Information

Part Number Description

FWSF-M/D-1310/CWDM-4-LC	Four Wavelength Plug-in Module for FWSF-CHASSIS-2, 1471nm, 1511nm, 1551nm, 1591nm, LC/PC connectors
FWSF-M/D-1310/CWDM-4-LA	Four Wavelength Plug-in Module for FWSF-CHASSIS-2, 1471nm, 1511nm, 1551nm, 1591nm, LC/APC connectors
FWSF-M/D-1310/CWDM-8-LC	Eight Wavelength Plug-in Module for FWSF-CHASSIS-2, 1471nm to 1611nm, LC/PC connectors
FWSF-M/D-1310/CWDM-8-LA	Eight Wavelength Plug-in Module for FWSF-CHASSIS-2, 1471nm to 1611nm, LC/APC connectors

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9