

5GHz Band SPDT Switch + LNA GaAs MMIC

■ GENERAL DESCRIPTION


The NJG1739K51 is a 5GHz band SPDT switch + low noise amplifier GaAs MMIC designed for wireless LAN front-end applications.

The NJG1739K51 features low current consumption, low insertion loss of transmit path and low noise figure of RX LNA mode.

The NJG1739K51 has ESD protection devices to achieve excellent ESD performances.

A small and ultra-thin package of QFN12-51 is adopted.

■ PACKAGE OUTLINE



NJG1739K51

■ APPLICATIONS

5GHz Band WLAN front-end application

■ FEATURES

- Operating voltage $V_{DD}=3.6V$ typ.
- Operating frequency freq=4900 to 5900MHz

[RX LNA mode]

- Operating current 8mA typ. @ $V_{DD}=3.6V$, $V_{CTL1}=V_{CTL3}=3.3V$, $V_{CTL2}=0V$
- Small signal gain 12.0dB typ.
- Noise figure 2.5dB typ.
- Input power 1dB compression 0dBm typ.

[RX Bypass mode]


- Operating current 4 μ A typ. @ $V_{DD}=3.6V$, $V_{CTL1}=3.3V$, $V_{CTL2}=V_{CTL3}=0V$
- Insertion loss 8.5dB typ.
- Input power 1dB compression +15dBm typ.

[TX mode]

- Insertion loss 0.5dB typ.
- Input power 0.1dB compression +29dBm typ.

- Package QFN12-51 (Package size: 2.0mm x 2.0mm x 0.375mm typ.)
- RoHS compliant and Halogen Free, MSL1

■ PIN CONFIGURATION



Note: Specifications and description listed in this datasheet are subject to change without notice.

■ TRUTH TABLE

“H”=V_{CTL}(H), “L”=V_{CTL}(L)

mode	VCTL1 (SW RX)	VCTL2 (SW TX)	VCTL3 (LNA)	STATE				
				IDD	LNA	Bypass	RX SW	TX SW
RX LNA	H	L	H	I _{DD1}	ON	OFF	ON	OFF
RX Bypass	H	L	L	I _{DD2}	OFF	ON	ON	OFF
TX	L	H	L	I _{DD2}	OFF	ON	OFF	ON
Sleep	L	L	L	I _{DD3}	OFF	OFF	OFF	OFF

■ ABSOLUTE MAXIMUM RATINGS

$T_a = +25^\circ\text{C}$

PARAMETERS	SYMBOL	CONDITIONS	RATINGS	UNITS
Supply voltage	V_{DD}		5.5	V
Control voltage	V_{CTL}		5.5	V
Input power 1	P_{IN1}	ANT terminal, $V_{DD}=3.6\text{V}$, $V_{CTL1}=V_{CTL3}=3.3\text{V}$, $V_{CTL2}=0\text{V}$	+15	dBm
Input power 2	P_{IN2}	TX terminal, $V_{DD}=3.6\text{V}$, $V_{CTL1}=V_{CTL3}=0\text{V}$, $V_{CTL2}=3.3\text{V}$	+25	dBm
Power dissipation	P_D	Four-layer FR4 PCB with through-hole (101.5x114.5mm), $T_j=150^\circ\text{C}$	1190	mW
Operation temperature	T_{opr}		-40 to +85	$^\circ\text{C}$
Storage temperature	T_{stg}		-55 to +150	$^\circ\text{C}$

■ ELECTRICAL CHARACTERISTICS 1 (DC Characteristics)

$V_{DD}=3.6\text{V}$, $V_{CTL(H)}=3.3\text{V}$, $V_{CTL(L)}=0\text{V}$, $T_a=+25^\circ\text{C}$, $Z_s=Z_i=50\Omega$

PARAMETERS	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Supply voltage	V_{DD}		3.0	3.6	5.0	V
Control voltage 1(High)	$V_{CTL1(H)}$		2.8	3.3	5.0	V
Control voltage 2(High)	$V_{CTL2(H)}$		2.8	3.3	5.0	V
Control voltage 3(High)	$V_{CTL3(H)}$		2.8	3.3	5.0	V
Control voltage 1(Low)	$V_{CTL1(L)}$		0.0	-	0.4	V
Control voltage 2(Low)	$V_{CTL2(L)}$		0.0	-	0.4	V
Control voltage 3(Low)	$V_{CTL3(L)}$		0.0	-	0.4	V
LNA operating current 1 (RX LNA mode)	I_{DD1}	RF OFF, $V_{CTL1}=V_{CTL3}=3.3\text{V}$, $V_{CTL2}=0\text{V}$	-	8	13	mA
LNA operating current 2 (RX Bypass mode)	I_{DD2}	RF OFF, $V_{CTL1}=3.3\text{V}$, $V_{CTL2}=V_{CTL3}=0\text{V}$	-	4	12	μA
LNA operating current 3 (Sleep mode)	I_{DD3}	RF OFF, $V_{CTL1}=V_{CTL2}=V_{CTL3}=0.4\text{V}$	-	4	12	μA
LNA operating current 4 (VCTL OPEN)	I_{DD4}	RF OFF, $V_{CTL1}=V_{CTL2}=V_{CTL3}=\text{open}$	-	4	12	μA
Control current 1	I_{CTL1}	RF OFF, $V_{CTL1}=3.3\text{V}$, $V_{CTL2}=V_{CTL3}=0\text{V}$	-	5	20	μA
Control current 2	I_{CTL2}	RF OFF, $V_{CTL2}=3.3\text{V}$, $V_{CTL1}=V_{CTL3}=0\text{V}$	-	5	20	μA
Control current 3	I_{CTL3}	RF OFF, $V_{CTL3}=3.3\text{V}$, $V_{CTL1}=V_{CTL2}=0\text{V}$	-	5	20	μA

■ ELECTRICAL CHARACTERISTICS 2 (RF Characteristics: RX LNA mode, LNA+SPDT SW)

$V_{DD}=3.6V$, $V_{CTL1}=V_{CTL3}=3.3V$, $V_{CTL2}=0V$, freq=4900 to 5900MHz,
 $T_a=+25^{\circ}C$, $Z_s=Z_l=50\Omega$, with application circuit

PARAMETERS	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Small signal gain 1	Gain1	Exclude PCB and connector losses*1	9.0	12.0	14.0	dB
Gain flatness 1	Gflat1	f=4900 to 4980MHz, f=5400 to 5480MHz, f=5820 to 5900MHz	-	-	0.3	dB
Isolation 1	ISL1		-	30	-	dB
Noise figure 1	NF1	Exclude PCB and connector losses*2	-	2.5	3.0	dB
Input power at 1dB compression 1	$P_{-1dB(IN)1}$		-	0	-	dBm
Input 3rd order Intercept point 1	IIP3_1	f1=freq, f2=freq+100kHz, $P_{IN}=-18dBm$	-	+9	-	dBm
Outband input 3rd order Intercept point 1	IIP3_OB1	f1=2450MHz, f2=f1+100kHz, $P_{IN}=-18dBm$	-	+2	-	dBm
ANT port return loss 1	RLi1		-	8.0	-	dB
LNAOUT port return loss 1	RLo1		-	9.0	-	dB
LNA switching time	Tsw1_1	10% V_{CTL} to 90% RF	-	250	400	ns
Other switching time	Tsw2_1	10% V_{CTL} to 90% RF	-	200	500	ns

*1) 0.64dB(4900MHz), 0.71dB(5400MHz), 0.79dB(5900MHz)

*2) 0.32dB(4900MHz), 0.35dB(5400MHz), 0.39dB(5900MHz)

■ ELECTRICAL CHARACTERISTICS 3 (RF Characteristics: RX Bypass mode, Bypass SW+SPDT SW)

$V_{DD}=3.6V$, $V_{CTL1}=3.3V$, $V_{CTL2}=V_{CTL3}=0V$, freq=4900 to 5900MHz,
 $T_a=+25^{\circ}C$, $Z_s=Z_l=50\Omega$, with application circuit

PARAMETERS	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Insertion loss 2	LOSS2	Exclude PCB and connector losses*3	6.0	8.5	10.5	dB
Input power at 1dB compression 2	$P_{-1dB(IN)2}$		-	+15	-	dBm
Input 3rd order Intercept point 2	IIP3_2	f1=freq, f2=freq+100kHz, $P_{IN}=-10dBm$	-	+14	-	dBm
ANT port return loss 2	RLi2		-	7.0	-	dB
LNAOUT port return loss 2	RLo2		-	12.0	-	dB

*3) 0.64dB(4900MHz), 0.71dB(5400MHz), 0.79dB(5900MHz)

■ ELECTRICAL CHARACTERISTICS 4 (RF Characteristics: TX mode, SPDT SW)

$V_{DD}=3.6V$, $V_{CTL1}=V_{CTL3}=0V$, $V_{CTL2}=3.3V$, freq=4900 to 5900MHz,
 $T_a=+25^{\circ}C$, $Z_s=Z_l=50\Omega$, with application circuit

PARAMETERS	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Insertion loss 3	LOSS3	$P_{IN}=+23dBm$, Exclude PCB and connector losses*4	-	0.5	0.8	dB
Input power at 0.1dB compression 3	$P_{-0.1dB(IN)3}$		-	+29	-	dBm
ANT port return loss 3	RLi3		-	16	-	dB
TX port return loss 3	RLo3		-	20	-	dB







*4) 0.65dB(4900MHz), 0.73dB(5400MHz), 0.81dB(5900MHz)

■ TERMINAL INFORMATION

Pin No.	SYMBOL	DESCRIPTION
1	ANT	RF transmitting/receiving terminal. No DC blocking capacitor is required for this port because of internal capacitor.
2	NC(GND)	No connected terminal. This terminal is not connected with internal circuit. Please connect to the PCB ground plane.
3	VCTL1	Control signal input terminal. This terminal is set to High-Level (+2.8 to +5.0V) or Low-Level (0 to +0.4V).
4	VCTL3	Control signal input terminal. This terminal is set to High-Level (+2.8 to +5.0V) or Low-Level (0 to +0.4V).
5	GND	Ground terminal. Please connect this terminal with ground plane as close as possible for excellent RF performance.
6	LNAOUT	RF receiving signal output terminal. No DC blocking capacitor is required for this port because of internal output matching circuit including DC blocking capacitor.
7	VDD	Positive voltage supply terminal. The positive voltage (+3.0 to +5.0V) has to be supplied. Please connect a bypass capacitor with GND terminal for excellent RF performance.
8	GND	Ground terminal. Please connect this terminal with ground plane as close as possible for excellent RF performance.
9	VCTL2	Control signal input terminal. This terminal is set to High-Level (+2.8 to +5.0V) or Low-Level (0 to +0.4V).
10	NC(GND)	No connected terminal. This terminal is not connected with internal circuit. Please connect to the PCB ground plane.
11	TX	RF transmitting signal input terminal. DC blocking capacitor is required for this port.
12	NC(GND)	No connected terminal. This terminal is not connected with internal circuit. Please connect to the PCB ground plane.
Exposed Pad	GND	Ground terminal. Please connect this terminal with ground plane as close as possible for excellent RF performance, and through holes for GND should be placed near by the pin connection


ELECTRICAL CHARACTERISTICS (RX LNA mode)

$V_{DD}=3.6V$, $V_{CTL1}=V_{CTL3}=3.3V$, $V_{CTL2}=0V$, $T_a=+25^{\circ}C$, $Z_s=Z_l=50\Omega$




ELECTRICAL CHARACTERISTICS (RX LNA mode)


$V_{DD}=3.6V$, $V_{CTL1}=V_{CTL3}=3.3V$, $V_{CTL2}=0V$, $T_a=+25^{\circ}C$, $Z_s=Z_L=50\Omega$




S11, S22 (f=50MHz to 10GHz)



S21, S12 (f=50MHz to 10GHz)




VSWRi, VSWRo (f=50MHz to 10GHz)




Zin, Zout (f=50MHz to 10GHz)

ELECTRICAL CHARACTERISTICS (RX LNA mode)

$V_{DD}=3.6V$, $V_{CTL1}=V_{CTL3}=3.3V$, $V_{CTL2}=0V$, $T_a=+25^{\circ}C$, $Z_s=Z_l=50\Omega$




S11, S22 (f=50MHz to 20GHz)



S21, S12 (f=50MHz to 20GHz)

ELECTRICAL CHARACTERISTICS (RX LNA mode)

$V_{CTL1}=V_{CTL3}=3.3V$, $V_{CTL2}=0V$, $Z_s=Z_l=50\Omega$




ELECTRICAL CHARACTERISTICS (RX LNA mode)

$V_{CTL1}=V_{CTL3}=3.3V$, $V_{CTL2}=0V$, $Z_s=Z_i=50\Omega$


Gain vs. Ambient Temperature

($V_{CTL1}=V_{CTL3}=3.3V$, $V_{CTL2}=0V$, $f=5400MHz$)




NF vs. Ambient Temperature

($V_{CTL1}=V_{CTL3}=3.3V$, $V_{CTL2}=0V$, $f=5400MHz$)




P-1dB vs. Ambient Temperature

($V_{CTL1}=V_{CTL3}=3.3V$, $V_{CTL2}=0V$, $f=5400MHz$)




IIP3 vs. Ambient Temperature

($V_{CTL1}=V_{CTL3}=3.3V$, $V_{CTL2}=0V$, $f=5400MHz$)






Outband IIP3 vs. Ambient Temperature

($V_{CTL1}=V_{CTL3}=3.3V$, $V_{CTL2}=0V$, $f=5400MHz$)



■ ELECTRICAL CHARACTERISTICS (RX LNA mode)

$V_{CTL1}=V_{CTL3}=3.3V$, $V_{CTL2}=0V$, $Z_s=Z_l=50\Omega$




ELECTRICAL CHARACTERISTICS (RX Bypass mode)

$V_{DD}=3.6V$, $V_{CTL1}=3.3V$, $V_{CTL2}=V_{CTL3}=0V$, $T_a=+25^{\circ}C$, $Z_s=Z_l=50\Omega$


Bypass mode Loss vs. frequency

($V_{DD}=3.6V$, $V_{CTL1}=3.3V$, $V_{CTL2}=V_{CTL3}=0V$)




Loss vs. Pin

($V_{DD}=3.6V$, $V_{CTL1}=3.3V$, $V_{CTL2}=V_{CTL3}=0V$, $f=5400MHz$)




Pout vs. Pin

($V_{DD}=3.6V$, $V_{CTL1}=3.3V$, $V_{CTL2}=V_{CTL3}=0V$, $f=5400MHz$)




P-1dB(IN) vs. frequency

($V_{DD}=3.6V$, $V_{CTL1}=3.3V$, $V_{CTL2}=V_{CTL3}=0V$)




Pout, IM3 vs. Pin

($V_{DD}=3.6V$, $V_{CTL1}=3.3V$, $V_{CTL2}=V_{CTL3}=0V$, $f_1=5400MHz$, $f_2=f_1+100kHz$)




IIP3, OIP3 vs. frequency

($V_{DD}=3.6V$, $V_{CTL1}=3.3V$, $V_{CTL2}=V_{CTL3}=0V$, $f_1=4900\sim5900MHz$, $f_2=f_1+100kHz$, $Pin=-10dBm$)




ELECTRICAL CHARACTERISTICS (RX Bypass mode)


$V_{DD}=3.6V$, $V_{CTL1}=3.3V$, $V_{CTL2}=V_{CTL3}=0V$, $T_a=+25^{\circ}C$, $Z_S=Z_L=50\Omega$




S11, S22 (f=50MHz to 10GHz)



S21, S12 (f=50MHz to 10GHz)



VSWRi, VSWRo (f=50MHz to 10GHz)




Zin, Zout (f=50MHz to 10GHz)

ELECTRICAL CHARACTERISTICS (RX Bypass mode)

$V_{CTL1}=3.3V$, $V_{CTL2}=V_{CTL3}=0V$, $Z_s=Z_l=50\Omega$


Loss vs. Ambient Temperature

($V_{CTL1}=3.3V$, $V_{CTL2}=V_{CTL3}=0V$, $f=5400MHz$)




P-1dB(IN) vs. Ambient Temperature

($V_{CTL1}=3.3V$, $V_{CTL2}=V_{CTL3}=0V$, $f=5400MHz$)




IIP3 vs. Ambient Temperature

($V_{CTL1}=3.3V$, $V_{CTL2}=V_{CTL3}=0V$, $f_1=5400MHz$, $f_2=f_1+100kHz$, $P_{in}=-10dBm$)




ANT Port Return Loss vs. Ambient Temperature

($V_{CTL1}=3.3V$, $V_{CTL2}=V_{CTL3}=0V$, $f=5400MHz$)





LNAOUT Port Return Loss vs. Ambient Temperature

($V_{CTL1}=3.3V$, $V_{CTL2}=V_{CTL3}=0V$, $f=5400MHz$)




■ ELECTRICAL CHARACTERISTICS (TX mode)

$V_{DD}=3.6V$, $V_{CTL1}=V_{CTL3}=0V$, $V_{CTL2}=3.3V$, $T_a=+25^{\circ}C$, $Z_s=Z_l=50\Omega$




ELECTRICAL CHARACTERISTICS (TX mode)


$V_{DD}=3.6V$, $V_{CTL1}=V_{CTL3}=0V$, $V_{CTL2}=3.3V$, $T_a=+25^{\circ}C$, $Z_s=Z_l=50\Omega$




S11, S22 (f=50MHz to 10GHz)



S21, S12 (f=50MHz to 10GHz)



VSWRi, VSWRo (f=50MHz to 10GHz)




Zin, Zout (f=50MHz to 10GHz)

■ ELECTRICAL CHARACTERISTICS (TX mode)

$V_{DD}=3.6V$, $V_{CTL1}=V_{CTL3}=0V$, $V_{CTL2}=3.3V$, $Z_s=Z_l=50\Omega$


Loss vs. Ambient Temperature

($V_{DD}=3.6V$, $V_{CTL1}=V_{CTL3}=0V$, $V_{CTL2}=3.3V$, $f=5400MHz$)




ANT Port Return Loss vs. Ambient Temperature

($V_{DD}=3.6V$, $V_{CTL1}=V_{CTL3}=0V$, $V_{CTL2}=3.3V$, $f=5400MHz$)




LNAOUT Port Return Loss vs. Ambient Temperature

($V_{DD}=3.6V$, $V_{CTL1}=V_{CTL3}=0V$, $V_{CTL2}=3.3V$, $f=5400MHz$)




APPLICATION CIRCUIT



PARTS LIST

ID No.	Value	Notes
C1	0.1μF	Murata MFG (GRM03 series)
C2, C3, C5	10pF	
C4	27pF	


■ APPLIED CIRCUIT BOARD EXAMPLE



PCB Information

Substrate: FR-4
 Thickness: 0.2mm
 Microstrip line width: 0.37mm ($Z_0=50\Omega$)
 Size: 26.0mm x 26.0mm

<PCB LAYOUT GUIDELINE>



-  PCB
-  PKG Terminal
-  PKG Outline
-  GND Via Hole
Diameter: $\phi = 0.2 / 0.3$ mm

PRECAUTIONS

- [1] All external parts should be placed as close as possible to the IC.
- [2] For avoiding the degradation of RF performance, the bypass capacitor (C1) should be placed as close as possible to VDD terminal.
- [3] For good RF performance, the ground terminals must be placed possibly close to ground plane of substrate, and through holes for GND should be placed near by the pin connection.

RECOMMENDED FOOTPRINT PATTERN (QFN12-51 PACKAGE Reference)



PKG: 2.0mm x 2.0mm

Pin pitch: 0.5mm

 : Land

 : Mask (Open area) *Metal mask thickness: 100μm

 : Resist (Open area)



■ NOISE FIGURE MEASUREMENT BLOCK DIAGRAM

Measuring instruments

NF Analyzer : Agilent N8975A

Noise Source : Agilent 346A

Setting the NF analyzer

Measurement mode form

Device under test : Amplifier

System downconverter : off

Mode setup form

Sideband : LSB


Averages : 16

Average mode : Point

Bandwidth : 4MHz

Loss comp : off


Tcold : setting the temperature of noise source (303K)



Calibration setup

* Preamplifier is used to improve NF measurement accuracy.

* Noise source, preamplifier and NF analyzer are connected directly.



Measurement Setup

* Noise source, DUT, preamplifier and NF analyzer are connected directly.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[NJR:](#)

[NJG1739K51-TE1](#)

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9