

# 74AC245, 74ACT245

## Octal Bidirectional Transceiver with 3-STATE Inputs/Outputs

### Features

- $I_{CC}$  and  $I_{OZ}$  reduced by 50%
- Non-inverting buffers
- Bidirectional data path
- A and B outputs source/sink 24mA
- ACT245 has TTL-compatible inputs

### General Description

The AC/ACT245 contains eight non-inverting bidirectional buffers with 3-STATE outputs and is intended for bus-oriented applications. Current sinking capability is 24mA at both the A and B ports. The Transmit/Receive ( $T/\bar{R}$ ) input determines the direction of data flow through the bidirectional transceiver. Transmit (active-HIGH) enables data from A ports to B ports; Receive (active-LOW) enables data from B ports to A ports. The Output Enable input, when HIGH, disables both A and B ports by placing them in a HIGH Z condition.

### Ordering Information


| Order Number | Package Number | Package Description                                                         |
|--------------|----------------|-----------------------------------------------------------------------------|
| 74AC245SC    | M20B           | 20-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-013, 0.300" Wide  |
| 74AC245SJ    | M20D           | 20-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide               |
| 74AC245MTC   | MTC20          | 20-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide |
| 74AC245PC    | N20A           | 20-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300" Wide      |
| 74ACT245SC   | M20B           | 20-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-013, 0.300" Wide  |
| 74ACT245SJ   | M20D           | 20-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide               |
| 74ACT245MSA  | MSA20          | 20-Lead Shrink Small Outline Package (SSOP), JEDEC MO-150, 5.3mm Wide       |
| 74ACT245MTC  | MTC20          | 20-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide |
| 74ACT245PC   | N20A           | 20-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300" Wide      |

Device also available in Tape and Reel. Specify by appending suffix letter "X" to the ordering number.



All packages are lead free per JEDEC: J-STD-020B standard.


## Connection Diagram




## Pin Description

| Pin Names        | Description                              |
|------------------|------------------------------------------|
| $\overline{OE}$  | Output Enable Input                      |
| $T/\overline{R}$ | Transmit/Receive Input                   |
| $A_0-A_7$        | Side A 3-STATE Inputs or 3-STATE Outputs |
| $B_0-B_7$        | Side B 3-STATE Inputs or 3-STATE Outputs |

## Logic Symbol



## IEEE/IEC



## Truth Table

| Inputs          |                  | Outputs             |
|-----------------|------------------|---------------------|
| $\overline{OE}$ | $T/\overline{R}$ |                     |
| L               | L                | Bus B Data to Bus A |
| L               | H                | Bus A Data to Bus B |
| H               | X                | HIGH-Z State        |

H = HIGH Voltage Level

L = LOW Voltage Level

X = Immaterial

## Absolute Maximum Ratings

Stresses exceeding the absolute maximum ratings may damage the device. The device may not function or be operable above the recommended operating conditions and stressing the parts to these levels is not recommended. In addition, extended exposure to stresses above the recommended operating conditions may affect device reliability. The absolute maximum ratings are stress ratings only.

| Symbol                | Parameter                                    | Rating                   |
|-----------------------|----------------------------------------------|--------------------------|
| $V_{CC}$              | Supply Voltage                               | -0.5V to +7.0V           |
| $I_{IK}$              | DC Input Diode Current<br>$V_I = -0.5V$      | -20mA                    |
|                       | $V_I = V_{CC} + 0.5$                         | +20mA                    |
| $V_I$                 | DC Input Voltage                             | -0.5V to $V_{CC} + 0.5V$ |
| $I_{OK}$              | DC Output Diode Current<br>$V_O = -0.5V$     | -20mA                    |
|                       | $V_O = V_{CC} + 0.5V$                        | +20mA                    |
| $V_O$                 | DC Output Voltage                            | -0.5V to $V_{CC} + 0.5V$ |
| $I_O$                 | DC Output Source or Sink Current             | $\pm 50mA$               |
| $I_{CC}$ or $I_{GND}$ | DC $V_{CC}$ or Ground Current per Output Pin | $\pm 50mA$               |
| $T_{STG}$             | Storage Temperature                          | -65°C to +150°C          |
| $T_J$                 | Junction Temperature                         | 140°C                    |

## Recommended Operating Conditions

The Recommended Operating Conditions table defines the conditions for actual device operation. Recommended operating conditions are specified to ensure optimal performance to the datasheet specifications. Fairchild does not recommend exceeding them or designing to absolute maximum ratings.

| Symbol                | Parameter                                                                                                  | Rating         |
|-----------------------|------------------------------------------------------------------------------------------------------------|----------------|
| $V_{CC}$              | Supply Voltage<br>AC                                                                                       | 2.0V to 6.0V   |
|                       | ACT                                                                                                        | 4.5V to 5.5V   |
| $V_I$                 | Input Voltage                                                                                              | 0V to $V_{CC}$ |
| $V_O$                 | Output Voltage                                                                                             | 0V to $V_{CC}$ |
| $T_A$                 | Operating Temperature                                                                                      | -40°C to +85°C |
| $\Delta V / \Delta t$ | Minimum Input Edge Rate, AC Devices:<br>$V_{IN}$ from 30% to 70% of $V_{CC}$ , $V_{CC}$ @ 3.3V, 4.5V, 5.5V | 125mV/ns       |
| $\Delta V / \Delta t$ | Minimum Input Edge Rate, ACT Devices:<br>$V_{IN}$ from 0.8V to 2.0V, $V_{CC}$ @ 4.5V, 5.5V                 | 125mV/ns       |

## DC Electrical Characteristics for AC

| Symbol                         | Parameter                                     | V <sub>CC</sub> (V) | Conditions                                                                                                                               | T <sub>A</sub> = +25°C |                   | T <sub>A</sub> = −40°C to +85°C |  | Units |
|--------------------------------|-----------------------------------------------|---------------------|------------------------------------------------------------------------------------------------------------------------------------------|------------------------|-------------------|---------------------------------|--|-------|
|                                |                                               |                     |                                                                                                                                          | Typ.                   | Guaranteed Limits |                                 |  |       |
| V <sub>IH</sub>                | Minimum HIGH Level Input Voltage              | 3.0                 | V <sub>OUT</sub> = 0.1V or V <sub>CC</sub> − 0.1V                                                                                        | 1.5                    | 2.1               | 2.1                             |  | V     |
|                                |                                               | 4.5                 |                                                                                                                                          | 2.25                   | 3.15              | 3.15                            |  |       |
|                                |                                               | 5.5                 |                                                                                                                                          | 2.75                   | 3.85              | 3.85                            |  |       |
| V <sub>IL</sub>                | Maximum LOW Level Input Voltage               | 3.0                 | V <sub>OUT</sub> = 0.1V or V <sub>CC</sub> − 0.1V                                                                                        | 1.5                    | 0.9               | 0.9                             |  | V     |
|                                |                                               | 4.5                 |                                                                                                                                          | 2.25                   | 1.35              | 1.35                            |  |       |
|                                |                                               | 5.5                 |                                                                                                                                          | 2.75                   | 1.65              | 1.65                            |  |       |
| V <sub>OH</sub>                | Minimum HIGH Level Output Voltage             | 3.0                 | I <sub>OUT</sub> = −50μA                                                                                                                 | 2.99                   | 2.9               | 2.9                             |  | V     |
|                                |                                               | 4.5                 |                                                                                                                                          | 4.49                   | 4.4               | 4.4                             |  |       |
|                                |                                               | 5.5                 |                                                                                                                                          | 5.49                   | 5.4               | 5.4                             |  |       |
|                                |                                               | 3.0                 | V <sub>IN</sub> = V <sub>IL</sub> or V <sub>IH</sub> , I <sub>OH</sub> = −12mA                                                           |                        | 2.56              | 2.46                            |  |       |
|                                |                                               | 4.5                 | V <sub>IN</sub> = V <sub>IL</sub> or V <sub>IH</sub> , I <sub>OH</sub> = −24mA                                                           |                        | 3.86              | 3.76                            |  |       |
|                                |                                               | 5.5                 | V <sub>IN</sub> = V <sub>IL</sub> or V <sub>IH</sub> , I <sub>OH</sub> = −24mA <sup>(1)</sup>                                            |                        | 4.86              | 4.76                            |  |       |
| V <sub>OL</sub>                | Maximum LOW Level Output Voltage              | 3.0                 | I <sub>OUT</sub> = 50μA                                                                                                                  | 0.002                  | 0.1               | 0.1                             |  | V     |
|                                |                                               | 4.5                 |                                                                                                                                          | 0.001                  | 0.1               | 0.1                             |  |       |
|                                |                                               | 5.5                 |                                                                                                                                          | 0.001                  | 0.1               | 0.1                             |  |       |
|                                |                                               | 3.0                 | V <sub>IN</sub> = V <sub>IL</sub> or V <sub>IH</sub> , I <sub>OL</sub> = 12mA                                                            |                        | 0.36              | 0.44                            |  |       |
|                                |                                               | 4.5                 | V <sub>IN</sub> = V <sub>IL</sub> or V <sub>IH</sub> , I <sub>OL</sub> = 24mA                                                            |                        | 0.36              | 0.44                            |  |       |
|                                |                                               | 5.5                 | V <sub>IN</sub> = V <sub>IL</sub> or V <sub>IH</sub> , I <sub>OL</sub> = 24mA <sup>(1)</sup>                                             |                        | 0.36              | 0.44                            |  |       |
| I <sub>IN</sub> <sup>(2)</sup> | Maximum Input Leakage Current                 | 5.5                 | V <sub>I</sub> = V <sub>CC</sub> , GND                                                                                                   |                        | ±0.1              | ±1.0                            |  | μA    |
| I <sub>OLD</sub>               | Minimum Dynamic Output Current <sup>(3)</sup> | 5.5                 | V <sub>OLD</sub> = 1.65V Max.                                                                                                            |                        |                   | 75                              |  | mA    |
| I <sub>OHD</sub>               |                                               | 5.5                 | V <sub>OHD</sub> = 3.85V Min.                                                                                                            |                        |                   | −75                             |  | mA    |
| I <sub>CC</sub> <sup>(2)</sup> | Maximum Quiescent Supply Current              | 5.5                 | V <sub>IN</sub> = V <sub>CC</sub> or GND                                                                                                 |                        | 4.0               | 40.0                            |  | μA    |
| I <sub>OZT</sub>               | Maximum I/O Leakage Current                   | 5.5                 | V <sub>I</sub> (OE) = V <sub>IL</sub> , V <sub>IH</sub> ; V <sub>I</sub> = V <sub>CC</sub> , GND; V <sub>O</sub> = V <sub>CC</sub> , GND |                        | ±0.3              | ±3.0                            |  | μA    |

## Notes:

1. All outputs loaded; thresholds on input associated with output under test.
2.  $I_{IN}$  and  $I_{CC}$  @ 3.0V are guaranteed to be less than or equal to the respective limit @ 5.5V  $V_{CC}$ .
3. Maximum test duration 2.0ms, one output loaded at a time.

## DC Electrical Characteristics for ACT

| Symbol           | Parameter                                     | V <sub>CC</sub> (V) | Conditions                                                                                                                               | T <sub>A</sub> = +25°C |                   | T <sub>A</sub> = −40°C to +85°C |  | Units |
|------------------|-----------------------------------------------|---------------------|------------------------------------------------------------------------------------------------------------------------------------------|------------------------|-------------------|---------------------------------|--|-------|
|                  |                                               |                     |                                                                                                                                          | Typ.                   | Guaranteed Limits |                                 |  |       |
| V <sub>IH</sub>  | Minimum HIGH Level Input Voltage              | 4.5                 | V <sub>OUT</sub> = 0.1V or V <sub>CC</sub> − 0.1V                                                                                        | 1.5                    | 2.0               | 2.0                             |  | V     |
|                  |                                               | 5.5                 |                                                                                                                                          | 1.5                    | 2.0               | 2.0                             |  |       |
| V <sub>IL</sub>  | Maximum LOW Level Input Voltage               | 4.5                 | V <sub>OUT</sub> = 0.1V or V <sub>CC</sub> − 0.1V                                                                                        | 1.5                    | 0.8               | 0.8                             |  | V     |
|                  |                                               | 5.5                 |                                                                                                                                          | 1.5                    | 0.8               | 0.8                             |  |       |
| V <sub>OH</sub>  | Minimum HIGH Level Output Voltage             | 4.5                 | I <sub>OUT</sub> = −50μA                                                                                                                 | 4.49                   | 4.4               | 4.4                             |  | V     |
|                  |                                               | 5.5                 |                                                                                                                                          | 5.49                   | 5.4               | 5.4                             |  |       |
|                  |                                               | 4.5                 | V <sub>IN</sub> = V <sub>IL</sub> or V <sub>IH</sub> , I <sub>OH</sub> = −24mA                                                           |                        | 3.86              | 3.76                            |  |       |
|                  |                                               | 5.5                 | V <sub>IN</sub> = V <sub>IL</sub> or V <sub>IH</sub> , I <sub>OH</sub> = −24mA <sup>(4)</sup>                                            |                        | 4.86              | 4.76                            |  |       |
| V <sub>OL</sub>  | Maximum LOW Level Output Voltage              | 4.5                 | I <sub>OUT</sub> = 50μA                                                                                                                  | 0.001                  | 0.1               | 0.1                             |  | V     |
|                  |                                               | 5.5                 |                                                                                                                                          | 0.001                  | 0.1               | 0.1                             |  |       |
|                  |                                               | 4.5                 | V <sub>IN</sub> = V <sub>IL</sub> or V <sub>IH</sub> , I <sub>OL</sub> = 24mA                                                            |                        | 0.36              | 0.44                            |  |       |
|                  |                                               | 5.5                 | V <sub>IN</sub> = V <sub>IL</sub> or V <sub>IH</sub> , I <sub>OL</sub> = 24mA <sup>(4)</sup>                                             |                        | 0.36              | 0.44                            |  |       |
| I <sub>IN</sub>  | Maximum Input Leakage Current                 | 5.5                 | V <sub>I</sub> = V <sub>CC</sub> , GND                                                                                                   |                        | ±0.1              | ±1.0                            |  | μA    |
| I <sub>CCT</sub> | Maximum I <sub>CC</sub> /Input                | 5.5                 | V <sub>I</sub> = V <sub>CC</sub> − 2.1V                                                                                                  | 0.6                    |                   | 1.5                             |  | mA    |
| I <sub>OLD</sub> | Minimum Dynamic Output Current <sup>(5)</sup> | 5.5                 | V <sub>OLD</sub> = 1.65V Max.                                                                                                            |                        |                   | 75                              |  | mA    |
| I <sub>OHD</sub> |                                               | 5.5                 | V <sub>OHD</sub> = 3.85V Min.                                                                                                            |                        |                   | −75                             |  | mA    |
| I <sub>CC</sub>  | Maximum Quiescent Supply Current              | 5.5                 | V <sub>IN</sub> = V <sub>CC</sub> or GND                                                                                                 |                        | 4.0               | 40.0                            |  | μA    |
| I <sub>OZT</sub> | Maximum I/O Leakage Current                   | 5.5                 | V <sub>I</sub> (OE) = V <sub>IL</sub> , V <sub>IH</sub> ; V <sub>I</sub> = V <sub>CC</sub> , GND; V <sub>O</sub> = V <sub>CC</sub> , GND |                        | ±0.3              | ±3.0                            |  | μA    |

**Notes:**

4. All outputs loaded; thresholds on input associated with output under test.
5. Maximum test duration 2.0ms, one output loaded at a time.

**AC Electrical Characteristics for AC**

| Symbol    | Parameter                                              | $V_{CC} (V)^{(6)}$ | $T_A = +25^{\circ}C,$<br>$C_L = 50pF$ |      |      | $T_A = -40^{\circ}C \text{ to } +85^{\circ}C,$<br>$C_L = 50pF$ |      | Units |
|-----------|--------------------------------------------------------|--------------------|---------------------------------------|------|------|----------------------------------------------------------------|------|-------|
|           |                                                        |                    | Min.                                  | Typ. | Max. | Min.                                                           | Max. |       |
| $t_{PLH}$ | Propagation Delay,<br>$A_n$ to $B_n$ or $B_n$ to $A_n$ | 3.3                | 1.5                                   | 5.0  | 8.5  | 1.0                                                            | 9.0  | ns    |
|           |                                                        | 5.0                | 1.5                                   | 3.5  | 6.5  | 1.0                                                            | 7.0  |       |
| $t_{PHL}$ | Propagation Delay,<br>$A_n$ to $B_n$ or $B_n$ to $A_n$ | 3.3                | 1.5                                   | 5.0  | 8.5  | 1.0                                                            | 9.0  | ns    |
|           |                                                        | 5.0                | 1.5                                   | 3.5  | 6.0  | 1.0                                                            | 7.0  |       |
| $t_{PZH}$ | Output Enable Time                                     | 3.3                | 2.5                                   | 7.0  | 11.5 | 2.0                                                            | 12.5 | ns    |
|           |                                                        | 5.0                | 1.5                                   | 5.0  | 8.5  | 1.0                                                            | 9.0  |       |
| $t_{PZL}$ | Output Enable Time                                     | 3.3                | 2.5                                   | 7.5  | 12.0 | 2.0                                                            | 13.5 | ns    |
|           |                                                        | 5.0                | 1.5                                   | 5.5  | 9.0  | 1.0                                                            | 9.5  |       |
| $t_{PHZ}$ | Output Disable Time                                    | 3.3                | 2.0                                   | 6.5  | 12.0 | 1.0                                                            | 12.5 | ns    |
|           |                                                        | 5.0                | 1.5                                   | 5.5  | 9.0  | 1.0                                                            | 10.0 |       |
| $t_{PLZ}$ | Output Disable Time                                    | 3.3                | 2.0                                   | 7.0  | 11.5 | 1.5                                                            | 13.0 | ns    |
|           |                                                        | 5.0                | 1.5                                   | 5.5  | 9.0  | 1.0                                                            | 10.0 |       |

**Note:**

6. Voltage range 3.3 is  $3.3V \pm 0.3V$ . Voltage range 5.0 is  $5.0V \pm 0.5V$ .

**AC Electrical Characteristics for ACT**

| Symbol    | Parameter                                              | $V_{CC} (V)^{(7)}$ | $T_A = +25^{\circ}C,$<br>$C_L = 50pF$ |      |      | $T_A = -40^{\circ}C \text{ to } +85^{\circ}C,$<br>$C_L = 50pF$ |      | Units |
|-----------|--------------------------------------------------------|--------------------|---------------------------------------|------|------|----------------------------------------------------------------|------|-------|
|           |                                                        |                    | Min.                                  | Typ. | Max. | Min.                                                           | Max. |       |
| $t_{PLH}$ | Propagation Delay,<br>$A_n$ to $B_n$ or $B_n$ to $A_n$ | 5.0                | 1.5                                   | 4.0  | 7.5  | 1.5                                                            | 8.0  | ns    |
| $t_{PHL}$ | Propagation Delay,<br>$A_n$ to $B_n$ or $B_n$ to $A_n$ | 5.0                | 1.5                                   | 4.0  | 8.0  | 1.0                                                            | 9.0  | ns    |
| $t_{PZH}$ | Output Enable Time                                     | 5.0                | 1.5                                   | 5.0  | 10.0 | 1.5                                                            | 11.0 | ns    |
| $t_{PZL}$ | Output Enable Time                                     | 5.0                | 1.5                                   | 5.5  | 10.0 | 1.5                                                            | 12.0 | ns    |
| $t_{PHZ}$ | Output Disable Time                                    | 5.0                | 1.5                                   | 5.5  | 10.0 | 1.0                                                            | 11.0 | ns    |
| $t_{PLZ}$ | Output Disable Time                                    | 5.0                | 2.0                                   | 5.0  | 10.0 | 1.5                                                            | 11.0 | ns    |


**Note:**

7. Voltage range 5.0 is  $5.0V \pm 0.5V$ .

**Capacitance**

| Symbol    | Parameter                     | Conditions             | Typ. | Units |
|-----------|-------------------------------|------------------------|------|-------|
| $C_{IN}$  | Input Capacitance             | $V_{CC} = \text{OPEN}$ | 4.5  | pF    |
| $C_{I/O}$ | Input/Output Capacitance      | $V_{CC} = 5.0V$        | 15.0 | pF    |
| $C_{PD}$  | Power Dissipation Capacitance | $V_{CC} = 5.0V$        | 45.0 | pF    |

## Physical Dimensions



**Figure 1. 20-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-013, 0.300" Wide**

Package drawings are provided as a service to customers considering Fairchild components. Drawings may change in any manner without notice. Please note the revision and/or date on the drawing and contact a Fairchild Semiconductor representative to verify or obtain the most recent revision. Package specifications do not expand the terms of Fairchild's worldwide terms and conditions, specifically the warranty therein, which covers Fairchild products.



Always visit Fairchild Semiconductor's online packaging area for the most recent package drawings:

<http://www.fairchildsemi.com/packaging/>






## Physical Dimensions (Continued)



DIMENSIONS ARE IN MILLIMETERS

## NOTES:

- CONFORMS TO JEDEC REGISTRATION MO-153, VARIATION AC, REF NOTE 6, DATE 7/93.
- DIMENSIONS ARE IN MILLIMETERS.
- DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLDS FLASH, AND TIE BAR EXTRUSIONS.
- DIMENSIONS AND TOLERANCES PER ANSI Y14.5M, 1982.




MTC20REV D1

Figure 3. 20-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide

Package drawings are provided as a service to customers considering Fairchild components. Drawings may change in any manner without notice. Please note the revision and/or date on the drawing and contact a Fairchild Semiconductor representative to verify or obtain the most recent revision. Package specifications do not expand the terms of Fairchild's worldwide terms and conditions, specifically the warranty therein, which covers Fairchild products.

Always visit Fairchild Semiconductor's online packaging area for the most recent package drawings:

<http://www.fairchildsemi.com/packaging/>

**Physical Dimensions** (Continued)**NOTES:**

- A. CONFORMS TO JEDEC REGISTRATION MS-001, VARIATIONS AD.
- B. ALL DIMENSIONS ARE IN MILLIMETERS
- C. DOES NOT INCLUDE MOLD FLASH OR PROTRUSIONS. MOLD FLASH OR PROTRUSIONS SHALL NOT EXCEED 0.25MM.
- D. DOES NOT INCLUDE DAMBAR PROTRUSIONS. DAMBAR PROTRUSIONS SHALL NOT EXCEED 0.25MM.
- E. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994.
- F. DRAWING FILE NAME: N20AREV8

**Figure 4. 20-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300" Wide**

Package drawings are provided as a service to customers considering Fairchild components. Drawings may change in any manner without notice. Please note the revision and/or date on the drawing and contact a Fairchild Semiconductor representative to verify or obtain the most recent revision. Package specifications do not expand the terms of Fairchild's worldwide terms and conditions, specifically the warranty therein, which covers Fairchild products.

Always visit Fairchild Semiconductor's online packaging area for the most recent package drawings:

<http://www.fairchildsemi.com/packaging/>





## TRADEMARKS

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

|                                                                                   |                                              |                                        |                                  |
|-----------------------------------------------------------------------------------|----------------------------------------------|----------------------------------------|----------------------------------|
| ACEx <sup>®</sup>                                                                 | FPS <sup>™</sup>                             | PDP-SPM <sup>™</sup>                   | SyncFET <sup>™</sup>             |
| Build it Now <sup>™</sup>                                                         | FRFET <sup>®</sup>                           | Power220 <sup>®</sup>                  | SYSTEM <sup>®</sup>              |
| CorePLUS <sup>™</sup>                                                             | Global Power Resource <sup>SM</sup>          | Power247 <sup>®</sup>                  | GENERAL                          |
| CROSSVOLT <sup>™</sup>                                                            | Green FPS <sup>™</sup>                       | POWEREDGE <sup>®</sup>                 | The Power Franchise <sup>®</sup> |
| CTL <sup>™</sup>                                                                  | Green FPS <sup>™</sup> e-Series <sup>™</sup> | Power-SPM <sup>™</sup>                 | the                              |
| Current Transfer Logic <sup>™</sup>                                               | GTO <sup>™</sup>                             | PowerTrench <sup>®</sup>               | power <sup>™</sup>               |
| EcoSPARK <sup>®</sup>                                                             | i-Lo <sup>™</sup>                            | Programmable Active Droop <sup>™</sup> | franchise                        |
| EZSWITCH <sup>™</sup> *                                                           | IntelliMAX <sup>™</sup>                      | QFET <sup>®</sup>                      | TinyBoost <sup>™</sup>           |
|  | ISOPLANAR <sup>™</sup>                       | QS <sup>™</sup>                        | TinyBuck <sup>™</sup>            |
|  | MegaBuck <sup>™</sup>                        | QT Optoelectronics <sup>™</sup>        | TinyLogic <sup>®</sup>           |
| Fairchild <sup>®</sup>                                                            | MICROCOUPLER <sup>™</sup>                    | Quiet Series <sup>™</sup>              | TINYOPTO <sup>™</sup>            |
| Fairchild Semiconductor <sup>®</sup>                                              | MicroFET <sup>™</sup>                        | RapidConfigure <sup>™</sup>            | TinyPower <sup>™</sup>           |
| FACT Quiet Series <sup>™</sup>                                                    | MicroPak <sup>™</sup>                        | SMART START <sup>™</sup>               | TinyPWM <sup>™</sup>             |
| FACT <sup>®</sup>                                                                 | MillerDrive <sup>™</sup>                     | SPM <sup>®</sup>                       | TinyWire <sup>™</sup>            |
| FAST <sup>®</sup>                                                                 | Motion-SPM <sup>™</sup>                      | STEALTH <sup>™</sup>                   | μSerDes <sup>™</sup>             |
| FastvCore <sup>™</sup>                                                            | OPTOLOGIC <sup>®</sup>                       | SuperFET <sup>™</sup>                  | UHC <sup>®</sup>                 |
| FlashWriter <sup>®</sup> *                                                        | OPTOPLANAR <sup>®</sup>                      | SuperSOT <sup>™</sup> -3               | Ultra FRFET <sup>™</sup>         |
|                                                                                   |                                              | SuperSOT <sup>™</sup> -6               | UniFET <sup>™</sup>              |
|                                                                                   |                                              | SuperSOT <sup>™</sup> -8               | VCX <sup>™</sup>                 |

\* EZSWITCH<sup>™</sup> and FlashWriter<sup>®</sup> are trademarks of System General Corporation, used under license by Fairchild Semiconductor.

## DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

## LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

## PRODUCT STATUS DEFINITIONS

### Definition of Terms

| Datasheet Identification | Product Status         | Definition                                                                                                                                                                                               |
|--------------------------|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Advance Information      | Formative or In Design | This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.                                                                       |
| Preliminary              | First Production       | This datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design. |
| No Identification Needed | Full Production        | This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.                                               |
| Obsolete                 | Not In Production      | This datasheet contains specifications on a product that has been discontinued by Fairchild Semiconductor. The datasheet is printed for reference information only.                                      |

Rev. I32

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9