

RS-WC-201 PRODUCT BRIEF



RS-WC-201

RS-WC-201: ADVANCED WI-FI FOR FOR M2M APPLICATIONS

The RS-WC-201 WiSeConnect™ module is a fully integrated 802.11 b/g/n module with advanced features for M2M, industrial, medical, enterprise and IOT (Internet of Things) applications. Powered with Wi-Fi Direct™, it can directly communicate with smartphones and tablet PCs without any Access Point based infrastructure. Integrated with Enterprise Security as well as TCP/IP and WLAN stacks, it can be designed quickly into any Host platform for secure and standards based Wi-Fi connectivity. The module also supports Access Point mode and can host data from a variety of sources such as sensors etc. in the module's in-built web server. Requiring no external BOM, the module integrates a MAC, Baseband Processor, RF Transceiver with power amplifier, a frequency reference and an antenna. The module comes with a comprehensive API set to make software integration quick and seamless. Based on Redpine Signals' 802.11n SoC RS9110, it is designed to provide wireless connectivity to devices that have a UART, SPI or USB interface.



Features

- 802.11b/g and single stream 802.11n
- Wi-Fi Direct™, Access Point and Client mode
- Enterprise Security - EAP-TLS, EAP-TTLS, EAP-FAST, PEAP-MSCHAP-V2
- Integrated TCP/IP stack, HTTP Server/Client, DHCP, DNS
- Over the air Firmware Upgrade
- Integrated antenna and option for external antenna
- Ultra low power operation with power save modes
- Single supply 3.1 to 3.6 V operation

Applications

- Consumer - Wi-Fi Connectivity for home appliances
- Enterprise - Wireless printers, Security cameras, Point of Sale terminals
- Industrial - M2M communication, industrial monitoring and control, data logging and streaming
- Medical - Patient monitoring, medical instrumentation with secure wireless connectivity


Specifications

Network Standard Support	IEEE 802.11b/g/n
Frequency band	2.400 - 2.500 GHz
Data Rates	802.11n: 6.5, 13, 19.5, 26, 39, 52, 58.5 Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11b: 1, 2, 5.5, 11 Mbps
Modulation Techniques	OFDM with BPSK, QPSK, 16-QAM, and 64-QAM 802.11b with CCK and DSSS
Connectivity	Wi-Fi Direct mode, Access Point mode and Client mode
Wireless Security	WPA/WPA2-Enterprise, WPA/WPA2-PSK, WPS Provisioning
Networking protocols	TCP, UDP, DHCP, ARP, IGMP, DNS client
HTTP Server	Integrated Web Server for browser based connectivity
Host Interfaces	SPI, USB, UART(AT Commands supported)
Data throughput	Up to 5.5 Mbps in SPI and USB modes, 90 kbps in UART mode at a benchmark baud rate of 115200 bps
Operating Temperature	-40°C to +85°C
Supply Voltage	3.1 - 3.6 V
Dimensions	35mm x 22mm

Evaluation Package

Redpine Signals provides a comprehensive evaluation package that includes an evaluation board, software, driver source code for the Host interface and documentation.

RS-WC-201 SYSTEM ARCHITECTURE



For additional information, please contact Sales at Redpine Signals, Inc.:

Redpine Signals, Inc. • 2107 North First Street • Suite 680 • San Jose, CA 95131

Phone: +1 408 748 3385 • Email: sales@redpinesignals.com

www.redpinesignals.com

Redpine Signals, Inc. reserves the right to make changes to the product(s) or information contained herein without notice. No Liability is assumed as a result of their use or application. Redpine, Redpine Signals, the Redpine logo, Driving Wireless Convergence, WiSeConnect and Lite-Fi are trademarks of Redpine Signals, Inc. All other company names, products and logos are registered trademarks of their respective companies.

© Copyright 2012 Redpine Signals, Inc. All Rights Reserved.

WiSeConnect™

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9