

## Type RN73 Series

### Key Features

- High precision - TCR 5ppm/°C and 10ppm/°C
- Tolerance down to 0.01%
- Thin film (nichrome)
- Choice of packages
- Stable high frequency performance
- Temperature range -55°C to +155°C

### Applications

- Communications
- Instrumentation
- Industrial controls
- Medical



The RN73 series is a high stability precision chip resistor range offering various power dissipations relating to chip size, TCR's down to 5ppm/°C and resistance tolerances to 0.01%. The resistor is produced with three sputtered layers giving optimum performance. Values are restricted to the E96 and E24 value grids. The RN73 has accurate and uniform physical dimensions to facilitate placement.

### Characteristics - Electrical

|                                      | 0402          |      |      |      |      |      | 0603          |      |      |      |      |      | 0805          |      |      |      |      |      |
|--------------------------------------|---------------|------|------|------|------|------|---------------|------|------|------|------|------|---------------|------|------|------|------|------|
| Rated Power @ 70°C:                  | 0.063W        |      |      |      |      |      | 0.063W        |      |      |      |      |      | 0.1W          |      |      |      |      |      |
| Resistance Range (Ohms) Min:<br>Max: | 49R9          | 49R9 | 49R9 | 49R9 | 49R9 | 49R9 | 24R9          | 24R9 | 24R9 | 4R7  | 24R9 | 4R7  | 24R9          | 24R9 | 24R9 | 4R3  | 24R9 | 4R3  |
|                                      | 5K0           | 15K  | 5K0  | 15K  | 5K0  | 15K  | 15K           | 100K | 15K  | 332K | 15K  | 332K | 30K           | 200K | 30K  | 511K | 30K  | 511K |
| Tolerance (%):                       | 0.01          |      | 0.05 |      | 0.1  |      | 0.01          |      | 0.05 |      | 0.1  |      | 0.01          |      | 0.05 |      | 0.1  |      |
| Code Letter:                         | L             |      | A    |      | B    |      | L             |      | A    |      | B    |      | L             |      | A    |      | B    |      |
| Selection Series:                    | E24 & E96     |      |      |      |      |      | E24 & E96     |      |      |      |      |      | E24 & E96     |      |      |      |      |      |
| Temp. Coefficient (ppm/°C):          | 5             | 10   | 5    | 10   | 5    | 10   | 5             | 10   | 5    | 10   | 5    | 10   | 5             | 10   | 5    | 10   | 5    | 10   |
| Code Letter:                         | A             | C    | A    | C    | A    | C    | A             | C    | A    | C    | A    | C    | A             | C    | A    | C    | A    | C    |
| Limiting Element Voltage:            | 25V           |      |      |      |      |      | 50V           |      |      |      |      |      | 100V          |      |      |      |      |      |
| Max. Overload Voltage:               | 50V           |      |      |      |      |      | 100V          |      |      |      |      |      | 200V          |      |      |      |      |      |
| Operating Temp. Range:               | -55 to +155°C |      |      |      |      |      | -55 to +155°C |      |      |      |      |      | -55 to +155°C |      |      |      |      |      |
| Climatic Category (°C):              | 55/125/55     |      |      |      |      |      | 55/125/55     |      |      |      |      |      | 55/125/55     |      |      |      |      |      |
| Insulation Resistance Dry Min:       | 1000MΩ        |      |      |      |      |      | 1000MΩ        |      |      |      |      |      | 1000MΩ        |      |      |      |      |      |
| Stability:                           | 0.5%          |      |      |      |      |      | 0.5%          |      |      |      |      |      | 0.5%          |      |      |      |      |      |

|                                      | 1206          |      |      |     |      |     | 1210          |      |      |     |      |     | 2010          |      |      |     |      |     |
|--------------------------------------|---------------|------|------|-----|------|-----|---------------|------|------|-----|------|-----|---------------|------|------|-----|------|-----|
| Rated Power @ 70°C:                  | 0.125W        |      |      |     |      |     | 0.2W          |      |      |     |      |     | 0.25W         |      |      |     |      |     |
| Resistance Range (Ohms) Min:<br>Max: | 24R9          | 24R9 | 24R9 | 4R7 | 24R9 | 4R7 | 24R9          | 24R9 | 24R9 | 4R7 | 24R9 | 4R7 | 24R9          | 24R9 | 24R9 | 4R7 | 24R9 | 4R7 |
|                                      | 50K           | 562K | 50K  | 1M0 | 50K  | 1M0 | 50K           | 500K | 50K  | 1M0 | 50K  | 1M0 | 100K          | 500K | 100K | 1M0 | 100K | 1M0 |
| Tolerance (%):                       | 0.01          |      | 0.05 |     | 0.1  |     | 0.01          |      | 0.05 |     | 0.1  |     | 0.01          |      | 0.05 |     | 0.1  |     |
| Code Letter:                         | L             |      | A    |     | B    |     | L             |      | A    |     | B    |     | L             |      | A    |     | B    |     |
| Selection Series:                    | E24 & E96     |      |      |     |      |     | E24 & E96     |      |      |     |      |     | E24 & E96     |      |      |     |      |     |
| Temp. Coefficient (ppm/°C):          | 5             | 10   | 5    | 10  | 5    | 10  | 5             | 10   | 5    | 10  | 5    | 10  | 5             | 10   | 5    | 10  | 5    | 10  |
| Code Letter:                         | A             | C    | A    | C   | A    | C   | A             | C    | A    | C   | A    | C   | A             | C    | A    | C   | A    | C   |
| Limiting Element Voltage:            | 150V          |      |      |     |      |     | 150V          |      |      |     |      |     | 150V          |      |      |     |      |     |
| Max. Overload Voltage:               | 300V          |      |      |     |      |     | 300V          |      |      |     |      |     | 300V          |      |      |     |      |     |
| Operating Temp. Range:               | -55 to +155°C |      |      |     |      |     | -55 to +155°C |      |      |     |      |     | -55 to +155°C |      |      |     |      |     |
| Climatic Category (°C):              | 55/125/55     |      |      |     |      |     | 55/125/55     |      |      |     |      |     | 55/125/55     |      |      |     |      |     |
| Insulation Resistance Dry Min:       | 1000MΩ        |      |      |     |      |     | 1000MΩ        |      |      |     |      |     | 1000MΩ        |      |      |     |      |     |
| Stability:                           | 0.5%          |      |      |     |      |     | 0.5%          |      |      |     |      |     | 0.5%          |      |      |     |      |     |

## Type RN73 Series

|                                | 2512          |      |      |      |      |      |
|--------------------------------|---------------|------|------|------|------|------|
| Rated Power @ 70°C:            | 0.5W          |      |      |      |      |      |
| Resistance Range (Ohms)   Min: | 24R9          | 24R9 | 24R9 | 4R7  | 24R9 | 4R7  |
|                                | Max:          | 100K | 500K | 100K | 1M0  | 100K |
| Tolerance (%):                 | 0.01          |      | 0.05 |      | 0.1  |      |
| Code Letter:                   | L             |      | A    |      | B    |      |
| Selection Series:              | E24 & E96     |      |      |      |      |      |
| Temp. Coefficient (ppm/°C):    | 5             | 10   | 5    | 10   | 5    | 10   |
| Code Letter:                   | A             | C    | A    | C    | A    | C    |
| Limiting Element Voltage:      | 150V          |      |      |      |      |      |
| Max. Overload Voltage:         | 300V          |      |      |      |      |      |
| Operating Temp. Range:         | -55 to +155°C |      |      |      |      |      |
| Climatic Category (°C):        | 55/125/55     |      |      |      |      |      |
| Insulation Resistance Dry Min: | 1000MΩ        |      |      |      |      |      |
| Stability:                     | 0.5%          |      |      |      |      |      |

### Characteristics - Environmental

|                                              | Requirement                                          |              | Test Method                                                                       |
|----------------------------------------------|------------------------------------------------------|--------------|-----------------------------------------------------------------------------------|
|                                              | Tol. ≤ 0.05%                                         | Tol. > 0.05% |                                                                                   |
| Temperature Coefficient of Resistance (TCR): | As per TCRs specified in value range table on page 1 |              | +25/-55/+25/+125/+25°C                                                            |
| Short Time Overload:                         | ΔR ±0.05%                                            | ΔR ±0.2%     | RCWV* 2.5 or max. overload voltage for 5 seconds                                  |
| Insulation Resistance:                       | ΔR ±0.2% for high power rating                       |              | Apply 100VDC for 1 minute                                                         |
| Endurance:                                   | >1000MΩ                                              |              | 70 ±2°C, max. working voltage for 1000hrs with 1.5hrs "ON" and 0.5hrs "OFF"       |
| Damp Heat with Load:                         | ΔR ±0.05%                                            | ΔR ±0.2%     | 40 ±2°C, 90 - 95% R.H. max. working voltage hrs with 1.5hrs "ON" and 0.5hrs "OFF" |
| Bending Strength:                            | ΔR ±0.05%                                            | ΔR ±0.3%     | Bending amplitude 3mm for 10 seconds                                              |
| Solderability:                               | ΔR ±0.5% for high power rating                       |              | 245 ±5°C for 3 seconds                                                            |
| Resistance to Soldering Heat:                | ΔR ±0.05%                                            | ΔR ±0.2%     | 260 ±5°C for 10 seconds                                                           |
| Dielectric Withstand Voltage:                | By type                                              |              | Max. overload voltage for 1 minute                                                |
| Thermal Shock:                               | ΔR ±0.05%                                            | ΔR ±0.25%    | -55°C to +150°C, 100 cycles                                                       |
| Low Temperature Operation:                   | ΔR ±0.05%                                            | ΔR ±0.2%     | 1 hour, -65°C, followed by 45 minutes of RCWV                                     |
|                                              | ΔR ±0.5% for high power rating                       |              |                                                                                   |

Reference Standards: MIL-STD-202, JIS-C 5201-1

Storage Temperature: 25±3°C; Humidity < 80%RH

### Power Derating Curve



For resistors operated in ambient temperatures above 70°C, power rating must be derated in accordance with this curve.

## Type RN73 Series

### Dimensions



| Part Number    | L           | W           | H           | D           | d           | Weight (g) 1000 pieces |
|----------------|-------------|-------------|-------------|-------------|-------------|------------------------|
| RN73 1E (0402) | 1.00+/-0.05 | 0.50+/-0.05 | 0.30+/-0.05 | 0.20+/-0.10 | 0.20+/-0.10 | 0.54                   |
| RN73 1J (0603) | 1.55+/-0.10 | 0.80+/-0.10 | 0.45+/-0.10 | 0.30+/-0.20 | 0.30+/-0.20 | 1.83                   |
| RN73 2A (0805) | 2.00+/-0.15 | 1.25+/-0.15 | 0.55+/-0.10 | 0.30+/-0.20 | 0.40+/-0.25 | 4.71                   |
| RN73 2B (1206) | 3.05+/-0.15 | 1.55+/-0.15 | 0.55+/-0.10 | 0.42+/-0.20 | 0.35+/-0.25 | 9.02                   |
| RN73 2E (1210) | 3.10+/-0.15 | 2.40+/-0.15 | 0.55+/-0.10 | 0.40+/-0.20 | 0.55+/-0.25 | 10                     |
| RN73 2H (2010) | 4.90+/-0.15 | 2.40+/-0.15 | 0.55+/-0.10 | 0.60+/-0.30 | 0.50+/-0.25 | 23.61                  |
| RN73 3A (2512) | 6.30+/-0.15 | 3.10+/-0.15 | 0.55+/-0.10 | 0.60+/-0.30 | 0.50+/-0.25 | 38.08                  |

### Marking Codes - Case Sizes 0805 to 2512

#### IEC 4 Digit Marking

| Resistance:   | 100Ω | 2.2KΩ | 10KΩ | 49.9KΩ | 100KΩ |
|---------------|------|-------|------|--------|-------|
| Marking Code: | 1000 | 2201  | 1002 | 4992   | 1003  |

### Case Sizes 0603

#### E24 3 Digit Marking - Example: 101=100Ω 102=1KΩ

| E24 | 10 | 11 | 12 | 13 | 15 | 16 | 18 | 20 | 22 | 24 | 27 | 30 |
|-----|----|----|----|----|----|----|----|----|----|----|----|----|
|     | 33 | 36 | 39 | 43 | 47 | 51 | 56 | 62 | 68 | 75 | 82 | 91 |

#### E96 3 Digit Marking - Examples: 14C=13K7Ω, 13C=13K3Ω, 68B=4K99Ω, 68X=49.9Ω



#### 0603 E96 Marking Code Table

| Code       | E96             |                 | Code            | E96             |                 | Code            | E96             |                 | Code             | E96              |                  |
|------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|------------------|------------------|------------------|
| 01         | 100             |                 | 25              | 178             |                 | 49              | 316             |                 | 73               | 562              |                  |
| 02         | 102             |                 | 26              | 182             |                 | 50              | 324             |                 | 74               | 576              |                  |
| 03         | 105             |                 | 27              | 187             |                 | 51              | 332             |                 | 75               | 590              |                  |
| 04         | 107             |                 | 28              | 191             |                 | 52              | 340             |                 | 76               | 604              |                  |
| 05         | 110             |                 | 29              | 196             |                 | 53              | 348             |                 | 77               | 619              |                  |
| 06         | 113             |                 | 30              | 200             |                 | 54              | 357             |                 | 78               | 634              |                  |
| 07         | 115             |                 | 31              | 205             |                 | 55              | 365             |                 | 79               | 649              |                  |
| 08         | 118             |                 | 32              | 210             |                 | 56              | 374             |                 | 80               | 665              |                  |
| 09         | 121             |                 | 33              | 215             |                 | 57              | 383             |                 | 81               | 681              |                  |
| 10         | 124             |                 | 34              | 221             |                 | 58              | 392             |                 | 82               | 698              |                  |
| 11         | 127             |                 | 35              | 226             |                 | 59              | 402             |                 | 83               | 715              |                  |
| 12         | 130             |                 | 36              | 232             |                 | 60              | 412             |                 | 84               | 732              |                  |
| 13         | 133             |                 | 37              | 237             |                 | 61              | 422             |                 | 85               | 750              |                  |
| 14         | 137             |                 | 38              | 243             |                 | 62              | 432             |                 | 86               | 768              |                  |
| 15         | 140             |                 | 39              | 249             |                 | 63              | 442             |                 | 87               | 787              |                  |
| 16         | 143             |                 | 40              | 255             |                 | 64              | 453             |                 | 88               | 806              |                  |
| 17         | 147             |                 | 41              | 261             |                 | 65              | 464             |                 | 89               | 825              |                  |
| 18         | 150             |                 | 42              | 267             |                 | 66              | 475             |                 | 90               | 845              |                  |
| 19         | 154             |                 | 43              | 274             |                 | 67              | 487             |                 | 91               | 866              |                  |
| 20         | 158             |                 | 44              | 280             |                 | 68              | 499             |                 | 92               | 887              |                  |
| 21         | 162             |                 | 45              | 287             |                 | 69              | 511             |                 | 93               | 909              |                  |
| 22         | 165             |                 | 46              | 294             |                 | 70              | 523             |                 | 94               | 931              |                  |
| 23         | 169             |                 | 47              | 301             |                 | 71              | 536             |                 | 95               | 953              |                  |
| 24         | 174             |                 | 48              | 309             |                 | 72              | 549             |                 | 96               | 976              |                  |
| Code       | A               | B               | C               | D               | E               | F               | G               | H               | X                | Y                | Z                |
| Multiplier | 10 <sup>0</sup> | 10 <sup>1</sup> | 10 <sup>2</sup> | 10 <sup>3</sup> | 10 <sup>4</sup> | 10 <sup>5</sup> | 10 <sup>6</sup> | 10 <sup>7</sup> | 10 <sup>-1</sup> | 10 <sup>-2</sup> | 10 <sup>-3</sup> |

## Type RN73 Series

### Recommend Land Pattern



| Type           | A   | B    | C         |
|----------------|-----|------|-----------|
| RN73 1E (0402) | 0.5 | 0.5  | 0.60 ±0.2 |
| RN73 1J (0603) | 0.8 | 1.0  | 0.90 ±0.2 |
| RN73 2A (0805) | 1.0 | 1.0  | 1.35 ±0.2 |
| RN73 2B (1206) | 2.0 | 1.15 | 1.70 ±0.2 |
| RN73 2E (1210) | 2.0 | 1.15 | 2.50 ±0.2 |
| RN73 2H (2010) | 3.6 | 1.4  | 2.50 ±0.2 |
| RN73 3A (2512) | 4.9 | 1.6  | 3.10 ±0.2 |

### Packaging Quantity & Reel Specifications



| Type           | øA         | øB        | øC         | W         | T         | Paper Tape (EA)    | Embossed Plastic Tape (EA) |
|----------------|------------|-----------|------------|-----------|-----------|--------------------|----------------------------|
| RN73 1E (0402) | 178.0 ±1.0 | 60.0 +1.0 | 13.5 ± 0.7 | 9.5 ±1.0  | 11.5 ±1.0 | *250 / 1000 / 5000 | -                          |
| RN73 1J (0603) | 178.0 ±1.0 | 60.0 +1.0 | 13.5 ± 0.7 | 9.5 ±1.0  | 11.5 ±1.0 | *250 / 1000 / 5000 | -                          |
| RN73 2A (0805) | 178.0 ±1.0 | 60.0 +1.0 | 13.5 ± 0.7 | 9.5 ±1.0  | 11.5 ±1.0 | *250 / 1000 / 5000 | -                          |
| RN73 2B (1206) | 178.0 ±1.0 | 60.0 +1.0 | 13.5 ± 0.7 | 9.5 ±1.0  | 11.5 ±1.0 | *250 / 1000 / 5000 | -                          |
| RN73 2E (1210) | 178.0 ±1.0 | 60.0 +1.0 | 13.5 ± 0.7 | 9.5 ±1.0  | 11.5 ±1.0 | *250 / 1000 / 5000 | -                          |
| RN73 2H (2010) | 178.0 ±1.0 | 60.0 +1.0 | 13.5 ± 0.7 | 13.5 ±1.0 | 15.5 ±1.0 | -                  | 4000                       |
| RN73 3A (2512) | 178.0 ±1.0 | 60.0 +1.0 | 13.5 ± 0.7 | 13.5 ±1.0 | 15.5 ±1.0 | -                  | 4000                       |

\* 250 piece packs supplied in sealed bags of cut tape length

## Type RN73 Series

### Paper Tape Specification



| Type           | A          | B          | W          | E          | F         | P <sub>0</sub> | P <sub>1</sub> | P <sub>2</sub> | φD <sub>0</sub> | T          |
|----------------|------------|------------|------------|------------|-----------|----------------|----------------|----------------|-----------------|------------|
| RN73 1E (0402) | 0.70 ±0.05 | 1.16 ±0.05 | 8.00 ±0.10 | 1.75 ±0.05 | 3.5 ±0.05 | 4.00 ±0.10     | 2.00 ±0.05     | 2.00 ±0.05     | 1.55 ±0.05      | 0.40 ±0.03 |
| RN73 1J (0603) | 1.10 ±0.05 | 1.90 ±0.05 | 8.00 ±0.10 | 1.75 ±0.05 | 3.5 ±0.05 | 4.00 ±0.10     | 4.00 ±0.10     | 2.00 ±0.05     | 1.55 ±0.05      | 0.60 ±0.03 |
| RN73 2A (0805) | 1.60 ±0.05 | 2.37 ±0.05 | 8.00 ±0.10 | 1.75 ±0.05 | 3.5 ±0.05 | 4.00 ±0.10     | 4.00 ±0.10     | 2.00 ±0.05     | 1.55 ±0.05      | 0.75 ±0.05 |
| RN73 2B (1206) | 2.00 ±0.05 | 3.55 ±0.05 | 8.00 ±0.10 | 1.75 ±0.05 | 3.5 ±0.05 | 4.00 ±0.10     | 4.00 ±0.10     | 2.00 ±0.05     | 1.55 ±0.05      | 0.75 ±0.05 |
| RN73 2E (1210) | 2.75 ±0.05 | 3.40 ±0.05 | 8.00 ±0.10 | 1.75 ±0.05 | 3.5 ±0.05 | 4.00 ±0.05     | 4.00 ±0.10     | 2.00 ±0.05     | 1.60 ±0.10      | 0.75 ±0.05 |

### Embossed Plastic Tape Specifications



| Type           | A          | B          | W          | E          | F         | P <sub>0</sub> | P <sub>1</sub> | P <sub>2</sub> | φD <sub>0</sub> | T          |
|----------------|------------|------------|------------|------------|-----------|----------------|----------------|----------------|-----------------|------------|
| RN73 2H (2010) | 2.85 ±0.10 | 5.45 ±0.10 | 12.0 ±0.10 | 1.75 ±0.10 | 5.5 ±0.05 | 4.00 ±0.05     | 4.00 ±0.10     | 2.00 ±0.05     | 1.50 +0.10      | 1.00 ±0.20 |
| RN73 3A (2512) | 3.40 ±0.10 | 6.65 ±0.10 | 12.0 ±0.10 | 1.75 ±0.10 | 5.5 ±0.05 | 4.00 ±0.05     | 4.00 ±0.10     | 2.00 ±0.05     | 1.50 +0.10      | 1.00 ±0.20 |

### How to Order

| RN73                                             | C                                                            | 2A                                                                                                                        | 100K                                                      | B                                                                    | TDF                                                                                                                                                                                      |
|--------------------------------------------------|--------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------|----------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Common Part                                      | Temp. Coefficient                                            | Package Size                                                                                                              | Resistor Value                                            | Tolerance                                                            | Packaging                                                                                                                                                                                |
| RN73 - High precision resistors (RoHS compliant) | A - ±5ppm/°C<br>*C - ±10ppm/°C<br><br>* Preferred stock item | 1E - 0402<br>* 1J - 0603<br>* 2A - 0805<br>2B - 1206<br>2E - 1210<br>2H - 2010<br>3A - 2512<br><br>* Preferred stock item | 100R (100 ohms)<br>1K0 (1000 ohms)<br>100K (100,000 ohms) | A - ±0.05%<br>*B - ±0.1%<br>L - ±0.01%<br><br>* Preferred stock item | TG - 250 Cut tape length (1E, 1J, 2A, 2B)<br>TDF - 1000 REEL (1E, 1J, 2A, 2B)<br>TD - 5000 REEL (1E, 1J, 2A, 2B, 2E)<br>TDG - 250 REEL (1E, 1J, 2A only)<br>TE - 4000 REEL (2H, 3A only) |

TE Connectivity, TE connectivity (logo) and TE (logo) are trademarks.

Other logos, product and Company names mentioned herein may be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information in this datasheet, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this datasheet are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9