

## Protect It! 7-Outlet Surge Protector, 7-ft. Cord, 2520 Joules, Fax/Modem Protection, RJ11

MODEL NUMBER: SUPER7TEL



### Highlights

- 7 outlets / 7-ft. cord
- 2520 joule rating
- Modem/fax surge protection
- \$75,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)

### Package Includes

- SUPER7TEL Surge Suppressor
- 6-ft. telephone cord
- Instruction manual with warranty information

### Description

Tripp Lite's SUPER7TEL surge suppressor offers complete AC and phone line surge suppression for comprehensive protection of workstations, desktop PCs, telecom systems and other sensitive electronics. Heavy grade AC surge suppression shields connected equipment from damage and performance problems due to transient surges. Set of RJ11 telephone line suppression jacks protect dialup and DSL modem lines, fax machines, cordless phones and more. SUPER7TEL offers 7 total outlets, 7 foot cord with space-saving angled plug and diagnostic LEDs to warn of wiring problems and suppressor damage. Heavy grade AC suppression rated at 2520 joules shields equipment from surges and line noise. Attractive light grey suppressor housing with keyhole mounting tabs and 3 designated transformer plug outlets offers convenient protection of desktop computer equipment and accessories. \$75,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only).

### Features

- 2520 joules AC surge suppression shields equipment from the strongest surges and line noise
- 7 AC outlets with room for 3 transformer plugs without blocking outlets covers computers and all peripherals
- Phone line surge suppression protects both dialup and DSL modems, plus fax machines, cordless phones and more (pair of RJ11 jacks, 2 wire, 1 line, includes 6 ft phone cable)
- 7 foot AC line cable with space-saving angle input plug conveniently reaches distant outlets
- Built-in power switch and 15 amp circuit breaker offers power control and overload protection over all outlets
- Fail-safe thermal fusing protects against fire and other damage in the event of an extreme, extended overvoltage or surge condition
- Diagnostic LEDs confirm outlet grounding and surge suppression status
- UL1449 3rd Edition Rated (330V all modes), UL1363 (Power Tap), UL497A (Communications), Meets FCC part 68 rules, cUL (Canada)
- Exceeds IEEE 587 category A & B surge suppression specifications
- \$75,000 Ultimate Lifetime connected equipment insurance (U.S., Canada, and Puerto Rico only)
- Automatic shutoff cuts power to outlets when the protection circuit has been compromised

## Specifications



| <b>OUTPUT</b>                                |  |
|--|--|
| Frequency Compatibility                      | 50 / 60 Hz   |
| Output Receptacles                           | (7) 5-15R  |
| Output (Watts)                               | 1800   |
| Circuit Breaker (amps)                       | 15   |
| Transformer Accommodation                    | Supports 3 large transformer plug accessories without covering remaining outlets, accepts up to 5 transformers total |
| Outlet Orientation                           | Single row of 5, plus 2 side mounted outlets   |
| Right-Angle Outlets                          | No   |
| <b>INPUT</b>                                 |  |
| Nominal Input Voltage(s) Supported           | 120V AC  |
| Recommended Electrical Service               | 120V (110-125V)  |
| Input Connection Type                        | NEMA 5-15P   |
| Input Plug Features                          | Space-saving right angle input plug  |
| Input Cord Length (ft.)                      | 7  |
| Input Cord Length (m)                        | 2.1  |
| Input Cord Gauge Type                        | 14 gauge, SJT  |
| Voltage Compatibility (VAC)                  | 120  |
| Maximum Surge Amps                           | 156000   |
| Right-Angle Plug                             | Yes  |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |  |
| Switches                                     | Two position on/off power switch   |
| Diagnostic LED Details                       | Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status                            |
| <b>SURGE / NOISE SUPPRESSION</b>             |  |
| AC Suppression Joule Rating                  | 2520   |
| AC Suppression Response Time                 | < 1 ns   |
| Protection Modes                             | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression                                   |
| Clamping Voltage (RMS)                       | 150  |
| UL1449 Let Through Rating                    | 330V - UL Verified   |
| EMI / RFI Filtering                          | Up to 20 dB  |
| <b>DATALINE SURGE SUPPRESSION</b>            |  |
| Telephone/DSL Protection                     | Yes  |



|  |   |
|--|---|
| Telephone/DSL Protection Details                     | 1 line  |
| Cable (Coax) Protection                              | No  |
| Network (Ethernet) Protection                        | No  |
| <b>PHYSICAL</b>                                      |   |
| Shipping Dimensions (hwd / in.)                      | 15.25 x 6.25 x 3.5  |
| Shipping Dimensions (hwd / cm)                       | 38.7 x 15.9 x 8.9   |
| Shipping Weight (lbs.)                               | 2.4   |
| Shipping Weight (kg)                                 | 1.1   |
| Unit Dimensions (hwd / in.)                          | 10.25 x 2.75 x 1.5  |
| Unit Dimensions (hwd / cm)                           | 26 x 7 x 3.8  |
| Unit Weight (lbs.)                                   | 2.2   |
| Unit Weight (kg)                                     | 1.0   |
| Material of Construction                             | Plastic   |
| Integrated Keyhole Mounting Tabs                     | Keyhole mounting tabs enable wall mounting                          |
| Housing Color  | Light Gray  |
| Receptacle Color                                     | Light Gray  |
| Color (AC Line Cord)                                 | Light Gray  |
| Outlets Measurement (Center to Center)               | Between Standard Outlets = 29mm; Between transformer outlets = 48mm |
| Keyhole Slot Mounting Measurement (Center to Center) | Distance between slots = 78mm; Distance between slot height = 24mm  |
| <b>CERTIFICATIONS</b>                                |   |
| UL1449 3rd Edition (AC Suppression)                  | UL1449 3rd Edition  |
| UL1363 (Power Tap)                                   | UL1363  |
| UL497A (Communications)                              | UL497A  |
| FCC Part 68 (Communications)                         | FCC Part 68   |
| cUL / CSA (Canada)                                   | cUL   |
| Industry Canada (Communications)                     | Industry Canada   |
| Approvals  | Exceeds IEEE 587 category A&B specifications                        |
| <b>WARRANTY</b>                                      |   |
| Product Warranty Period (Worldwide)                  | Lifetime limited warranty   |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

|   |  |
|---|--|
| Connected Equipment Insurance<br>(U.S., Canada & Puerto Rico) | \$75,000 <a href="#">Ultimate Lifetime Insurance</a> |
|---|--|

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>

## Данный компонент на территории Российской Федерации

### Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9