

		DESIGNED FOR USE WITH RD-316/U FLEXIBLE CABLE OR EQUIVALENT		REVISIONS																																																																				
		CABLE ENTRY DIAMETER MINIMUM		REV	DESCRIPTION	DATE	APPROVED																																																																	
		FERRULE .135 HOUSING .067 CONTACT .025		01	RELEASED	03/21/95	AD																																																																	
COPY IN PUERTO RICO DESIGN CONTROL REQUIRED																																																																								
<table><tr><th>ELECTRICAL</th><th>MECHANICAL</th><th>ENVIRONMENTAL</th></tr><tr><td>Nominal Impedance (Ohms) 50</td><td>Interface Dimensions MIL-STD-348A, Fig. 310.1</td><td>Temperature Rating -65°C to +105°C</td></tr><tr><td>Frequency Range (GHz) DC to MAX</td><td>Recommended Mating</td><td>Vibration MIL-STD-202, Method 204, Condition D</td></tr><tr><td>Operating Frequency of Cable per MIL-C-17</td><td>Torque 7-10 In-Lbs</td><td>Shock MIL-STD-202, Method 213, Condition I</td></tr><tr><td>Volt Rating (VRMS MAX) @ Sea Level 250</td><td>Mating Characteristics:</td><td>Thermal Shock MIL-STD-202, Method 107, Condition B, Except High Temp +85°C</td></tr><tr><td>VSWR 1.15 + .03f(GHz)</td><td>Insertion (MAX Lbs) N/A</td><td>Moisture Resistance MIL-STD-202, Method 106</td></tr><tr><td>Insertion Loss (dB MAX) .15 √f(GHz)</td><td>Withdrawal (MIN Oz) N/A</td><td>Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray</td></tr><tr><td>RF Leakage (dB MIN) -(60-fGHz)</td><td>Force to Engage and Disengage (In-Lbs MAX) 2.0</td><td></td></tr><tr><td>Corona, 70,000 Ft (VRMS MIN) 190</td><td>Center Contact Captivation</td><td></td></tr><tr><td>Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 750</td><td>Axial (Lbs) 6.0</td><td></td></tr><tr><td>Contact Resistance (Milliohms MAX)</td><td>Radial (In-Oz) 4.0</td><td></td></tr><tr><td>Center Contact 4.0</td><td>Cable Retention</td><td></td></tr><tr><td>Outer Contact 2.0</td><td>Axial Force (Lbs MIN) 25</td><td></td></tr><tr><td>Cable to Housing 0.5</td><td>Torque (In-Oz) N/A</td><td></td></tr><tr><td>RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 500</td><td>Weight (Grams) 4.6</td><td></td></tr><tr><td>I.R.(Megohms MIN) 10,000</td><td></td><td></td></tr></table>		ELECTRICAL	MECHANICAL	ENVIRONMENTAL	Nominal Impedance (Ohms) 50	Interface Dimensions MIL-STD-348A, Fig. 310.1	Temperature Rating -65°C to +105°C	Frequency Range (GHz) DC to MAX	Recommended Mating	Vibration MIL-STD-202, Method 204, Condition D	Operating Frequency of Cable per MIL-C-17	Torque 7-10 In-Lbs	Shock MIL-STD-202, Method 213, Condition I	Volt Rating (VRMS MAX) @ Sea Level 250	Mating Characteristics:	Thermal Shock MIL-STD-202, Method 107, Condition B, Except High Temp +85°C	VSWR 1.15 + .03f(GHz)	Insertion (MAX Lbs) N/A	Moisture Resistance MIL-STD-202, Method 106	Insertion Loss (dB MAX) .15 √f(GHz)	Withdrawal (MIN Oz) N/A	Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray	RF Leakage (dB MIN) -(60-fGHz)	Force to Engage and Disengage (In-Lbs MAX) 2.0		Corona, 70,000 Ft (VRMS MIN) 190	Center Contact Captivation		Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 750	Axial (Lbs) 6.0		Contact Resistance (Milliohms MAX)	Radial (In-Oz) 4.0		Center Contact 4.0	Cable Retention		Outer Contact 2.0	Axial Force (Lbs MIN) 25		Cable to Housing 0.5	Torque (In-Oz) N/A		RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 500	Weight (Grams) 4.6		I.R.(Megohms MIN) 10,000			<table><tr><td>HOUSING COUPLING NUT CAP</td><td>STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303</td><td>PASSIVATE PER QQ-P-35</td></tr><tr><td>DIELECTRIC</td><td>TFE FLUOROCARBON PER ASTM-D-1457</td><td>N/A</td></tr><tr><td>CENTER CONTACT</td><td>BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197 ALLOY C17300, CONDITION H</td><td>GOLD PLATE PER MIL-G-45204</td></tr><tr><td>RETAINING RING</td><td>BERYLLIUM COPPER PER ASTM-B-194, ALLOY C17200, CONDITION H</td><td>N/A</td></tr><tr><td>GASKET</td><td>SILICONE RUBBER PER ZZ-R-765</td><td>N/A</td></tr><tr><td>SHRINK TUBING</td><td>HEAT SHRINKABLE POLYOLEFIN COMPOUND MIL-I-23053/4</td><td>N/A</td></tr><tr><td>FERRULE</td><td>COPPER OR BRASS ALLOY ROCKWELL F65 MAXIMUM</td><td>TIN-LEAD PLATE PER MIL-P-81728 OVER COPPER PLATE PER MIL-C-14550</td></tr></table>		HOUSING COUPLING NUT CAP	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER QQ-P-35	DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A	CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197 ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204	RETAINING RING	BERYLLIUM COPPER PER ASTM-B-194, ALLOY C17200, CONDITION H	N/A	GASKET	SILICONE RUBBER PER ZZ-R-765	N/A	SHRINK TUBING	HEAT SHRINKABLE POLYOLEFIN COMPOUND MIL-I-23053/4	N/A	FERRULE	COPPER OR BRASS ALLOY ROCKWELL F65 MAXIMUM	TIN-LEAD PLATE PER MIL-P-81728 OVER COPPER PLATE PER MIL-C-14550
ELECTRICAL	MECHANICAL	ENVIRONMENTAL																																																																						
Nominal Impedance (Ohms) 50	Interface Dimensions MIL-STD-348A, Fig. 310.1	Temperature Rating -65°C to +105°C																																																																						
Frequency Range (GHz) DC to MAX	Recommended Mating	Vibration MIL-STD-202, Method 204, Condition D																																																																						
Operating Frequency of Cable per MIL-C-17	Torque 7-10 In-Lbs	Shock MIL-STD-202, Method 213, Condition I																																																																						
Volt Rating (VRMS MAX) @ Sea Level 250	Mating Characteristics:	Thermal Shock MIL-STD-202, Method 107, Condition B, Except High Temp +85°C																																																																						
VSWR 1.15 + .03f(GHz)	Insertion (MAX Lbs) N/A	Moisture Resistance MIL-STD-202, Method 106																																																																						
Insertion Loss (dB MAX) .15 √f(GHz)	Withdrawal (MIN Oz) N/A	Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray																																																																						
RF Leakage (dB MIN) -(60-fGHz)	Force to Engage and Disengage (In-Lbs MAX) 2.0																																																																							
Corona, 70,000 Ft (VRMS MIN) 190	Center Contact Captivation																																																																							
Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 750	Axial (Lbs) 6.0																																																																							
Contact Resistance (Milliohms MAX)	Radial (In-Oz) 4.0																																																																							
Center Contact 4.0	Cable Retention																																																																							
Outer Contact 2.0	Axial Force (Lbs MIN) 25																																																																							
Cable to Housing 0.5	Torque (In-Oz) N/A																																																																							
RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 500	Weight (Grams) 4.6																																																																							
I.R.(Megohms MIN) 10,000																																																																								
HOUSING COUPLING NUT CAP	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER QQ-P-35																																																																						
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A																																																																						
CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197 ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204																																																																						
RETAINING RING	BERYLLIUM COPPER PER ASTM-B-194, ALLOY C17200, CONDITION H	N/A																																																																						
GASKET	SILICONE RUBBER PER ZZ-R-765	N/A																																																																						
SHRINK TUBING	HEAT SHRINKABLE POLYOLEFIN COMPOUND MIL-I-23053/4	N/A																																																																						
FERRULE	COPPER OR BRASS ALLOY ROCKWELL F65 MAXIMUM	TIN-LEAD PLATE PER MIL-P-81728 OVER COPPER PLATE PER MIL-C-14550																																																																						
<table><tr><th>COMPONENT</th><th>MATERIAL</th><th>FINISH</th></tr><tr><td>UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES</td><td colspan="2">DRAWN BY AD DATE 03/21/95</td></tr><tr><td>FRAC. DEC. ANGLES</td><td colspan="2">CHECKED BY</td></tr><tr><td>± 1/64 ±.005 ± 1°</td><td colspan="2">APPD BY</td></tr><tr><td rowspan="3">These drawings and specifications are the property of M/A COM Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.</td><td>USE ASSY PROCEDURE</td><td>TITLE OSM RIGHT ANGLE CABLE PLUG CRIMP ATTACHMENT</td></tr><tr><td>408-04982 NO. A.P. (20-490)</td><td>AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599</td></tr><tr><td>SIZE B</td><td>CODE IDENT NO. 26805</td><td>1250-1295-02</td></tr><tr><td>SCALE 2 : 1</td><td colspan="2">REV 01</td></tr><tr><td colspan="2">SHEET 1 OF 1</td><td></td></tr></table>		COMPONENT	MATERIAL	FINISH	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	DRAWN BY AD DATE 03/21/95		FRAC. DEC. ANGLES	CHECKED BY		± 1/64 ±.005 ± 1°	APPD BY		These drawings and specifications are the property of M/A COM Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.	USE ASSY PROCEDURE	TITLE OSM RIGHT ANGLE CABLE PLUG CRIMP ATTACHMENT	408-04982 NO. A.P. (20-490)	AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599	SIZE B	CODE IDENT NO. 26805	1250-1295-02	SCALE 2 : 1	REV 01		SHEET 1 OF 1																																															
COMPONENT	MATERIAL	FINISH																																																																						
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	DRAWN BY AD DATE 03/21/95																																																																							
FRAC. DEC. ANGLES	CHECKED BY																																																																							
± 1/64 ±.005 ± 1°	APPD BY																																																																							
These drawings and specifications are the property of M/A COM Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.	USE ASSY PROCEDURE	TITLE OSM RIGHT ANGLE CABLE PLUG CRIMP ATTACHMENT																																																																						
	408-04982 NO. A.P. (20-490)	AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599																																																																						
	SIZE B	CODE IDENT NO. 26805	1250-1295-02																																																																					
SCALE 2 : 1	REV 01																																																																							
SHEET 1 OF 1																																																																								

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9