

PART NAME		NON-METALLIC ENCLOSURE (STYLE B)										PART No.		NBB-10247 & NBB-10267 & NBB-15247 & NBB-22247																					
MATERIAL:												FINISH:												INTERNAL HINGED PANEL MOUNTING BRACKETS, STAINLESS STEEL LOCKING HASP, AIR AND MOISTURE VENTS AND GALVANIZED STEEL INTERNAL PANEL ARE NOT INCLUDED, BUT CAN BE PURCHASED SEPARATELY.											
UL LISTED INDOOR VERSION												BODY _____ LIGHT GRAY																							
SOLID BODY & COVER _____ ABS/PC BLENDED PLASTIC												COVER _____ LIGHT GRAY OR CLEAR																							
UL94-5VB FLAMMABILITY RATING												LATCHES & HINGES _____ NON-METALLIC																							
CLEAR COVER _____ POLYCARBONATE PLASTIC												WALL MOUNTING BRACKETS _____ STAINLESS STEEL																							
UL94V-0 FLAMMABILITY RATING																																			
UV STABILIZED																																			
UL LISTED OUTDOOR VERSION																																			
SOLID BODY & COVER _____ PBT/PC BLENDED PLASTIC																																			
UL94-5VA FLAMMABILITY RATING																																			
UV STABILIZED																																			
ABS VERSION																																			
SOLID BODY & COVER _____ ABS																																			
UL94-HB FLAMMABILITY RATING																																			
ALL VERSIONS																																			
GASKET _____ MODIFIED POLYURETHANE																																			
COVER INCLUDES GRAY POLYURETHANE GASKET.																																			
INDUSTRY STANDARDS:																																			
UL LISTED INDOOR VERSION																																			
UL508 TYPE 1, 2, 3, 3R, 4, 4X INDOOR, 12 & 13																																			
NEMA TYPE 1, 2, 3, 3R, 4, 4X, 12 & 13																																			
IEC529-IP65																																			
UL LISTED OUTDOOR VERSION																																			
UL508 TYPE 1, 2, 3, 3R, 4, 4X, 12 & 13																																			
NEMA TYPE 1, 2, 3, 3R, 4, 4X, 12 & 13																																			
IEC529-IP65																																			
ABS VERSION																																			
NEMA TYPE 1, 2, 3, 3R, 4, 4X, 12 & 13																																			
IEC529-IP65																																			

0.575 [15] DIA. BOSS WITH M5 x 0.8mm THREADED BRASS INSERT (4) PLACES (FAR SIDE)

0.476 [12] DIA. BOSS WITH 0.166 [4] DIA. HOLE x 0.325 [8] DEEP (36) PLACES BOSSSES ACCEPT M5 METRIC OR #10 STD. SHEET METAL SCREWS x 0.250 [6] LG. (NOT SUPPLIED)

0.725 [18] DIA. BOSS WITH M5 x 0.8mm THREADED BRASS INSERT (4) PLACES

VIEW LESS COVER

NOTE: UNIT COMES COMPLETE WITH (4) WALL MOUNTING BRKTS. & (4) M5 x 10mm LG. TRUSS HD. MACHINE SCREWS (NOT SHOWN)

DIMENSIONS = INCHES [MILLIMETERS]

NOTE: ALL DIMENSIONS HAVE ±0.039 [±1] TOLERANCE UNLESS OTHERWISE SPECIFIED

UL LISTED INDOOR VERSION		UL LISTED OUTDOOR VERSION		ABS VERSION		DIMENSIONS																			
PART NO.		PART NO.		PART NO.																					
SOLID COVER	CLEAR COVER	SOLID COVER	CLEAR COVER	SOLID COVER	SOLID COVER	A	B	C	D	E	F	G	H	J	K	L	M	N	P	R	S	T	U	V	W
NBB-10247	NBB-10267	NBB-15247		NBB-22247		11.727 [298]	10.894 [277]	10.424 [265]	9.335 [237]	8.969 [228]	6.902 [175]	15.680 [398]	14.877 [378]	14.167 [360]	13.265 [337]	12.801 [325]	10.828 [275]	5.110 [130]	1.185 [30]	15.105 [384]	15.035 [382]	11.147 [283]	11.090 [282]	0.986 [25]	0.986 [25]

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9