

R591 RADIALL coaxial subminiature switches have a typical operating life exceeding 25 million cycles. Excellent RF & repeatability characteristics along with a guaranteed life of 10 million cycles make these switches ideal for Automated Test Equipment (ATE) and other measurement applications. These miniature switches are also an excellent choice for Mil/Aero applications due to their small size, light weight, as well as outstanding shock and vibration handling capabilities.

**PART NUMBER SELECTION**

R 591 . . . . .

Updated revision



(4) : The "QLF" trademark (quick lock formula®) standard applies to QMA and QN series and guarantees the full intermateability between suppliers using this trademark. Using QLF certified connectors also guarantees the specified level of RF performances.



(5) : Connector SMA 2.9 is equivalent to "K connector®", registered trademark of Anritsu.

In the continual goal to improve our products, we reserve the right to make any modification judged necessary.

**GENERAL SPECIFICATIONS**

| Operating mode   |            | Normally open  |                     | Latching              |                     |
|--|------------|--|---------------------|-----------------------|---------------------|
| <b>Nominal operating voltage</b><br>(across operating temperature)                     | Vdc        | <b>12</b> (10.2 / 13)  | <b>28</b> (21 / 30) | <b>12</b> (10.2 / 13) | <b>28</b> (21 / 30) |
| <b>Coil resistance (+/-10%)</b>  | Ohms       | 48   | 250                 | 60                    | 285                 |
| <b>Operating current at 23°C</b>   | mA         | 250  | 110                 | 200                   | 98                  |
| <b>Average power</b>   |            | See Power Rating Chart on general catalog  |                     |                       |                     |
| <b>TTL input</b>   | High Level | 2.2 to 5.5 Volts   |                     |                       |                     |
|  | Low Level  | 0 to 0.8 Volts   |                     |                       |                     |
| <b>Switching time (max)</b>  | ms         | 10   |                     |                       |                     |
| <b>Life</b>  |            | 10 million cycles (SMA, QMA) / 2 million cycles (SMA 2.9)  |                     |                       |                     |
| <b>Connectors</b>  |            | SMA / QMA / SMA 2.9  |                     |                       |                     |
| <b>Actuator terminals</b>  |            | <b>Solder Pins</b> : double row connector for wrapping, soldering (250°C max / 30 sec), or connecting to 2.54 mm pitch female connector. <b>9 pin micro-D</b> receptacle M83513/07-A according to MIL-C-85513. |                     |                       |                     |
| <b>Operating temperature range</b>   | °C         | -40 to +85   |                     |                       |                     |
| <b>Storage temperature range</b>   | °C         | -55 to +85   |                     |                       |                     |
| <b>Sine vibration</b><br>(According to MIL STD 202, Method 204D, Cond. D)              |            | 10-2000 Hz, 20g  | operating           |                       |                     |
| <b>Random vibration</b><br>(According to MIL STD 202, Method 214A, Profile I, Cond. F) |            | 50-2000 Hz, 20.71grms  | operating           |                       |                     |
| <b>Shock</b><br>(According to MIL STD 202, Method 213B, Cond. C)                       |            | 100g / 6 ms, ½ sine  | operating           |                       |                     |

**RF PERFORMANCES**

| Connectors | Frequency Range GHz |           | V.S.W.R. (max) | Insertion Loss (max) dB | Isolation (min) dB | Impedance Ohms |
|------------|---------------------|-----------|----------------|-------------------------|--------------------|----------------|
| SMA / QMA  | DC – 6              | DC – 3    | 1.20           | 0.20                    | 80                 | 50             |
|            |                     | 3 – 6     | 1.30           | 0.30                    | 70                 |                |
| SMA        | DC – 26.5           | DC – 3    | 1.20           | 0.20                    | 80                 | 50             |
|            |                     | 3 – 8     | 1.30           | 0.30                    | 70                 |                |
|            |                     | 8 – 12.4  | 1.40           | 0.40                    | 60                 |                |
|            |                     | 12.4 – 18 | 1.50           | 0.50                    | 60                 |                |
| SMA2.9     | DC – 40             | 18 – 26.5 | 1.60           | 0.60                    | 55                 | 50             |
|            |                     | DC – 3    | 1.20           | 0.20                    | 80                 |                |
|            |                     | 3 – 8     | 1.30           | 0.30                    | 70                 |                |
|            |                     | 8 – 12.4  | 1.40           | 0.40                    | 60                 |                |
|            |                     | 12.4 – 18 | 1.50           | 0.50                    | 60                 |                |
|            |                     | 18 – 26.5 | 1.70           | 0.70                    | 55                 |                |
|            |                     | 26.5 – 40 | 2.20           | 1.10                    | 45                 |                |

In the continual goal to improve our products, we reserve the right to make any modification judged necessary.

**TYPICAL RF PERFORMANCES**

**TYPICAL OUTLINE DRAWING (1)**

| Connectors         | SMA        | SMA 2.9  | QMA         |
|--------------------|------------|----------|-------------|
| A max (mm/ inches) | 7.4/ 0.291 | 6.5/0.26 | 10.8/ 0.425 |



(1) : For SP4T, ways 3 and 6 not connected

all dimensions are in mm/ inches

In the continual goal to improve our products, we reserve the right to make any modification judged necessary.

R591 series electrical schematics



In the continual goal to improve our products, we reserve the right to make any modification judged necessary.

R591 series electrical schematics

LATCHING GLOBAL RESET WITH POSITIVE COMMON  
R591 -2- -1-



LATCHING GLOBAL RESET WITH SUPPRESSION DIODES  
R591 -2- -3-



LATCHING GLOBAL RESET WITH POSITIVE COMMON AND SUPPRESSION DIODES  
R591 -2- -4-




LATCHING SEPARATED RESET WITHOUT OPTION  
R591 -6- -0-



LATCHING SEPARATED RESET WITH POSITIVE COMMON  
R591 -6- -1-




LATCHING SEPARATED RESET WITH SUPPRESSION DIODES  
R591 -6- -3-



In the continual goal to improve our products, we reserve the right to make any modification judged necessary.

R591 series electrical schematics



Pin identification

Solder pins (top view)\*



9 pin Micro-D (top view )



- NC : not connected
- For SP4T, ways 3 and 6 not connected
- Pin R = reset of all paths

\* : compatible with 2.54 mm pitch double row 16 contact femelle connector

| Type                         |                 | PIN        |     |    |    |    |    |    |    |        |        |        |        |        |        |        |
|------------------------------|-----------------|------------|-----|----|----|----|----|----|----|--------|--------|--------|--------|--------|--------|--------|
|                              |                 | C          | V   | 1  | 2  | 3  | 4  | 5  | 6  | R      | R1     | R2     | R3     | R4     | R5     | R6     |
| Normally open                | negative common | -C         | NC  | +1 | +2 | +3 | +4 | +5 | +6 | NC     | NC     | NC     | NC     | NC     | NC     | NC     |
|                              | positive common | +C         | NC  | -1 | -2 | -3 | -4 | -5 | -6 | NC     | NC     | NC     | NC     | NC     | NC     | NC     |
| Latching                     | negative common | -C         | NC  | +1 | +2 | +3 | +4 | +5 | +6 | +reset | NC     | NC     | NC     | NC     | NC     | NC     |
| global reset                 | positive common | +C         | NC  | -1 | -2 | -3 | -4 | -5 | -6 | -reset | NC     | NC     | NC     | NC     | NC     | NC     |
| Latching                     | negative common | -C         | NC  | +1 | +2 | +3 | +4 | +5 | +6 | NC     | +res.1 | +res.2 | +res.3 | +res.4 | +res.5 | +res.6 |
| individual reset             | positive common | +C         | NC  | -1 | -2 | -3 | -4 | -5 | -6 | NC     | -res.1 | -res.2 | -res.3 | -res.4 | -res.5 | -res.6 |
| Normally open with TTL drive |                 | Gnd or RTN | Vcc | E1 | E2 | E3 | E4 | E5 | E6 | NC     | NC     | NC     | NC     | NC     | NC     | NC     |

In the continual goal to improve our products, we reserve the right to make any modification judged necessary.

## Данный компонент на территории Российской Федерации

### Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9