


# 3M™ MetPak™ 2-FB Socket

2 mm 5-Row, Right Angle, Solder or Press-Fit Tail, Guide Fingers

MP2 Series



- End-to-end stackable
- Offset dual-beam contact minimizes insertion force
- Molded guide fingers provide integrated alignment
- Alignment wafer for true position
- Mates with MP2-P inverse headers and elevated inverse headers, MP2-PXXXE, for extended card applications
- Protective Push-Cap on Press-Fit Only
- Meets IEC 61076-4-104 Futurebus+® global standard
- See the Regulatory Information Appendix (RIA) in the “RoHS compliance” section of [www.3Mconnector.com](http://www.3Mconnector.com) for compliance information (RIA E1 & C1 apply)

Date Modified: May 13, 2010

TS-1117-B  
Sheet 1 of 4

## Physical

### Insulation:

Material: High Temp LCP  
Flammability: UL 94V-0  
Color: Beige

### Contact:

Material: Copper Alloy

### Plating:

Underplating: 50  $\mu$ " [1.27  $\mu$ m] Nickel  
Wiping Area: See Ordering Information  
Solder Tails: See Ordering Information

## Electrical

**Current Rating:** Signal: 1.5 A – All contacts simultaneously

**Insulation Resistance:** 10<sup>3</sup> M $\Omega$

**Withstanding Voltage:** 1000 V<sub>AC</sub>

## Environmental

**Temperature Rating:** -55°C to +125°C

**Process Temperature Rating:** 260°C (Profile per J-STD-020C)

**Moisture Sensitivity Level:** 1 (per J-STD-020C)

UL File No.: E68080

MetPak is a trademark of 3M Company.  
Futurebus+ is a registered trademark of the Institute of Electrical and Electronic Engineers, Inc. (IEEE)

**3M**




Electronic Solutions Division  
Interconnect Solutions  
<http://www.3Mconnector.com>

3M is a trademark of 3M Company.  
For technical, sales or ordering information call  
**800-225-5373**


# 3M™ MetPak™ 2-FB Socket

2 mm 5-Row, Right Angle, Solder or Press-Fit Tail, Guide Fingers


MP2 Series



**ASSEMBLED TO PCB AND MATED WITH MP2-PXXX-5XXX-XXXX**



**PRESS-FIT AND SOLDER TAIL PRODUCT (CAPPED)**



**MATED WITH MP2-PXXX-5XXX-XXXX**

| mm<br>[inch]           |    |      |       |
|------------------------|----|------|-------|
| Tolerance Unless Noted |    |      |       |
|                        | 0  | 0.0  | 0.00  |
| mm                     | ±3 | ±0.3 | ±0.13 |


[ ] Dimensions for Reference Only

## Notes:

1. Refer to IEC 61076-4-104 Futurebus+® global standard.
2. "Press Fit" describes a contact tail having a compliant section designed to make a reliable electrical connection with a plated through-hole (PTH) in a printed circuit board, typically a "back plane."



## Ordering Information



\*Contact 3M Sales Representative for information on special fill patterns and mono blocked pairs

TS-1117-B  
Sheet 2 of 4



**Electronic Solutions Division**  
**Interconnect Solutions**  
<http://www.3Mconnector.com>

3M is a trademark of 3M Company.  
For technical, sales or ordering information call  
**800-225-5373**

# 3M™ MetPak™ 2-FB Socket

2 mm 5-Row, Right Angle, Solder or Press-Fit Tail, Guide Fingers

MP2 Series

| Table 1 - Connector & Row Lengths |                       |                      |      |                |
|-----------------------------------|-----------------------|----------------------|------|----------------|
| Pin Count                         | Dim. "A"<br>mm [inch] | Dim "B"<br>mm [inch] | Rows | Block<br>Count |
| 030                               | 11.95 [0.471]         | 10.00 [0.394]        | 5    | 1              |
| 060                               | 23.95 [0.943]         | 22.00 [0.866]        | 5    | 2              |
| 090                               | 35.95 [1.415]         | 34.00 [1.339]        | 5    | 3              |
| 120                               | 47.95 [1.888]         | 46.00 [1.811]        | 5    | 4              |
| 150                               | 59.95 [2.361]         | 58.00 [2.283]        | 5    | 5              |
| 180                               | 71.95 [2.833]         | 70.00 [2.756]        | 5    | 6              |
| 210                               | 83.95 [3.305]         | 82.00 [3.228]        | 5    | 7              |
| 240                               | 95.95 [3.778]         | 94.00 [3.701]        | 5    | 8              |

| Table 2 - Tail Length                              |            |              |
|----------------------------------------------------|------------|--------------|
| Contact-to-PC Board Tail<br>Termination Option No. |            | Dim. "C"     |
| Solder                                             | Press-Fit* |              |
| 1                                                  |            | 4.35 [0.171] |
|                                                    | 1          | 3.53 [0.139] |

\*Compliant-Pin Tail

| Table 3 - Plating & Regulatory |                   |                   |                                                                                                                                                                                 |
|--------------------------------|-------------------|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Plating Suffix                 | Press-Fit Tails*  | Solder Tails      | Plating Composition                                                                                                                                                             |
| TG30                           | RIA E2 & C2 apply | RIA E3 & C2 apply | 0.76 µm [30 µ"] Min. Au Contact Area<br>2.54 µm [100 µ"] Min. SnPb Tail Area<br>1.27 µm [50 µ"] Min. Ni all over                                                                |
| TR30                           | RIA E2 & C2 apply | RIA E3 & C2 apply | 0.08 µm [3 µ"] Min. Au Contact Area<br>0.67 µm [27 µ"] Min. PdNi Contact Area<br>2.54 µm [100 µ"] Min. SnPb Tail Area<br>1.27 µm [50 µ"] Min. Ni all over                       |
| KR                             | RIA E1 & C1 apply | RIA E1 & C1 apply | 0.76 µm [30 µ"] Min. Au Contact Area<br>2.54 µm [100 µ"] Min. Matt Whisker Mitigating Sn Tail Area<br>1.27 µm [50 µ"] Min. Ni all over                                          |
| LR                             | RIA E1 & C1 apply | RIA E1 & C1 apply | 0.08 µm [3 µ"] Min. Au Contact Area<br>0.67 µm [27 µ"] Min. PdNi Contact Area<br>2.54 µm [100 µ"] Min. Matt Whisker Mitigating Sn Tail Area<br>1.27 µm [50 µ"] Min. Ni all over |


\*Compliant-Pin Tail

TS-1117-B  
Sheet 3 of 4

# 3M™ MetPak™ 2-FB Socket

2 mm 5-Row, Right Angle, Solder or Press-Fit Tail, Guide Fingers

MP2 Series



## RECOMMENDED PCB HOLE MOUNTING PATTERN

Table 4 – HOLE PLATING For TG30 and TR30 FINISHES ONLY

| HOLE | Finished Dia. MM [in]   | Cu Thickness [mm [in] | SnPb Thickness microns [μ"] | Drilled Hole Dia. mm [in] |
|------|-------------------------|-----------------------|-----------------------------|---------------------------|
| "D"  | 0.65-0.80 [.0256-.0315] | 0.025 [.001] min.     | 15 [600] max.               | 0.81-0.86 [.0319-.0339]   |

Table 5 – HOLE PLATING For KR and LR FINISHES ONLY

| HOLE | Finished Dia. MM [in]     | Cu Thickness [mm [in]     | Immersion Matte Sn Thickness microns [μ"] | Electrolytic Au Thickness microns [μ"] | OSP ENTEK Thickness microns [μ"] | Drilled Hole Dia. mm [in]                              |
|------|---------------------------|---------------------------|-------------------------------------------|----------------------------------------|----------------------------------|--------------------------------------------------------|
| "D"  | 0.700-0.800 [.0276-.0315] | 0.025-0.045 [0.001-0.002] | 0.5 - 2.5 [20 - 100]                      | 0.1 - 0.5 [4 - 20]                     | 0.2 - 0.5 [8 - 20]               | 0.830-0.860 [.0330-.0340] or 0.85 mm [#66] TWIST DRILL |

TS-1117-B  
Sheet 4 of 4



Electronic Solutions Division  
Interconnect Solutions  
<http://www.3Mconnector.com>

3M is a trademark of 3M Company.  
For technical, sales or ordering information call  
**800-225-5373**

#### **Important Notice**

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

#### **Warranty; Limited Remedy; Limited Liability.**

This product will be free from defects in material and manufacture for a period of ninety (90) days from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.**



#### **3M Electronics Solutions Division**

6801 River Place Blvd.  
Austin, TX 78726-9000  
U.S.A.  
1-800-225-5373  
[www.3Mconnector.com](http://www.3Mconnector.com)

Please recycle. Printed in USA.  
© 3M 2010. All rights reserved.  
RIA-2217B-E

3M is a trademark of 3M Company.

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9