

1353A Multi-Conductor - AES/EBU Digital Audio Cable

For more Information
please call

1-800-Belden1

**General Description:**

24 AWG Bonded-Pairs stranded (7x32) bare copper conductors, polyolefin insulation, PVC jacket.

Usage (Overall)

Suitable Applications:

Field Deployable Cat 5e Patch, CobraNet, eSnake, Ethersound, Digital Audio over Ethernet

Physical Characteristics (Overall)**Conductor**

AWG:

# Pairs	AWG	Stranding	Conductor Material	Dia. (in.)
1	24	7x32	BC - Bare Copper	.022

Total Number of Conductors:

2

Insulation

Insulation Material:

Insulation Material	Wall Thickness (in.)	Dia. (in.)
PO - Polyolefin	.0085	.041

Outer Shield

Outer Shield Material:

Outer Shield Material
Unshielded

Outer Jacket

Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (in.)
PVC - Polyvinyl Chloride	.022

Overall Cable

Overall Nominal Diameter:

0.126 in.

Pair

Pair Color Code Chart:

Number	Color
1	White/Brown Stripe & Brown

Mechanical Characteristics (Overall)

Operating Temperature Range: -20°C To +60°C

Bulk Cable Weight: 8 lbs/1000 ft.

Max. Recommended Pulling Tension: 18 lbs.

Min. Bend Radius/Minor Axis: 1.500 in.

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

NEC(UL) Specification: CMR

CEC/C(UL) Specification: CMG

EU Directive 2011/65/EU (RoHS II): Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 03/15/2007

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MIL Order #39 (China RoHS): Yes

1353A Multi-Conductor - AES/EBU Digital Audio Cable

Other Specification: NEMA WC-63.1 Category 5, ICEA 661, Category 5e Patch, TIA/EI-568-B.2, Category 5e

Applicable Patents:

Country

www.belden.com/p

Flame Test

UL Flame Test: UL1666 Riser

CSA Flame Test: FT4

Suitability

Suitability - Indoor: Yes

Plenum/Non-Plenum

Plenum (Y/N): No

Electrical Characteristics (Overall)

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/ft)

14.500

Nominal Velocity of Propagation:

VP (%)

70

Maximum Delay:

Delay (ns/100 m)

510

Maximum Conductor DC Resistance:

DCR @ 20°C (Ohm/100 m)

9

Max. Operating Voltage - UL:

Voltage

300 V RMS

Maximum DCR Unbalanced:

DCR Unbalance @ 20°C (%)

3

Electrical Characteristics-Premise (Overall)

Premise Cable Electrical Table 1:

Freq. (MHz)	Max. Attenuation (dB/100 m)	Min RL (dB)	Min. SRL (dB)
1	2.400	20.000	23.0
4	4.900	23.000	23.0
6	6.000		
8	6.900	24.500	23.0
10	7.800	25.000	23.0
12	8.400		
16	9.900	25.000	23.0
20	11.100	25.000	23.0
25	12.500	24.300	22.0
31.25	14.100	23.600	21.0
62.5	20.400	21.500	18.0
100	26.400	20.100	16.0

Premise Cable Electrical Table 2:

Freq. (MHz)	Fitted Impedance
1	105 ± 15
4	100 ± 15
8	100 ± 15
10	100 ± 15
16	100 ± 15
20	100 ± 15
25	100 ± 15
31.25	100 ± 15
62.5	100 ± 15
100	100 ± 15

Notes (Overall)

Notes: EtherNet/IP is a trademark of ControlNet International, Ltd. under license by Open DeviceNet Vendor Association, Inc. Operating temperatures are subject to length de-rating.

1353A Multi-Conductor - AES/EBU Digital Audio Cable

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
1353A N3UU1000	1,000 FT	9.000 LB	GREEN, MIL		1 PR #24 PP FRPVC
1353A 001U1000	1,000 FT	9.000 LB	BROWN		1 PR #24 PP FRPVC
1353A 002U1000	1,000 FT	9.000 LB	RED		1 PR #24 PP FRPVC
1353A 003U1000	1,000 FT	9.000 LB	ORANGE		1 PR #24 PP FRPVC
1353A 004U1000	1,000 FT	9.000 LB	YELLOW		1 PR #24 PP FRPVC
1353A 006U1000	1,000 FT	9.000 LB	BLUE, LIGHT		1 PR #24 PP FRPVC
1353A 007U1000	1,000 FT	9.000 LB	VIOLET		1 PR #24 PP FRPVC
1353A 008U1000	1,000 FT	9.000 LB	GRAY		1 PR #24 PP FRPVC
1353A 009U1000	1,000 FT	9.000 LB	WHITE		1 PR #24 PP FRPVC
1353A 010U1000	1,000 FT	9.000 LB	BLACK		1 PR #24 PP FRPVC
1353A 0101000	1,000 FT	9.000 LB	BLACK		1 PR #24 PP FRPVC
1353A 010500	500 FT	5.500 LB	BLACK		1 PR #24 PP FRPVC

Revision Number: 1 Revision Date: 02-28-2014

© 2014 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9