

**GPP TRANSIENT VOLTAGE SUPPRESSOR**  
**1500 WATT PEAK POWER 6.5 WATTS STEADY STATE**

**FEATURES**

- \* Plastic package has underwriters laboratory
- \* Glass passivated chip construction
- \* 1500 watt surge capability at 1ms
- \* Excellent clamping capability
- \* Low zener impedance
- \* Fast response time

**MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS**


Ratings at 25 °C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load,

For capacitive load, derate current by 20%.



1.5KE



**MAXIMUM RATINGS** (@ TA=25 °C unless otherwise noted)

| RATINGS                                                                                            | SYMBOL           | VALUE        | UNITS            |
|----------------------------------------------------------------------------------------------------|------------------|--------------|------------------|
| Peak Power Dissipation at TA = 25°C, TP = 1mS (Note 1)                                             | PPPM             | Minimum 1500 | W                |
| Steady State Power Dissipation at TL = 75°C lead length, .375" (9.5 mm) (Note 2)                   | PM(AV)           | 6.5          | W                |
| Peak Forward Surge Current, 8.3mS Single half sine-wave superimposed on rated load (JEDEC METHODE) | IFSM             | 200          | A                |
| Typical Current Squared Time                                                                       | I <sup>2</sup> T | 166          | A <sup>2</sup> S |
| Maximum instantaneous forwards voltage at 50A for unidirectional only (Note 4)                     | VF               | 3.5/5.0      | V                |
| Operating and Storage Temperature Range                                                            | TJ, TSTG         | -55 to + 150 | °C               |

- NOTES : 1. Non-repetitive current pulse, per Fig.3 and derated above TA = 25°C per Fig.2.  
 2. Mounted on 0.2 X 0.2" (5.0 X 5.0mm) copper pad to each terminal.  
 3. "Fully ROHS compliant", "100% Sn plating (Pb-free)".  
 4. VF =3.5V max. for devices of V(BR) ≤220V and VF =5.0Volts for device of V(BR) ≥220V.

2017-11  
REV: B

## RATING AND CHARACTERISTICS CURVES ( 1.5KE6.8 THRU 1.5KE440CA )




FIG.1 PEAK PULSE POWER RATING CURVE




FIG.2 PULSE DERATING CURVE




FIG.3 PULSE WAVEFORM




FIG.4 TYPICAL JUNCTION CAPACITANCE BIDIRECTIONAL




FIG.5 STEADY STATE POWER DERATING CURVE




FIG.6 MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT UNIDIRECTIONAL

RATING AND CHARACTERISTICS CURVES ( 1.5KE6.8 THRU 1.5KE440CA )




FIG.7 INCREMENTAL CLAMPING VOLTAGE CURVE UNIDIRECTIONAL




FIG.8 INCREMENTAL CLAMPING VOLTAGE CURVE UNIDIRECTIONAL




FIG.9 INCREMENTAL CLAMPING VOLTAGE CURVE BIDIRECTIONAL




FIG.10 INCREMENTAL CLAMPING VOLTAGE CURVE BIDIRECTIONAL




FIG.11 INSTANTANEOUS FORWARD VOLTAGE CHARACTERISTICS CURVE




FIG.12 BREAKDOWN VOLTAGE TEMPERATURE COEFFICIENT CURVE

## TRANSIENT VOLTAGE SUPPRESSORS

1500W SERIES TVS DIODES/ 1.5KE ( CASE 10 ) 1500W

| TYPE      | Breakdown Voltage |      |          | Reverse Stand off Voltage<br>VWM (Volts) | Maximum Reverse Leakage at VWM<br>ID(uA) | Maximum Peak Pulse Current<br>Ippm (Amps) | Maximum Clamping Voltage at Ippm<br>VC (Volts) |
|-----------|-------------------|------|----------|------------------------------------------|------------------------------------------|-------------------------------------------|------------------------------------------------|
|           | VBR (Volts)       |      | @IT (mA) |                                          |                                          |                                           |                                                |
|           | MIN.              | MAX. |          |                                          |                                          |                                           |                                                |
| 1.5KE6.8  | 6.12              | 7.48 | 10       | 5.50                                     | 1000                                     | 139                                       | 10.8                                           |
| 1.5KE6.8A | 6.45              | 7.14 | 10       | 5.80                                     | 1000                                     | 143                                       | 10.5                                           |
| 1.5KE7.5  | 6.75              | 8.25 | 10       | 6.05                                     | 500                                      | 128                                       | 11.7                                           |
| 1.5KE7.5A | 7.13              | 7.88 | 10       | 6.40                                     | 500                                      | 133                                       | 11.3                                           |
| 1.5KE8.2  | 7.38              | 9.02 | 10       | 6.63                                     | 200                                      | 120                                       | 12.5                                           |
| 1.5KE8.2A | 7.79              | 8.61 | 10       | 7.02                                     | 200                                      | 124                                       | 12.1                                           |
| 1.5KE9.1  | 8.19              | 10.0 | 1.0      | 7.37                                     | 50                                       | 109                                       | 13.8                                           |
| 1.5KE9.1A | 8.65              | 9.55 | 1.0      | 7.78                                     | 50                                       | 112                                       | 13.4                                           |
| 1.5KE10   | 9.00              | 11.0 | 1.0      | 8.10                                     | 10                                       | 100                                       | 15.0                                           |
| 1.5KE10A  | 9.50              | 10.5 | 1.0      | 8.55                                     | 10                                       | 103                                       | 14.5                                           |
| 1.5KE11   | 9.90              | 12.1 | 1.0      | 8.92                                     | 5.0                                      | 92.6                                      | 16.2                                           |
| 1.5KE11A  | 10.5              | 11.6 | 1.0      | 9.40                                     | 5.0                                      | 96.2                                      | 15.6                                           |
| 1.5KE12   | 10.8              | 13.2 | 1.0      | 9.72                                     | 5.0                                      | 86.7                                      | 17.3                                           |
| 1.5KE12A  | 11.4              | 12.6 | 1.0      | 10.2                                     | 5.0                                      | 89.8                                      | 16.7                                           |
| 1.5KE13   | 11.7              | 14.3 | 1.0      | 10.5                                     | 5.0                                      | 78.9                                      | 19.0                                           |
| 1.5KE13A  | 12.4              | 13.7 | 1.0      | 11.1                                     | 5.0                                      | 82.4                                      | 18.2                                           |
| 1.5KE15   | 13.5              | 16.5 | 1.0      | 12.1                                     | 5.0                                      | 68.2                                      | 22.0                                           |
| 1.5KE15A  | 14.3              | 15.8 | 1.0      | 12.8                                     | 5.0                                      | 70.8                                      | 21.2                                           |
| 1.5KE16   | 14.4              | 17.6 | 1.0      | 12.9                                     | 5.0                                      | 63.8                                      | 23.5                                           |
| 1.5KE16A  | 15.2              | 16.8 | 1.0      | 13.6                                     | 5.0                                      | 66.7                                      | 22.5                                           |
| 1.5KE18   | 16.2              | 19.8 | 1.0      | 14.5                                     | 5.0                                      | 56.6                                      | 26.5                                           |
| 1.5KE18A  | 17.1              | 18.9 | 1.0      | 15.3                                     | 5.0                                      | 59.5                                      | 25.2                                           |
| 1.5KE20   | 18.0              | 22.0 | 1.0      | 16.2                                     | 5.0                                      | 51.5                                      | 29.1                                           |
| 1.5KE20A  | 19.0              | 21.0 | 1.0      | 17.1                                     | 5.0                                      | 54.2                                      | 27.7                                           |
| 1.5KE22   | 19.8              | 24.2 | 1.0      | 17.8                                     | 5.0                                      | 47                                        | 31.9                                           |
| 1.5KE22A  | 20.9              | 23.1 | 1.0      | 18.8                                     | 5.0                                      | 49                                        | 30.6                                           |
| 1.5KE24   | 21.6              | 26.4 | 1.0      | 19.4                                     | 5.0                                      | 43.2                                      | 34.7                                           |
| 1.5KE24A  | 22.8              | 25.2 | 1.0      | 20.5                                     | 5.0                                      | 45.2                                      | 33.2                                           |
| 1.5KE27   | 24.3              | 29.7 | 1.0      | 21.8                                     | 5.0                                      | 38.4                                      | 39.1                                           |
| 1.5KE27A  | 25.7              | 28.4 | 1.0      | 23.1                                     | 5.0                                      | 40                                        | 37.5                                           |
| 1.5KE30   | 27.0              | 33.0 | 1.0      | 24.3                                     | 5.0                                      | 34.5                                      | 43.5                                           |
| 1.5KE30A  | 28.5              | 31.5 | 1.0      | 25.6                                     | 5.0                                      | 36.2                                      | 41.4                                           |
| 1.5KE33   | 29.7              | 36.3 | 1.0      | 26.8                                     | 5.0                                      | 31.4                                      | 47.7                                           |
| 1.5KE33A  | 31.4              | 34.7 | 1.0      | 28.2                                     | 5.0                                      | 32.8                                      | 45.7                                           |
| 1.5KE36   | 32.4              | 39.6 | 1.0      | 29.1                                     | 5.0                                      | 28.8                                      | 52.0                                           |
| 1.5KE36A  | 34.2              | 37.8 | 1.0      | 30.8                                     | 5.0                                      | 30.1                                      | 49.9                                           |
| 1.5KE39   | 35.1              | 42.9 | 1.0      | 31.6                                     | 5.0                                      | 26.6                                      | 56.4                                           |
| 1.5KE39A  | 37.1              | 41.0 | 1.0      | 33.3                                     | 5.0                                      | 27.8                                      | 53.9                                           |
| 1.5KE43   | 38.7              | 47.3 | 1.0      | 34.8                                     | 5.0                                      | 24.2                                      | 61.9                                           |
| 1.5KE43A  | 40.9              | 45.2 | 1.0      | 36.8                                     | 5.0                                      | 25.3                                      | 59.3                                           |
| 1.5KE47   | 42.3              | 51.7 | 1.0      | 38.1                                     | 5.0                                      | 22.1                                      | 67.8                                           |
| 1.5KE47A  | 44.7              | 49.4 | 1.0      | 40.2                                     | 5.0                                      | 23.1                                      | 64.8                                           |
| 1.5KE51   | 45.9              | 56.1 | 1.0      | 41.3                                     | 5.0                                      | 20.4                                      | 73.5                                           |
| 1.5KE51A  | 48.5              | 53.6 | 1.0      | 43.6                                     | 5.0                                      | 21.4                                      | 70.1                                           |
| 1.5KE56   | 50.4              | 61.6 | 1.0      | 45.4                                     | 5.0                                      | 18.6                                      | 80.5                                           |
| 1.5KE56A  | 53.2              | 58.8 | 1.0      | 47.8                                     | 5.0                                      | 19.5                                      | 77.0                                           |

## TRANSIENT VOLTAGE SUPPRESSORS

1500W SERIES TVS DIODES/ 1.5KE ( CASE 10 ) 1500W

| TYPE      | Breakdown Voltage          |      |                         | Reverse Stand off Voltage<br>V <sub>WM</sub><br>(Volts) | Maximum Reverse Leakage at V <sub>WM</sub><br>I <sub>D</sub> (uA) | Maximum Peak Pulse Current<br>I <sub>PPM</sub><br>(Amps) | Maximum Clamping Voltage at I <sub>PPM</sub><br>V <sub>C</sub> (Volts) |
|-----------|----------------------------|------|-------------------------|---------------------------------------------------------|-------------------------------------------------------------------|----------------------------------------------------------|------------------------------------------------------------------------|
|           | V <sub>BR</sub><br>(Volts) |      | @I <sub>T</sub><br>(mA) |                                                         |                                                                   |                                                          |                                                                        |
|           | MIN.                       | MAX. |                         |                                                         |                                                                   |                                                          |                                                                        |
| 1.5KE62   | 55.8                       | 68.2 | 1.0                     | 50.2                                                    | 5.0                                                               | 16.9                                                     | 89.0                                                                   |
| 1.5KE62A  | 58.9                       | 65.1 | 1.0                     | 53.0                                                    | 5.0                                                               | 17.6                                                     | 85.0                                                                   |
| 1.5KE68   | 61.2                       | 74.8 | 1.0                     | 55.1                                                    | 5.0                                                               | 15.3                                                     | 98.0                                                                   |
| 1.5KE68A  | 64.6                       | 71.4 | 1.0                     | 58.1                                                    | 5.0                                                               | 16.3                                                     | 92.0                                                                   |
| 1.5KE75   | 67.5                       | 82.5 | 1.0                     | 60.7                                                    | 5.0                                                               | 13.9                                                     | 109                                                                    |
| 1.5KE75A  | 71.3                       | 78.8 | 1.0                     | 64.1                                                    | 5.0                                                               | 14.6                                                     | 104                                                                    |
| 1.5KE82   | 73.8                       | 90.2 | 1.0                     | 66.4                                                    | 5.0                                                               | 12.7                                                     | 118                                                                    |
| 1.5KE82A  | 77.9                       | 86.1 | 1.0                     | 70.1                                                    | 5.0                                                               | 13.3                                                     | 113                                                                    |
| 1.5KE91   | 81.9                       | 100  | 1.0                     | 73.7                                                    | 5.0                                                               | 11.5                                                     | 131                                                                    |
| 1.5KE91A  | 86.5                       | 95.5 | 1.0                     | 77.8                                                    | 5.0                                                               | 12.0                                                     | 125                                                                    |
| 1.5KE100  | 90.0                       | 110  | 1.0                     | 81.0                                                    | 5.0                                                               | 10.4                                                     | 144                                                                    |
| 1.5KE100A | 95.0                       | 105  | 1.0                     | 85.5                                                    | 5.0                                                               | 10.9                                                     | 137                                                                    |
| 1.5KE110  | 99.0                       | 121  | 1.0                     | 89.2                                                    | 5.0                                                               | 9.5                                                      | 158                                                                    |
| 1.5KE110A | 105                        | 116  | 1.0                     | 94.0                                                    | 5.0                                                               | 9.9                                                      | 152                                                                    |
| 1.5KE120  | 108                        | 132  | 1.0                     | 97.2                                                    | 5.0                                                               | 8.7                                                      | 173                                                                    |
| 1.5KE120A | 114                        | 126  | 1.0                     | 102                                                     | 5.0                                                               | 9.1                                                      | 165                                                                    |
| 1.5KE130  | 117                        | 143  | 1.0                     | 105                                                     | 5.0                                                               | 8.0                                                      | 187                                                                    |
| 1.5KE130A | 124                        | 137  | 1.0                     | 111                                                     | 5.0                                                               | 8.4                                                      | 179                                                                    |
| 1.5KE150  | 135                        | 165  | 1.0                     | 121                                                     | 5.0                                                               | 7.0                                                      | 215                                                                    |
| 1.5KE150A | 143                        | 158  | 1.0                     | 128                                                     | 5.0                                                               | 7.2                                                      | 207                                                                    |
| 1.5KE160  | 144                        | 176  | 1.0                     | 130                                                     | 5.0                                                               | 6.5                                                      | 230                                                                    |
| 1.5KE160A | 152                        | 168  | 1.0                     | 136                                                     | 5.0                                                               | 6.8                                                      | 219                                                                    |
| 1.5KE170  | 153                        | 187  | 1.0                     | 138                                                     | 5.0                                                               | 6.1                                                      | 244                                                                    |
| 1.5KE170A | 162                        | 179  | 1.0                     | 145                                                     | 5.0                                                               | 6.4                                                      | 234                                                                    |
| 1.5KE180  | 162                        | 198  | 1.0                     | 146                                                     | 5.0                                                               | 5.8                                                      | 258                                                                    |
| 1.5KE180A | 171                        | 189  | 1.0                     | 154                                                     | 5.0                                                               | 6.1                                                      | 246                                                                    |
| 1.5KE200  | 180                        | 220  | 1.0                     | 162                                                     | 5.0                                                               | 5.2                                                      | 287                                                                    |
| 1.5KE200A | 190                        | 210  | 1.0                     | 171                                                     | 5.0                                                               | 5.5                                                      | 274                                                                    |
| 1.5KE220  | 198                        | 242  | 1.0                     | 175                                                     | 5.0                                                               | 4.4                                                      | 344                                                                    |
| 1.5KE220A | 209                        | 231  | 1.0                     | 185                                                     | 5.0                                                               | 4.6                                                      | 328                                                                    |
| 1.5KE250  | 225                        | 275  | 1.0                     | 202                                                     | 5.0                                                               | 4.2                                                      | 360                                                                    |
| 1.5KE250A | 237                        | 263  | 1.0                     | 214                                                     | 5.0                                                               | 4.4                                                      | 344                                                                    |
| 1.5KE300  | 270                        | 330  | 1.0                     | 243                                                     | 5.0                                                               | 3.5                                                      | 430                                                                    |
| 1.5KE300A | 285                        | 315  | 1.0                     | 256                                                     | 5.0                                                               | 3.6                                                      | 414                                                                    |
| 1.5KE350  | 315                        | 385  | 1.0                     | 284                                                     | 5.0                                                               | 3.0                                                      | 504                                                                    |
| 1.5KE350A | 333                        | 368  | 1.0                     | 300                                                     | 5.0                                                               | 3.1                                                      | 482                                                                    |
| 1.5KE400  | 360                        | 440  | 1.0                     | 324                                                     | 5.0                                                               | 2.6                                                      | 574                                                                    |
| 1.5KE400A | 380                        | 420  | 1.0                     | 342                                                     | 5.0                                                               | 2.7                                                      | 548                                                                    |
| 1.5KE440  | 396                        | 484  | 1.0                     | 356                                                     | 5.0                                                               | 2.4                                                      | 631                                                                    |
| 1.5KE440A | 418                        | 462  | 1.0                     | 376                                                     | 5.0                                                               | 2.5                                                      | 602                                                                    |

- Notes :
1.  $V_{BR}$  measured after  $I_T$  applied for 300ms.  $I_T$  = square pulse or equivalent.
  2. For bidirectional use C or CA suffixs for all types (ex. 1.5KE6.8C,1.5KE440CA) electrical characteristics apply in both directions.
  3. For bidirectional types having  $V_{WM}$  of 10 volts and less, the  $I_D$  limit is doubled.
  4. All devices UL listed file# E211196.




## Attachment information about 1.5KEXX (C) A

### 1. Internal Circuit



### 2. Marking on the body



## PACKAGING OF DIODE AND BRIDGE RECTIFIERS

### REEL PACK

| PACKAGE | PACKING CODE | EA PER REEL | EA PER INNER BOX | COMPONENT SPACE (mm) | TAPE SPACE (mm) | REEL DIA (mm) | CARTON SIZE (mm) | EA PER CARTON | GROSS WEIGHT(Kg) |
|---------|--------------|-------------|------------------|----------------------|-----------------|---------------|------------------|---------------|------------------|
| 1.5KE   | -T           | 1,200       | 1,200            | 10.0                 | 52              | 330           | 355*350*335      | 4,800         | 8.05             |

## DISCLAIMER NOTICE

Rectron Inc reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. Rectron Inc or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on RECTRON data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. Rectron Inc does not assume any liability arising out of the application or use of any product or circuit.

Rectron products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of Rectron Inc. Customers using or selling Rectron components for use in such applications do so at their own risk and shall agree to fully indemnify Rectron Inc and its subsidiaries harmless against all claims, damages and expenditures.

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9