

D
Dimensioning and tolerancing per ASME Y14.5M-2009

B

A

D

C

B


A

4		3		2		1							
THIS DRAWING IS UNPUBLISHED.		RELEASED FOR PUBLICATION		LOC		DIST		REVISIONS					
© COPYRIGHT		ALL RIGHTS RESERVED.						P	LTR	DESCRIPTION	DATE	DWN	APVD
									A1	ECR-13-008545	24MAY2013	XZ	LZ

REPLACED BY OCEAN STYLE APPLICATOR PART NUMBER 2151787-1

FOR REPLACEMENT PARTS FOR APPLICATOR 1852105
REFER TO ADDITIONAL PAGE(S). SPARE PARTS KIT (IF LISTED)
WILL REMAIN AVAILABLE.

THE REPLACEMENT OCEAN STYLE APPLICATOR HAS THE
SAME TERMINATOR/PRESS INTERFACE AS APPLICATOR
1852105

THIS DRAWING IS A CONTROLLED DOCUMENT.				DWN X. ZHAO		 TE Connectivity				
DIMENSIONS:				CHK L. ZHANG						
				APVD L. ZHANG		NAME SIDE FEED HDM APPLICATOR				
				PRODUCT SPEC						
				APPLICATION SPEC						
				MATERIAL		FINISH		WEIGHT		SIZE A3
								SCALE	SHEET 1 OF 2	REV A1

Dimensioning and tolerancing per ASME Y14.5M-2009

8

7

6

5

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

20

PART NUMBER	REV	FIRST USED	POWER UNIT	FEED TYPE
1852105-1	A	122500-1	LEADMAKER	POST FEED
1852105-2	A	565435-5	BENCH MODEL K	PRE FEED
1852105-3	A	354500-1	BENCH MODEL G	PRE FEED

127

126

128

128

127

126

POS D

POS C

POS B

POS A

35

36

125

37

38

73

39

74

40

103

45

87

111

24

93

30

50

108

51

77

109

29

86

81

111

94

8

98

56

34

100

102

2

3

4

28

5

41

9

12

11

16

10

94

1

80

46

44

43

42

100

102

2

3

4

28

5

41

9

12

11

16

10

94

AMP-O-ELECTRIC TERM GUARD

G TERMINATOR GUARD

79

78

△

△

△

△

△

RECOMMENDED SPARE PARTS

GREASE LIGHTLY

GUARD MUST BE IN PLACE WHEN OPERATING APPLICATOR IN A BENCH MACHINE

TERMINAL NAME: PLUG CONTACT

TYCO PN	MANUF PIN	CONNEC TERMINAL	AMP CRIMP SPECS
1572767-1	161A13369X		
-	-	PAD LTR	
-	-	A	CRIMP HEIGHT
-	-	B	WIRE SIZE
-	-	C	
-	-	D	
-	-	CRIMP	SIZE
-	-	WIRE	TYPE
-	-	INSUL	RANGE
-	-	FEED	
-	-	APPL INSTRUCTIONS	
-	-	SET UP GAGE	

WIRE STRIP LENGTH

TERM APPL SPEC

FEED

APPL INSTRUCTIONS

SET UP GAGE

.088 - .103

NONE

.299

408-8040

458637-1

129

128

127

126

125

124

123

122

121

120

119

118

117

116

115

114

113

112

111

110

109

108

107

106

105

104

103

102

101

100

99

98

97

96

95

94

93

92

91

90

89

88

87

86

85

84

83

82

81

80

79

78

77

76

75

74

73

72

71

70

69

68

67

66

65

64

63

62

61

60

59

58

57

56

55

54

53

52

51

50

49

48

47

46

45

44

43

42

41

40

39

38

37

36

35

34

33

32

31

30

29

28

27

26

25

24

23

22

21

20

19

18

17

16

15

14

13

12

11

10

9

8

7

6

5

4

3

2

1

POST-FEED 1 5/8 STROKE

PRE-FEED 1 1/8 STROKE

PRE-FEED 1 5/8 STROKE

47

91

48

91

49

91

8

34

8

34

24

30

24

30

ITEM 30 LOCATED AT FRONT HOLES

FEED TRACK POSITION

22

19

22

19

24

30

24

30

LEADMAKER & BENCH MACHINE

AMP 4565 REV 31MAR2008

AMP-O-ELECTRIC TERM GUARD

G TERMINATOR GUARD

79

78

△

△

△

△

△

RECOMMENDED SPARE PARTS

GREASE LIGHTLY

GUARD MUST BE IN PLACE WHEN OPERATING APPLICATOR IN A BENCH MACHINE

TERMINAL NAME: PLUG CONTACT

TYCO PN	MANUF PIN	CONNEC TERMINAL	AMP CRIMP SPECS
1572767-1	161A13369X		
-	-	PAD LTR	
-	-	A	CRIMP HEIGHT
-	-	B	WIRE SIZE
-	-	C	
-	-	D	
-	-	CRIMP	SIZE
-	-	WIRE	TYPE
-	-	INSUL	RANGE
-	-	FEED	
-	-	APPL INSTRUCTIONS	
-	-	SET UP GAGE	

WIRE STRIP LENGTH

TERM APPL SPEC

FEED

APPL INSTRUCTIONS

SET UP GAGE

.088 - .103

NONE

.299

408-8040

458637-1

129

128

127

126

125

124

123

122

121

120

119

118

117

116

115

114

113

112

111

110

109

108

107

106

105

104

103

102

101

100

99

98

97

96

95

94

93

92

91

90

89

88

87

86

85

84

83

82

81

80

79

78

77

76

75

74

73

72

71

70

69

68

67

66

65

64

63

62

61

60

59

58

57

56

55

54

53

52

51

50

49

48

47

46

45

44

43

42

41

40

39

38

37

36

35

34

33

32

31

30

29

28

27

26

25

24

23

22

21

20

19

18

17

16

15

14

13

12

11

10

9

8

7

6

5

4

3

2

1

POST-FEED 1 5/8 STROKE

PRE-FEED 1 1/8 STROKE

PRE-FEED 1 5/8 STROKE

47

91

48

91

49

91

8

34

8

34

24

30

24

30

ITEM 30 LOCATED AT FRONT HOLES

FEED TRACK POSITION

22

19

22

19

24

30

24

30

LEADMAKER & BENCH MACHINE

AMP 4565 REV 31MAR2008

AMP-O-ELECTRIC TERM GUARD

G TERMINATOR GUARD

79

78

△

△

△

△

△

RECOMMENDED SPARE PARTS

GREASE LIGHTLY

GUARD MUST BE IN PLACE WHEN OPERATING APPLICATOR IN A BENCH MACHINE

TERMINAL NAME: PLUG CONTACT

TYCO PN	MANUF PIN	CONNEC TERMINAL	AMP CRIMP SPECS
1572767-1	161A13369X		
-	-	PAD LTR	
-	-	A	CRIMP HEIGHT
-	-	B	WIRE SIZE
-	-	C	
-	-	D	
-	-	CRIMP	SIZE
-	-	WIRE	TYPE
-	-	INSUL	RANGE
-	-	FEED	
-	-	APPL INSTRUCTIONS	
-	-	SET UP GAGE	

WIRE STRIP LENGTH

TERM APPL SPEC

FEED

APPL INSTRUCTIONS

SET UP GAGE

.088 - .103

NONE

.299

408-8040

458637-1

129

128

127

126

125

124

123

122

121

120

119

118

117

116

115

114

113

112

111

110

109

108

107

106

105

104

103

102

101

100

99

98

97

96

95

94

93

92

91

90

89

88

87

86

85

84

83

82

81

80

79

78

77

76

75

74

73

72

71

70

69

68

67

66

65

64

63

62

61

60

59

58

57

56

55

54

53

52

51

50

49

48

47

46

45

44

43

42

41

40

39

38

37

36

35

34

33

32

31

30

29

28

27

26

25

24

23

22

21

20

19

18

17

16

15

14

13

12

11

10

9

8

7

6

5

4

3

2

1

POST-FEED 1 5/8 STROKE

PRE-FEED 1 1/8 STROKE

PRE-FEED 1 5/8 STROKE

47

91

48

91

49

91

8

34

8

34

24

30

24

30

ITEM 30 LOCATED AT FRONT HOLES

FEED TRACK POSITION

22

19

22

19

24

30

24

30

LEADMAKER & BENCH MACHINE

AMP 4565 REV 31MAR2008

AMP-O-ELECTRIC TERM GUARD

G TERMINATOR GUARD

79

78

△

△

△

△

△

RECOMMENDED SPARE PARTS

GREASE LIGHTLY

GUARD MUST BE IN PLACE WHEN OPERATING APPLICATOR IN A BENCH MACHINE

TERMINAL NAME: PLUG CONTACT

TYCO PN	MANUF PIN	CONNEC TERMINAL	AMP CRIMP SPECS
1572767-1	161A13369X		
-	-	PAD LTR	
-	-	A	CRIMP HEIGHT
-	-	B	WIRE SIZE
-	-	C	
-	-	D	
-	-	CRIMP	SIZE
-	-	WIRE	TYPE
-	-	INSUL	RANGE
-	-	FEED	
-	-	APPL INSTRUCTIONS	
-	-	SET UP GAGE	

WIRE STRIP LENGTH

TERM APPL SPEC

FEED

APPL INSTRUCTIONS

SET UP GAGE

.088 - .103

NONE

.299

408-8040

458637-1

129

128

127

126

125

124

123

122

121

120

119

118

117

116

115

114

113

112

111

110

109

108

107

106

105

104

103

102

101

100

99

98

97

96

95

94

93

92

91

90

89

88

87

86

85

84

83

82

81

80

79

78

77

76

75

74

73

72

71

70

69

68

67

66

65

64

63

62

61

60

59

58

57

56

55

54

53

52

51

50

49

48

47

46

45

44

43

42

41

40

39

38

37

36

35

34

33

32

31

30

29

28

27

26

25

24

23

22

21

20

19

18

17

16

15

14

13

12

11

10

9

8

7

6

5

4

3

2

1

POST-FEED 1 5/8 STROKE

PRE-FEED 1 1/8 STROKE

PRE-FEED 1 5/8 STROKE

47

91

48

91

49

91

8

34

8

34

24

30

24

30

ITEM 30 LOCATED AT FRONT HOLES

FEED TRACK POSITION

22

19

22

19

24

30

24

30

LEADMAKER & BENCH MACHINE

AMP 4565 REV 31MAR2008

AMP-O-ELECTRIC TERM GUARD

G TERMINATOR GUARD

79

78

△

△

△

△

△

RECOMMENDED SPARE PARTS

GREASE LIGHTLY

GUARD MUST BE IN PLACE WHEN OPERATING APPLICATOR IN A BENCH MACHINE

TERMINAL NAME: PLUG CONTACT

TYCO PN	MANUF PIN	CONNEC TERMINAL	AMP CRIMP SPECS
1572767-1	161A13369X		
-	-	PAD LTR	
-	-	A	CRIMP HEIGHT
-	-	B	WIRE SIZE
-	-	C	
-	-	D	
-	-	CRIMP	SIZE
-	-	WIRE	TYPE
-	-	INSUL	RANGE
-	-	FEED	
-	-	APPL INSTRUCTIONS	
-	-	SET UP GAGE	

WIRE STRIP LENGTH

TERM APPL SPEC

FEED

APPL INSTRUCTIONS

SET UP GAGE

.088 - .103

NONE

.299

408-8040

458637-1

129

128

127

126

125

124

123

122

121

120

119

118

117

116

115

114

113

112

111

110

109

108

107

106

105

104

103

102

101

100

99

98

97

96

95

94

93

92

91

90

89

88

87

86

85

84

83

82

81

80

79

78

77

76

75

74

73

72

71

70

69

68

67

66

65

64

63

62

61

60

59

58

57

56

55

54

53

52

51

50

49

48

47

46

45

44

43

42

41

40

39

38

37

36

35

34

33

32

31

30

29

28

27

26

25

24

23

22

21

20

19

18

17

16

15

14

13

12

11

10

9

8

7

6

5

4

3

2

1

POST-FEED 1 5/8 STROKE

PRE-FEED 1 1/8 STROKE

PRE-FEED 1 5/8 STROKE

47

91

48

91

49

91

8

34

8

34

24

30

24

30

ITEM 30 LOCATED AT FRONT HOLES

FEED TRACK POSITION

22

19

22

19

24

30

24

30

LEADMAKER & BENCH MACHINE

AMP 4565 REV 31MAR2008

AMP-O-ELECTRIC TERM GUARD

G TERMINATOR GUARD

79

78

△

△

△

△

△

RECOMMENDED SPARE PARTS

GREASE LIGHTLY

GUARD MUST BE IN PLACE WHEN OPERATING APPLICATOR IN A BENCH MACHINE

TERMINAL NAME: PLUG CONTACT

TYCO PN	MANUF PIN	CONNEC TERMINAL	AMP CRIMP SPECS
1572767-1	161A13369X		
-	-	PAD LTR	
-	-	A	CRIMP HEIGHT
-	-	B	WIRE SIZE
-	-	C	
-	-	D	
-	-	CRIMP	SIZE
-	-	WIRE	TYPE
-	-	INSUL	RANGE
-	-	FEED	
-	-	APPL INSTRUCTIONS	
-	-	SET UP GAGE	

WIRE STRIP LENGTH

TERM APPL SPEC

FEED

APPL INSTRUCTIONS

SET UP GAGE

.088 - .103

NONE

.299

408-8040

458637-1

129

128

127

126

125

124

123

122

121

120

119

118

117

116

115

114

113

112

111

110

109

108

107

106

105

104

103

102

101

100

99

98

97

96

95

94

93

92

91

90

89

88

87

86

85

84

83

82

81

80

79

78

77

76

75

74

73

72

71

70

69

68

67

66

65

64

63

62

61

60

59

58

57

56

55

54

53

52

51

50

49

48

47

46

45

44

43

42

41

40

39

38

37

36

35

34

33

32

31

30

29

28

27

26

25

24

23

22

21

20

19

18

17

16

15

14

13

12

11

10

9

8

7

6

5

4

3

2

1

POST-FEED 1 5/8 STROKE

PRE-FEED 1 1/8 STROKE

PRE-FEED 1 5/8 STROKE

47

91

48

91

49

91

8

34

8

34

24

30

24

30

ITEM 30 LOCATED AT FRONT HOLES

FEED TRACK POSITION

22

19

22

19

24

30

24

30

LEADMAKER & BENCH MACHINE

AMP 4565 REV 31MAR2008

AMP-O-ELECTRIC TERM GUARD

G TERMINATOR GUARD

79

78

△

△</

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9