

# 2SC5200/FJL4315


## NPN Epitaxial Silicon Transistor

### Applications

- High-Fidelity Audio Output Amplifier
- General Purpose Power Amplifier

### Features

- High Current Capability:  $I_C = 15A$ .
- High Power Dissipation : 150watts.
- High Frequency : 30MHz.
- High Voltage :  $V_{CEO}=230V$
- Wide S.O.A for reliable operation.
- Excellent Gain Linearity for low THD.
- Complement to 2SA1943/FJL4215.
- Thermal and electrical Spice models are available.
- Same transistor is also available in:
  - TO3P package, 2SC5242/FJA4313 : 130 watts
  - TO220 package, FJP5200 : 80 watts
  - TO220F package, FJPF5200 : 50 watts



### Absolute Maximum Ratings\* $T_a = 25^\circ C$ unless otherwise noted

| Symbol         | Parameter                                                                 | Ratings     | Units              |
|----------------|---------------------------------------------------------------------------|-------------|--------------------|
| $BV_{CBO}$     | Collector-Base Voltage                                                    | 230         | V                  |
| $BV_{CEO}$     | Collector-Emitter Voltage                                                 | 230         | V                  |
| $BV_{EBO}$     | Emitter-Base Voltage                                                      | 5           | V                  |
| $I_C$          | Collector Current(DC)                                                     | 15          | A                  |
| $I_B$          | Base Current                                                              | 1.5         | A                  |
| $P_D$          | Total Device Dissipation( $T_C=25^\circ C$ )<br>Derate above $25^\circ C$ | 150<br>1.04 | W<br>W/ $^\circ C$ |
| $T_J, T_{STG}$ | Junction and Storage Temperature                                          | - 50 ~ +150 | $^\circ C$         |

\* These ratings are limiting values above which the serviceability of any semiconductor device may be impaired.

### Thermal Characteristics\* $T_a=25^\circ C$ unless otherwise noted

| Symbol          | Parameter                            | Max. | Units        |
|-----------------|--------------------------------------|------|--------------|
| $R_{\theta JC}$ | Thermal Resistance, Junction to Case | 0.83 | $^\circ C/W$ |

\* Device mounted on minimum pad size

### $h_{FE}$ Classification

| Classification | R        | O        |
|----------------|----------|----------|
| $h_{FE1}$      | 55 ~ 110 | 80 ~ 160 |

# Electrical Characteristics\* T<sub>a</sub>=25°C unless otherwise noted

| Symbol               | Parameter                            | Test Condition                           | Min. | Typ. | Max. | Units |
|----------------------|--------------------------------------|------------------------------------------|------|------|------|-------|
| BV <sub>CBO</sub>    | Collector-Base Breakdown Voltage     | I <sub>C</sub> =5mA, I <sub>E</sub> =0   | 230  |      |      | V     |
| BV <sub>CEO</sub>    | Collector-Emitter Breakdown Voltage  | I <sub>C</sub> =10mA, R <sub>BE</sub> =∞ | 230  |      |      | V     |
| BV <sub>EBO</sub>    | Emitter-Base Breakdown Voltage       | I <sub>E</sub> =5mA, I <sub>C</sub> =0   | 5    |      |      | V     |
| I <sub>CBO</sub>     | Collector Cut-off Current            | V <sub>CB</sub> =230V, I <sub>E</sub> =0 |      |      | 5.0  | μA    |
| I <sub>EBO</sub>     | Emitter Cut-off Current              | V <sub>EB</sub> =5V, I <sub>C</sub> =0   |      |      | 5.0  | μA    |
| h <sub>FE1</sub>     | DC Current Gain                      | V <sub>CE</sub> =5V, I <sub>C</sub> =1A  | 55   |      | 160  |       |
| h <sub>FE2</sub>     | DC Current Gain                      | V <sub>CE</sub> =5V, I <sub>C</sub> =7A  | 35   | 60   |      |       |
| V <sub>CE(sat)</sub> | Collector-Emitter Saturation Voltage | I <sub>C</sub> =8A, I <sub>B</sub> =0.8A |      | 0.4  | 3.0  | V     |
| V <sub>BE(on)</sub>  | Base-Emitter On Voltage              | V <sub>CE</sub> =5V, I <sub>C</sub> =7A  |      | 1.0  | 1.5  | V     |
| f <sub>T</sub>       | Current Gain Bandwidth Product       | V <sub>CE</sub> =5V, I <sub>C</sub> =1A  |      | 30   |      | MHz   |
| C <sub>ob</sub>      | Output Capacitance                   | V <sub>CB</sub> =10V, f=1MHz             |      | 200  |      | pF    |

\* Pulse Test: Pulse Width=20μs, Duty Cycle≤2%

## Ordering Information

| Part Number | Marking | Package | Packing Method | Remarks      |
|-------------|---------|---------|----------------|--------------|
| 2SC5200RTU  | C5200R  | TO-264  | TUBE           | hFE1 R grade |
| 2SC5200OTU  | C5200O  | TO-264  | TUBE           | hFE1 O grade |
| FJL4315RTU  | J4315R  | TO-264  | TUBE           | hFE1 R grade |
| FJL4315OTU  | J4315O  | TO-264  | TUBE           | hFE1 O grade |

## Typical Characteristics




Figure 1. Static Characteristic




Figure 2. DC current Gain




Figure 3. Base-Emitter Saturation Voltage




Figure 4. Collector-Emitter Saturation Voltage




Figure 5. Base-Emitter On Voltage




Figure 6. Thermal Resistance

## Typical Characteristics




Figure 7. Power Derating




Figure 8. Safe Operating Area





## TRADEMARKS

The following are registered and unregistered trademarks and service marks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

|                                                                                              |                                                                                            |                            |                                                                                     |
|----------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|----------------------------|-------------------------------------------------------------------------------------|
| ACEx®                                                                                        | Green FPS™                                                                                 | Power247®                  | SuperSOT™-8                                                                         |
| Build it Now™                                                                                | Green FPS™ e-Series™                                                                       | POWEREDGE®                 | SyncFET™                                                                            |
| CorePLUS™                                                                                    | GTO™                                                                                       | Power-SPM™                 | The Power Franchise®                                                                |
| CROSSVOLT™                                                                                   | i-Lo™                                                                                      | PowerTrench®               |  |
| CTL™                                                                                         | IntelliMAX™                                                                                | Programmable Active Droop™ | TinyBoost™                                                                          |
| Current Transfer Logic™                                                                      | ISOPLANAR™                                                                                 | QFET®                      | TinyBuck™                                                                           |
| EcoSPARK®                                                                                    | MegaBuck™                                                                                  | QS™                        | TinyLogic®                                                                          |
|  Fairchild® | MICROCOUPLER™                                                                              | QT Optoelectronics™        | TINYOPTO™                                                                           |
| Fairchild Semiconductor®                                                                     | MicroFET™                                                                                  | Quiet Series™              | TinyPower™                                                                          |
| FACT Quiet Series™                                                                           | MicroPak™                                                                                  | RapidConfigure™            | TinyPWM™                                                                            |
| FACT®                                                                                        | MillerDrive™                                                                               | SMART START™               | TinyWire™                                                                           |
| FAST®                                                                                        | Motion-SPM™                                                                                | SPM®                       | μSerDes™                                                                            |
| FastvCore™                                                                                   | OPTOLOGIC®                                                                                 | STEALTH™                   | UHC®                                                                                |
| FPS™                                                                                         | OPTOPLANAR®                                                                                | SuperFET™                  | UniFET™                                                                             |
| FRFET®                                                                                       |  PDP-SPM™ | SuperSOT™-3                | VCX™                                                                                |
| Global Power ResourceSM                                                                      | Power220®                                                                                  | SuperSOT™-6                |                                                                                     |

## DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

## LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

## PRODUCT STATUS DEFINITIONS

### Definition of Terms

| Datasheet Identification | Product Status         | Definition                                                                                                                                                                                               |
|--------------------------|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Advance Information      | Formative or In Design | This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.                                                                       |
| Preliminary              | First Production       | This datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design. |
| No Identification Needed | Full Production        | This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.                                                   |
| Obsolete                 | Not In Production      | This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.                                      |

Rev. I31

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9