

# Mini-SAS HD

## Next generation SAS storage interface

### DESCRIPTION

The Mini-SAS HD product is the next generation SAS storage interface addressing channel bandwidth requirements of 6 Gb/s to 12 Gb/s meeting or exceeding the respective SAS 2.1 and proposed SAS 3.0 specifications. The Mini-SAS HD product provides greater port density (11mm port-to-port) versus the existing Mini-SAS 2.0 product (19.01mm port-to-port). FCI's Mini-SAS HD product is fully compliant to the SFF-8643 and SFF-8644 industry specifications. Internal and external connector configurations of the Mini-SAS HD product include 1X1 (4x), 1X2 (8x), and 1X4(16x) and enables 4x and 8x internal & external cable assembly solutions which include EEPROM communication. The Mini-SAS HD profile design is PCI Express compatible and can be utilized in PCI Express architecture applications.



### FEATURES & BENEFITS

- IMLA based board connector insures compliance to the SAS 2.1 & proposed 3.0 electrical performance criteria
- Internal and external board connector and cable assemblies provide end-to-end application solutions
- 1X1, 1X2 and 1X4 connector/cage assemblies offer product family design flexibility
- All board connectors and configurations are fully 6G and 12G compliant allowing for use of same part numbers when system speeds increase from 6G to 12G
- Metal cages on the external connector and cables provide 360° EMI shielding and replaces problematic EMC elastomeric gaskets
- Cable assemblies offered in 4x and 8x configurations
- Eye-of-the-needle connector and cage single step termination yields consistent application to the PCB
- The external cable strain relief results in an axial pull force in excess of 20 lbs
- Cable latch design reduces cable insertion force and un-mating issues
- Pull tabs are available in multiple lengths in Pantone 279 color to meet many application needs.
- Positive stop feature on the casting prevents external cable assembly mating over-travel.
- Hybrid external cables (mini-SAS HD to mini-SAS) allow for backwards compatible cabling with legacy system hardware

### TARGET MARKETS / APPLICATIONS

- **DATA**
  - Servers
  - RAID systems
  - Storage racks
- **EXTERNAL STORAGE SYSTEMS**
  - SAS/SATA HBA interfaces
  - Direct-attached storage (DAS)
- **COMMUNICATIONS**
  - Switches

### TECHNICAL INFORMATION

#### ■ MATERIALS

- Board Receptacle Contact: Copper alloy
- Board Receptacle Housing: Thermoplastic high temperature UL94V-0
- Board Receptacle Plating: Gold over Nickel
- Plug Paddle Card: Copper/FR4 – Gold over Nickel plating.

#### ■ ELECTRICAL PERFORMANCE

- Impedance: 100 +/- 15Ω
- Voltage Rating: 30 Volts AC (RMS)/DC Max
- Current Rating: 0.5 Amps Max

#### ■ APPROVALS AND CERTIFICATIONS

- RoHS conforms to EU directive 2002/95/EC
- UL Approval

#### ■ PACKAGING

- Board Receptacle: Tray
- Plug/Cable Assembly: Bag

#### ■ ENVIRONMENTAL

- Thermal Shock (temperature cycling): conforms to EIA-364-32
- Temperature life (heat aging): conforms to EIA-361-17, 105°C for 500 hours
- Operating temperature range : -40°C to 80°C

#### ■ MECHANICAL PERFORMANCE

- Durability: 250 cycles

#### ■ SPECIFICATIONS

- Product Spec: GS-12-651
- Application Specification: GS-20-0327



Internal Mini-SAS HD  
Cables



External Mini-SAS HD  
Cables



External Mini-SAS HD  
Connectors



Internal Mini-SAS HD  
Connectors

## PART NUMBERS External and Internal Board Connectors

| Part Number    | Product Description                                           | Signal Pairs |
|----------------|---------------------------------------------------------------|--------------|
| 10112626-101LF | Mini-SAS HD 1 X 1 External Assembly (6 & 12 Gb/s per channel) | 8 Pairs      |
| 10112627-101LF | Mini-SAS HD 1 X 2 External Assembly (6 & 12 Gb/s per channel) | 16 Pairs     |
| 10112628-101LF | Mini-SAS HD 1 X 4 External Assembly (6 & 12 Gb/s per channel) | 32 Pairs     |
| 10112632-101LF | Mini-SAS HD 1 X 1 Internal Assembly (6 & 12 Gb/s per channel) | 8 Pairs      |
| 10112633-101LF | Mini-SAS HD 1 X 2 Internal Assembly (6 & 12 Gb/s per channel) | 16 Pairs     |
| 10112634-101LF | Mini-SAS HD 1 X 4 Internal Assembly (6 & 12 Gb/s per channel) | 32 Pairs     |

## PART NUMBERS External and Internal Cable Assemblies

| Part Number | Product Description                                                                                                                                               | Signal Pairs |
|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|
| 10112041    | Mini-SAS HD to mini-SAS HD passive external cable assembly - 4x configuration – SAS 2.1 ( 6Gb/s ) compatible                                                      | 8 pairs      |
| 10117771    | Mini-SAS HD to mini-SAS passive external cable assembly - SAS 2.1 ( 6Gb/s ) compatible - 4x configuration on mini-SAS HD end and universal keying on mini-SAS end | 8 pairs      |
| 10112359    | Mini-SAS HD to mini-SAS HD passive external cable assembly - 8x configuration – SAS 2.1 ( 6Gb/s ) compatible                                                      | 16 pairs     |
| 10117947    | Mini-SAS HD to mini-SAS passive external cable assembly - SAS 2.1 ( 6Gb/s ) compatible - 8x configuration on mini-SAS HD end and universal keying on mini-SAS end | 16 pairs     |
| 10117949    | Mini-SAS HD to mini-SAS HD passive external cable assembly - 4x configuration – proposed SAS 3.0 ( 12Gb/s ) compatible                                            | 8 pairs      |
| 10117950    | Mini-SAS HD to mini-SAS HD passive external cable assembly - 8x configuration-proposed SAS 3.0 ( 12Gb/s ) compatible                                              | 16 pairs     |
| 10119217    | Mini-SAS HD to mini-SAS HD passive internal cable assembly - 4x configuration – SAS 2.1 ( 6Gb/s ) compatible                                                      | 8 pairs      |
| 10119312    | Mini-SAS HD to mini-SAS HD passive internal cable assembly - 4x configuration – SAS 3.0 ( 12Gb/s ) compatible                                                     | 8 pairs      |
| 10119577    | Mini-SAS HD to mini-SAS HD passive internal cable assembly - 8x configuration – SAS 2.1 ( 6Gb/s ) compatible                                                      | 16 pairs     |
| 10119576    | Mini-SAS HD to mini-SAS HD passive internal cable assembly - 8x configuration – SAS 3.0 ( 12Gb/s ) compatible                                                     | 16 pairs     |

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9