

# Vision System FH Series

Industry's Fastest Compact Vision System

The Fastest **FH**



» Easy to Integrate in Machines

» Increase Machine Speed

» Perform High-precision Machine Operation

# Industry's Fastest\* Compact Vision System A New Concept in Image Processing That Considers

It's time to move beyond simply increasing the speed of image processing and start seriously shortening Machine cycle time. This is the concept that gave birth to OMRON's FH-series Vision System and its best-in-the-industry speed.

Manufacturing Machines are operated through the interaction of sensors, PLCs, servomotors, and other devices. Vision Systems measure positions and perform inspections, and the results are used to control the operation of Machines. The demand for faster, more precise Vision System operation is the primary requirement. The FH-series Vision System provides higher speed and precision for Machine cycle time and is loaded with all of the performance required to move Machines quickly and at high precision into a compact Controller for embedding into Machine. And even though the Camera/communications interfaces, image processing algorithms, and other features of this complete image processing system are built into one housing, the flexibility of a PC-based image processing system is also provided to help increase efficiency in the frequent reuse of Machine designs and in design changes.

\*Based on OMRON investigation in May 2013.



Shorter Machine Cycle Times

Logic control



- Sysmac is a trademark or registered trademark of OMRON corporation in Japan and other countries for OMRON factory automation products.
- Think&See is a trademark or registered trademark of OMRON Corporation in Japan and other countries.
- EtherCAT® is registered trademark and patented technology, licensed by Beckhoff Automation GmbH, Germany.
- Windows, Microsoft® Visual Studio® are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.
- The Microsoft .NET software is used to connect users, information, systems, and devices.
- QR Code is registered trademarks of DENSO WAVE INCORPORATED in Japan and in other countries.
- Other company names and product names in this document are the trademarks or registered trademarks of their respective companies.
- The product photographs and figures that are used in this catalog may vary somewhat from the actual products.
- Microsoft product screen shot(s) reprinted with permission from Microsoft Corporation.

# Machine Cycle Time

## Increase Machine Speed >> p4



- **High-speed Response to Execution Instructions from a PLC**

A high-speed image bus and 4-core CPU processing increase the speed at every step, from image input to data output.


- **Multiple camera inspections provide total judgement results**

Calculations are easy to set for the results from four parallel tasks.

- **Quickly Outputting Measurement Results to a PLC**

You can output results to an NJ-series Machine Automation Controller on an EtherCAT communications cycle of 500  $\mu$ s.

## Perform High-precision Machine Operation >> p8



- **Measurements for Out-of-focus or Rotated Images**

The new Shape Search III processing item provides superior stability.

- **No Worker-dependence in Calibration Accuracy**

Vision master calibration is provided.

## Easy to Integrate in Machines >> p10



- **Shared Machine Interface**

Microsoft® .NET is supported.

- **Display Only Required Menu Commands on the Operation Interface**

User interface customization is supported.

- **Fast Support for Additional Measurement Needs**


Complete processing item libraries are provided.

## Process Higher-resolution Images without Increasing the Machine Cycle Time




### High-speed Image Input **Fastest: 3.3 ms**

Camera resolution, driven by higher expectations for quality, continues to increase. OMRON has greatly reduced the input time and image transfer time to provide high-speed processing to match the speed of Machine applications for high-resolution images. Even with more Cameras and higher resolution, high-speed image input will contribute to increasing throughput.





### Realtime Image Transfer

High-resolution Cameras capture large amounts of data, which can make a bottleneck out of the transfer speed time in addition to the image input time. An FH-series Controller provides a faster, multi-line image bus to enable realtime transfer of large amounts of image data for high-resolution Cameras or multiple Cameras. If high-precision measurements were sacrificed due to speed, the FH Series returns your precision without increasing cycle time.



### Ultra-high-speed Searching **Shape Search III**

New technology makes search algorithms nine times faster than before. Even for unstable image conditions, including light interference, overlapping shapes, gloss, and incomplete images, stable searching is possible without reducing speed, resulting in a increased stability.




## Four-core CPU\* to Meet High-speed Demands for Different Machines


\*for high speed controllers only

### Case1 Perform Calculations for Multiple Cameras without Delay

Even when the measurement results of sequential operations are dependent on the speed of the independent action, parallel processing allows high speed performance without any dwell time. The measurement results from four cores can be easily calculated on one Controller to achieve continuous interaction without any special programming.




### Measuring the Next Workpiece without Waiting Time



### Frequently Waiting for Processing with a Standard Vision Sensor

The lack of the ability for standard Vision Sensors to handle parallel processing creates waiting time everywhere. If the Machine cycle time cannot be increased, a Controller must be added for each process to perform parallel processing, increasing costs.





## Four-core CPU\* to Meet High-speed Demands for Different Machines

\*for high speed controllers only

### Case2 Machine Cycle Time Reduced to 1/4\* of Previous Time

Four cores process triggers, so the trigger interval can be 1/4th\* of previous models.


\*In-house comparison.



#### Multi-input Function Continuous High-speed Image Capture

### Higher Speed from Advanced Image Capture and Parallel Measurements



Each camera has its own image buffer for storing image data that is separate from the main memory used for measurement processing. This allows for up to 256 frames of continuous high-speed image capture even while the main memory is processing measurement data.



\*The number of images that can be captured depends on the Controller and the Camera that is connected to it. Refer to the user's manual for details.

### Case3 Process Multiple Lines in Parallel without Any Waiting Time

Four controllers are compressed into one without increasing the line cycle time. You can greatly reduce costs for processes that involve many lines.



# Fast Output of Measurement Results to Reduce Machine Cycle Time


## EtherCAT Machine Control Network

EtherCAT is a high-speed open network that is ideal for Machine control. You can use EtherCAT to connect to NJ-series Machine Automation Controllers and motion control G5-series Servomotors and Servo Drives to increase the control speed over everyday communications protocols from workpiece detection to starting axis motion.


### ■ Features

- Communications cycle as low as 500  $\mu$ s
- Motion control that is synchronized with the communications cycle

### Communications Cycle



### Time from Trigger Input to Producing Measurement Results





Note: The times given above are typical times. They depend on parameter settings.

## Positioning Solution That Eliminates Workpiece Dwell Time: Continuous Alignment Patent Pending

For a Machine that requires micron precision, one alignment is not always enough to obtain an acceptable error level, but executing multiple alignments greatly increases the processing time. OMRON provides control methods that eliminate workpiece dwell time, the main cause of increased processing time. Our Sysmac Automation Platform achieves high-speed, high-precision control that continuously detects workpiece positions and successively updates the travel distance to quickly approach the target position.





### [Previous Vision Sensors]



The dotted box indicates the target precision range.

### [Sysmac]




The dotted box indicates the target precision range.

Note: Please ask your OMRON representative for details.

# The High-precision Object Detection Required for Positioning Think & See


## Low-error Position Detection Even with Blurry Images

Over the years, OMRON has perfected techniques to search for and match templates at high speed. From these techniques Shape Search III provides advanced robustness, which is critical on FA sites. When measuring lamination of glass or other processes where the distance to the workpiece from the Camera varies, size differences and focal shifts can occur. Even in cases like this, the new Shape Search III algorithm detects positions with limited error.



## Stable Searching with Limited Error Even under Adverse Conditions


Stable searching is possible even under the following adverse conditions, which occur far too often in actual measurement applications.



## Visualization of Comparisons Enables Easy Setup of High-precision Searching

Patent Pending

Advanced searching is accompanied by many parameters that must be tuned to match the application. However, it is difficult for the person making the settings to see the internal process. Extensive time is required to make the most of tool performance. With Shape Search III, you can visualize comparisons between the model data and a part of the measurement object to easily see when comparisons are not matched well for the inspection. Visualization of the comparison level, allows for parameters to be adjusted simply to obtain the best performance.




## Converting Measurement Results to Output User Units

### Support for the Main Stages and Robots Used for 2D Positioning

The FH Controllers contain special setup displays for the stages and robots that are commonly used on FA sites. You just fill in the settings to easily output axis travel amounts for stages and robots.

User Interface Example



Application Examples




| Item   |        |                                 |                               |
|--------|--------|---------------------------------|-------------------------------|
| Stages | XY     | θ axis: Direct drive            | Camera axis movement: None    |
|        |        |                                 | Camera axis movement: X axis  |
|        |        |                                 | Camera axis movement: Y axis  |
|        |        |                                 | Camera axis movement: XY axes |
|        | XYθ    | θ axis: Linear drive            | Camera axis movement: None    |
|        |        |                                 | Camera axis movement: X axis  |
|        |        |                                 | Camera axis movement: Y axis  |
|        |        |                                 | Camera axis movement: XY axes |
|        | θXY    | θ axis: Direct drive            | Camera axis movement: None    |
|        |        |                                 | Camera axis movement: X axis  |
|        |        | θ axis: Linear drive            | Camera axis movement: Y axis  |
|        |        |                                 | Camera axis movement: XY axes |
| Robots | UVW    | Direct fulcrum motion           | Camera axis movement: None    |
|        |        |                                 | Camera axis movement: X axis  |
|        | UVWR   | Rotary fulcrum motion           | Camera axis movement: Y axis  |
|        |        |                                 | Camera axis movement: XY axes |
|        | 3 axes | Control method: Fixed positions | Camera axis movement: X axis  |
|        |        |                                 | Camera axis movement: Y axis  |

### Vision Master Calibration for High-precision Positioning Even with Normal Lenses

To perform high-precision positioning, the coordinate system must be accurately aligned between image processing and the stage or robot. Calibration is used to achieve this. Normally trial and error in the actual application environment is necessary, which requires experience in moving sampling points and a experience with the influence of minor tilt in the Camera installation, the influence of lens distortion, and other factors. With an FH Controller, all you need to do is set a minimum number of conditions. Movement patterns for the sampling points are automatically calculated to optimize the stage/robot axis travel ranges, imaging processing field of view, and other factors, and the required axis travel amounts are sent to the PLC. By moving the system according to the instructions, optimum sampling is achieved and the coordinate systems for image processing and the stage/robot are accurately aligned. Correction coefficients are simultaneously calculated for Camera tilt and lens distortion. If you use the calibration conversion parameters that are made with this function, you can easily achieve high-precision positioning even for normal lenses with high distortion rates.


› Page 15: Setup Flow for Vision Master Calibration



## Easily Integrate Interfaces into the Machine

### Easy Integration into an Machine Monitor Support for .NET User Interface Controls

Custom .NET controls are supported so that you can easily display FH Controller measurement images and measurement results on a Machine PC.



#### Easy Customization

① Custom controls for FH measurement images and measurement results are laid out on Microsoft Visual Studio®.

② Instead of writing the program code from scratch to build interfaces, you can easily build the interfaces simply by pasting custom controls.



### Easy Setting and Operation Using a Touch Pen

NEW

The Touch Panel Monitor FH-MT12 has been added to the FH Series. The FH-MT12 is equipped with a 12.1-inch screen that is ideal for replacement of existing models. You can adjust all the settings by touching the screen.

- 12.1 inch XGA
- Panel mountable
- VESA mountable



# Design the Connected Components with One Software Application

## Develop Machine Control Programs with One Software Application: Sysmac Studio

Use the Automation Software Sysmac Studio to set up all of the slaves connected via EtherCAT. Simulate and debug motion control, logic, drives, and sensing on an integrated platform to reduce the work required for Machine design.

### One Software



Sysmac Studio version 1.07 or higher supports the FH Series.



NJ-series  
Machine Automation Controller




FH-series  
Vision System




G5-series  
Servomotors and Servo Drives

## Minimize Commissioning and Adjustment Work with Simulations


Integrated simulations linked to an NJ-series Machine Automation Controller lets you verify the NJ-series program logic and check how the FH-series Vision System responds to each control signal. You can directly edit the EtherCAT I/O map to send measurement commands to the FH-series Vision System.



EtherCAT  
Configuration  
Window



I/O Map Window



Programming  
Window



Data Trace Window

# Easy Setup with Program Scalability

## Customize Original Operation Interfaces

### Arrange the Interface Elements Flexibly

You can flexibly change the image display composition to display an entire image, enlarge part of an image, or display images from different Cameras.

### Nine screen layout


Up to 9 screens can be stored depending on the application or user classification.

### Show only the buttons you need

Choose from our library of buttons and position them anywhere on-screen to best support your daily operation, without ‘screen clutter’.

### Move windows freely

Drag and drop windows where you want. You can also change the box size and delete.



## Hide Unnecessary Adjustment Commands

With only menu operations on the Controller, you can customize the setting displays in dialog boxes for processing items. For example, you can set up the interface to hide any parameters from the operator.

### Freely Lay Out Dialog Box Contents




### Completed



Only a parameter required for daily operation can be displayed.

## Completely Different Operation Interfaces for the Designer and Operator

Accounts can be used to keep completely different operation interfaces for the designer and the operator. You can set up to eight levels of security for up to 50 items for each account. You can record operation logs for each account to enable smoothly isolating problems when troubleshooting.



## Flow Viewer Builds the Measurement Process with Flow Chart Programming


Just add any of the large variety of processing items to the measurement flow to build the basic program for image processing.

All processing items have menus for easy setup and adjustment.

Easily build the best imaging processing for each application to smoothly complete testing and adjustments without programming.

### Flowchart

Just add processing items from the processing item list to visually edit the flow.



### Processing Item List

### Folders

You can group processing units into named folders. By managing related processing together and hiding lower levels, you can display even long measurement flows in a way that easily shows the overall flow.

### Flowchart Output

You can save the flowchart as an image file.


### Branching

You can use conditional branching to branch according to the execution results of the previous processing units or you can use branching controls with external commands through parallel I/O, PLC Links, or no-protocol communications.

>Page 25: Controlling Flow Branching Conditions from an External Device.


## Easy Multi-language Support: Change between 9 Languages

You can change display messages between nine different languages: Japanese, English, Chinese (traditional or simplified), German, French, Italian, Spanish, and Korean. You can display the best language for the user for applications in other countries.



## High-precision Alignment Library

### Alignment Calculations



Four specialized processing items for alignment calculations are supported. These can be combined to easily execute alignments that require complex calculations on previous systems models or computers.

#### Movement Single Position

The axis movement that is required to match the measured position angle to the reference position angle is calculated.

#### Convert Position Data

The position angle after the specified axis movement is calculated.

#### Movement Multi Points

The axis movements that are required to match the measured position angles to the corresponding reference position angles are calculated.


#### Position Data Calculation

The specified position angle is calculated from the measured position.

### Examples of Available Alignments


#### Alignment Using Positions and Angles

The alignment based on positions and angles using the Movement Single Position processing item is available to align the positions of workpieces with different sizes. This alignment allows the use of offsets to achieve flexible positioning.



#### Alignment with Side Measurements


This alignment method measures the sides of the workpiece using the Movement Multi Points processing item. You can use this method to position the workpiece without alignment marks or when its corners cannot be measured.




#### Alignment Using Corresponding Points

The Movement Multi Points processing item is used for alignment based on relational positions.

This method is used to align the respective positions on sub-strates.





## Setup Aids




## Optimum Focus and Aperture Settings

Until now, focus and brightness settings were adjusted according to experience and intuition. But now they can be evaluated numerically and visually on graphs. This allows quick verification of optimum focus and aperture settings to eliminate inconsistencies in settings caused by worker differences so that you can achieve even higher levels of measurement accuracy.




- Camera installation and setup are easy.
- Errors can be generated when the focus or aperture changes.
- You can determine the numerical values for the focus and aperture for the master workpiece so that essentially anyone can reproduce the same conditions.

## Calibration




## Vision Master Calibration

With Vision Master Calibration, the FH-series Vision System automatically calculates the movement patterns for sampling points to optimize the stage/robot axis travel ranges, imaging processing field of view, and other factors, and the required axis movements are sent to the PLC. By moving the system accordingly, optimum sampling is achieved and the coordinate systems for image processing and the stage/robot are accurately aligned. Correction coefficients are simultaneously calculated for Camera tilt and lens distortion. If you use the calibration conversion parameters that are made with this function, you can easily achieve high-precision positioning even for normal lenses with high distortion rates.




## Precise Rotational Position Estimation

### Previous Methods



In order to estimate a rotational center position precisely, it is required to move to sampling points to ensure a large rotational angle in the  $\theta$  direction on the stage. With the previous methods, users had to calculate such sampling points and program the stage axis movements to move to the sampling points on the PLC. Finding the best sampling points was a trial and error process that required a significant amount of time.

### FH Series



The FH-series Vision System automatically calculates sampling points in the field of view to ensure the maximum rotational angle in the  $\theta$  direction on the stage and sends the stage axis movement requests to the PLC to move to the sampling points.

"Movement to sampling points by combining parallel movement and rotational movement", which was difficult to implement due to requiring complex calculations, can be now easily achieved by moving stage axes according to the instructions from the FH-series Vision System.

## Automatically Calculated Calibration Data

Both affine transformation parameters and distortion correction parameters are calculated at the same time.

### Affine Transformation

Positional relationship of Camera and stage

Stage axis movement per Camera pixel

Stage axis orthogonality


### Distortion Correction

Trapezoidal compensation parameter

Lens distortion compensation parameter

## Inspection and Measurement Process Library

### Search



A complete array of search tools are provided to meet an array of requirements. Minute difference detection is supported without false detection.

#### Sensitive Search

This allows the recognition of very subtle differences that cannot be detected through ordinary search processes, by dividing the registered model image into several regions and carefully matching them. Delicate threshold setting is not required saving time in the registration process.




Different conditions for dividing the model image can be set.


#### Flexible Search

When inspecting workpieces with some variations in shape, these characteristics are sometimes recognized erroneously as defects. Flexible Search ensures accurate searches regardless of some variations in print quality or shape, by registering several images of non-defective products as models. It helps you decrease your inspection failure rate by rejecting defective products only.

#### Inspection of characters on IC chips




### Edges



These processing items let you measure positions, widths, and the number of edges from edge extraction.


#### Circular Scan Edge Position

You can measure the center coordinates, diameter, and radius of a round workpiece without performing any calculations simply by drawing one measurement region.



#### Circular Scan Edge Width

You can measure the center coordinates, width, and thickness of a ring-shaped workpiece without requiring additional calculation.



### Defects




These processing items are ideal for external appearance inspections for damage, foreign matter, etc.

#### Inspections of Scratches and Dirt

Subtle scratches and dirt can be detected with more fine-tuned conditions compared to conventional inspections. Since you can clearly distinguish defects to be detected from the background, the failure detection rate can be decreased. Profiles of defects and comparison elements can be displayed on the screen in real time. You can adjust by confirming the settings and detection results on the image. Fine parameters for defect detection allow fine settings at the pixel level.



#### Scratch detection profile displayed on the screen




**Comparison element display**  
Intervals and sizes of comparing elements are displayed.

**Profile display**  
Defects of each direction for detection are displayed as wave profiles.

#### Fine Matching

It is useful for detecting scratches, chipped edges or subtle dirt in complex backgrounds.



#### Defect

It is useful for detecting scratches and dirt in plain backgrounds.



## Character Inspections/OCR



These processing items provide the functions that are required for inspections of characters such as dates and lot codes.


### Stable Reading of Difficult-to-read Characters

Sometimes characters printed may be too close to each other, and character strings may be printed on curved surfaces. Even these instance, stable reading is now possible.

#### Touching characters




#### Curved character strings



### Correct Segmentation of Close or Touching Characters

When characters are too close to each other or touching, previous methods often failed to segment out each character; sometimes two characters at once or over-segmentation into character fragments. OMRON's newly developed optimized character segmentation method generates a number of extraction candidates from an entire character string to find out a correct answer from these candidates, ensuring overall consistency. This unique segmentation method brings robust character recognition for touching, distorted and/or inclined characters that have been previously difficult to read.




### Easy Installation with Built-in Dictionary

Many previous character reading methods required dictionary setup before usage, which was tedious step. In contrary, based on OMRON's long and rich experiences in FA fields, possible variations of fonts and printing are already included and optimized to provide sophisticated performance as it is.

Characters from most printers can be read, including dot and impact printers. **Handles Approx. 80 Fonts**



## Codes



FH enables bar / 2D codes reading as well.

Printing quality evaluation based on ISO standards is supported.

Applicable standards: ISO/IEC 15415 (The data matrix standard in ECC 200 is supported) and ISO/IEC 15416

FH can provide judgement of the code quality based on standardized printing quality criteria.



## Glue Bead Inspection




You can inspect coating of a specified color for gaps or runoffs along the coating path.


### Automatic Extraction of Complex Measurement Region Shapes

Measurement regions are no longer restricted to combinations of rectangles and circles. You can freely set the shape according to the outline of the workpiece. It's easy to set the measurement regions. Just specify one portion of the region to extract, and a continuous region with a similar color is extracted automatically. You can set precise regions for measurements even for scratch inspections or labeling on workpieces with complex shapes. This method to set measurement regions can be used for Gravity and Area, Color Data, Labeling, Defect, and Precise Defect processing items.


Specify part of the area to extract as the measurement region.



The region with a similar color to the specified area is extracted automatically.




# Image Filter Library



## Advanced Filter

The image filter library has been condensed into one processing item. This allows you to easily set complex filtering as required for external inspections.




You set up to 16 of the 24 different filters.

**Advanced Filter**


Many different filter functions can be set with just one processing unit.

The average image is obtained from multiple images.




## Labeling Filter

This filter uses label processing to output an extracted image that contains only the specified characteristic labels.




## Calculations between Images

You can perform arithmetic operations, bit operations, averaging, or maximum/minimum operations between two images.




## Custom Filter

You can set the mask coefficients as required for these filters. The mask size can be up to 21 × 21. You can more flexibly set image smoothing, edge extractions, dilation, and erosion.




## Brightness Correct Filter

These filter cut out uneven lighting and changes in brightness caused by work-piece surface irregularities to make characteristic features stand out clearly.




## Stripe Removal Filter II

The stripped pattern is filtered out so that only required aspects are shown clearly. Vertical, horizontal, and diagonal stripes can be removed.



## High Dynamic Range to Easily Combine Images

To simply combine images, you must set the imaging conditions and create the images that you want to obtain. With OMRON's high dynamic range function, all you need to do is to set the upper and lower brightness images on a graph of the image brightness distribution to make the adjustments.




## What is Real Color Sensing?



Patented

In order to secure stable measurements in different inspection environments, FH Series feature Omron's proprietary Real Color Sensing processing, in addition to the conventional color image processing.

### Color Segmentation Processing




Color images taken by the camera are processed after being converted into black and white pixels. The color extracted is represented as white, and the other colors as black. Based on minimum information, high speed processing is possible. Since color data is limited only to brightness, however, it takes a long time to make optical adjustments for extracting color features.

### Color Image Processing



Color images are converted into 256 levels of black-and-white brightness and the contrasts of specific colors is enhanced. More precise, stable results can be produced compared to color segmentation. However, this method has difficulty in capturing subtle variations in color because all colors are converted into black-and-white brightness levels. Therefore, it is difficult to detect subtle changes in images with low contrast.

### Real Color Sensing



Different colors are represented as different positions in the 3D RGB space. Subtle variations in color can be recognized by representing them as distances between different color pixels comprising this space. Thus, scratches and dirt can be detected accurately even in images with low contrast.




Edges are detected reliably even when the contrast between the background and subject is low.

Previous image processing

OMRON FH series

# Utility Library

Unit Macro/  
Unit Calculation Macro



## Unit Macro

Unit Macro let you easily achieve flow control that normally requires complex programming from the user interface. Improvements to the setup from the user interface provides ease of selection and modification of the programming process.

① Select the process to use

② Set the parameters

③ Insert the process

Registered images

Reference Variable List

Function Guidance

Variables can be used in Unit Macro to access processing item data and system data.

For example, it would previously have been long and complicated to change the set parameters of a processing item for each product model. With a Unit Calculation Macro processing item, the flow is shorter and setting changes are easy to achieve.

Previous Vision Sensors

FH/FZ-series Unit Macro

Easy to change

Just enter the values of the variables to update the parameters.

' Branching for each product model  
Select INDEX@  
Case 0  
ExtCond0@ = 1 ' Area  
ExtParam0@ = 0  
ExtParam1@ = 10000  
Case 1  
ExtCond0@ = 4 ' Elliptic major axis  
ExtParam0@ = 0  
ExtParam1@ = 100  
Case 2  
ExtCond0@ = 7 ' Rectangle width  
ExtParam0@ = 0  
ExtParam1@ = 200  
End Select

## Unit Calculation Macro

You can create expressions that require multiple lines in one processing item. In addition to making calculations, you can also make judgements based on the calculation results of the processing items.

Judgement condition for calculation results

Example 1: Multiline Expression

DET# = A0@ \* B1@ - A1@ \* B0@ ' Calculates intersection  
CX# = (B0@ \* C1@ - B1@ \* C0@) / DET# ' X coordinate of intersection  
CY# = (A1@ \* C0@ - A0@ \* C1@) / DET# ' Y coordinate of intersection

Example 2: Calculations to Drive Branching or Loops

Max# = 0  
For i& = 0 To 10  
If (Max # < value#(i&)) Then  
Max# = value#(i&)  
EndIf  
Next  
RESULTDATA#(0) = Max#

## User Data



User Data

### Ideal for Managing Inspection Standards and for Statistical Analysis of Inspection Results

Shared data used within scene groups as constants and variables in the measurement flow can be set as user data. With the shared data, you can use the measurement flow in many new ways, including standard values, conditional branching flags, and counters.

#### Application Example 1 Unified Management of Judgment Values

When setting up complex scene data, such as the data required for inspection of many different models, you can unify management of important judgment values for inspections to easily manage and then adjust them later. Also, if you isolate in advance the settings that are critical to inspection performance (and normally known only to the designer) as user data, the locations that require adjustment can be clarified so that the user can more easily make adjustments.

#### Application Example 2 Statistical Information on Productivity Indices

User data can be used as variables that can be read and written in the inspection flow. It can also be used for counters for the number of inspected workpieces or the number of NG workpieces. Math functions can be used to calculate failure rates and display them onscreen so that productivity can be checked at any time.

#### Adjustment of All User Data in a List


| No. | Data    | Comment                  |
|-----|---------|--------------------------|
| 0   | 00.0000 | Man 1-A Search Judgement |
| 1   | 00.0000 | Man 1-B Search Judgement |
| 2   | 00.0000 | Man 2-A Search Judgement |
| 3   | 00.0000 | Man 2-B Search Judgement |
| 4   | 0.0000  | NG Counter               |
| 5   | 0.0000  |                          |
| 6   | 0.0000  |                          |
| 7   | 0.0000  |                          |
| 8   | 0.0000  |                          |
| 9   | 0.0000  |                          |

#### Indices Displayed Onscreen with the Result Display Function




### Application Method

All you have to do is set a User Data processing item in the inspection flow.



The data that is set as user data is used as shared constants and variables in different scenes.



## Trend Monitor




Trend Monitor

### Results Analysis with Trend Monitors


You can graph trends in measurement values to output warnings before failures occur. This helps provide feedback to earlier processes to prevent NGs in advance and to analyze the causes of NGs.

#### Prevent High Defect Rates in Advance




You can set the warning range to output warnings before NGs become frequent to provide feedback to earlier processes.

#### Cause Analysis when Defects Occur



## Optimum Operation both Online and Offline

You can log measurement images longterm, or you can perform verifications and adjustments on a computer without stopping the FH-series Vision System.



## 1 Daily Monitoring

## 2 Periodic Adjustments and Inspection Adjustments

### 3 Handling Unstable Inspections or Measurement Failure

## 4 Adding Inspections or Making Changes for New Models

CSV files allow you to easily understand the parameter settings. Also, you can easily change any of the settings.

## 1 Comparisons

[illegible]


## 2 Remote Adjustment

Setting changes

## Remote Operation Centralizes Monitoring and Adjustment of multiple controllers

You can check the status and adjust the settings of multiple units on one computer.

This enables efficient adjustment of Camera images when commissioning a system and application of test adjustment results.



### Application Example 1

#### Operating Several FH from One Location

1

When commissioning an installation from one location you can adjust the camera for all the controllers located along the line. There's no need to go to and from each Controller, and you can compare Camera images under various conditions to adjust them.

2

If setting changes are necessary to add a new model, you can do all the required work at the same time without making trips to all of the Controllers.

3

You can easily balance the thresholds between Controllers when increasing inspection stability through testing at the production line.

### Application Example 2

#### Display images from multiple controllers

1

Space savings with a single monitor installation.

2

Single location programming for multiple controllers facilitates adjustments and reduces programmer movement.

Note: Ask your OMRON representative about obtaining simulation software for a computer.

## Saving and Using Measurement Images

### Save Images Directly in JPEG or BMP Format

You can easily view images on a computer or attach them to reports. With BMP files, you can measure them again on the Vision controller.

### Restricting the Areas of Saved Images


By restricting the areas that are saved, file sizes are smaller so you can continue to log even more files.



### Save Both Filtered and Unfiltered Images

You can save both the filtered images that were actually measured and the raw images taken directly from the Camera. You can therefore tell if an NG was caused by the input image or by the filter settings.

#### Filtered Images




#### Unfiltered Images



# Utilities That Don't Stop Your Machines


## Making Confirmations and Adjustments without Stopping Production Non-stop adjustment

Parallel processing on Four-core CPU not only speeds up measurements, but it enables parallel processing of measurements and adjustments. Automatic distributed processing means that measurements are not delayed when adjustments are applied.




## Doubly effective when combined with the Non-stop adjustment mode NG analyzer

You can display in a structured manner a graph showing the results measured at once on logging images. This lets you identify the cause of a given NG much more quickly. You can also measure all images again after changing a given setting, to check the reliability of the new setting. Adjustment and troubleshooting has never been so quick, simple and reliable.



## Save All Images Even during Measurements High speed logging

The Four-core CPU can also perform parallel processing of measurements and image logging, with high-speed connection to a high-capacity hard disk (3terabytes). Trend analysis of saved images, quickly isolates NG's and facilitates countermeasures.



- \*1 All images can be saved under the following conditions:
- 300,000-pixel camera x 1 unit . Measurement time: 20 ms
  - Images can be saved continuously for approx. five days when a 3-terabyte HDD is used (based on 8 hours of operation a day).

### Issues


Since logging was not possible during measurement, the user had to choose either measurement or logging. Accordingly, not all images could be saved or image input triggers had to be delayed depending on the measurement trigger intervals.

### Resolution

Measurement and image logging are processed completely in parallel. As a result, you can save all images.


# Seamless Communications with Peripheral Devices

## Complete Interfaces for All Connected Devices



## Controlling Flow Branching Conditions from an External Device

You can control branching by using commands and signal inputs from external devices as branching conditions for the measurement flow.




## Communication Command Macro

You can shorten the communications time by using commands for complex controls or by shortening multiple commands. You can also define how the Vision System responds to the communications commands. For example, you can define one command to change both a scene and perform measurements.

Customize I/O command

| No.                                   | Bus/IO | Command name | Function name |
|---------------------------------------|--------|--------------|---------------|
| <input checked="" type="checkbox"/> 0 | True   | CMD0000      | FUNC_0000     |
| <input type="checkbox"/> 1            | True   | CMD0001      | FUNC_0001     |
| <input type="checkbox"/> 2            | True   | CMD0002      | FUNC_0002     |
| <input type="checkbox"/> 3            | True   | CMD0003      | FUNC_0003     |
| <input type="checkbox"/> 4            | True   | CMD0004      | FUNC_0004     |
| <input type="checkbox"/> 5            | True   | CMD0005      | FUNC_0005     |
| <input type="checkbox"/> 6            | True   | CMD0006      | FUNC_0006     |
| <input type="checkbox"/> 7            | True   | CMD0007      | FUNC_0007     |
| <input type="checkbox"/> 8            | True   | CMD0008      | FUNC_0008     |
| <input type="checkbox"/> 9            | True   | CMD0009      | FUNC_0009     |

You can define up to 256 commands




# Options for More Power Customization

## Application Producer provides a Development Environment to Build and Simulate Applications


You can further customize the standard controller features of the FH-series Vision System. In Application Producer custom control units allow development of original interfaces with Microsoft® Visual Studio®. The software command reference helps create original processing items, and more.

Application Producer Main Window




- ① Create workspaces.
- ② Select and change between workspaces.
- ③ Start the program in the selected workspace.
- ④ Add projects.
- ⑤ Open Microsoft® Visual Studio® projects.
- ⑥ Start the XML generation tool.
- ⑦ Open setup files.
- ⑧ Create installation files.


### Customization Example: GUI Customization



Start Add Project and select the template that will serve as a base for customization. Selecting an interface template as a base first greatly reduces the work that is required compared with programming interfaces from scratch.



The Application Producer will automatically generate a project file from the selected template so that you can open it in Microsoft® Visual Studio®. You can develop interfaces just by dragging FH-series custom controls and Windows-based controls.



Instead of writing the program code from scratch to build an interface, you can easily build the interface simply by pasting custom controls. You can immediately check and debug the operation of the GUI objects that you add.

# Easily Control Lights from Vision System


## Camera-mount Lighting Controller FLV-TCC Series



### Simple wiring and space saving

Wiring from the control panel to remote Cameras and Lights is simplified.

The more Cameras and Lights are connected to the Vision System Controller, the more effective in simplifying wiring and saving space.




## OMRON's Light Lineup

### Standard Model FLV Series

#### ■ Direct Ring Light



#### ■ Bar Light



#### ■ Coaxial Light




#### ■ Edge Type Light



#### ■ Edge Type Light



#### ■ Direct Back Light



#### ■ Dome Light



#### ■ Shadowless Light



### High-brightness Model FL Series

#### ■ Bar Light



#### ■ Direct Ring Light



OMRON also provides many other models of Lights.  
Please ask your OMRON representative for details.

# Vision System FH-Series

## Easier to Embed in Machine, Shorter Machine Cycle Times


- Calculations are easy to set for the results from four parallel tasks.
- Synchronous control of devices connected via EtherCAT is possible.
- The new Shape Search III processing item enables fast, precise, and stable measurements.
- Microsoft® .NET is supported to share machine interface with PC.
- User interface customization is supported.



## System configuration

### EtherCAT connections for FH series

Example of the FH Sensor Controllers (4-camera type)



\*1. To use STP (shielded twisted-pair) cable of category 5 or higher with double shielding (braiding and aluminum foil tape) for EtherCAT and RJ45 connector.  
\*2. To use STP (shielded twisted-pair) cable of category 5 or higher for Ethernet and RJ45 connector.

## Ordering Information

### FH Series Sensor Controllers

| Item                                                                                | CPU                             | No. of cameras | Output  | Model      |
|-------------------------------------------------------------------------------------|---------------------------------|----------------|---------|------------|
|  | High-speed Controllers (4 core) | 2              | NPN/PNP | FH-3050    |
|                                                                                     |                                 | 4              | NPN/PNP | FH-3050-10 |
|                                                                                     |                                 | 8              | NPN/PNP | FH-3050-20 |
|                                                                                     | Standard Controllers (2 core)   | 2              | NPN/PNP | FH-1050    |
|                                                                                     |                                 | 4              | NPN/PNP | FH-1050-10 |
|                                                                                     |                                 | 8              | NPN/PNP | FH-1050-20 |

### FZ5 Lite Series Sensor Controllers

| Item                                                                                | CPU              | No. of cameras | Output | Model       |
|-------------------------------------------------------------------------------------|------------------|----------------|--------|-------------|
|  | Lite Controllers | 2              | NPN    | FZ5-L350    |
|                                                                                     |                  |                | PNP    | FZ5-L355    |
|                                                                                     |                  | 4              | NPN    | FZ5-L350-10 |
|                                                                                     |                  |                | PNP    | FZ5-L355-10 |

**Note:** Refer to the FZ5 Series Data sheet (Cat. No. Q203) for details.

## Cameras

| Item                                                                                | Descriptions                                                                        | Color / Monochrome                                                                                                                                                                      | Image Acquisition Time | Model     |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|-----------|
|    | High-speed CMOS Cameras (Lens required)                                             | 12 million pixels<br>(Up to four cameras can be connected to one Controller. Up to eight cameras other than 12 million-pixel cameras can be connected to a FH-3050-20 or a FH-1050-20.) | Color                  | FH-SC12   |
|                                                                                     |                                                                                     | Monochrome                                                                                                                                                                              | 25.7 ms *              | FH-SM12   |
|    | High-speed CMOS Cameras (Lens required)                                             | 4 million pixels                                                                                                                                                                        | Color                  | FH-SC04   |
|                                                                                     |                                                                                     |                                                                                                                                                                                         | Monochrome             | FH-SM04   |
|                                                                                     |                                                                                     | 2 million pixels                                                                                                                                                                        | Color                  | FH-SC02   |
|                                                                                     |                                                                                     |                                                                                                                                                                                         | Monochrome             | FH-SM02   |
|                                                                                     |                                                                                     | 300,000 pixels                                                                                                                                                                          | Color                  | FH-SC     |
|                                                                                     |                                                                                     |                                                                                                                                                                                         | Monochrome             | FH-SM     |
|    | Digital CCD Cameras (Lens required)                                                 | 5 million pixels<br>(When connecting FZ5-L35□, up to two cameras can be connected.)                                                                                                     | Color                  | FZ-SC5M2  |
|                                                                                     |                                                                                     |                                                                                                                                                                                         | Monochrome             | FZ-S5M2   |
|    | Digital CCD Cameras (Lens required)                                                 | 2 million pixels                                                                                                                                                                        | Color                  | FZ-SC2M   |
|                                                                                     |                                                                                     |                                                                                                                                                                                         | Monochrome             | FZ-S2M    |
|    | Digital CCD Cameras (Lens required)                                                 | 300,000 pixels                                                                                                                                                                          | Color                  | FZ-SC     |
|                                                                                     |                                                                                     |                                                                                                                                                                                         | Monochrome             | FZ-S      |
|    | High-speed CCD Cameras (Lens required)                                              | 300,000 pixels                                                                                                                                                                          | Color                  | FZ-SHC    |
|                                                                                     |                                                                                     |                                                                                                                                                                                         | Monochrome             | FZ-SH     |
|    | Small Digital CCD Cameras (Lenses for small camera required)                        | 300,000-pixel flat type                                                                                                                                                                 | Color                  | FZ-SFC    |
|                                                                                     |                                                                                     |                                                                                                                                                                                         | Monochrome             | FZ-SF     |
|   | Small Digital CCD Cameras (Lenses for small camera required)                        | 300,000-pixel pen type                                                                                                                                                                  | Color                  | FZ-SPC    |
|                                                                                     |                                                                                     |                                                                                                                                                                                         | Monochrome             | FZ-SP     |
|  | Intelligent Compact CMOS Cameras (Camera + Manual Focus Lens + High power Lighting) | Narrow view                                                                                                                                                                             | Color                  | FZ-SQ010F |
|                                                                                     |                                                                                     | Standard view                                                                                                                                                                           | Color                  | FZ-SQ050F |
|                                                                                     |                                                                                     | Wide View (long-distance)                                                                                                                                                               | Color                  | FZ-SQ100F |
|                                                                                     |                                                                                     | Wide View (short-distance)                                                                                                                                                              | Color                  | FZ-SQ100N |

\* Frame rate in high speed mode when the camera is connected using two camera cables. For other conditions, please refer to the chart below.

| Model                  |             |                    | FH-SM02 | FH-SC02 | FH-SM04 | FH-SC04 | FH-SM12 | FH-SC12 |
|------------------------|-------------|--------------------|---------|---------|---------|---------|---------|---------|
| Image Acquisition Time | 2 Cables *1 | High Speed Mode *2 | 4.6ms   |         | 8.5ms   |         | 25.7ms  |         |
|                        |             | Standard Mode      | 9.7ms   |         | 17.9ms  |         | 51.3ms  |         |
|                        | 1 Cables    | High Speed Mode *2 | 9.2ms   |         | 17.0ms  |         | 51.3ms  |         |
|                        |             | Standard Mode      | 19.3ms  |         | 35.8ms  |         | 102.0ms |         |

\*1. Two Camera ports of the controller are used per one camera.

\*2. Up to 5 m Camera Cable length.

## Camera Cables

| Item                                                                                | Descriptions                                                                                                         | Model    |
|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|----------|
|  | Camera Cable<br>Cable length: 2 m, 3 m, 5m, or 10 m *2                                                               | FZ-VS3   |
|  | Bend resistant Camera Cable<br>Cable length: 2 m, 3 m, 5m, or 10 m *2                                                | FZ-VSB3  |
|  | Right-angle Camera Cable *1<br>Cable length: 2 m, 3 m, 5m, or 10 m *2                                                | FZ-VSL3  |
|  | Bend resistant Right-angle Camera Cable *1<br>Cable length: 2 m, 3 m, 5 m, or 10 m *2                                | FZ-VSLB3 |
|  | Long-distance Camera Cable<br>Cable length: 15 m *2                                                                  | FZ-VS4   |
|  | Long-distance Right-angle Camera Cable *1<br>Cable length: 15 m *2                                                   | FZ-VSL4  |
|  | Cable Extension Unit<br>Up to two Extension Units and three Cables can be connected. (Maximum cable length: 45 m *2) | FZ-VSJ   |

\*1 This Cable has an L-shaped connector on the Camera end.

\*2 The maximum cable length depends on the Camera being connected, and the model and length of the Cable being used. For further information, please refer to the "Cameras / Cables Connection Table" and "Maximum Extension Length Using Cable Extension Units FZ-VSJ table".  
When a high-speed CMOS camera FH-S□02/-S□04/-S□12 is used in the high speed mode of transmission speed, two camera cables are required.

## Cameras / Cables Connection Table

| Type of camera                                          | Model               | Cable length | High-speed CMOS cameras * |                                              |                                            |                                              |                                            |                                              |                                            |
|---------------------------------------------------------|---------------------|--------------|---------------------------|----------------------------------------------|--------------------------------------------|----------------------------------------------|--------------------------------------------|----------------------------------------------|--------------------------------------------|
|                                                         |                     |              | 300,000-pixel             | 2 million-pixel                              |                                            | 4 million-pixel                              |                                            | 12 million-pixel                             |                                            |
|                                                         |                     |              | FH-SM/SC                  | FH-SM02/SC02                                 |                                            | FH-SM04/SC04                                 |                                            | FH-SM12/SC12                                 |                                            |
|                                                         |                     |              | —                         | High speed mode of transmission speed select | Standard mode of transmission speed select | High speed mode of transmission speed select | Standard mode of transmission speed select | High speed mode of transmission speed select | Standard mode of transmission speed select |
| Camera Cables<br>Right-angle camera cables              | FZ-VS3<br>FZ-VSL3   | 2 m          | Yes                       | Yes                                          | Yes                                        | Yes                                          | Yes                                        | Yes                                          | Yes                                        |
|                                                         |                     | 3 m          | Yes                       | Yes                                          | Yes                                        | Yes                                          | Yes                                        | Yes                                          | Yes                                        |
|                                                         |                     | 5 m          | Yes                       | Yes                                          | Yes                                        | Yes                                          | Yes                                        | Yes                                          | Yes                                        |
|                                                         |                     | 10 m         | Yes                       | No                                           | Yes                                        | No                                           | Yes                                        | No                                           | Yes                                        |
| Bend resistant camera cables<br>Bend resistant          | FZ-VSB3<br>FZ-VSLB3 | 2 m          | Yes                       | Yes                                          | Yes                                        | Yes                                          | Yes                                        | Yes                                          | Yes                                        |
|                                                         |                     | 3 m          | Yes                       | Yes                                          | Yes                                        | Yes                                          | Yes                                        | Yes                                          | Yes                                        |
|                                                         |                     | 5 m          | Yes                       | Yes                                          | Yes                                        | Yes                                          | Yes                                        | Yes                                          | Yes                                        |
|                                                         |                     | 10 m         | Yes                       | No                                           | Yes                                        | No                                           | Yes                                        | No                                           | Yes                                        |
| Long-distance camera cable<br>Long-distance right-angle | FZ-VS4<br>FZ-VSL4   | 15 m         | Yes                       | No                                           | Yes                                        | No                                           | Yes                                        | No                                           | Yes                                        |





| Type of camera                                                       | Model               | Cable length | Digital CCD cameras |                 |                 | Small digital CCD cameras<br>Pen type / flat type | High-speed CCD cameras | Intelligent compact CMOS cameras |
|----------------------------------------------------------------------|---------------------|--------------|---------------------|-----------------|-----------------|---------------------------------------------------|------------------------|----------------------------------|
|                                                                      |                     |              | 300,000-pixel       | 2 million-pixel | 5 million-pixel |                                                   |                        |                                  |
|                                                                      |                     |              | FZ-S/SC             | FZ-S2M/SC2M     | FZ-S5M2/SC5M2   | FZ-SF/SFC<br>FZ-SP/SPC                            | FZ-SH/SHC              | FZ-SQ□                           |
| Camera Cables<br>Right-angle camera cables                           | FZ-VS3<br>FZ-VSL3   | 2 m          | Yes                 | Yes             | Yes             | Yes                                               | Yes                    | Yes                              |
|                                                                      |                     | 3 m          | Yes                 | Yes             | Yes             | Yes                                               | Yes                    | Yes                              |
|                                                                      |                     | 5 m          | Yes                 | Yes             | Yes             | Yes                                               | Yes                    | Yes                              |
|                                                                      |                     | 10 m         | Yes                 | Yes             | No              | Yes                                               | Yes                    | Yes                              |
| Bend resistant camera cables<br>Bend resistant<br>Right-angle        | FZ-VSB3<br>FZ-VSLB3 | 2 m          | Yes                 | Yes             | Yes             | Yes                                               | Yes                    | Yes                              |
|                                                                      |                     | 3 m          | Yes                 | Yes             | Yes             | Yes                                               | Yes                    | Yes                              |
|                                                                      |                     | 5 m          | Yes                 | Yes             | Yes             | Yes                                               | Yes                    | Yes                              |
|                                                                      |                     | 10 m         | Yes                 | Yes             | No              | Yes                                               | Yes                    | Yes                              |
| Long-distance camera cable<br>Long-distance right-angle camera cable | FZ-VS4<br>FZ-VSL4   | 15 m         | Yes                 | Yes             | No              | Yes                                               | Yes                    | Yes                              |

## Maximum Extension Length Using Cable Extension Units FZ-VSJ

| Item                      | Model                                        | Transmission speed (*1) | No. of CH used for connection (*2) | Maximum cable length using 1 Camera Cable (*1) | Max. number of connectable Extension Units | Using Cable Extension Units FZ-VSJ |                                                                  |
|---------------------------|----------------------------------------------|-------------------------|------------------------------------|------------------------------------------------|--------------------------------------------|------------------------------------|------------------------------------------------------------------|
|                           |                                              |                         |                                    |                                                |                                            | Max. cable length                  | Connection configuration                                         |
| High-speed CMOS Cameras   | FH-SM/SC                                     | ---                     | ---                                | 15 m<br>(Using FZ-VS4/VSL4)                    | 2                                          | 45 m                               | [Configuration 1]<br>Camera cable: 15 m × 3<br>Extension Unit: 2 |
|                           | FH-SM02/SC02<br>FH-SM04/SC04<br>FH-SM12/SC12 | Standard                | 1                                  | 15 m<br>(Using FZ-VS4/VSL4)                    | 2                                          | 45 m                               | [Configuration 1]<br>Camera cable: 15 m × 3<br>Extension Unit: 2 |
|                           |                                              |                         | 2                                  | 15 m<br>(Using FZ-VS4/VSL4)                    | 4 (*3)                                     | 45 m                               | [Configuration 2]<br>Camera cable: 15 m × 6<br>Extension Unit: 4 |
|                           |                                              | High speed              | 1                                  | 5 m<br>(Using FZ-VS□/VSL□)                     | 2                                          | 15 m                               | [Configuration 3]<br>Camera cable: 5 m × 3<br>Extension Unit: 2  |
|                           |                                              |                         | 2                                  | 5 m<br>(Using FZ-VS□/VSL□)                     | 4 (*3)                                     | 15 m                               | [Configuration 4]<br>Camera cable: 5 m × 6<br>Extension Unit: 4  |
|                           | FZ-S/SC<br>FZ-S2M/SC2M                       | ---                     | ---                                | 15 m<br>(Using FZ-VS4/VSL4)                    | 2                                          | 45 m                               | [Configuration 1]<br>Camera cable: 15 m × 3<br>Extension Unit: 2 |
| Digital CCD Cameras       | FZ-S5M2/SC5M2                                | ---                     | ---                                | 5 m<br>(Using FZ-VS□/VSL□)                     | 2                                          | 15 m                               | [Configuration 3]<br>Camera cable: 5 m × 3<br>Extension Unit: 2  |
| Small Digital CCD Cameras | FZ-SF/SFC<br>FZ-SP/SPC                       | ---                     | ---                                | 15 m<br>(Using FZ-VS4/VSL4)                    | 2                                          | 45 m                               | [Configuration 1]<br>Camera cable: 15 m × 3<br>Extension Unit: 2 |
| High-speed CCD Cameras    | FZ-SH/SHC                                    | ---                     | ---                                | 15 m<br>(Using FZ-VS4/VSL4)                    | 2                                          | 45 m                               | [Configuration 1]<br>Camera cable: 15 m × 3<br>Extension Unit: 2 |
| Intelligent Compact       | FZ-SQ□                                       | ---                     | ---                                | 15 m<br>(Using FZ-VS4/VSL4)                    | 2                                          | 45 m                               | [Configuration 1]<br>Camera cable: 15 m × 3<br>Extension Unit: 2 |

- \*1 The FH-S□□□ enables switching between standard and high speed modes. In high speed mode, images can be transferred approximately two times faster than in standard mode, but the connectable cable length will be shorter.
- \*2 The FH-S□□□ has two channels to connect Camera Cables. Connection to two channels makes image transfer two times faster than connection to one channel: high speed mode using two channels can transfer approximately four times as many images as standard mode using one channel.
- \*3 Each channel can be used to connect up to two Cable Extension Units: up to four extension units, two channels x two units, can be connected by using two channels.

## Connection Configuration

|                 | Connection configuration using the maximum length of Camera Cables                | Remarks                                                  |
|-----------------|-----------------------------------------------------------------------------------|----------------------------------------------------------|
| Configuration 1 |  |                                                          |
| Configuration 2 |  | Camera cable connector CH2<br>Camera cable connector CH1 |
| Configuration 3 |  |                                                          |
| Configuration 4 |  | Camera cable connector CH2<br>Camera cable connector CH1 |

\*4 Select the Camera Cables between the Controller and Extension Unit, between the Extension Units, and between the Extension Unit and Camera according to the connected Camera.  
Different types or lengths of Camera Cables can be used for (1), (2), and (3) as well as for (4), (5), and (6). However, the type and length of Camera Cable (1) must be the same as those of Camera Cable (4), (2) must be the same as (5), and (3) must be the same as (6).

## Touch Panel Monitor

| Item                                                                                | Descriptions                                                   | Model   |
|-------------------------------------------------------------------------------------|----------------------------------------------------------------|---------|
|  | Touch Panel Monitor 12.1 inches<br>For FH Sensor Controllers * | FH-MT12 |

\* FH Series Sensor Controllers version 5.32 or higher is required.

## Touch Panel Monitor Cables

| Item                                                                                | Descriptions                                                                          | Model         |
|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------|
|  | DVI-Analog Conversion Cable for Touch Panel Monitor<br>Cable length: 2 m, 5 m or 10 m | FH-VMDA       |
|  | RS-232C Cable for Touch Panel Monitor<br>Cable length: 2 m, 5 m or 10 m               | XW2Z-□□□PP-1* |
|  | USB Cable for Touch Panel Monitor<br>Cable length: 2 m or 5 m                         | FH-VUAB       |

\* Insert the cables length into □□□ in the model number as follows. 2 m = 200, 5 m = 500, 10 m = 010.

A video signal cable and an operation signal cable are required to connect the Touch Panel Monitor.

| Signal                       | Cable                       | 2 m | 5 m | 10 m |
|------------------------------|-----------------------------|-----|-----|------|
| Video signal                 | DVI-Analog Conversion Cable | Yes | Yes | Yes  |
| Touch panel operation signal | USB Cable                   | Yes | Yes | No   |
|                              | RS-232C Cable               | Yes | Yes | Yes  |

## Parallel I/O Cables/Encoder Cable

| Item                                                                                | Descriptions                                                                                                                                                                                                                              | Model          |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|
|  | Parallel I/O Cable *1<br>Cable length: 2 m or 5 m                                                                                                                                                                                         | XW2Z-S013-□ *2 |
|  | Parallel I/O Cable for Connector-terminal Conversion Unit *1<br>Cable length: 0.5 m, 1 m, 1.5 m, 2 m, 3 m, 5 m<br>Connector-Terminal Block Conversion Units can be connected<br>(Terminal Blocks Recommended Products: OMRON XW2R-□34G-T) | XW2Z-□□□EE *3  |
|  | Connector-Terminal Block Conversion Units, General-purpose devices                                                                                                                                                                        | XW2R-□34G-T *4 |
|  | Encoder Cable for line-driver<br>Cable length: 1.5 m                                                                                                                                                                                      | FH-VR          |

\*1 2 Cables are required for all I/O signals.

\*2 Insert the cables length into □ in the model number as follows. 2 m = 2, 5 m = 5

\*3 Insert the cables length into □□□ in the model number as follows. 0.5 m = 050, 1 m = 100, 1.5 m = 150, 2 m = 200, 3 m = 300, 5 m = 500

\*4 Insert the wiring method into □ in the model number as follows. Phillips screw = J, Slotted screw (rise up) = E, Push-in spring = P  
Refer to the XW2R Series catalog (Cat. No. G077) for details.

## Recommended EtherCAT and EtherNet/IP Communications Cables

Use Straight STP (shielded twisted-pair) cable of category 5 or higher with double shielding (braiding and aluminum foil tape) for EtherCAT.  
Use Straight or cross STP (shielded twisted-pair) cable of category 5 or higher for EtherNet/IP.

| Item                                                                             | Descriptions                 |                                                                                                                                                                                                                                                                            |                         |                                    | Model                          |
|----------------------------------------------------------------------------------|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------------------|--------------------------------|
|  | For EtherCAT                 | Standard type Cable with Connectors on Both Ends (RJ45/RJ45)<br>Wire Gauge and Number of Pairs: AWG27, 4-pair Cable, Cable Sheath material: LSZH *1,<br>Cable color: Blue, Yellow, or Green,<br>Cables length: 0.2m, 0.3m, 0.5m, 1m, 1.5m, 2m, 3m, 5m, 7.5m, 10m, 15m, 20m |                         |                                    | XS6W-6LSZH8SS□CM-Y *2          |
|  |                              | Rugged type Cable with Connectors on Both Ends (RJ45/RJ45)<br>Wire Gauge and Number of Pairs: AWG22, 2-pair Cable<br>Cables length: 0.3m, 0.5m, 1m, 2m, 3m, 5m, 10m, 15m                                                                                                   |                         |                                    | XS5W-T421-□MD-K *2             |
|  |                              | Rugged type Cable with Connectors on Both Ends (M12/RJ45)<br>Wire Gauge and Number of Pairs: AWG22, 2-pair Cable<br>Cables length: 0.3m, 0.5m, 1m, 2m, 3m, 5m, 10m, 15m                                                                                                    |                         |                                    | XS5W-T421-□MC-K *2             |
|  |                              | Rugged type Cable with Connectors on Both Ends (M12 L/RJ45)<br>Wire Gauge and Number of Pairs: AWG22, 2-pair Cable<br>Cables length: 0.3m, 0.5m, 1m, 2m, 3m, 5m, 10m, 15m                                                                                                  |                         |                                    | XS5W-T422-□MC-K *2             |
| --                                                                               | For EtherCAT and EtherNet/IP | Wire Gauge and Number of Pairs: AWG24, 4-pair Cable                                                                                                                                                                                                                        | Cables                  | Hitachi Metals, Ltd.               | NETSTAR-C5E<br>SAB 0.5 × 4P *3 |
| --                                                                               |                              |                                                                                                                                                                                                                                                                            |                         | Kuramo Electric Co.                | KETH-SB *3                     |
| --                                                                               |                              |                                                                                                                                                                                                                                                                            |                         | SWCC Showa Cable Systems Co.       | FAE-5004 *3                    |
| --                                                                               |                              | Wire Gauge and Number of Pairs: AWG22, 2-pair Cable                                                                                                                                                                                                                        | RJ45 Connectors         | Panduit Corporation                | MPS588-C *3                    |
| --                                                                               |                              |                                                                                                                                                                                                                                                                            | Cables                  | Kuramo Electric Co.                | KETH-PSB-OMR *4                |
| --                                                                               |                              |                                                                                                                                                                                                                                                                            |                         | Nihon Electric Wire&Cable Co.,Ltd. | PNET/B *4                      |
|  |                              |                                                                                                                                                                                                                                                                            | RJ45 Assembly Connector | OMRON                              | XS6G-T421-1 *4                 |
| --                                                                               | For EtherNet/IP              | Wire Gauge and Number of Pairs: 0.5 mm, 4-pair Cable                                                                                                                                                                                                                       | Cables                  | Fujikura Ltd.                      | F-LINK-E 0.5mm × 4P *5         |
| --                                                                               |                              |                                                                                                                                                                                                                                                                            | RJ45 Connectors         | Panduit Corporation                | MPS588 *5                      |

**Note:** Please be careful while cable processing, for EtherCAT, connectors on both ends should be shield connected and for EtherNet/IP, connectors on only one end should be shield connected.

\*1 The lineup features Low Smoke Zero Halogen cables for in-cabinet use and PUR cables for out-of-cabinet use.

\*2 For details, refer to Cat.No.G019.

\*3 We recommend you to use above cable for EtherCAT and EtherNet/IP, and RJ45 Connector together.

\*4 We recommend you to use above cable for EtherCAT and EtherNet/IP, and RJ45 Assembly Connector together.

\*5 We recommend you to use above cable For EtherNet/IP and RJ45 Connectors together.

## Automation Software Sysmac Studio

Please purchase a DVD and licenses the first time you purchase the Sysmac Studio. DVDs and licenses are available individually. The license does not include the DVD.

| Product                                           | Specifications                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Model              |        |
|---------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|--------|
|                                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Number of licenses | Media  |
| Sysmac Studio<br>Standard Edition<br>Ver.1.□□     | The Sysmac Studio is the software that provides an integrated environment for setting, programming, debugging and maintenance of machine automation controllers including the NJ Series, EtherCat Slave, and the HMI.<br>Sysmac Studio runs on the following OS.<br>Windows XP (Service Pack 3 or higher, 32-bit version) /<br>Windows Vista (32-bit version) / Windows 7 (32-bit/64-bit version) /<br>Windows 8 (32-bit/64-bit version) / Windows 8.1 (32-bit/64-bit version) | -- (Media only)    | DVD *1 |
|                                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 1 license          | —      |
|                                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 3 license          | —      |
|                                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 10 license         | —      |
|                                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 30 license         | —      |
|                                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 50 license         | —      |
| Sysmac Studio<br>Vision Edition<br>Ver.1.□□ *2 *3 | Sysmac Studio Vision Edition is a limited license that provides selected functions required for FH-serise/<br>FQ-M-series Vision Sensor settings.                                                                                                                                                                                                                                                                                                                              | 1 license          | —      |

**Note:** 1. Site licenses are available for users who will run Sysmac Studio on multiple computers. Ask your OMRON sales representative for details.  
2. Sysmac Studio version 1.07 or higher supports the FH Series. Sysmac Studio does not support the FZ5 Series.

\*1 The same media is used for both the Standard Edition and the Vision Edition.

\*2 With the Vision Edition, you can use only the setup functions for FH-series/FQ-M-series Vision Sensors.

\*3 This product is a license only. You need the Sysmac Studio Standard Edition DVD media to install it.

## Development Environment

Please purchase a CD-ROM and licenses the first time you purchase the Application Producer. CD-ROMs and licenses are available individually. The license does not include the CD-ROM.

| Product              | Specifications                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Number of Model Standards licenses | Media  | Model   |
|----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------|--------|---------|
|                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                    |        |         |
| Application Producer | Software components that provide a development environment to further customize the standard controller features of the FH Series.<br>System requirements:<br>• CPU: Intel Pentium Processor (SSE2 or higher)<br>• OS: Windows 7 Professional (32/64bit) or Enterprise(32/64bit) or Ultimate (32/64bit),<br>Windows 8 Pro(32/64bit) or Enterprise(32/64bit),<br>Windows 8.1 Pro(32/64bit) or Enterprise(32/64bit)<br>• .NET Framework: .NET Framework 3.5 or higher<br>• Memory: At least 2 GB RAM<br>Available disk space: At least 2 GB<br>• Browser: Microsoft® Internet Explorer 6.0 or later<br>• Display: XGA (1024 × 768), True Color (32-bit) or higher<br>• Optical drive: CD/DVD drive<br>The following software is required to customize the software:<br>Microsoft® Visual Studio® 2010 Professional or<br>Microsoft® Visual Studio® 2008 Professional or<br>Microsoft® Visual Studio® 2012 Professional | — (Media only)                     | CD-ROM | FH-AP1  |
|                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 1 license                          | —      | FH-AP1L |

## Accessories

| Item                                                                                |                                                                                                                                                                                              | Descriptions                      |                                                                  |                                | Model             |
|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|------------------------------------------------------------------|--------------------------------|-------------------|
|    | LCD Monitor 8.4 inches<br>For Box-type Controllers*1                                                                                                                                         |                                   |                                                                  |                                | FZ-M08            |
|    | LED Monitor Cable<br>Cable length: 2 m or 5 m (When you connect a LCD Monitor FZ-M08 to FH sensor controller, please use it in combination with a DVI-I -RGB Conversion Connector FH-VMRGB.) |                                   |                                                                  |                                | FZ-VM             |
|   | DVI-I -RGB Conversion Connector                                                                                                                                                              |                                   |                                                                  |                                | FH-VMRGB          |
|  | USB Memory                                                                                                                                                                                   | 2 GB                              |                                                                  | FZ-MEM2G                       |                   |
|                                                                                     |                                                                                                                                                                                              | 8 GB                              |                                                                  | FZ-MEM8G                       |                   |
|  | SD Card                                                                                                                                                                                      | 2 GB                              |                                                                  | HMC-SD291                      |                   |
|                                                                                     |                                                                                                                                                                                              | 4 GB                              |                                                                  | HMC-SD491                      |                   |
|  | Display/USB Switcher                                                                                                                                                                         |                                   |                                                                  |                                | FZ-DU             |
| —                                                                                   | Mouse Recommended Products<br>Driverless wired mouse<br>(A mouse that requires the mouse driver to be installed is not supported.)                                                           |                                   |                                                                  |                                | ---               |
|  | EtherCAT junction slaves                                                                                                                                                                     | 3 port                            | Power supply voltage:<br>20.4 to 28.8 VDC<br>(24 VDC -15 to 20%) | Current consumption:<br>0.08 A | GX-JC03           |
|  |                                                                                                                                                                                              | 6 port                            |                                                                  | Current consumption:<br>0.17 A | GX-JC06           |
|  | Industrial Switching Hubs<br>for EtherNet/IP and Ether-<br>net                                                                                                                               | 3 port                            | Failure detection: None                                          | Current consumption:<br>0.08 A | W4S1-03B          |
|  |                                                                                                                                                                                              | 5 port                            | Failure detection: None                                          | Current consumption:<br>0.12 A | W4S1-05B          |
|                                                                                     |                                                                                                                                                                                              | 5 port                            | Failure detection:<br>Supported                                  |                                | W4S1-05C          |
| —                                                                                   | Calibration Plate                                                                                                                                                                            |                                   |                                                                  |                                | FZD-CAL           |
| —                                                                                   | External Lighting                                                                                                                                                                            |                                   |                                                                  | —                              | FLV Series *2     |
|                                                                                     |                                                                                                                                                                                              |                                   |                                                                  |                                | FL Series *2      |
|  | Lighting Controller<br>(Required to control<br>external lighting from a Controller)                                                                                                          | For FLV-Series                    | Camera Mount Light-<br>ing Controller                            |                                | FLV-TCC Series *2 |
|  |                                                                                                                                                                                              |                                   | Analog Lighting Con-<br>troller                                  |                                | FLV-ATC Series *2 |
|  |                                                                                                                                                                                              | For FL-Series                     | Camera Mount Light-<br>ing Controller                            |                                | FL-TCC Series *2  |
|  | For Intelligent<br>Compact Camera                                                                                                                                                            | Mounting Bracket                  |                                                                  |                                | FQ-XL             |
|  |                                                                                                                                                                                              | Mounting Brackets                 |                                                                  |                                | FQ-XL2            |
|  |                                                                                                                                                                                              | Polarizing Filter At-<br>tachment |                                                                  |                                | FQ-XF1            |
| —                                                                                   | Mounting Bracket for FZ-S□                                                                                                                                                                   |                                   |                                                                  |                                | FZ-S-XLC          |
|                                                                                     | Mounting Bracket for FZ-S□2M                                                                                                                                                                 |                                   |                                                                  |                                | FZ-S2M-XLC        |
|                                                                                     | Mounting Bracket for FZ-SH□                                                                                                                                                                  |                                   |                                                                  |                                | FZ-SH-XLC         |
|                                                                                     | Mounting Bracket for FH-S□, FZ-S□5M2                                                                                                                                                         |                                   |                                                                  |                                | FH-SM-XLC         |
|                                                                                     | Mounting Bracket for FH-S□12                                                                                                                                                                 |                                   |                                                                  |                                | FH-SM12-XLC       |

\*1 It can be used in FH series.

\*2 Refer to the Vision Accessory Catalog (Cat. No. Q198) for details.

## Lenses

### C-mount Lens for 1/3-inch image sensor (Recommend: FZ-S□/FZ-SH□/FH-S□)

| Model                      | 3Z4S-LE SV-03514V                                                                 | 3Z4S-LE SV-04514V                                                                 | 3Z4S-LE SV-0614V                                                                  | 3Z4S-LE SV-0813V                                                                  | 3Z4S-LE SV-1214V                                                                  | 3Z4S-LE SV-1614V                                                                  | 3Z4S-LE SV-2514V                                                                  | 3Z4S-LE SV-3518V                                                                  | 3Z4S-LE SV-5018V                                                                   | 3Z4S-LE SV-7527V                                                                    | 3Z4S-LE SV-10035V                                                                   |
|----------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Appearance/Dimensions (mm) |  |  |  |  |  |  |  |  |  |  |  |
| Focal length               | 3.5 mm                                                                            | 4.5 mm                                                                            | 6 mm                                                                              | 8 mm                                                                              | 12 mm                                                                             | 16 mm                                                                             | 25 mm                                                                             | 35 mm                                                                             | 50 mm                                                                              | 75 mm                                                                               | 100 mm                                                                              |
| Aperture (F No.)           | 1.4 to Close                                                                      | 1.4 to Close                                                                      | 1.4 to Close                                                                      | 1.3 to Close                                                                      | 1.4 to Close                                                                      | 1.4 to Close                                                                      | 1.4 to Close                                                                      | 1.8 to Close                                                                      | 1.8 to Close                                                                       | 2.7 to Close                                                                        | 3.5 to Close                                                                        |
| Filter size                | —                                                                                 | —                                                                                 | M27.0 P0.5                                                                        | M25.5 P0.5                                                                        | M27.0 P0.5                                                                        | M27.0 P0.5                                                                        | M27.0 P0.5                                                                        | M27.0 P0.5                                                                        | M30.5 P0.5                                                                         | M30.5 P0.5                                                                          | M30.5 P0.5                                                                          |
| Maximum sensor size        | 1/3 inch                                                                          | 1/3 inch                                                                          | 1/3 inch                                                                          | 1/3 inch                                                                          | 1/3 inch                                                                          | 1/3 inch                                                                          | 1/3 inch                                                                          | 1/3 inch                                                                          | 1/3 inch                                                                           | 1/3 inch                                                                            | 1/3 inch                                                                            |
| Mount                      | C mount                                                                           |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                    |                                                                                     |                                                                                     |

### C-mount Lens for 2/3-inch image sensor (Recommend: FZ-S□2M/FZ-S□5M2) (3Z4S-LE SV-7525H and 3Z4S-LE SV-10028H can also be used for FH-S□02 and FH-S□04)

| Model                      | 3Z4S-LE SV-0614H                                                                  | 3Z4S-LE SV-0814H                                                                  | 3Z4S-LE SV-1214H                                                                  | 3Z4S-LE SV-1614H                                                                  | 3Z4S-LE SV-2514H                                                                  | 3Z4S-LE SV-3514H                                                                  | 3Z4S-LE SV-5014H                                                                  | 3Z4S-LE SV-7525H                                                                   | 3Z4S-LE SV-10028H                                                                   |
|----------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Appearance/Dimensions (mm) |  |  |  |  |  |  |  |  |  |
| Focal length               | 6 mm                                                                              | 8 mm                                                                              | 12 mm                                                                             | 16 mm                                                                             | 25 mm                                                                             | 35 mm                                                                             | 50 mm                                                                             | 75 mm                                                                              | 100 mm                                                                              |
| Aperture (F No.)           | 1.4 to 16                                                                         | 1.4 to 16                                                                         | 1.4 to 16                                                                         | 1.4 to 16                                                                         | 1.4 to 16                                                                         | 1.4 to 16                                                                         | 1.4 to 16                                                                         | 2.5 to Close                                                                       | 2.8 to Close                                                                        |
| Filter size                | M40.5 P0.5                                                                        | M35.5 P0.5                                                                        | M27.0 P0.5                                                                        | M27.0 P0.5                                                                        | M27.0 P0.5                                                                        | M35.5 P0.5                                                                        | M40.5 P0.5                                                                        | M34.0 P0.5                                                                         | M37.5 P0.5                                                                          |
| Maximum sensor size        | 2/3 inch                                                                          | 2/3 inch                                                                          | 2/3 inch                                                                          | 2/3 inch                                                                          | 2/3 inch                                                                          | 2/3 inch                                                                          | 2/3 inch                                                                          | 1 inch                                                                             | 1 inch                                                                              |
| Mount                      | C mount                                                                           |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                    |                                                                                     |

### C-mount Lens for 1-inch image sensor (Recommend: FH-S□02/FH-S□04) (3Z4S-LE SV-7525H with focal length of 75 mm and 3Z4S-LE SV-10028H with focal length of 100 mm are also available.)

| Model                      | 3Z4S-LE VS-0618H1                                                                   | 3Z4S-LE VS-0814H1                                                                   | 3Z4S-LE VS-1214H1                                                                   | 3Z4S-LE VS-1614H1N                                                                  | 3Z4S-LE VS-2514H1                                                                   | 3Z4S-LE VS-3514H1                                                                   | 3Z4S-LE VS-5018H1                                                                    |
|----------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| Appearance/Dimensions (mm) |  |  |  |  |  |  |  |
| Focal length               | 6 mm                                                                                | 8 mm                                                                                | 12 mm                                                                               | 16 mm                                                                               | 25 mm                                                                               | 35 mm                                                                               | 50 mm                                                                                |
| Aperture (F No.)           | 1.8 to 16                                                                           | 1.4 to 16                                                                           | 1.4 to 16                                                                           | 1.4 to 16                                                                           | 1.4 to 16                                                                           | 1.4 to 16                                                                           | 1.8 to 16                                                                            |
| Filter size                | Can not be used a filter                                                            | M55.0 P0.75                                                                         | M35.5 P0.5                                                                          | M30.5 P0.5                                                                          | M30.5 P0.5                                                                          | M30.5 P0.5                                                                          | M40.5 P0.5                                                                           |
| Maximum sensor size        | 1 inch                                                                              | 1 inch                                                                              | 1 inch                                                                              | 1 inch                                                                              | 1 inch                                                                              | 1 inch                                                                              | 1 inch                                                                               |
| Mount                      | C mount                                                                             |                                                                                     |                                                                                     |                                                                                     |                                                                                     |                                                                                     |                                                                                      |

### M42-mount Lens for large image sensor (Recommend: FH-S□12)

| Model                      | 3Z4S-LE VS-L1828/M42-10                                                             | 3Z4S-LE VS-L2526/M42-10                                                             | 3Z4S-LE VS-L3528/M42-10                                                             | 3Z4S-LE VS-L5028/M42-10                                                             | 3Z4S-LE VS-L8540/M42-10                                                             | 3Z4S-LE VS-L10028/M42-10                                                             |
|----------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| Appearance/Dimensions (mm) |  |  |  |  |  |  |
| Focal length               | 18 mm                                                                               | 25 mm                                                                               | 35 mm                                                                               | 50 mm                                                                               | 85 mm                                                                               | 100 mm                                                                               |
| Aperture (F No.)           | 2.8 to 16                                                                           | 2.6 to 16                                                                           | 2.8 to 16                                                                           | 2.8 to 16                                                                           | 4.0 to 16                                                                           | 2.8 to 16                                                                            |
| Filter size                | M55.0 P0.75                                                                         | M55.0 P0.75                                                                         | M62.0 P0.75                                                                         | M62.0 P0.75                                                                         | M52.0 P0.75                                                                         | M52.0 P0.75                                                                          |
| Maximum sensor size        | 1.8 inch                                                                            |                                                                                     |                                                                                     |                                                                                     |                                                                                     |                                                                                      |
| Mount                      | M42 mount                                                                           |                                                                                     |                                                                                     |                                                                                     |                                                                                     |                                                                                      |

### Lenses for small camera

| Model                      | FZ-LES3                                                                             | FZ-LES6                                                                             | FZ-LES16                                                                            | FZ-LES30                                                                            |
|----------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Appearance/Dimensions (mm) |  |  |  |  |
| Focal length               | 3 mm                                                                                | 6 mm                                                                                | 16 mm                                                                               | 30 mm                                                                               |
| Aperture (F No.)           | 2.0 to 16                                                                           | 2.0 to 16                                                                           | 3.4 to 16                                                                           | 3.4 to 16                                                                           |

# Vibrations and Shocks Resistant C-mount Lens for 2/3-inch image sensor

(Recommend: FZ-S□/FZ-S□2M/FZ-S□5M2/FZ-SH□/FH-S□)

(Vibrations and Shocks Resistant Lenses for 1-inch image sensors and for large image sensors are also available. Ask your OMRON representative for details.)

| Model                          | 3Z4S-LE<br>VS-MC15-□□□□□ *1                                                       |       |       |       |      |      |       |     |     | 3Z4S-LE<br>VS-MC20-□□□□□ *1                                                         |       |       |        |     |      |       |     |     |
|--------------------------------|-----------------------------------------------------------------------------------|-------|-------|-------|------|------|-------|-----|-----|-------------------------------------------------------------------------------------|-------|-------|--------|-----|------|-------|-----|-----|
| Appearance/<br>Dimensions (mm) |  |       |       |       |      |      |       |     |     |  |       |       |        |     |      |       |     |     |
| Focal length                   | 15 mm                                                                             |       |       |       |      |      |       |     |     | 20 mm                                                                               |       |       |        |     |      |       |     |     |
| Filter size                    | M27.0 P0.5                                                                        |       |       |       |      |      |       |     |     | M27.0 P0.5                                                                          |       |       |        |     |      |       |     |     |
| Optical magnification          | 0.03 ×                                                                            |       |       | 0.2 × |      |      | 0.3 × |     |     | 0.04 ×                                                                              |       |       | 0.25 × |     |      | 0.4 × |     |     |
| Aperture<br>(fixed F No.) *2   | 2                                                                                 | 5.6   | 8     | 2     | 5.6  | 8    | 2     | 5.6 | 8   | 2                                                                                   | 5.6   | 8     | 2      | 5.6 | 8    | 2     | 5.6 | 8   |
| Depth of field (mm) *3         | 183.1                                                                             | 512.7 | 732.4 | 4.8   | 13.4 | 19.2 | 2.3   | 6.5 | 9.2 | 110.8                                                                               | 291.2 | 416.0 | 3.4    | 9.0 | 12.8 | 1.5   | 3.9 | 5.6 |
| Maximum sensor size            | 2/3 inch                                                                          |       |       |       |      |      |       |     |     | 2/3 inch                                                                            |       |       |        |     |      |       |     |     |
| Mount                          | C Mount                                                                           |       |       |       |      |      |       |     |     | C Mount                                                                             |       |       |        |     |      |       |     |     |

| Model                          | 3Z4S-LE<br>VS-MC25N-□□□□□ *1                                                      |       |       |        |     |      |       |     |     | 3Z4S-LE<br>VS-MC30-□□□□□ *1                                                         |       |       |        |      |      |        |     |     |
|--------------------------------|-----------------------------------------------------------------------------------|-------|-------|--------|-----|------|-------|-----|-----|-------------------------------------------------------------------------------------|-------|-------|--------|------|------|--------|-----|-----|
| Appearance/<br>Dimensions (mm) |  |       |       |        |     |      |       |     |     |  |       |       |        |      |      |        |     |     |
| Focal length                   | 25 mm                                                                             |       |       |        |     |      |       |     |     | 30 mm                                                                               |       |       |        |      |      |        |     |     |
| Filter size                    | M27.0 P0.5                                                                        |       |       |        |     |      |       |     |     | M27.0 P0.5                                                                          |       |       |        |      |      |        |     |     |
| Optical magnification          | 0.05 ×                                                                            |       |       | 0.25 × |     |      | 0.5 × |     |     | 0.06 ×                                                                              |       |       | 0.15 × |      |      | 0.45 × |     |     |
| Aperture<br>(fixed F No.) *2   | 2                                                                                 | 5.6   | 8     | 2      | 5.6 | 8    | 2     | 5.6 | 8   | 2                                                                                   | 5.6   | 8     | 2      | 5.6  | 8    | 2      | 5.6 | 8   |
| Depth of field (mm) *3         | 67.2                                                                              | 188.2 | 268.8 | 3.2    | 9.0 | 12.8 | 1.0   | 2.7 | 3.8 | 47.1                                                                                | 131.9 | 188.4 | 8.2    | 22.9 | 32.7 | 1.1    | 3.2 | 4.6 |
| Maximum sensor size            | 2/3 inch                                                                          |       |       |        |     |      |       |     |     | 2/3 inch                                                                            |       |       |        |      |      |        |     |     |
| Mount                          | C Mount                                                                           |       |       |        |     |      |       |     |     | C Mount                                                                             |       |       |        |      |      |        |     |     |

| Model                          | 3Z4S-LE<br>VS-MC35-□□□□□ *1                                                         |     |      |       |     |     |        |     |     | 3Z4S-LE<br>VS-MC50-□□□□□ *1                                                           |      |       |       |      |      |        |     |     |
|--------------------------------|-------------------------------------------------------------------------------------|-----|------|-------|-----|-----|--------|-----|-----|---------------------------------------------------------------------------------------|------|-------|-------|------|------|--------|-----|-----|
| Appearance/<br>Dimensions (mm) |  |     |      |       |     |     |        |     |     |  |      |       |       |      |      |        |     |     |
| Focal length                   | 35 mm                                                                               |     |      |       |     |     |        |     |     | 50 mm                                                                                 |      |       |       |      |      |        |     |     |
| Filter size                    | M27.0 P0.5                                                                          |     |      |       |     |     |        |     |     | M27.0 P0.5                                                                            |      |       |       |      |      |        |     |     |
| Optical magnification          | 0.26 ×                                                                              |     |      | 0.3 × |     |     | 0.65 × |     |     | 0.08 ×                                                                                |      |       | 0.2 × |      |      | 0.48 × |     |     |
| Aperture<br>(fixed F No.) *2   | 1.9                                                                                 | 5.6 | 8    | 1.9   | 5.6 | 8   | 1.9    | 5.6 | 8   | 2                                                                                     | 5.6  | 8     | 2     | 5.6  | 8    | 2      | 5.6 | 8   |
| Depth of field (mm) *3         | 2.8                                                                                 | 8.4 | 11.9 | 2.2   | 6.5 | 9.2 | 0.6    | 1.7 | 2.5 | 33.8                                                                                  | 75.6 | 108.0 | 6.0   | 13.4 | 19.2 | 1.3    | 2.9 | 4.1 |
| Maximum sensor size            | 2/3 inch                                                                            |     |      |       |     |     |        |     |     | 2/3 inch                                                                              |      |       |       |      |      |        |     |     |
| Mount                          | C Mount                                                                             |     |      |       |     |     |        |     |     | C Mount                                                                               |      |       |       |      |      |        |     |     |

| Model                          | 3Z4S-LE<br>VS-MC75-□□□□□ *1                                                         |      |      |       |      |      |        |     |     |
|--------------------------------|-------------------------------------------------------------------------------------|------|------|-------|------|------|--------|-----|-----|
| Appearance/<br>Dimensions (mm) |  |      |      |       |      |      |        |     |     |
| Focal length                   | 75 mm                                                                               |      |      |       |      |      |        |     |     |
| Filter size                    | M27.0 P0.5                                                                          |      |      |       |      |      |        |     |     |
| Optical magnification          | 0.14 ×                                                                              |      |      | 0.2 × |      |      | 0.62 × |     |     |
| Aperture<br>(fixed F No.) *2   | 3.8                                                                                 | 5.6  | 8    | 3.8   | 5.6  | 8    | 3.8    | 5.6 | 8   |
| Depth of field (mm) *3         | 17.7                                                                                | 26.1 | 37.2 | 9.1   | 13.4 | 19.2 | 1.3    | 1.9 | 2.7 |
| Maximum sensor size            | 2/3 inch                                                                            |      |      |       |      |      |        |     |     |
| Mount                          | C Mount                                                                             |      |      |       |      |      |        |     |     |

\*1 Insert the iris range into □□□□□ in the model number as follows.

F=1.9 to 3.8: blank

F=5.6: FN056

F=8: FN080

\*2 F-number can be selected from maximum aperture, 5.6, and 8.0.

\*3 When circle of least confusion is 40 μm.

## Extension Tubes

| Lenses   | For M42 mount Lenses *                                                                         | For C mount Lenses *                                                                                               | For Small Digital CCD Cameras                                                |
|----------|------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------|
| Model    | 3Z4S-LE VS-EXR/M42                                                                             | 3Z4S-LE SV-EXR                                                                                                     | FZ-LESR                                                                      |
| Contents | Set of 5 tubes<br>(20 mm, 10 mm, 8 mm, 2 mm, and 1 mm)<br>Maximum outer diameter: 47.5 mm dia. | Set of 7 tubes<br>(40 mm, 20 mm, 10 mm, 5 mm, 2.0 mm,<br>1.0 mm, and 0.5 mm)<br>Maximum outer diameter: 30 mm dia. | Set of 3 tubes<br>(15 mm, 10 mm, 5 mm)<br>Maximum outer diameter: 12 mm dia. |

\* Do not use the 0.5-mm, 1.0-mm, and 2.0-mm Extension Tubes attached to each other. Since these Extension Tubes are placed over the threaded section of the Lens or other Extension Tube, the connection may loosen when more than one 0.5-mm, 1.0-mm or 2.0-mm Extension Tube are used together.

Reinforcement is required to protect against vibration when Extension Tubes exceeding 30 mm are used.

When using the Extension Tube, check it on the actual device before using it.

# FH-Series

## Ratings and Specifications (FH Sensor Controllers)

| Type                  |                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | High-speed Controllers (4 core)                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                                                                           | Standard Controllers (2 core)                                                                                                                                                          |                                                               |                |                                                                                                                                                                                        |  |
|-----------------------|--------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| Model                 |                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | NPN                                                                                                                                                                                                                                                                                    | FH-3050                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | FH-3050-10                                                                                                                                | FH-3050-20                                                                                                                                                                             | FH-1050                                                       | FH-1050-10     | FH-1050-20                                                                                                                                                                             |  |
|                       |                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | PNP                                                                                                                                                                                                                                                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                                                                           |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
| Main functions        | Controller type                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                                                                                                                                                                        | Box-type controllers                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                           |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
|                       | No. of Cameras                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                                                                                                                                                                        | 2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 4                                                                                                                                         | 8                                                                                                                                                                                      | 2                                                             | 4              | 8                                                                                                                                                                                      |  |
|                       | Connected Camera                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                                                                                                                                                                        | Can be connected to all cameras.<br>(FZ-S series/FH-S series)                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                                                                                           | Can be connected to all cameras.<br>(FZ-S series/FH-S series)<br>(Can be connected to up to four 12 million-pixel cameras or up to eight cameras other than 12 million-pixel cameras.) | Can be connected to all cameras.<br>(FZ-S series/FH-S series) |                | Can be connected to all cameras.<br>(FZ-S series/FH-S series)<br>(Can be connected to up to four 12 million-pixel cameras or up to eight cameras other than 12 million-pixel cameras.) |  |
|                       | Processing resolution (FZ-S)         | When connected to a intelligent compact camera                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                                                                                                                                                                                                                                                                        | 752 (H) × 480 (V)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                           |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
|                       |                                      | When connected to a 300,000-pixel camera                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                                                                                                                                                                                                                                        | 640 (H) × 480 (V)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                           |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
|                       |                                      | When connected to a 2 million-pixel camera                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                                                                                                                                                                                                                        | 1600 (H) × 1200 (V)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                                                                                                                           |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
|                       |                                      | When connected to a 5 million-pixel camera                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                                                                                                                                                                                                                        | 2448 (H) × 2044 (V)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                                                                                                                           |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
|                       | Processing resolution (FH-S)         | When connected to a 300,000-pixel camera                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                                                                                                                                                                                                                                        | 640 (H) × 480 (V)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                           |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
|                       |                                      | When connected to a 2 million-pixel camera                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                                                                                                                                                                                                                        | 2040 (H) × 1088 (V)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                                                                                                                           |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
|                       |                                      | When connected to a 4 million-pixel camera                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                                                                                                                                                                                                                        | 2040 (H) × 2048 (V)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                                                                                                                           |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
|                       |                                      | When connected to a 12 million-pixel camera                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                                                                                                                                                                                                                        | 4084 (H) × 3072 (V)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                                                                                                                           |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
|                       | No. of scenes                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                                                                                                                                                                        | 128                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                                                                                                                           |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
|                       | Number of logged images *1           | When connected to a intelligent compact camera                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Connected to 1 camera(Color): 232, Connected to 2 camera(Color): 116<br>Connected to 3 camera(Color): 77, Connected to 4 camera(Color): 58<br>Connected to 5 camera(Color): 46, Connected to 6 camera(Color): 38<br>Connected to 7 camera(Color): 33, Connected to 8 camera(Color): 29 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                                                                           |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
|                       |                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | When connected to a 300,000-pixel camera (FZ-S/FH-S)                                                                                                                                                                                                                                   | Connected to 1 camera(Color): 270, Connected to 1 camera(Monochrome): 272<br>Connected to 2 camera(Color): 135, Connected to 2 camera(Monochrome): 136<br>Connected to 3 camera(Color/Monochrome): 90<br>Connected to 4 camera(Color): 67, Connected to 4 camera(Monochrome): 68<br>Connected to 5 camera(Color/Monochrome): 54<br>Connected to 6 camera(Color/Monochrome): 45<br>Connected to 7 camera(Color/Monochrome): 38<br>Connected to 8 camera(Color): 33, Connected to 8 camera(Monochrome): 34 |                                                                                                                                           |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
|                       |                                      | When connected to a 2 million-pixel camera (FH-S)                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                                                                                                                                                                                                                                                                        | Connected to 1 camera(Color/Monochrome): 37, Connected to 2 camera(Color/Monochrome): 18<br>Connected to 3 camera(Color/Monochrome): 12, Connected to 4 camera(Color/Monochrome): 9<br>Connected to 5 camera(Color/Monochrome): 7, Connected to 6 camera(Color/Monochrome): 6<br>Connected to 7 camera(Color/Monochrome): 5, Connected to 8 camera(Color/Monochrome): 4                                                                                                                                  |                                                                                                                                           |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
|                       |                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | When connected to a 2 million-pixel camera (FZ-S)                                                                                                                                                                                                                                      | Connected to 1 camera(Color/Monochrome): 43, Connected to 2 camera(Color/Monochrome): 21<br>Connected to 3 camera(Color/Monochrome): 14, Connected to 4 camera(Color/Monochrome): 10<br>Connected to 5 camera(Color/Monochrome): 8, Connected to 6 camera(Color/Monochrome): 7<br>Connected to 7 camera(Color/Monochrome): 6, Connected to 8 camera(Color/Monochrome): 5                                                                                                                                 |                                                                                                                                           |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
|                       |                                      | When connected to a 4 million-pixel camera (FH-S)                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                                                                                                                                                                                                                                                                        | Connected to 1 camera(Color/Monochrome): 20, Connected to 2 camera(Color/Monochrome): 10<br>Connected to 3 camera(Color/Monochrome): 6, Connected to 4 camera(Color/Monochrome): 5<br>Connected to 5 camera(Color/Monochrome): 4, Connected to 6 camera(Color/Monochrome): 3<br>Connected to 7 camera(Color/Monochrome): 2, Connected to 8 camera(Color/Monochrome): 2                                                                                                                                   |                                                                                                                                           |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
|                       |                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | When connected to a 5 million-pixel camera (FZ-S)                                                                                                                                                                                                                                      | Connected to 1 camera(Color/Monochrome): 16, Connected to 2 camera(Color/Monochrome): 8<br>Connected to 3 camera(Color/Monochrome): 5, Connected to 4 camera(Color/Monochrome): 4<br>Connected to 5 camera(Color/Monochrome): 3, Connected to 6 camera(Color/Monochrome): 2<br>Connected to 7 camera(Color/Monochrome): 2, Connected to 8 camera(Color/Monochrome): 2                                                                                                                                    |                                                                                                                                           |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
|                       |                                      | When connected to a 12 million-pixel camera (FH-S)                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                                                                                                                                                                                                                                                                        | Connected to 1 camera(Color/Monochrome): 6, Connected to 2 camera(Color/Monochrome): 3<br>Connected to 3 camera(Color/Monochrome): 2, Connected to 4 camera(Color/Monochrome): 2                                                                                                                                                                                                                                                                                                                         |                                                                                                                                           |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
|                       |                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Operation                                                                                                                                                                                                                                                                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                                                                           | Mouse or similar device                                                                                                                                                                |                                                               |                |                                                                                                                                                                                        |  |
|                       | Settings                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                                                                                                                                                                        | Create series of processing steps by editing the flowchart (Help messages provided).                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                           |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
| External interface    | Serial communications                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                                                                                                                                                                        | RS-232C: 1 CH                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                                                                                           |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
|                       | EtherNet communications              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                                                                                                                                                                        | No-protocol (TCP/UDP) 1000BASE-T                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                                                                           |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
|                       |                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                                                                                                                                                                        | 1 port                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 2 port                                                                                                                                    | 2 port                                                                                                                                                                                 | 1 port                                                        | 2port          | 2port                                                                                                                                                                                  |  |
|                       | EtherNet/IP communications           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                                                                                                                                                                        | Ethernet port baud rate: 1 Gbps (1000 BASE-T)                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                                                                                           |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
|                       | EtherCAT communications              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                                                                                                                                                                        | EtherCAT protocol (100BASE-TX)                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                                                                                                                           |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
|                       | Parallel I/O                         | (In the 2-line random trigger mode)<br>17 inputs (STEP0/ENCTRIG_Z0, STEP1/ENCTRIG_Z1, ENCTRIG_A0 to 1, ENCTRIG_B0 to 1, DSA0 to 1, DIO to 7, DI_LINE0)<br>37 outputs (RUN0 to 1, READY0 to 1, BUSY0 to 1, OR0 to 1, ERROR0 to 1, GATE0 to 1, STGOUT0/SHTOUT0, STGOUT1/SHTOUT1, STGOUT2 to 7, DO0 to 15, ACK)<br>(In the 5-line to 8-line random trigger mode)<br>19 inputs, STEP0 to 7, DI_LINE0 to 2, DIO to 7)<br>34 outputs (READY0 to 7, BUSY0 to 7, OR0 to 7, ACK, ERROR, STGOUT/SHTOUT0 to 7) |                                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                                                                           |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
|                       |                                      | Encoder interface                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | RS422-A line driver level. Phase A/B: single-phase 4MHz (multiplying phase difference of 1MHz by 4 times), Phase Z: 1MHz                  |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
|                       |                                      | Monitor interface                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | DVI-I(Single Link) output IF × 1ch                                                                                                        |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
|                       | USB interface                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                                                                                                                                                                        | 4 channels (supports USB 1.1 and 2.0)                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                           |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
|                       | SD card interface                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                                                                                                                                                                        | SDHC card of Class4 or higher rating is recommended.                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                           |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
| Ratings               | Power supply voltage                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                                                                                                                                                                        | 20.4 to 26.4 VDC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                                                                           |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
|                       | Current consumption (at 24.0 VDC) *2 | When connected to a intelligent compact camera                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Connected to 2 cameras                                                                                                                                                                                                                                                                 | 5.0 A max.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 5.4 A max.                                                                                                                                | 6.4 A max.                                                                                                                                                                             | 4.7 A max.                                                    | 5.0 A max.     | 5.9 A max.                                                                                                                                                                             |  |
|                       |                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Connected to 4 cameras                                                                                                                                                                                                                                                                 | —                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 7.0 A max.                                                                                                                                | 8.1 A max.                                                                                                                                                                             | —                                                             | 6.5 A max.     | 7.5 A max.                                                                                                                                                                             |  |
|                       |                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Connected to 8 cameras                                                                                                                                                                                                                                                                 | —                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | —                                                                                                                                         | 11.5 A max.                                                                                                                                                                            | —                                                             | —              | 10.9 A max.                                                                                                                                                                            |  |
|                       |                                      | When connected to a 300,000-pixel camera, 2 million-pixel camera, 4 million-pixel camera, 5 million-pixel camera or 12 million-pixel camera                                                                                                                                                                                                                                                                                                                                                         | Connected to 2 cameras                                                                                                                                                                                                                                                                 | 4.1 A max.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 4.2 A max.                                                                                                                                | 5.2 A max.                                                                                                                                                                             | 3.6 A max.                                                    | 3.7 A max.     | 4.5 A max.                                                                                                                                                                             |  |
|                       |                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Connected to 4 cameras                                                                                                                                                                                                                                                                 | —                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 4.8 A max.                                                                                                                                | 5.6 A max.                                                                                                                                                                             | —                                                             | 4.3 A max.     | 5.0 A max.                                                                                                                                                                             |  |
|                       |                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Connected to 8 cameras                                                                                                                                                                                                                                                                 | —                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | —                                                                                                                                         | 6.8 A max.                                                                                                                                                                             | —                                                             | —              | 6.2 A max.                                                                                                                                                                             |  |
|                       | Insulation resistance                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                                                                                                                                                                        | Between DC power supply and controller FG: 20 MΩ or higher (rated voltage 250 V)                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                                                                           |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
| Operation Environment | Noise Immunity                       | Fast transient burst                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | DC Power Supply                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Direct infusion: 2 KV Pulse rising: 5 ns Pulse width: 50 ns Burst continuation time: 15 ms/0.75 ms Period: 300 ms Application time: 1 min |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
|                       |                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | I/O line                                                                                                                                                                                                                                                                               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Cramp: 1 KV Pulse rising: 5 ns Pulse width: 50 ns Burst continuation time: 15 ms/0.75 ms Period: 300 ms Application time: 1 min           |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
|                       | Ambient temperature range            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                                                                                                                                                                        | Operating: 0 to 50 °C Storage: -20 to 65 °C (with no icing or condensation)                                                                                                                                                                                                                                                                                                                                                                                                                              |                                                                                                                                           |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
|                       | Ambient humidity range               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                                                                                                                                                                        | Operating and storage: 35% to 85% (with no condensation)                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                                                                           |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
|                       | Ambient atmosphere                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                                                                                                                                                                        | No corrosive gases                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                                                           |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
|                       | Grounding                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                                                                                                                                                                        | Type D grounding (100Ω or less grounding resistance) Conventional type 3 grounding                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                                                           |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
| Dimensions            | Degree of protection                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                                                                                                                                                                        | IEC60529 IP20                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                                                                                           |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
|                       | Dimensions                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                                                                                                                                                                        | 190 × 115 × 182.5 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                           |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
|                       | Weight                               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                                                                                                                                                                        | Approx. 3.2 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Approx. 3.4 kg                                                                                                                            | Approx. 3.4 kg                                                                                                                                                                         | Approx. 3.2 kg                                                | Approx. 3.4 kg | Approx. 3.4 kg                                                                                                                                                                         |  |
| Case materials        |                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Cover: zinc-plated steel plate, side plate: aluminum (A6063)                                                                                                                                                                                                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                                                                           |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |
| Accessories           |                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Controller (1) / user manual (one Japanese and one English versions) / Instruction Installation Manual (1) / Power supply terminal block connector (1) / Ferrite core (2, FH-3050 and FH-1050), 4 (FH-3050-10 and FH-1050-10), and 8 (FH-3050-20 and FH-1050-20)                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                                                                           |                                                                                                                                                                                        |                                                               |                |                                                                                                                                                                                        |  |

\*1 The image logging capacity changes when multiple cameras of different types are connected at the same time.

\*2 The current consumption when the maximum number of cameras supported by each controller are connected.

If a lighting controller model is connected to a lamp, the current consumption is as high as when an intelligent compact camera is connected.

## Ratings and Specifications (Cameras)

### High-speed CMOS cameras

| Model                                  | FH-SM                                                                        |  | FH-SC          |  | FH-SM02                                                             |  | FH-SC02         |  | FH-SM04                                 |  | FH-SC04         |  | FH-SM12                                                             |  | FH-SC12 |  |
|----------------------------------------|------------------------------------------------------------------------------|--|----------------|--|---------------------------------------------------------------------|--|-----------------|--|-----------------------------------------|--|-----------------|--|---------------------------------------------------------------------|--|---------|--|
| Image elements                         | CMOS image elements (1/3-inch equivalent)                                    |  |                |  | CMOS image elements (2/3-inch equivalent)                           |  |                 |  | CMOS image elements (1-inch equivalent) |  |                 |  | CMOS image elements (1.76-inch equivalent)                          |  |         |  |
| Color/Monochrome                       | Monochrome                                                                   |  | Color          |  | Monochrome                                                          |  | Color           |  | Monochrome                              |  | Color           |  | Monochrome                                                          |  | Color   |  |
| Effective pixels                       | 640 (H) × 480 (V)                                                            |  |                |  | 2040 (H) × 1088 (V)                                                 |  |                 |  | 2040 (H) × 2048 (V)                     |  |                 |  | 4084 (H) × 3072 (V)                                                 |  |         |  |
| Imaging area H x V (opposing corner)   | 4.8 × 3.6 (6.0 mm)                                                           |  |                |  | 11.26 × 5.98 (12.76 mm)                                             |  |                 |  | 11.26 × 11.26 (15.93 mm)                |  |                 |  | 22.5 × 16.9 (28.14 mm)                                              |  |         |  |
| Pixel size                             | 7.4 (μm) × 7.4 (μm)                                                          |  |                |  | 5.5 (μm) × 5.5 (μm)                                                 |  |                 |  | 5.5 (μm) × 5.5 (μm)                     |  |                 |  | 5.5 (μm) × 5.5 (μm)                                                 |  |         |  |
| Shutter function                       | Electronic shutter; Shutter speeds can be set from 20 μs to 100 ms.          |  |                |  | Electronic shutter; Shutter speeds can be set from 25 μs to 100 ms. |  |                 |  |                                         |  |                 |  | Electronic shutter; Shutter speeds can be set from 60 μs to 100 ms. |  |         |  |
| Partial function                       | 1 to 480 lines                                                               |  | 2 to 480 lines |  | 1 to 1088 lines                                                     |  | 2 to 1088 lines |  | 1 to 2048 lines                         |  | 2 to 2048 lines |  | 4 to 3072 lines (4-line increments)                                 |  |         |  |
| Frame rate (Image Acquisition Time)    | 308 fps (3.3 ms)                                                             |  |                |  | 219 fps (4.6 ms) *                                                  |  |                 |  | 118 fps (8.5 ms) *                      |  |                 |  | 38.9 fps (25.7 ms) *                                                |  |         |  |
| Lens mounting                          | C mount                                                                      |  |                |  |                                                                     |  |                 |  |                                         |  |                 |  | M42 mount                                                           |  |         |  |
| Field of vision, installation distance | Selecting a lens according to the field of vision and installation distance  |  |                |  |                                                                     |  |                 |  |                                         |  |                 |  |                                                                     |  |         |  |
| Ambient temperature range              | Operating: 0 to 40 °C, Storage: -25 to 65 °C (with no icing or condensation) |  |                |  |                                                                     |  |                 |  |                                         |  |                 |  |                                                                     |  |         |  |
| Ambient humidity range                 | Operating and storage: 35% to 85% (with no condensation)                     |  |                |  |                                                                     |  |                 |  |                                         |  |                 |  |                                                                     |  |         |  |
| Weight                                 | Approx.105 g                                                                 |  |                |  | Approx.110 g                                                        |  |                 |  |                                         |  |                 |  | Approx.320 g                                                        |  |         |  |
| Accessories                            | Instruction manual                                                           |  |                |  |                                                                     |  |                 |  |                                         |  |                 |  |                                                                     |  |         |  |

\* Frame rate in high speed mode when the camera is connected using two camera cables.

### Digital CCD Cameras

| Model                                     | FZ-S                                                                               | FZ-SC | FZ-S2M                                                                               | FZ-SC2M | FZ-S5M2                                                                            | FZ-SC5M2 |
|-------------------------------------------|------------------------------------------------------------------------------------|-------|--------------------------------------------------------------------------------------|---------|------------------------------------------------------------------------------------|----------|
| Image elements                            | Interline transfer reading all pixels,<br>CCD image elements (1/3-inch equivalent) |       | Interline transfer reading all pixels,<br>CCD image elements (1/1.8-inch equivalent) |         | Interline transfer reading all pixels,<br>CCD image elements (2/3-inch equivalent) |          |
| Color/Monochrome                          | Monochrome                                                                         | Color | Monochrome                                                                           | Color   | Monochrome                                                                         | Color    |
| Effective pixels                          | 640 (H) × 480 (V)                                                                  |       | 1600 (H) × 1200 (V)                                                                  |         | 2448 (H) × 2044 (V)                                                                |          |
| Imaging area H x V<br>(opposing corner)   | 4.8 × 3.6 (6.0mm)                                                                  |       | 7.1 × 5.4 (8.9mm)                                                                    |         | 8.4 × 7.1 (11mm)                                                                   |          |
| Pixel size                                | 7.4 (μm) × 7.4 (μm)                                                                |       | 4.4 (μm) × 4.4 (μm)                                                                  |         | 3.45 (μm) × 3.45 (μm)                                                              |          |
| Shutter function                          | Electronic shutter; select shutter speeds from 20 μs to 100 ms                     |       |                                                                                      |         |                                                                                    |          |
| Partial function                          | 12 to 480 lines                                                                    |       | 12 to 1200 lines                                                                     |         | 12 to 2044 lines                                                                   |          |
| Frame rate<br>(Image Acquisition Time)    | 80 fps (12.5 ms)                                                                   |       | 30 fps (33.3 ms)                                                                     |         | 16 fps (62.5 ms)                                                                   |          |
| Lens mounting                             | C mount                                                                            |       |                                                                                      |         |                                                                                    |          |
| Field of vision,<br>installation distance | Selecting a lens according to the field of vision and installation distance        |       |                                                                                      |         |                                                                                    |          |
| Ambient temperature<br>range              | Operating: 0 to 50 °C<br>Storage: -25 to 65 °C<br>(with no icing or condensation)  |       | Operating: 0 to 40 °C<br>Storage: -25 to 65 °C<br>(with no icing or condensation)    |         |                                                                                    |          |
| Ambient humidity range                    | Operating and storage: 35% to 85% (with no condensation)                           |       |                                                                                      |         |                                                                                    |          |
| Weight                                    | Approx. 55 g                                                                       |       | Approx. 76 g                                                                         |         | Approx.140 g                                                                       |          |
| Accessories                               | Instruction manual                                                                 |       |                                                                                      |         |                                                                                    |          |

### Small CCD Digital Cameras

| Model                                  | FZ-SF                                                                                                                   | FZ-SFC | FZ-SP              | FZ-SPC |
|----------------------------------------|-------------------------------------------------------------------------------------------------------------------------|--------|--------------------|--------|
| Image elements                         | Interline transfer reading all pixels, CCD image elements (1/3-inch equivalent)                                         |        |                    |        |
| Color/Monochrome                       | Monochrome                                                                                                              | Color  | Monochrome         | Color  |
| Effective pixels                       | 640 (H) × 480 (V)                                                                                                       |        |                    |        |
| Imaging area H × V (opposing corner)   | 4.8 × 3.6 (6.0mm)                                                                                                       |        |                    |        |
| Pixel size                             | 7.4 (μm) × 7.4 (μm)                                                                                                     |        |                    |        |
| Shutter function                       | Electronic shutter; select shutter speeds from 20 μm to 100 ms                                                          |        |                    |        |
| Partial function                       | 12 to 480 lines                                                                                                         |        |                    |        |
| Frame rate (Image Acquisition Time)    | 80 fps (12.5ms)                                                                                                         |        |                    |        |
| Lens mounting                          | Special mount (M10.5 P0.5)                                                                                              |        |                    |        |
| Field of vision, installation distance | Selecting a lens according to the field of vision and installation distance                                             |        |                    |        |
| Ambient temperature range              | Operating: 0 to 50 °C (camera amp)<br>0 to 45 °C (camera head)<br>Storage: -25 to 65 °C (with no icing or condensation) |        |                    |        |
| Ambient humidity range                 | Operating and storage: 35% to 85% (with no condensation)                                                                |        |                    |        |
| Weight                                 | Approx. 150 g                                                                                                           |        |                    |        |
| Accessories                            | Instruction manual, installation bracket,<br>Four mounting brackets (M2)                                                |        | Instruction manual |        |

## High-speed CCD Cameras


| Model                                  | FZ-SH                                                                           | FZ-SHC |
|----------------------------------------|---------------------------------------------------------------------------------|--------|
| Image elements                         | Interline transfer reading all pixels, CCD image elements (1/3-inch equivalent) |        |
| Color/Monochrome                       | Monochrome                                                                      | Color  |
| Effective pixels                       | 640 (H) × 480 (V)                                                               |        |
| Imaging area H x V (opposing corner)   | 4.8 × 3.6 (6.0mm)                                                               |        |
| Pixel size                             | 7.4 (μm) × 7.4 (μm)                                                             |        |
| Shutter function                       | Electronic shutter; select shutter speeds from 1/10 to 1/50,000 s               |        |
| Partial function                       | 12 to 480 lines                                                                 |        |
| Frame rate (Image Acquisition Time)    | 204 fps (4.9ms)                                                                 |        |
| Field of vision, installation distance | Selecting a lens according to the field of vision and installation distance     |        |
| Ambient temperature range              | Operating: 0 to 40 °C<br>Storage: -25 to 65 °C (with no icing or condensation)  |        |
| Ambient humidity range                 | Operating and storage: 35% to 85% (with no condensation)                        |        |
| Weight                                 | Approx. 105 g                                                                   |        |
| Accessories                            | Instruction manual                                                              |        |

## Intelligent Compact CMOS Cameras


| Model                                | FZ-SQ010F                                                                                             | FZ-SQ050F              | FZ-SQ100F               | FZ-SQ100N               |
|--------------------------------------|-------------------------------------------------------------------------------------------------------|------------------------|-------------------------|-------------------------|
| Image elements                       | CMOS color image elements (1/3-inch equivalent)                                                       |                        |                         |                         |
| Color/Monochrome                     | Color                                                                                                 |                        |                         |                         |
| Effective pixels                     | 752 (H) × 480 (V)                                                                                     |                        |                         |                         |
| Imaging area H x V (opposing corner) | 4.51 × 2.88 (5.35mm)                                                                                  |                        |                         |                         |
| Pixel size                           | 6.0 (μm) × 6.0 (μm)                                                                                   |                        |                         |                         |
| Shutter function                     | 1/250 to 1/32,258                                                                                     |                        |                         |                         |
| Partial function                     | 8 to 480 lines                                                                                        |                        |                         |                         |
| Frame rate (Image Acquisition Time)  | 60 fps (16.7 ms)                                                                                      |                        |                         |                         |
| Field of vision                      | 7.5 × 4.7 to 13 × 8.2 mm                                                                              | 13 × 8.2 to 53 × 33 mm | 53 × 33 to 240 × 153 mm | 29 × 18 to 300 × 191 mm |
| Installation distance                | 38 to 60 mm                                                                                           | 56 to 215 mm           | 220 to 970 mm           | 32 to 380 mm            |
| LED class *                          | Risk Group2                                                                                           |                        |                         |                         |
| Ambient temperature range            | Operating: 0 to 50 °C<br>Storage: -25 to 65 °C                                                        |                        |                         |                         |
| Ambient humidity range               | Operating and storage: 35% to 85% (with no condensation)                                              |                        |                         |                         |
| Weight                               | Approx. 150 g                                                                                         |                        | Approx. 140 g           |                         |
| Accessories                          | Mounting bracket (FQ-XL), polarizing filter attachment (FQ-XF1), instruction manual and warning label |                        |                         |                         |

\* Applicable standards: IEC62471-2


### • Narrow View FZ-SQ010F




### • Standard FZ-SQ050F



### • Wide View (Long-distance) FZ-SQ100F



### • Wide View (Short-distance) FZ-SQ100N



## Ratings and Specifications (Cable, Monitor)

### Camera Cables

| Model                            | FZ-VS3<br>(2 m)                                                           | FZ-VSB3<br>(2 m) | FZ-VSL3<br>(2 m) | FZ-VSLB3<br>(2 m) |
|----------------------------------|---------------------------------------------------------------------------|------------------|------------------|-------------------|
| Shock resistiveness (durability) | 10 to 150 Hz single amplitude 0.15 mm<br>3 directions, 8 strokes, 4 times |                  |                  |                   |
| Ambient temperature range        | Operation and storage: 0 to 65 °C<br>(with no icing or condensation)      |                  |                  |                   |
| Ambient humidity range           | Operation and storage: 40 to 70%RH<br>(with no condensation)              |                  |                  |                   |
| Ambient atmosphere               | No corrosive gases                                                        |                  |                  |                   |
| Material                         | Cable sheath, connector: PVC                                              |                  |                  |                   |
| Minimum bending radius           | 69mm                                                                      | 69mm             | 69mm             | 69mm              |
| Weight                           | Approx. 170 g                                                             | Approx. 180 g    | Approx. 170 g    | Approx. 180 g     |

### Cable Extension Unit

| Model                     | FZ-VSJ                                                                          |
|---------------------------|---------------------------------------------------------------------------------|
| Power supply voltage *1   | 11.5 to 13.5 VDC                                                                |
| Current consumption *2    | 1.5 A max.                                                                      |
| Ambient temperature range | Operating: 0 to 50 °C; Storage: -25 to 65 °C<br>(with no icing or condensation) |
| Ambient humidity range    | Operating and storage: 35 to 85%<br>(with no condensation)                      |
| Weight                    | Approx. 240 g                                                                   |
| Accessories               | Instruction Sheet and 4 mounting screws                                         |

\*1 A 12-VDC power supply must be provided to the Cable Extension Unit when connecting the Intelligent Compact Camera, or the Lighting Controller.

\*2 The current consumption shows when connecting the Cable Extension Unit to an external power supply.

### Long-distance Camera Cables

| Model                            | FZ-VS4 (15 m)                                                             | FZ-VSL4 (15 m) |
|----------------------------------|---------------------------------------------------------------------------|----------------|
| Shock resistiveness (durability) | 10 to 150 Hz single amplitude 0.15 mm<br>3 directions, 8 strokes, 4 times |                |
| Ambient temperature range        | Operation and storage: 0 to 65 °C<br>(with no icing or condensation)      |                |
| Ambient humidity range           | Operation and storage: 40 to 70%RH<br>(with no condensation)              |                |
| Ambient atmosphere               | No corrosive gases                                                        |                |
| Material                         | Cable sheath, connector: PVC                                              |                |
| Minimum bending radius           | 78 mm                                                                     |                |
| Weight                           | Approx. 1400 g                                                            |                |

### Encoder Cable

| Model                     | FH-VR                                                                             |
|---------------------------|-----------------------------------------------------------------------------------|
| Vibration resistiveness   | 10 to 150 Hz single amplitude 0.1 mm<br>3 directions, 8 strokes, 10 times         |
| Ambient temperature range | Operation: 0 to 50 °C; Storage: -10 to 60 °C<br>(with no icing or condensation)   |
| Ambient humidity range    | Operation and storage: 35 to 85%RH<br>(with no condensation)                      |
| Ambient atmosphere        | No corrosive gases                                                                |
| Material                  | Cable Jacket: Heat, oil and flame resistant PVC<br>Connector: polycarbonate resin |
| Minimum bending radius    | 65 mm                                                                             |
| Weight                    | Approx. 104 g                                                                     |

### Touch Panel Monitor

| Model                 | FH-MT12                   |                                                                                                                                     |
|-----------------------|---------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| Major Function        | Display area              | 12.1 inch                                                                                                                           |
|                       | Resolution                | 1024 (V) × 768 (H)                                                                                                                  |
|                       | Number of color           | 16,700,000 colors (8 bit/color)                                                                                                     |
|                       | Brightness                | 500cd/m <sup>2</sup> (Typ)                                                                                                          |
|                       | Contrast Ratio            | 600:1 (Typ)                                                                                                                         |
|                       | Viewing angle             | Left and right: each 80°, upward: 80°, downward: 60°                                                                                |
|                       | Backlight Unit            | LED, edge-light                                                                                                                     |
|                       | Backlight lifetime        | About 100,000hour                                                                                                                   |
| External interface    | Touch panel               | 4wire resistive touch screen                                                                                                        |
|                       | Video input               | analog RGB                                                                                                                          |
|                       | Touch panel signal        | USB<br>RS-232C                                                                                                                      |
| Ratings               | Power supply voltage      | 24 VDC (21.6 to 26.4 VDC)                                                                                                           |
|                       | Current consumption       | Between DC power supply and touch panel monitor                                                                                     |
|                       | Insulation resistance     | FG: 20 MΩ or higher (rated voltage 250 V)                                                                                           |
| Operating environment | Ambient temperature range | Operating: 0 to 50°C, Storage: -20 to +65°C (with no icing or condensation)                                                         |
|                       | Ambient humidity range    | Operating and Storage: 20 to 85 %RH (with no icing or condensation)                                                                 |
|                       | Ambient environment       | No corrosive gas                                                                                                                    |
|                       | Vibration resistance      | 10 to 150 Hz, one-side amplitude 0.1 mm (Max. acceleration 15 m/s <sup>2</sup> )<br>10 times for 8 minutes for each three direction |
|                       | Degree of protection      | Panel mounting: IP65 on the front                                                                                                   |
| Operation             | Touch pen                 |                                                                                                                                     |
| Structure             | Mounting                  | Panel mounting, VESA mounting                                                                                                       |
|                       | Weight                    | Approx.2.6 kg                                                                                                                       |
|                       | Material                  | Front panel: PC/PBT, Front Sheet: PET, Rear case: SUS                                                                               |

**Note:** FH Series Sensor Controllers version 5.32 or higher is required. It cannot be used in FZ series.

### Touch Panel Monitor Cables

| Model                | FH-VMDA (2 m)                                                                                    | FH-VUAB (2 m) | XW2Z-200PP-1 (2 m)                                    |
|----------------------|--------------------------------------------------------------------------------------------------|---------------|-------------------------------------------------------|
| Cable type           | DVI-Analog Conversion Cable                                                                      | USB Cable     | RS-232C Cable                                         |
| Vibration resistance | 10 to 150 Hz, one-side amplitude 0.1 mm, 10 times for 8 minutes for each three direction         |               |                                                       |
| Ambient Temperature  | Operating Condition: 0 to 50°C, Storage Condition: -10 to 60°C (with no icing or condensation)   |               |                                                       |
| Ambient Humidity     | Operating Condition: 35 to 85%RH, Storage Condition: 35 to 85%RH (with no icing or condensation) |               |                                                       |
| Ambient environment  | No corrosive gases                                                                               |               |                                                       |
| Material             | Cable outer sheath, Connector: PVC                                                               |               | Cable outer sheath: PVC,<br>Connector: ABS/Ni Plating |
| Minimum bend radius  | 36 mm                                                                                            | 25 mm         | 59 mm                                                 |
| Weight               | Approx.220 g                                                                                     | Approx.75 g   | Approx.162 g                                          |

## LCD Monitor

| Model                     | FZ-M08                                                                       |
|---------------------------|------------------------------------------------------------------------------|
| Size                      | 8.4 inches                                                                   |
| Type                      | Liquid crystal color TFT                                                     |
| Resolution                | 1,024 × 768 dots                                                             |
| Input signal              | Analog RGB video input, 1 channel                                            |
| Power supply voltage      | 21.6 to 26.4 VDC                                                             |
| Current consumption       | Approx. 0.7 A max.                                                           |
| Ambient temperature range | Operating: 0 to 50 °C; Storage: -25 to 65 °C (with no icing or condensation) |
| Ambient humidity range    | Operating and storage: 35 to 85% (with no condensation)                      |
| Weight                    | Approx. 1.2 kg                                                               |
| Accessories               | Instruction Sheet and 4 mounting brackets                                    |

## LED Monitor Cable

| Model                     | FZ-VM                                                                        |
|---------------------------|------------------------------------------------------------------------------|
| Vibration resistiveness   | 10 to 150 Hz single amplitude 0.15 mm<br>3 directions, 8 strokes, 4 times    |
| Ambient temperature range | Operation: 0 to 50 °C; Storage: -20 to 65 °C (with no icing or condensation) |
| Ambient humidity range    | Operation and storage: 35 to 85%RH (with no condensation)                    |
| Ambient atmosphere        | No corrosive gases                                                           |
| Material                  | Cable sheath: heat-resistant PVC Connector: PVC                              |
| Minimum bending radius    | 75 mm                                                                        |
| Weight                    | Approx. 170 g                                                                |

**Note:** When you connect a LCD Monitor FZ-M08 to FH sensor controller, please use it in combination with a DVI-I -RGB Conversion Connector FH-VMRGB.

## EtherCAT Communications Specifications

| Item                          | Specifications                                                                                              |
|-------------------------------|-------------------------------------------------------------------------------------------------------------|
| Communications standard       | IEC61158 Type 12                                                                                            |
| Physical layer                | 100 BASE-TX (IEEE802.3)                                                                                     |
| Modulation                    | Base band                                                                                                   |
| Baud rate                     | 100 Mbps                                                                                                    |
| Topology                      | Depends on the specifications of the EtherCAT master.                                                       |
| Transmission Media            | Twisted-pair cable of category 5 or higher (double-shielded straight cable with aluminum tape and braiding) |
| Transmission Distance         | Distance between nodes: 100 m or less                                                                       |
| Node address setting          | 00 to 9                                                                                                     |
| External connection terminals | RJ45 × 2 (shielded) IN: EtherCAT input data, OUT: EtherCAT output data                                      |
| Send/receive PDO data sizes   | Input 56 to 280 bytes/line (including input data, status, and unused areas) Up to 8 lines can be set. *     |
|                               | Output 28 bytes/line (including output data and unused areas) Up to 8 lines can be set. *                   |
| Mailbox data size             | Input 512 bytes                                                                                             |
|                               | Output 512 bytes                                                                                            |
| Mailbox                       | Emergency messages, SDO requests, and SDO information                                                       |
| Refreshing methods            | I/O-synchronized refreshing (DC)                                                                            |

\* This depends on the upper limit of the master.

## Version Information



### FH Series and Programming Devices

Use the latest version of Sysmac Studio Standard Edition/Vision Edition.

| FH Series                    | Version of FH Series | Corresponding version of Sysmac Studio Standard Edition/Vision Edition       |
|------------------------------|----------------------|------------------------------------------------------------------------------|
| FH-3050 (-□)<br>FH-1050 (-□) | Version 5.30         | Supported by version 1.10.80 or higher.                                      |
|                              | Version 5.20         | Supported by version 1.10 or higher.                                         |
|                              | Version 5.10         | Supported by version 1.07.43 or higher.                                      |
|                              | Version 5.00         | Supported by version 1.07 or higher. Not supported by version 1.06 or lower. |

## Components and Functions


### Example of the FH Sensor Controllers BOX type (4-camera type)



|      | Name                       | Description                                                                             |
|------|----------------------------|-----------------------------------------------------------------------------------------|
| [1]  | POWER LED                  | Lit while power is ON.                                                                  |
| [2]  | ERROR LED                  | Lit when an error has occurred.                                                         |
| [3]  | RUN LED                    | Lit while the controller is in Measurement Mode.                                        |
| [4]  | ACCESS LED                 | Lit while the memory is accessed.                                                       |
| [5]  | SD POWER LED               | Lit while power is supplied to the SD card and the card is usable.                      |
| [6]  | SD BUSY LED                | Blinks while the SD memory card is accessed.                                            |
| [7]  | EtherCAT RUN LED           | Lit while EtherCAT communications are usable.                                           |
| [8]  | EtherCAT LINK/ACT IN LED   | Lit when connected with an EtherCAT device, and blinks while performing communications. |
| [9]  | EtherCAT LINK/ACT OUT LED  | Lit when connected with an EtherCAT device, and blinks while performing communications. |
| [10] | EtherCAT ERR LED           | Lit when EtherCAT communications have become abnormal.                                  |
| [11] | EtherNet NET RUN1 LED      | Lit while EtherNet communications are usable.                                           |
| [12] | EtherNet NET LINK/ACK1 LED | Lit when connected with an EtherNet device, and blinks while performing communications. |
| [13] | EtherNet NET RUN2 LED      | Lit when EtherNet communications are usable.                                            |
| [14] | EtherNet NET LINK/ACK2 LED | Lit when connected with an EtherNet device, and blinks while performing communications. |

|   | Name                                      | Description                                                                                                                                                                                            |
|---|-------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| A | SD memory card installation connector     | Install the SD memory card. Do not plug or unplug the SD card during measurement operation. Otherwise measurement time may be affected or data may be destroyed.                                       |
| B | EtherNet connector                        | Connect an EtherNet device.                                                                                                                                                                            |
| C | USB connector                             | Connect a USB device. Do not plug or unplug it during measurement operation. Otherwise measurement time may be affected or data may be destroyed.                                                      |
| D | RS-232C connector                         | Connect an external device such as a programmable controller.                                                                                                                                          |
| E | DVI-I connector                           | Connect a monitor.                                                                                                                                                                                     |
| F | I/O connector (control lines, data lines) | Connect the controller to external devices such as a sync sensor and PLC.                                                                                                                              |
| G | EtherCAT address setup volume             | Used to set a node address (00 to 99) as an EtherCAT communication device.                                                                                                                             |
| H | EtherCAT communication connector (IN)     | Connect the opposed EtherCAT device.                                                                                                                                                                   |
| I | EtherCAT communication connector (OUT)    | Connect the opposed EtherCAT device.                                                                                                                                                                   |
| J | Encoder connector                         | Connect an encoder.                                                                                                                                                                                    |
| K | Camera connector                          | Connect cameras.                                                                                                                                                                                       |
| L | Power supply terminal connector           | Connect a DC power supply. Wire the controller independently on other devices. Wire the ground line. Be sure to ground the controller alone. Perform wiring using the attached power supply connector. |

### Example of the FZ5-Lite Sensor Controllers LCD-integrated type (4-camera type)



|      | Name                                      | Description                                                                                                                                                                                                                                                                                             |
|------|-------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| [1]  | POWER LED                                 | Lit while power is ON.                                                                                                                                                                                                                                                                                  |
| [2]  | RUN LED                                   | Lit while the controller is in Run Mode.                                                                                                                                                                                                                                                                |
| [3]  | ERROR LED                                 | Lit when an error has occurred.                                                                                                                                                                                                                                                                         |
| [4]  | I/O connector (control lines, data lines) | Connect the controller to external devices such as a sync sensor and PLC.                                                                                                                                                                                                                               |
| [5]  | Camera connector                          | Connect cameras.                                                                                                                                                                                                                                                                                        |
| [6]  | Power                                     | Connect a DC power supply. Wire the power supply unit independently of other devices. After wiring, replace the terminal cover.                                                                                                                                                                         |
| [7]  | Monitor connector (analog RGB)            | Connect a monitor. (Provided with Lite controller type only)                                                                                                                                                                                                                                            |
| [8]  | RS-232C/RS-422 connector                  | Connect an external device such as a personal computer or PLC.                                                                                                                                                                                                                                          |
| [9]  | USB connector                             | Connect a track ball, mouse and USB memory. A total of four USB ports are provided and any of them can be used. However, when connecting two or more USB memories, do not connect them to adjacent ports. Doing so may cause the USB memories to come into contact, resulting in malfunction or damage. |
| [10] | EtherNet connector                        | Connect the controller to a personal computer.                                                                                                                                                                                                                                                          |

# FH-Series

## Processing Items

| Group       | Icon | Processing Item                                                                                                                                                                                                                                                   | Corresponding Page in the Catalog |
|-------------|------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|
| Measurement |      | Search<br>Used to identify the shapes and calculate the position of measurement objects.                                                                                                                                                                          | P16                               |
|             |      | Flexible Search<br>Recognizing the shapes of workpieces with variation and detecting their positions.                                                                                                                                                             | P16                               |
|             |      | Sensitive Search<br>Search a small difference by dividing the search model in detail, and calculating the correlation.                                                                                                                                            | P16                               |
|             |      | ECM Search<br>Used to search the similar part of model form input image. Detect the evaluation value and position.                                                                                                                                                |                                   |
|             |      | EC Circle Search<br>Extract circles using "round " shape information and get position, radius and quantity in high preciseness.                                                                                                                                   |                                   |
|             |      | Shape Search II<br>Used to search the similar part of model from input image regardless of environmental changes. Detect the evaluation value and position.                                                                                                       | P16                               |
|             |      | Shape Search III<br>Robust detection of positions is possible at high-speed and with high precision incorporating environmental fluctuations, such as differences in individual shapes of the workpieces, pose fluctuations, noise superimposition and shielding. | P16                               |
|             |      | EC Corner<br>This processing item measures a corner position (corner) of a workpiece.                                                                                                                                                                             |                                   |
|             |      | Ec Cross<br>The center position of a crosshair shape is measured using the lines created by the edge information on each side of the crosshair.                                                                                                                   |                                   |
|             |      | Classification<br>Used when various kinds of products on the assembly line need to be sorted and identified.                                                                                                                                                      | P16                               |
|             |      | Edge Position<br>Measure position of measurement objects according to the color change in measurement area.                                                                                                                                                       | P16                               |
|             |      | Edge Pitch<br>Detect edges by color change in measurement area. Used for calculating number of pins of IC and connectors.                                                                                                                                         | P16                               |
|             |      | Scan Edge Position<br>Measure peak/bottom edge position of workpieces according to the color change in separated measurement area.                                                                                                                                | P16                               |
|             |      | Scan Edge Width<br>Measure max/min/average width of workpieces according to the color change in separated measurement area.                                                                                                                                       | P16                               |
|             |      | Circular Scan Edge Position<br>Measure center axis, diameter and radius of circular workpieces.                                                                                                                                                                   | P16                               |
|             |      | Circular Scan Edge Width<br>Measure center axis, width and thickness of ring workpieces.                                                                                                                                                                          | P16                               |
|             |      | Intersection<br>Calculate approximate lines from the edge information on two sides of a square workpiece to measure the angle formed at the intersection of the two lines.                                                                                        | P16                               |
|             |      | Color Data<br>Used for detecting presence and mixed varieties of products by using color average and deviation.                                                                                                                                                   |                                   |
|             |      | Gravity and Area<br>Used to measure area, center of gravity of workpieces by extracting the color to be measured.                                                                                                                                                 |                                   |
|             |      | Labeling<br>Used to measure number, area and gravity of workpieces by extracting registered color.                                                                                                                                                                |                                   |
|             |      | Label Data<br>Selecting one region of extracted Labeling, and get that measurement. Area and Gravity position can be got and judged.                                                                                                                              |                                   |
|             |      | Defect<br>Used for appearance measurement of plain-color measurement objects such as defects, stains and burrs.                                                                                                                                                   | P16                               |
|             |      | Precise Defect<br>Check the defect on the object. Parameters for extraction defect can be set precisely.                                                                                                                                                          | P16                               |
|             |      | Fine Matching<br>Difference can be detected by overlapping and comparing (matching) registered fine images with input images.                                                                                                                                     | P16                               |
|             |      | Character Inspect<br>Recognize character according correlation search with model image registered in [Model Dictionary].                                                                                                                                          | P17                               |
|             |      | Date Verification<br>Reading character string is verified with internal date.                                                                                                                                                                                     | P17                               |
|             |      | Model Dictionary<br>Register character pattern as dictionary. The pattern is used in [Character Inspection].                                                                                                                                                      |                                   |
|             |      | 2DCode *2<br>Recognize 2D code and display where the code quality is poor.                                                                                                                                                                                        | P17                               |
|             |      | Barcode *1<br>Recognize barcode, verify and output decoded characters.                                                                                                                                                                                            | P17                               |
|             |      | OCR<br>Recognize and read characters in images as character information.                                                                                                                                                                                          | P17                               |
|             |      | OCR User Dictionary<br>Register dictionary data to use for OCR.                                                                                                                                                                                                   | P17                               |
|             |      | Circle Angle<br>Used for calculating angle of inclination of circular measurement objects.                                                                                                                                                                        |                                   |
|             |      | Glue Bead Inspection<br>You can inspect coating of a specified color for gaps or runoffs along the coating path.                                                                                                                                                  | P17                               |
| Input Image |      | To input images from cameras. And set up the conditions to input images from cameras. (To FZ5 Sensor Controllers only)                                                                                                                                            |                                   |
|             |      | To input images from cameras. And set up the conditions to input images from cameras. (For FH Sensor Controllers only)                                                                                                                                            |                                   |

| Group               | Icon | Processing Item                                                                                                                                                                                                               | Corresponding Page in the Catalog |
|---------------------|------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|
| Input Image         |      | Camera Image Input HDR<br>Create high-dynamic range images by acquiring several images with different conditions.                                                                                                             |                                   |
|                     |      | Camera Image Input HDR Lite<br>HDR function for FZ-SQ□ Intelligent Compact Cameras.                                                                                                                                           |                                   |
|                     |      | Camera Switch<br>To switch the cameras used for measurement. Not input images from cameras again.                                                                                                                             |                                   |
|                     |      | Measurement Image Switching<br>To switch the images used for measurement. Not input images from camera again.                                                                                                                 |                                   |
| Compensate image    |      | Position Compensation<br>Used when positions are differed. Correct measurement is performed by correcting position of input images.                                                                                           | P18                               |
|                     |      | Filtering<br>Used for processing images input from cameras in order to make them easier to be measured.                                                                                                                       | P18                               |
|                     |      | Background Suppression<br>To enhance contrast of images by extracting color in specified brightness.                                                                                                                          | P18                               |
|                     |      | Brightness Correct Filter<br>Track brightness change of entire screen and remove gradual brightness change such as uneven brightness.                                                                                         | P18                               |
|                     |      | Color Gray Filter<br>Color image is converted into monochrome images to emphasize specific color.                                                                                                                             | P18                               |
|                     |      | Extract Color Filter<br>Convert color image to color extracted image or binary image.                                                                                                                                         | P18                               |
|                     |      | Anti Color Shading<br>To remove the irregular color/pattern by uniformizing max.2 specified colors.                                                                                                                           | P18                               |
|                     |      | Stripes Removal Filter II<br>Remove the background pattern of vertical, horizontal and diagonal stripes.                                                                                                                      | P19                               |
|                     |      | Polar Transformation<br>Rectify the image by polar transformation. Useful for OCR or pattern inspection printed on circle.                                                                                                    | P18                               |
|                     |      | Trapezoidal Correction<br>Rectify the trapezoidal deformed image.                                                                                                                                                             | P18                               |
|                     |      | Machine Simulator<br>How the alignment marks would move on the image when each stage or robot axis is controlled can be checked.                                                                                              |                                   |
|                     |      | Image Subtraction<br>The registered model image and measurement image are compared and only the different pixels are extracted and converted to an image.                                                                     |                                   |
|                     |      | Advanced filter<br>Process the images acquired from cameras in order to make them easier to measure. This processing item consolidates existing image conversion filtering into one processing item and adds extra functions. | P18                               |
|                     |      | Panorama<br>Combine multiple image to create one big image.                                                                                                                                                                   | P18                               |
|                     |      | Unit Macro<br>Advanced arithmetic processing can be easily incorporated into workflow as Unit Macro processing items.                                                                                                         | P20                               |
| Support measurement |      | Unit Calculation Macro<br>This function is convenient when the user wants to calculate a value using an original calculation formula or change the set value or system data of a processing item.                             | P20                               |
|                     |      | Calculation<br>Used when using the judge results and measured values of Procterm which are registered in processing units.                                                                                                    |                                   |
|                     |      | Line Regression<br>Used for calculating regression line from plural measurement coordinate.                                                                                                                                   |                                   |
|                     |      | Circle Regression<br>Used for calculating regression circle from plural measurement coordinate.                                                                                                                               |                                   |
|                     |      | Precise Calibration<br>Used for calibration corresponding to trapezoidal distortion and lens distortion.                                                                                                                      | P15                               |
|                     |      | User Data<br>Used for setting of the data that can be used as common constants and variables in scene group data.                                                                                                             | P21                               |
|                     |      | Set Unit Data<br>Used to change the Procterm data (setting parameters, etc.) that has been set up in a scene.                                                                                                                 |                                   |
|                     |      | Get Unit Data<br>Used to get one data (measured results, setting parameters, etc.) of Procterm that has been set up in a scene.                                                                                               |                                   |
|                     |      | Set Unit Figure<br>Used for re-setting the figure data (model, measurement area ) registered in an unit.                                                                                                                      |                                   |
|                     |      | Get Unit Figure<br>Used for get the figure data (model, measurement area ) registered in an unit.                                                                                                                             |                                   |
|                     |      | Trend Monitor<br>Used for displaying the information about results on the monitor, facilitating to avoid NG and analyze causes.                                                                                               | P21                               |
|                     |      | Image Logging<br>Used for saving the measurement images to the memory and USB memory.                                                                                                                                         |                                   |
|                     |      | Image Conversion Logging<br>Used for saving the measurement images in JPEG and BMP format.                                                                                                                                    |                                   |
|                     |      | Data Logging<br>Used for saving the measurement data to the memory and USB memory.                                                                                                                                            |                                   |
|                     |      | Elapsed Time<br>Used for calculating the elapsed time since the measurement trigger input.                                                                                                                                    |                                   |
|                     |      | Wait<br>Processing is stopped only at the set time. The standby time is set by the unit of [ms].                                                                                                                              |                                   |

| Group               | Icon | Processing Item           | Corresponding Page in the Catalog                                                                                                                                                                                                                             |
|---------------------|------|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Support measurement |      | Focus                     | Focus setting is supported.                                                                                                                                                                                                                                   |
|                     |      | Iris                      | Focus and aperture setting is supported.                                                                                                                                                                                                                      |
|                     |      | Parallelize *3            | A part of the measurement flow is divided into two or more tasks and processed in parallel to shorten the measurement time. This processing item is placed at the top of processing to be performed in parallel.                                              |
|                     |      | Parallelize Task *3       | A part of the measurement flow is divided into two or more tasks and processed in parallel to shorten the measurement time. This processing item is placed immediately before processing to be performed in parallel between Parallelize and Parallelize End. |
|                     |      | Statistics                | Used when you need to calculate an average of multiple measurement results.                                                                                                                                                                                   |
|                     |      | Reference Calib Data      | Calibration data and distortion compensation data held under other processing items can be referenced.                                                                                                                                                        |
|                     |      | Position Data Calculation | The specified position angle is calculated from the measured positions.                                                                                                                                                                                       |
|                     |      | Stage Data                | Sets and stores data related to stages.                                                                                                                                                                                                                       |
|                     |      | Robot Data                | Sets and stores data related to robots.                                                                                                                                                                                                                       |
|                     |      | Vision Master Calibration | This processing item automatically calculates the entire axis movement amount of the control equipment necessary for calibration.                                                                                                                             |
|                     |      | PLC Master Calibration    | Calibration data is created using a communication command from PLC.                                                                                                                                                                                           |
|                     |      | Convert Position Data     | The position angle after the specified axis movement is calculated.                                                                                                                                                                                           |
|                     |      | Movement Single Position  | The axis movement that is required to match the measured position angle to the reference position angle is calculated.                                                                                                                                        |
|                     |      | Movement Multi Points     | The axis movements that are required to match the measured position angles to the corresponding reference position angles are calculated.                                                                                                                     |
|                     |      | Detection Point           | Obtains position/angle information by referring to the coordinate values measured with the Measurement Processing Unit.                                                                                                                                       |
|                     |      | Camera Calibration        | By setting the camera calibration, the measurement result can be converted and output as actual dimensions.                                                                                                                                                   |
|                     |      | Data Save                 | The set data can be saved in the controller main unit or as scene data. The data is held even after the FH/FZ power is turned off.                                                                                                                            |
|                     |      |                           |                                                                                                                                                                                                                                                               |
| Group               | Icon | Processing Item           | Corresponding Page in the Catalog                                                                                                                                                                                                                             |
| Branch              |      | Conditional Branch        | Used where more than two kinds of products on the production line need to be detected separately.                                                                                                                                                             |
|                     |      | End                       | This Procltem must be set up as the last processing unit of a branch.                                                                                                                                                                                         |
|                     |      | DI Branch                 | Same as Procltem "Branch". But you can change the targets of conditional branching via external inputs.                                                                                                                                                       |
|                     |      | Control Flow Normal       | Set the measurement flow processing into the wait state in which the specific no-protocol command can be executed.                                                                                                                                            |
|                     |      | Control Flow PLC Link     | Set the measurement flow processing into the wait state in which the specific PLC Link command can be executed.                                                                                                                                               |
|                     |      | Control Flow Parallel     | Set the measurement flow processing into the wait state in which the specific parallel command can be executed.                                                                                                                                               |
|                     |      | Control Flow Fieldbus     | Set the measurement flow processing into the wait state in which the specific Fieldbus command can be executed.                                                                                                                                               |
| Output results      |      | Selective Branch          | Easily branch to multiple destinations.                                                                                                                                                                                                                       |
|                     |      | Data Output               | Used when you need to output data to the external devices such as PLC or PC via serial ports.                                                                                                                                                                 |
|                     |      | Parallel Data Output      | Used when you need to output data to the external devices such as PLC or PC via parallel ports.                                                                                                                                                               |
|                     |      | Parallel Judgement Output | Used when you need to output judgement results to the external devices such as PLC or PC via parallel ports.                                                                                                                                                  |
| Output result       |      | Fieldbus Data Output      | Outputs data to an external device, such as a Programmable Controller, through a fieldbus interface.                                                                                                                                                          |
|                     |      | Result Display            | Used for displaying the texts or the figures in the camera image.                                                                                                                                                                                             |
|                     |      | Display Image File        | Display selected image file.                                                                                                                                                                                                                                  |
|                     |      | Display Last NG Image     | Display the last NG images.                                                                                                                                                                                                                                   |

\*1 Bar Codes that can be read : JAN/EAN/UPC (including add-on codes), Code 39, Codabar (NW-7), ITF (Interleaved 2 of 5), Code 93, Code 128, GS1-128, GS1 DataBar (RSS-14 / RSS Limited / RSS Expanded), Pharmacode

\*2 2D Codes that can be read : Data Matrix (ECC200), QR Code

\*3 FZ5-L3□□ controllers do not support.

## Dimensions


(Unit: mm)

### Sensor Controllers


#### FH-series Box-type

FH-3050/-3050-10/-3050-20

FH-1050/-1050-10/-1050-20



## FZ5-series Lite Box-type FZ5-L350/-L355/-L350-10/-L355-10




## Cameras

### High-speed CMOS Camera


#### 300,000-pixel camera

FH-SC  
FH-SM




#### 2 million-pixel camera

FH-SC02  
FH-SM02




#### 4 million-pixel camera

FH-SC04  
FH-SM04




#### 12 million-pixel camera

FH-SC12  
FH-SM12




## Digital CCD Cameras


**300,000-pixel camera**  
FZ-S  
FZ-SC



**2 million-pixel camera**  
FZ-S2M  
FZ-SC2M




**5 million-pixel camera**  
FZ-S5M2  
FZ-SC5M2



## High-speed CCD Camera


FZ-SH  
FZ-SHC




## Small digital CCD cameras

**Camera head**

Flat camera  
FZ-SF  
FZ-SFC




**Pen-shaped camera**  
FZ-SP  
FZ-SPC




**Camera amplifier**

Can be used for both flat cameras and pen-shaped cameras




## Intelligent Compact CMOS Cameras


**Narrow view / Standard**  
FZ-SQ010F  
FZ-SQ050F




\*1. The mounting brackets can be connected to either side.



**Wide View**  
FZ-SQ100F (long-distance)  
FZ-SQ100N (short-distance)



\*1. The mounting brackets can be connected to either side.




Tightening torque: 1.2 N·m

## Cables

### Camera Cable


Camera Cable

FZ-VS3




### Bend resistant Camera Cable

FZ-VSB3




### Right-angle Camera Cable

FZ-VSL3




### Bend resistant Right-angle Camera Cable

FZ-VSLB3




### Long-distance Camera Cable

FZ-VS4



### Long-distance Right-angle Camera Cable

FZ-VSL4



\*1. Cable is available in 2m/3m/5m/10m.


\*2. Each camera cables has polarity.

Please ensure that the name plate side of the cable is connected to the controller.

\*3. Cable is available in 15m.


## Camera Cable Extension Unit

FZ-VSJ




## Extension Tubes for Small Camera

FZ-LESR



## Lens for Small Camera


FZ-LES Series



\* Overall length is available in 16.4mm/19.7mm/23.1mm/25.5mm.

## Encoder Cable


FH-VR



\*1. Cable is available in 1.5 m.

## Parallel I/O Cable




XW2Z-S013-□



\*1. Cable is available in 2m/5m.

## Touch Panel Monitor


FH-MT12



Note: 1. Panel thickness : 1.6 to 4.8 mm  
2. No burr allowed


## DVI-Analog Conversion Cable for Touch Panel Monitor

FH-VMDA




## RS-232C Cable for Touch Panel Monitor

XW2Z-□□□PP-1



## USB Cable for Touch Panel Monitor


FH-VUAB



\*1. Cable is available in 2m/5m/10m.  
\*2. Cable is available in 2m/5m.


## LCD Monitor

FZ-M08



## LED Monitor Cable

FZ-VM




\*1. cable is available in 2m/5m.

# FH-Series

## Optical Chart



### Meaning of Optical Chart

The X axis of the optical chart shows the field of vision (mm) (\*1), and the Y axis of the optical chart shows the camera installation distance (mm) (\*2).





- \*1. The lengths of the fields of vision given in the optical charts are the lengths of the Y axis.
- \*2. The vertical axis represents WD for small cameras.

### High-speed CMOS Camera FH-S□12, 12 million-pixel





### High-speed CMOS Camera FH-S□04, 4 million-pixel

3Z4S-LE



### High-speed CMOS Camera FH-S□02, 2million-pixel


3Z4S-LE



## High-speed CMOS Camera FH-S□, High-speed CCD Camera FZ-SH□, Digital CCD Camera FZ-S□, 300,000-pixel

3Z4S-LE


- SV-10035V
- SV-7527V
- SV-5018V
- SV-3518V
- SV-2514V
- SV-1614V
- SV-1214V
- SV-0813V
- SV-0614V
- SV-04514V
- SV-03514V



## Digital CCD Camera FZ-S□5M2, 5 million-pixel

3Z4S-LE


- SV-10028H
- SV-7525H
- SV-5014H
- SV-3514H
- SV-2514H
- SV-1614H
- SV-1214H
- SV-0814H
- SV-0614H



## Digital CCD Camera FZ-S□2M, 2 million-pixel


3Z4S-LE

- SV-10028H
- SV-7525H
- SV-5014H
- SV-3514H
- SV-2514H
- SV-1614H
- SV-1214H
- SV-0814H
- SV-0614H




## Small Digital CCD Cameras FZ-SF□, FZ-SP□, 300,000-pixel

- FZ-LES30
- FZ-LES16
- FZ-LES6
- FZ-LES3




\* The vertical axis represents WD, not installation distance.


High-speed CMOS Camera  
FH-S□,  
High-speed CCD Camera  
FZ-SH□,  
Digital CCD Camera  
FZ-S□,  
300,000-pixel  
(Vibrations and shocks resistant)



Digital CCD Camera  
FZ-S□5M2,  
5 million-pixel  
(Vibrations and shocks resistant)



Digital CCD Camera  
FZ-S□2M,  
2 million-pixel  
(Vibrations and shocks resistant)



## Related Manuals

| Man.No. | Model number | Manual                                                                |
|---------|--------------|-----------------------------------------------------------------------|
| Z340    | FH/FZ5       | Vision System FH/FZ5 Series User's Manual                             |
| Z341    | FH/FZ5       | Vision System FH/FZ5 Series Processing Item Function Reference Manual |
| Z342    | FH/FZ5       | Vision System FH/FZ5 Series User's Manual for Communications Settings |
| Z343    | FH           | Vision System FH Series Operation Manual for Sysmac Studio            |

# Terms and Conditions Agreement

## **Read and understand this catalog.**

Please read and understand this catalog before purchasing the products. Please consult your OMRON representative if you have any questions or comments.

## **Warranties.**

- (a) Exclusive Warranty. Omron's exclusive warranty is that the Products will be free from defects in materials and workmanship for a period of twelve months from the date of sale by Omron (or such other period expressed in writing by Omron). Omron disclaims all other warranties, express or implied.
- (b) Limitations. OMRON MAKES NO WARRANTY OR REPRESENTATION, EXPRESS OR IMPLIED, ABOUT NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OF THE PRODUCTS. BUYER ACKNOWLEDGES THAT IT ALONE HAS DETERMINED THAT THE PRODUCTS WILL SUITABLY MEET THE REQUIREMENTS OF THEIR INTENDED USE.

Omron further disclaims all warranties and responsibility of any type for claims or expenses based on infringement by the Products or otherwise of any intellectual property right. (c) Buyer Remedy. Omron's sole obligation hereunder shall be, at Omron's election, to (i) replace (in the form originally shipped with Buyer responsible for labor charges for removal or replacement thereof) the non-complying Product, (ii) repair the non-complying Product, or (iii) repay or credit Buyer an amount equal to the purchase price of the non-complying Product; provided that in no event shall Omron be responsible for warranty, repair, indemnity or any other claims or expenses regarding the Products unless Omron's analysis confirms that the Products were properly handled, stored, installed and maintained and not subject to contamination, abuse, misuse or inappropriate modification. Return of any Products by Buyer must be approved in writing by Omron before shipment. Omron Companies shall not be liable for the suitability or unsuitability or the results from the use of Products in combination with any electrical or electronic components, circuits, system assemblies or any other materials or substances or environments. Any advice, recommendations or information given orally or in writing, are not to be construed as an amendment or addition to the above warranty.

See <http://www.omron.com/global/> or contact your Omron representative for published information.

## **Limitation on Liability; Etc.**

OMRON COMPANIES SHALL NOT BE LIABLE FOR SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, LOSS OF PROFITS OR PRODUCTION OR COMMERCIAL LOSS IN ANY WAY CONNECTED WITH THE PRODUCTS, WHETHER SUCH CLAIM IS BASED IN CONTRACT, WARRANTY, NEGLIGENCE OR STRICT LIABILITY.

Further, in no event shall liability of Omron Companies exceed the individual price of the Product on which liability is asserted.

## **Suitability of Use.**

Omron Companies shall not be responsible for conformity with any standards, codes or regulations which apply to the combination of the Product in the Buyer's application or use of the Product. At Buyer's request, Omron will provide applicable third party certification documents identifying ratings and limitations of use which apply to the Product. This information by itself is not sufficient for a complete determination of the suitability of the Product in combination with the end product, machine, system, or other application or use. Buyer shall be solely responsible for determining appropriateness of the particular Product with respect to Buyer's application, product or system. Buyer shall take application responsibility in all cases.

NEVER USE THE PRODUCT FOR AN APPLICATION INVOLVING SERIOUS RISK TO LIFE OR PROPERTY OR IN LARGE QUANTITIES WITHOUT ENSURING THAT THE SYSTEM AS A WHOLE HAS BEEN DESIGNED TO ADDRESS THE RISKS, AND THAT THE OMRON PRODUCT(S) IS PROPERLY RATED AND INSTALLED FOR THE INTENDED USE WITHIN THE OVERALL EQUIPMENT OR SYSTEM.

## **Programmable Products.**

Omron Companies shall not be responsible for the user's programming of a programmable Product, or any consequence thereof.

## **Performance Data.**

Data presented in Omron Company websites, catalogs and other materials is provided as a guide for the user in determining suitability and does not constitute a warranty. It may represent the result of Omron's test conditions, and the user must correlate it to actual application requirements. Actual performance is subject to the Omron's Warranty and Limitations of Liability.

## **Change in Specifications.**

Product specifications and accessories may be changed at any time based on improvements and other reasons. It is our practice to change part numbers when published ratings or features are changed, or when significant construction changes are made. However, some specifications of the Product may be changed without any notice. When in doubt, special part numbers may be assigned to fix or establish key specifications for your application. Please consult with your Omron's representative at any time to confirm actual specifications of purchased Product.

## **Errors and Omissions.**

Information presented by Omron Companies has been checked and is believed to be accurate; however, no responsibility is assumed for clerical, typographical or proofreading errors or omissions.

**Note:** Do not use this document to operate the Unit.

**OMRON Corporation**    **Industrial Automation Company**  
Tokyo, JAPAN

**Contact:** [www.ia.omron.com](http://www.ia.omron.com)

**Regional Headquarters**

**OMRON EUROPE B.V.**

**Sensor Business Unit**

Carl-Benz-Str. 4, D-71154 Nufringen, Germany  
Tel: (49) 7032-811-0/Fax: (49) 7032-811-199

**OMRON ELECTRONICS LLC**

2895 Greenspoint Parkway, Suite 200  
Hoffman Estates, IL 60169 U.S.A  
Tel: (1) 847-843-7900/Fax: (1) 847-843-7787

**OMRON ASIA PACIFIC PTE. LTD.**

No. 438A Alexandra Road # 05-05/08 (Lobby 2),  
Alexandra Technopark,  
Singapore 119967  
Tel: (65) 6835-3011/Fax: (65) 6835-2711

**OMRON (CHINA) CO., LTD.**

Room 2211, Bank of China Tower,  
200 Yin Cheng Zhong Road,  
PuDong New Area, Shanghai, 200120, China  
Tel: (86) 21-5037-2222/Fax: (86) 21-5037-2200

**Authorized Distributor:**

© OMRON Corporation 2013-2015 All Rights Reserved.  
In the interest of product improvement,  
specifications are subject to change without notice.

CSM\_10\_1\_0115

**Cat. No. Q197-E1-04**

0115(0613)

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Omron:

[XW2Z-S013-5](#) [XW2Z-S013-2](#)

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9