

3M™ Round Conductor Round Cable for CC-Link/LT

18 AWG Stranded, ETFE / PVC

79100 Series



- Designed for factory automation applications
- Conforms to CC-Link/LT
- Recommended for use with 3M™ Link Connectors
- 18 AWG [0.75 mm²] conductor wire permits IDC termination
- RoHS Compliant. See the Regulatory Information Appendix (RIA) in the “RoHS compliance” section of www.3Mconnector.com for compliance information. (RIA E1 & C1 apply)

Date Modified: July 22, 2010

TS-2325-C
Sheet 1 of 2

Physical

Jacket Material: Oil Resistant Polyvinyl Chloride (PVC) 1.0 mm nominal thickness

Color: Black

Insulator Material: ETFE (Fluorocarbon polymer)

Color: Black, Red, White, Green

Marking: 3M™ Cable 79100-075-4ZLT 0.75 mm² x 4 for CC-Link/LT

3M™ Cable E42769-K AWM Style 20276 I A 80C 30V VW-1 FT1

Conductors:

Description: 0.75 mm² [18 AWG], 7 strands x 0.08 mm [22 AWG], Tinned Stranded Copper

Mating Connectors: Link Connector, 38104-F018-F00 FL, 38104-B018-B0M FL, TS-2098

Electrical

Voltage Rating: UL: 30 V AWM: 30 V

Insulation Resistance: >1 x 10¹⁰ Ω / 10 ft [3 m]

Withstand Voltage: 1,500 V_{AC} for one minute

Unbalanced Tested

Characteristic Impedance: 53.49 Ω

Capacitance: 106nF/km(32pF/ft)@1MHz

Inductance: 0.09 uH/ft (0.30uH/m)

Propagation Delay: 1.74 ns/ft (5.70ns/m)

Velocity of Propagation: 58.52%

Balanced Tested

79.8 Ω@1MHz

79.1 Ω@5MHz

88.0nF/km(26.8pF/ft)@1kHz

0.14 uH/ft (0.45uH/m)

1.74 ns/ft (5.70ns/m)

58.74%

Balanced-Specification

90±30Ω @1MHz

90±30Ω @5MHz

Note: Unbalanced is measured between ground signal – ground conductors. Balanced is measured between conductors within a pair.

Environmental

Temperature Rating: 80°C Max

Flammability Rating: VW-1 (UL) FT1 (CSA)


UL File No. E42769-K

3M™ Round Conductor Round Cable for CC-Link/LT

18 AWG Stranded, ETFE / PVC

79100 Series

Product Dimensions



Ordering Information

79100 - 075 - 4ZLT

Note: Available in standard 200 meter rolls, please specify length when ordering. Contact 3M for availability of additional conductor counts and/or custom roll lengths.

TS-2325-C
Sheet 2 of 2

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for a period of one (1) year from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.**



3M Electronics Solutions Division

6801 River Place Blvd.
Austin, TX 78726-9000
U.S.A.
1-800-225-5373
www.3Mconnector.com

Please recycle. Printed in USA.
© 3M 2010. All rights reserved.
RIA-2217B-E

3M is a trademark of 3M Company.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9