

GECA40


40 Watt Series



Commercial Wide-Range Input

2 Year Warranty

- Wide-Range AC Input 90-264 VAC
- Industry Standard Footprint - 3"x 5"x 1.25"
- Conducted EMI Exceeds FCC Class B and CISPR 22 Class B
- Single and Multiple Outputs
- Approved to UL60950-1: 2003, CSA-22.2 No. 60950-1-03, IEC and EN60950-1
- CB Report Available
- RoHS Compliant
- CE Marked to LVD



CONDOR

Specifications

Unless otherwise noted, all parameters are nominal values measured at 120 VAC @25°C and 0-95% relative humidity, non-condensing. For limits at unusual operating conditions, consult factory.

AC Input

Universal Input 90-264 VAC, 47-63 Hz single phase.

Input Current

Maximum input current at 120 VAC, 60 Hz with full rated output load:
Multiple models 1.7 A, Single models 1.0 A.

Hold-Up Time

10 ms minimum with 40 W load, nominal line (120 VAC).

Output Power

40 W continuous, 45 W peak. Peak ratings are for 60 s maximum duration, 10% duty cycle. During peak load condition, output regulation may exceed total regulation limits.

Overload Protection

Fully protected against short circuit and output overload. Short circuit protection is cycling type power limit on V1 and V2, foldback type on V3.

Overvoltage Protection

On V1 is 120% to 160%. See chart.

Efficiency

75 to 80% at full rated load, nominal input voltage, depending on model and load distribution.

Turn-on Time

Less than 2 seconds.

Input Protection

Internal AC fuse provided. Designed to blow only if a catastrophic failure occurs in the unit. Fuse does not blow on overload or short circuit.

Inrush Current

Inrush is limited by internal thermistors. Inrush at 240 VAC under cold start conditions will not exceed 37A.

Temperature Coefficient

0.03%/°C typical on all outputs.

Temperature Range

Designed for 0 to 45°C operation at full rated output power; derate output current and total output power by 2.5% per °C above 45°C.

Output Noise

0.5% rms, 1% pk-pk typical (see chart), 20 MHz bandwidth, differential mode. Measured with noise probe directly across output terminals of the power supply with load terminated with 0.1 μ F capacitor.

Transient Response

Main output—500 μ s typical response time for return to within 0.5% of final value for a 50% load step change. $\Delta i / \Delta t < 0.2$ A/ μ s. Maximum voltage deviation is 3.5%. Startup/ shutdown overshoot less than 3%.

Switching Frequency

70 kHz $\pm$ 10 kHz.

Voltage Adjustment

Provided on V1. Adjustable voltages are preset at factory. Outputs are capable of minimum $\pm$ 5% change from nominal setting. Multiple output models - V2 voltage will track V1 adjustment.

EMI/EMC Compliance

All models include built-in EMI filtering to meet the following emissions requirements:

EMI SPECIFICATIONS

Conducted Emissions
Static Discharge
RF Field Susceptibility
Fast Transients/Bursts
Surge Susceptibility

COMPLIANCE LEVEL

EN55022 Class B; FCC Class B
EN61000-4-2, Level 3
EN61000-4-3, Level 3
EN61000-4-4, Level 3
EN61000-4-5, Level 3

Safety Approvals

SL Power Electronics, Corp. declares under our sole responsibility that all GECA models are in conformity with the applicable requirements of EN60950 following the provisions of the Low Voltage Directive 73/23/EEC.

All GECA models are approved to UL60950-1: 2003, CSA-22.2 No. 60950-1-03, IEC and EN60950-1

MTBF

120kHrs.

GECA40

40 Watt Series

Commercial Wide-Range Input

Commercial Model	Output No.	Output (V)	Current Minimum	Current Maximum	Line Regulation	Load Regulation	V1 OVP Set Point	Ripple & Noise(P-P)
GECA40AG	V1	+5 V	0.35 A	3.5 A	+/-0.5%	+/-3%	6.6 +/-0.9 V	50 mV
	V2	+12 V	0 A	2 A	+/-1%	+/-10%		120 mV
	V3	-12 V	0 A	0.3 A	+/-1%	+/-5%		120 mV
GECA40BG	V1	+5 V	0.35 A	3.5 A	+/-0.5%	+/-3%	6.6 +/-0.9 V	50 mV
	V2	+12V	0 A	2 A	+/-1%	+/-10%		120 mV
	V3	-5 V	0 A	0.3 A	+/-1%	+/-5%		50 mV
GECA40HG	V1	+3.3 V	0.4 A	4 A	+/-0.5%	+/-3%	4.4 +/-0.6 V	50 mV
	V2	+12 V	0 A	2 A	+/-1%	+/-10%		120 mV
	V3	-12 V	0 A	0.3 A	+/-1%	+/-5%		120 mV
GECA40DG	V1	+5 V	0.35 A	3.5 A	+/-0.5%	+/-3%	6.6 +/-0.9 V	50 mV
	V2	+24 V	0 A	1.2 A	+/-1%	+/-10%		240 mV
	V3	-12 V	0 A	0.3 A	+/-1%	+/-5%		120 mV
GECA40-5G	V1	5 V	0 A	7 A	+/-0.5%	+/-3%	7.0 +/-1.0 V	50 mV
GECA40-12G	V1	12 V	0 A	3.3 A	+/-0.5%	+/-3%	16.8 +/-2.4 V	120 mV
GECA40-15G	V1	15 V	0 A	2.7 A	+/-0.5%	+/-3%	21.0 +/-3.0 V	150 mV
GECA40-24G	V1	24 V	0 A	1.7 A	+/-0.5%	+/-3%	33.6 +/-4.8 V	240 mV

Environmental Specifications

ENVIRONMENT	OPERATING	NON-OPERATING
Temperature (A)	0 to 45°C	-40 to +85°C
Humidity (A)	20 to 90% RH	10 to 95% RH
Shock (B)	20 g _{pk}	40 g _{pk}
Altitude	-500 to 10,000 ft	-500 to 40,000 ft
Vibration (C)	1.5 g _{rms} 0.0032 g ² /Hz	5 g _{rms} 0.026 g ² /Hz

- A. Units should be allowed to warm up/operate under non-condensing conditions before application of power.
- B. Shock testing—half-sinusoidal, 10 ± 3 ms duration, ± direction, 3 orthogonal axes, total 6 shocks.
- C. Random vibration—10 to 2000Hz, 6dB/octave roll-off from 350 to 2000Hz, 3 orthogonal axes. Tested for 10 min./axis operating and 1 hr./axis non-operating.

GECA40 Series Mechanical Specifications

CON 1:
MOLEX P/N 26-60-4030, w/center PIN Removed
0.156 [3.96 mm] CTR Header

CON 2:
MOLEX P/N 26-60-4060, 0.156 [3.96 mm] CTR Header

Input J1

PIN 1)	AC Line
PIN 3)	AC Neutral

Output J2

	Multiple Output Models	Single Output Models
PIN 1)	Output 2	Output 1
PIN 2)	Common	Output 1
PIN 3)	Common	Output 1
PIN 4)	Output 1	Common
PIN 5)	Output 1	Common
PIN 6)	Output 3	Common

Mating Connector MOLEX

	Housing P/N	Contacts P/N
Input	09-50-3031	08-52-0072
Output	09-50-3061	08-52-0072


Note: 5A maximum recommended current per Connector PIN

Weight

1.0 lbs Max [0.45 kg Max.]

Tolerance

X.XX=0.030
X.XXX=0.010 [0.mm]



SL Power Electronics, Corp. • 6050 King Drive • Ventura CA, 93003 • Phone:805.486.4565 • Fax:805.487.8911 • Email:info@slpower.com • www.slpower.com

Data Sheet © 2006 SL Power Electronics, Corp. The information and specifications contained in this data sheet are believed to be correct at time of publication.

However, SL Power accepts no responsibility for consequences arising from reproduction errors or inaccuracies. Specifications are subject to change without notice.

Rev.8/30/06

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9