

ORIGINAL

This document is the property of Amphenol Corporation and is delivered on the express condition that is not to be disclosed, reproduced or used, in whole or in part, for manufacture or sale by anyone other than Amphenol Corporation without its prior consent, and that no right is granted to disclose or to use any information in this document.

The marking on this product doesn't contain environmental hazardous materials per Material Specification SS-00259 for Sony GP compliant or per directive 2011/65/EU for RoHS compliant or per IEC 61249-2-21 for Halogen-Free compliant.

REVISIONS				
SYM	ECN No.	DESCRIPTION	DATE	APPROVED
A	NE-14070	NEW RELEASE	04/28/2014	HANK HSU








TABLE 1

DIM A	APPLICABLE PCB THK
2.40	1.57~1.60
3.59	2.36~2.79
3.98	3.18



PART NUMBER SYSTEM									
G40H	D	X	X	X	X	X	XX	-	X
Mini SAS HD Integrated Connector									
Connector Style D: V/T.w/enclosing wall.85 ohm									
Number of Integration X: OPTION 1: 1X1 2: 1X2									
Contact Finish X: OPTION 3: 30u" Gold									
Terminal Style X: OPTION 2: SMT, 100u" MIN MATTE TIN PLATING									
Verification Code X: OPTION BLANK: STANDARD									
Compliant Code XX: OPTION HR: Halogen-Free & RoHS									
BOARDLOCK CODE X: OPTION 1: 2.40 mm 2: 3.59 mm 3: 3.98 mm									
Variation Code X: OPTION 1: with Cap 2: without Cap									
Packing Code X: OPTION 1: Tray 2: Tape & Reel 3: Narrow Tray									



NOTES:

- INSULATOR: HIGH TEMPERATURE UL94V-0, COLOR: NC(BRACKET), BK(HOUSING)
- TERMINAL: COPPER ALLOYBRASS
CONTACT AREA: OPTION
SOLDERING AREA: OPTION
UNDER PLTING.: Ni 100u" MIN.
- THIS PRODUCT DOESN'T CONTAIN ENVIRONMENTAL HAZARDOUS PER DIRECTIVE 2011/65/EU FOR RoHS AND PER IEC 61249-2-21 FOR HALOGEN-FREE COMPLIANT.







TOLERANCE		DRAWN APPROVALS		DATE	TITLE			Amphenol® Amphenol Corporation Amphenol Taiwan Corporation		
X.		DESIGNED		04/28/2014	MINI SAS HD INTEGRATED CONNECTOR 0.75 PITCH, V/T, SMT TYPE			PART No. G40HDXXXXXXHR		
X.X ±0.30		Hank Hsu								
X.XX ±0.20		CHECKED								
X.XXX ±0.10		Sondra Sang		04/28/2014						
ANGULAR ±2°		APPROVED		04/28/2014				UNIT mm SIZE A3 PART No. G40HDXXXXXXHR		
		Hank Hsu								
UNLESS OTHERWISE SPECIFIED		DWG TYPE		PROJECT CODE	SCALE			DWG No.		
		CUST DWG		T515	NA			1 OF 3		
								REV. A		

ORIGINAL

This document is the property of Amphenol Corporation and is delivered on the express condition that it is not to be disclosed, reproduced or used, in whole or in part, for manufacture or sale by anyone other than Amphenol Corporation without its prior consent, and that no right is granted to disclose or to use any information in this document.

The marking on this product doesn't contain environmental hazardous materials per Material Specification SS-00259 for Sony GP compliant or per directive 2011/65/EU for RoHS compliant or per IEC 61249-2-21 for Halogen-Free compliant.

REVISIONS				
SYM	ECN No.	DESCRIPTION	DATE	APPROVED
A	NE-14070	NEW RELEASE	04/28/2014	HANK HSU




TOLERANCE		DRAWN	APPROVALS	DATE	TITLE			Amphenol® Amphenol Corporation Amphenol Taiwan Corporation			
X. X.X ±0.30 X.XX ±0.20 X.XXX ±0.10		DESIGNED	Hank Hsu	04/28/2014	MINI SAS HD INTEGRATED CONNECTOR 0.75 PITCH, V/T, SMT TYPE						
		CHECKED	Sondra Sang	04/28/2014							
ANGULAR ±2°		APPROVED	Hank Hsu	04/28/2014			UNIT mm	SIZE A3	PART No.	G40HDXXXXXXHR	
UNLESS OTHERWISE SPECIFIED		DWG TYPE CUST DWG	PROJECT CODE T515				SCALE NA	SHEET 2 OF 3	DWG No.	G40HDXXXXXXHR	REV. A

ORIGINAL


This document is the property of Amphenol Corporation and is delivered on the express condition that is not to be disclosed, reproduced or used, in whole or in part, for manufacture or sale by anyone other than Amphenol Corporation without its prior consent, and that no right is granted to disclose or to use any information in this document.

The marking on this product doesn't contain environmental hazardous materials per Material Specification SS-00259 for Sony GP compliant or per directive 2011/65/EU for RoHS compliant or per IEC 61249-2-21 for Halogen-Free compliant.

REVISIONS				
SYM	ECN No.	DESCRIPTION	DATE	APPROVED
A	NE-14070	NEW RELEASE	04/28/2014	HANK HSU



1X1 RECOMMENDED PCB LAYOUT
(ALL TOLERANCES ARE ± 0.05)



1X2 RECOMMENDED PCB LAYOUT
(ALL TOLERANCES ARE ± 0.05)

NOTES:

1. RECOMMENDED PCB HOLE $\varnothing 1.20$ IS NPTH FOR ORIENTATION POST.
2. RECOMMENDED PCB ELLIPTICAL HOLE 0.5×1.45 IS PTH FOR BOARD-LOCK.
3. MINIMUM PCB THICKNESS: 1.57MM
4. PIN ASSIGNMENTS PLEASE REFER TO SERIAL ATTACHED SCSI-3 (SAS-3) STANDARD.

TOLERANCE		DRAWN APPROVALS		DATE		TITLE			Amphenol® Amphenol Corporation Amphenol Taiwan Corporation								
X.		DESIGNED		Hank Hsu		04/28/2014		MINI SAS HD INTEGRATED CONNECTOR 0.75 PITCH, V/T, SMT TYPE									
X.X ±0.30		CHECKED		Sondra Sang		04/28/2014											
X.XX ±0.20		APPROVED		Hank Hsu		04/28/2014											
X.XXX ±0.10																	
ANGULAR ±2°										UNIT mm		SIZE A3		PART No. G40HDXXXXXXHR			
UNLESS OTHERWISE SPECIFIED		DWG TYPE CUST DWG		PROJECT CODE T515						SCALE NA		SHEET 3 OF 3		DWG No. G40HDXXXXXXHR		REV. A	

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9