









THIS DRAWING IS A CONTROLLED DOCUMENT. 1583005


USED ON —												
TOOL NUMBER  -1 	WIRE SIZE mm ² [AWG] 	INSULATION DIAMETER mm [in.] 	INSULATION ADJUSTER 	FLIP LOCATOR 	STRIP LENGTH mm [in.] 	CRIMP HEIGHT mm [in.] 	CONTACT PART NUMBERS 				CONTACT DESCRIPTION	APPLIC. SPECIFIC.
							LOOSE PIECE 		STRIP FORM 			
91509-1 91509-3	0.50-0.89 [20-18] 1.25-1.42 [16]	2.29-3.30 [.090-.130]	YES	NO	4.75 ± 0.38 [.187 ± .015]	1.27 ± 0.05 [.050 ± .002] 1.52 ± 0.08 [.060 ± .003]	42566-[] 60196-3 62228-1 42638-2	62228-1	42452-[] 60196-[] 62026-1 60214-[] 60621-1	61084-1 61758-[] 61919-1 61939-1 62137-[]	187 FASTON Contacts	114-2036 and 114-35000
91511-1 91511-3	0.20-0.38 [24-22] 0.32-0.96 [22-18]	1.02-1.52 [.040-.060] 1.52-2.54 [.060-.100]	NO	NO	4.75 ± 0.38 [.187 ± .015]	0.76 ± 0.05 [.030 ± .002] 1.14 ± 0.05 [.045 ± .002]	- 42922-[]		42067-[] 42415-[] 42635-[]		110 FASTON Contacts	114-2036 and 114-35000
91514-1 91514-3	0.32-0.96 [22-18]	1.52-2.54 [.060-.100] 2.29-3.30 [.090-.130]	YES	NO	6.35 ± 0.38 [.250 ± .015]	1.40 ± 0.10 [.055 ± .004]	41969-[] 42731-[] 60878-2 61316-1 170187-[]		41772-[] 42640-[] 60294-2 170183-[]		250 FASTON contacts	114-2036 and 114-35000
91581-1 91581-3	0.50-0.85 [20-18]	2.03-3.05 [.080-.120]	NO	NO	4.5 ± 0.38 [.177 ± .015]	0.97-1.10 [.038-.043] 1.42-1.55 [.056-.061]	170042-[] 172799-[] 170041-[]		170015-[] 170033-[] 170014-[]		110 FASTON Contacts	114-2036 and 114-35000
91593-1 91593-3	0.51-0.89 [20-18] 1.25-1.38 [16]	1.90-3.00 [.075-.118] 2.40-3.40 [.094-.134]	YES	NO	4.50 ± 0.50 [.177 ± .020]	1.10-1.24 [.043-.049] 1.35-1.54 [.053-.061]	170331-[]		170325-[]		187 POSITIVE LOCK FASTON Contacts	114-5041
2031929-1 2031929-3	0.32-0.96 [22-18]	1.52-2.54 [.060-.100]	NO	NO	4.75 ± 0.38 [.187 ± .015]	1.14 ± 0.05 [.045 ± .002]	42470-[]		42068-[]		110 FASTON Contacts	114-2036 and 114-35000
2063247-1 2063247-3	0.31-0.56 (22-20) 0.76-0.89 (18)	2.03-2.65 (.080-.104) 2.13-3.05 (.084-.120)	YES	NO	4.78 ± 0.38 (.188 ± .015)	1.37 ± 0.05 (.054 ± .002) 1.57 ± 0.05 (.062 ± .002)	-		42490-[]		187 FASTON Contacts	114-2036
2063846-1 2063846-3	0.20-0.38 [24-22] 0.32-0.96 [22-18]	1.02-1.52 [.040-.060] 1.52-2.54 [.060-.100]	NO	NO	4.75 ± 0.38 [.187 ± .015]	0.76 ± 0.05 [.030 ± .002] 1.14 ± 0.05 [.045 ± .002]	61454-1 42470-[]		42067-[] 42415-[] 42068-[]		110 FASTON Contacts	114-2036 and 114-35000

-  LIST OF APPLIED CONTACT PART NUMBERS MAY NOT BE COMPLETE AND IS SUBJECT TO CHANGE. FOR CURRENT INFORMATION ON TERMINAL PART NUMBERS, CONTACT THE TOOLING ASSISTANCE CENTER : 1-800-722-1111.
2. AMP, CERTI-CRIMP, and FASTON ARE TRADEMARKS.
-  -1 IS A CERTICRIMP II HAND TOOL ASSEMBLY.
-3 IS A CERTICRIMP II HEAD SUB-ASSEMBLY.
4. THE HAND TOOL INSTRUCTION SHEET, ALSO KNOWN AS AN "IS", FOR MOST CERTI-CRIMP II TOOLS USE IS 408-8547. IF THE TOOL HAS A FLIP LOCATOR USE IS 408-10414.

CERTI-CRIMP II DATA SHEET

DWG: M. YOUNGER 21FEB2012		MATERIAL: -	HEAT TREAT: -
CHK: B.A.WOLFE 22FEB2012		 TE Connectivity	
APVD: B.A. WOLFE 22FEB2012			
NAME: CERTI-CRIMP II TOOL DATA SHEET FASTON & POSITIVE LOCK CONTACT FAMILY			
SCALE: -	SIZE: A1	DRAWING NO: 1583005	SHEET: 1 of 2

DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED:	
		0 PLC ± -	1 PLC ± -
		2 PLC ± -	3 PLC ± -
		4 PLC ± -	

ANGLES: -	SURFACE TEXTURE: 
-----------	--

D5	REVISED	11/2015	AW	BAW
P	LTR	REVISION RECORD	DATE	DWN

APVD	DATE	DATE	DATE	DATE
------	------	------	------	------

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TFCO. IT IS TO BE USED ONLY FOR THE PURPOSES AND APPLICATIONS SPECIFIED HEREIN. IT IS NOT TO BE REPRODUCED, COPIED, OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, WITHOUT AUTHORIZATION FROM TFCO. (www.tfcoco.com)

LOC A
DIST 00

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION AND ITS WORLDWIDE SUBSIDIARIES AND AFFILIATES ("TE"). IT MAY NOT BE DISCLOSED TO ANYONE, OTHER THAN TE PERSONNEL, WITHOUT AUTHORIZATION FROM TE. (www.TE.com).

- ① LIST OF APPLIED CONTACT PART NUMBERS MAY NOT BE COMPLETE AND IS SUBJECT TO CHANGE. FOR CURRENT INFORMATION ON TERMINAL PART NUMBERS, CONTACT THE TOOLING ASSISTANCE CENTER :
1-800-722-1111.
2. AMP, CERTI-CRIMP, and FASTON ARE TRADEMARKS.
- ③ -1 IS A CERTICRIMP II HAND TOOL ASSEMBLY.
-3 IS A CERTICRIMP II HEAD SUB-ASSEMBLY.
4. THE HAND TOOL INSTRUCTION SHEET, ALSO KNOWN AS AN "IS", FOR MOST CERTI-CRIMP II TOOLS USE IS 408-8547. IF THE TOOL HAS A FLIP LOCATOR USE IS 408-10414.

	-	SEE SHEET 1		-	-	-
P	LTR	REVISION RECORD		DATE	DWN	APVD

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9