Material:
- Body: Polyamide PA 6 25 % Glass-fiber Reinforced
- Seal: Tefabloc

Characteristics:
- PG thread
- Multi-holed seal inserts

Technical properties:
- Gas- and watertight
- Completely twist protected
- Combinable with various sealing inserts

Applications:
- Machines and devices
- Measuring and control engineering
- Plant installations

Locknuts and seal rings sold separately, see pages 23 and 35.

PROTECTION IP68 RATING



See page 7 for dimensions.

Temperature Range PA 6
-30 to 120°C (-22 to 248°F)

Outer thread	Hole Quantity	Hole diameter mm	Cat. No. Light Grey	Cat. No Black	Std. Pk.
PG 7	1	4	5315800	5315600	50
PG 7	1	5	5315801	5315601	50
PG 9	1	5	5315810	5315610	50
PG 9	2	1	5315811	5315611	50
PG 9	2	3	5315812	5315612	50
PG 9	2	3.5	5315813	5315613	50
PG 9	2	4	5315814	5315614	50
PG 9	3	3	5315815	5315615	50
PG 9	4	3	5315816	5315616	50
PG 9	4	4	5315817	5315617	50
PG 11	2	2.3	5315820	5315620	50
PG 11	2	3	5315821	5315621	50
PG 11	2	3.5	5315110	5315500	50
PG 11	2	4	5315822	5315622	50
PG 11	2	5	5315111	5315501	50
PG 11	2	6	5315112	5315502	50
PG 11	3	3	5315823	5315623	50
PG 11	3	3.5	5315113	5315503	50
PG 11	3	4	5315824	5315624	50
PG 11	3	5	5315114	5315504	50
PG 11	3	5.3	5315825	5315625	50
PG 11	4	1.5	5315826	5315626	50
PG 11	4	3.5	5315827	5315627	50
PG 11	6	2	5315828	5315628	50
PG 11	6	2.5	5315829	5315629	50
PG 13.5	2	3	5315830	5315630	50
PG 13.5	2	5	5315831	5315631	50
PG 13.5	2	6	5315130	5315510	50
PG 13.5	3	2	5315832	5315632	50
PG 13.5	3	3	5315833	5315633	50
PG 13.5	3	4	5315834	5315634	50
PG 13.5	3	5.3	5315835	5315635	50
PG 13.5	3	6	5315836	5315636	50
PG 13.5	4	3	5315837	5315637	50
PG 13.5	4	4	5315838	5315638	50
PG 13.5	4	5	5315839	5315639	50
PG 13.5	4	5.3	5315840	5315640	50
PG 13.5	6	3.5	5315841	5315641	50
PG 13.5	10	2	5315842	5315642	50
PG 16	2	4	5315850	5315650	50
PG 16	2	5	5315851	5315651	50
PG 16	2	6	5315852	5315652	50
PG 16	2	7	5315160	5315515	50
PG 16	2	8	5315853	5315653	50
PG 16	2	9	5315854	5315654	50
PG 16	3	3	5315855	5315655	50
PG 16	3	4	5315856	5315656	50
PG 16	3	5	5315857	5315516	50
PG 16	3	5.6	5315858	5315658	50
PG 16	3	6	5315859	5315659	50
PG 16	3	7	5315860	5315660	50
PG 16	3	8	5315861	5315661	50

Outer thread	Hole Quantity	Hole diameter mm	Cat. No. Light Grey	Cat. No Black	Std. Pk.
PG 16	4	4	5315862	5315662	50
PG 16	4	5	5315863	5315663	50
PG 16	4	6	5315864	5315664	50
PG 16	5	4	5315865	5315665	50
PG 16	5	5	5315866	5315666	50
PG 16	6	4	5315867	5315667	50
PG 16	7	4	5315868	5315668	50
PG 21	2	4.5	5315869	5315669	20
PG 21	2	8	5315870	5315670	20
PG 21	2	8.7	5315871	5315671	20
PG 21	2	9	5315872	5315672	20
PG 21	2	11	5315873	5315673	20
PG 21	3	7	5315210	5315520	20
PG 21	3	8	5315211	5315521	20
PG 21	3	9	5315874	5315674	20
PG 21	4	5	5315875	5315675	20
PG 21	4	6	5315212	5315522	20
PG 21	4	7.5	5315876	5315676	20
PG 21	4	8	5315213	5315523	20
PG 21	5	5	5315877	5315677	20
PG 21	5	6	5315214	5315524	20
PG 21	5	6.5	5315215	5315525	20
PG 21	6	4	5315878	5315678	20
PG 21	6	5	5315879	5315679	20
PG 21	6	6	5315216	5315526	20
PG 21	6	6.5	5315217	5315527	20
PG 21	6	7	5315218	5315528	20
PG 21	7	6	5315219	5315529	20
PG 21	8	4	5315880	5315683	20
PG 21	8	5	5315220	5315530	20
PG 21	11	5	5315221	5315531	20
PG 21	21	2	5315881	5315684	20
PG 21	28	3	5315222	5315532	20
PG 29	2	9	5315289	5315690	20
PG 29	2	11	5315891	5315691	20
PG 29	2	12	5315892	5315692	20
PG 29	3	9	5315893	5315693	20
PG 29	3	11	5315894	5315694	20
PG 29	4	8	5315290	5315540	20
PG 29	4	9	5315895	5315695	20
PG 29	4	10	5315896	5315696	20
PG 29	6	6	5315897	5315697	20
PG 29	6	6.5	5315292	5315542	20
PG 29	6	7	5315293	5315543	20
PG 29	7	6	5315294	5315544	20
PG 29	7	7	5315898	5315698	20
PG 29	8	5	5315899	5315699	20
PG 29	8	6	5315295	5315545	20
PG 29	10	6	5315900	5315700	20
PG 29	11	5	5315296	5315546	20
PG 29	28	3	5315297	5315547	20

Cable Gland / Industrial Multi-Conductor (Metric) - Polyamide

Material:
- Body: polyamide PA 6 25% Glass-fiber Reinforced
- Seal: Tefabloc

Characteristics:
- Metric Thread
- Multi-holed seal inserts

Technical properties:
- Gas- and watertight
- Completely twist protected
- Combinable with various sealing inserts

Applications:
- Machines and devices
- Measuring and control engineering
- Plant installations

Locknuts and seal rings sold separately, see pages 23 and 35.



Temperature Range PA 6
-30 to 120°C (-22 to 248°F)

PROTECTION IP68 RATING

See page 7 for dimensions.

Outer thread	Hole Quantity	Hole diameter mm	Cat. No. Light Grey	Cat. No. Black	Std. Pk.
M 16 x 1.5	2	1	**5316100**	**5318100**	50
M 16 x 1.5	2	3	**5316101**	**5318101**	50
M 16 x 1.5	2	3.5	**5316102**	**5318102**	50
M 16 x 1.5	2	4	**5316103**	**5318103**	50
M 16 x 1.5	3	3	**5316104**	**5318104**	50
M 20 x 1.5/13	2	3	**5316200**	**5318200**	50
M 20 x 1.5/16	2	4	**5316201**	**5318201**	50
M 20 x 1.5/16	2	5	**5316202**	**5318202**	50
M 20 x 1.5/16	2	6	**5316203**	**5318203**	50
M 20 x 1.5/16	2	7	**5316204**	**5318204**	50
M 20 x 1.5/13	3	2	**5316205**	**5318205**	50
M 20 x 1.5/16	3	3	**5316206**	**5318206**	50
M 20 x 1.5/16	3	4	**5316207**	**5318207**	50
M 20 x 1.5/16	3	5	**5316208**	**5318208**	50
M 20 x 1.5/16	3	5.6	**5316209**	**5318209**	50
M 20 x 1.5/16	3	6	**5316210**	**5318210**	50
M 20 x 1.5/13	4	3	**5316211**	**5318211**	50
M 20 x 1.5/16	4	4	**5316212**	**5318212**	50
M 20 x 1.5/16	5	4	**5316213**	**5318213**	50
M 20 x 1.5/16	5	5	**5316214**	**5318214**	50
M 20 x 1.5/13	6	3.5	**5316215**	**5318215**	50
M 20 x 1.5/16	6	4	**5316216**	**5318216**	50
M 20 x 1.5/13	10	2	**5316217**	**5318217**	50
M 25 x 1.5	2	4.5	**5316300**	**5318300**	20
M 25 x 1.5	2	8	**5316301**	**5318301**	20
M 25 x 1.5	3	7	**5316302**	**5318302**	20
M 25 x 1.5	3	8	**5316303**	**5318303**	20
M 25 x 1.5	4	5	**5316304**	**5318304**	20
M 25 x 1.5	4	6	**5316305**	**5318305**	20
M 25 x 1.5	5	5	**5316306**	**5318306**	20
M 25 x 1.5	5	6	**5316307**	**5318307**	20
M 25 x 1.5	5	6.5	**5316308**	**5318308**	20
M 25 x 1.5	6	4	**5316309**	**5318309**	20
M 25 x 1.5	6	5	**5316310**	**5318310**	20
M 25 x 1.5	8	4	**5316311**	**5318311**	20
M 25 x 1.5	8	5	**5316312**	**5318312**	20
M 25 x 1.5	21	2	**5316313**	**5318313**	20
M 32 x 1.5	2	9	**5316400**	**5318400**	20
M 32 x 1.5	2	11	**5316401**	**5318401**	20
M 32 x 1.5	2	12	**5316402**	**5318402**	20
M 32 x 1.5	3	9	**5316403**	**5318403**	20
M 32 x 1.5	3	11	**5316404**	**5318404**	20
M 32 x 1.5	4	8	**5316405**	**5318405**	20
M 32 x 1.5	4	9	**5316406**	**5318406**	20
M 32 x 1.5	4	10	**5316407**	**5318407**	20
M 32 x 1.5	6	6	**5316408**	**5318408**	20
M 32 x 1.5	6	6.5	**5316409**	**5318409**	20
M 32 x 1.5	6	7	**5316410**	**5318410**	20
M 32 x 1.5	7	6	**5316411**	**5318411**	20
M 32 x 1.5	7	7	**5316412**	**5318412**	20
M 32 x 1.5	8	5	**5316413**	**5318413**	20
M 32 x 1.5	8	6	**5316414**	**5318414**	20
M 32 x 1.5	10	6	**5316415**	**5318415**	20
M 32 x 1.5	11	5	**5316416**	**5318416**	20
M 32 x 1.5	28	3	**5316417**	**5318417**	20

Cable Gland / Industrial Multi-Conductor (PG) - Nickel-Plated Brass

Material:
- Body: Nickel-Plated Brass
- Seal: Tefabloc
- Sealing ring for outer thread: Nitril

Characteristics:
- PG thread
- Multi-holed seal inserts

Technical properties:
- Gas- and watertight
- Completely twist protected
- Combinable with various sealing inserts

Applications:
- Machines and devices
- Measuring and control engineering
- Plant installations

Locknuts sold separately, see page 24.





Temperature Range MS
-25 to 120°C (-13 to 248°F)

PROTECTION IP68 RATING

See page 12 for dimensions.

Outer thread	Hole Quantity	Hole diameter mm	Cat. No.	Std. Pk.
PG 7	1	4	**4248640**	50
PG 7	1	5	**4248641**	50
PG 9	1	5	**4248642**	50
PG 9	2	1	**4248643**	50
PG 9	2	3	**4248644**	50
PG 9	2	3.5	**4248645**	50
PG 9	2	4	**4248646**	50
PG 9	3	3	**4248647**	50
PG 9	4	3	**4248648**	50
PG 9	4	4	**4248649**	50
PG 11	2	2.3	**4248650**	50
PG 11	2	3	**4248651**	50
PG 11	2	3.5	**4248405**	50
PG 11	2	4	**4248652**	50
PG 11	2	5	**4248660**	50
PG 11	2	6	**4248661**	50
PG 11	3	3	**4248653**	50
PG 11	3	3.5	**4248407**	50
PG 11	3	4	**4248654**	50
PG 11	3	5	**4248662**	50
PG 11	3	5.3	**4248655**	50
PG 11	4	1.5	**4248656**	50
PG 11	4	3.5	**4248657**	50
PG 11	6	2	**4248658**	50
PG 11	6	2.5	**4248659**	50
PG 13.5	2	3	**4248663**	50
PG 13.5	2	5	**4248664**	50
PG 13.5	2	6	**4248404**	50
PG 13.5	3	2	**4248665**	50
PG 13.5	3	3	**4248666**	50
PG 13.5	3	4	**4248667**	50
PG 13.5	3	5.3	**4248668**	50
PG 13.5	3	6	**4248669**	50
PG 13.5	4	3	**4248670**	50
PG 13.5	4	4	**4248671**	50
PG 13.5	4	5	**4248673**	50
PG 13.5	4	5.3	**4248672**	50
PG 13.5	6	3.5	**4248674**	50
PG 13.5	10	2	**4248675**	50
PG 16	2	4	**4248678**	50
PG 16	2	5	**4248679**	50
PG 16	2	6	**4248680**	50
PG 16	2	7	**4248409**	50
PG 16	2	8	**4248681**	50
PG 16	2	9	**4248682**	50
PG 16	3	3	**4248683**	50
PG 16	3	4	**4248684**	50
PG 16	3	5	**4248677**	50
PG 16	3	5.6	**4248685**	50
PG 16	3	6	**4248686**	50
PG 16	3	7	**4248695**	50
PG 16	3	8	**4248687**	50

Outer thread	Hole Quantity	Hole diameter mm	Cat. No.	Std. Pk.
PG 16	4	4	**4248688**	50
PG 16	4	5	**4248689**	50
PG 16	4	6	**4248694**	50
PG 16	5	4	**4248690**	50
PG 16	5	5	**4248691**	50
PG 16	6	4	**4248692**	50
PG 16	7	4	**4248693**	50
PG 21	2	4.5	**4248696**	20
PG 21	2	8	**4248697**	20
PG 21	2	8.7	**4248698**	20
PG 21	2	9	**4248699**	20
PG 21	2	11	**4248700**	20
PG 21	3	7	**4248542**	20
PG 21	3	8	**4248531**	20
PG 21	3	9	**4248701**	20
PG 21	4	5	**4248702**	20
PG 21	4	6	**4248529**	20
PG 21	4	7.5	**4248709**	20
PG 21	4	8	**4248703**	20
PG 21	5	5	**4248704**	20
PG 21	5	6	**4248539**	20
PG 21	5	6.5	**4248541**	20
PG 21	6	4	**4248705**	20
PG 21	6	5	**4248706**	20
PG 21	6	6	**4248713**	20
PG 21	6	6.5	**4248710**	20
PG 21	6	7	**4248715**	20
PG 21	7	6	**4248714**	20
PG 21	8	4	**4248707**	20
PG 21	8	5	**4248543**	20
PG 21	11	5	**4248712**	20
PG 21	21	2	**4248708**	20
PG 21	28	3	**4248711**	20
PG 29	2	9	**4248716**	20
PG 29	2	11	**4248717**	20
PG 29	3	9	**4248719**	20
PG 29	3	11	**4248720**	20
PG 29	4	8	**4248629**	20
PG 29	4	9	**4248721**	20
PG 29	4	10	**4248722**	20
PG 29	6	6	**4248627**	20
PG 29	6	6.5	**4248610**	20
PG 29	6	7	**4248614**	20
PG 29	7	6	**4248631**	20
PG 29	7	7	**4248723**	20
PG 29	8	5	**4248724**	20
PG 29	8	6	**4248632**	20
PG 29	10	6	**4248725**	20
PG 29	11	5	**4248634**	20
PG 29	28	3	**4248612**	20

Material:
- Body: Nickel-Plated Brass
- Seal: Tefabloc
- Sealing ring for outer thread: Nitril

Characteristics:
- Metric thread
- Multi-holed seal inserts
- Extended thread available

Technical properties:
- Gas- and watertight
- Completely twist protected
- Combinable with various sealing inserts

Applications:
- Machines and devices
- Measuring and control engineering
- Plant installations

Locknuts sold separately, see page 24.





Temperature Range MS
-25 to 120°C (-13 to 248°F)

PROTECTION IP68 RATING

See page 12 for dimensions.

Outer thread	Hole Quantity	Hole diameter mm	Cat. No.	Std. Pk.
M 16 x 1.5/9	2	1	**4249600**	50
M 16 x 1.5/9	2	3	**4249601**	50
M 16 x 1.5/9	2	3.5	**4249602**	50
M 16 x 1.5/9	2	4	**4249603**	50
M 16 x 1.5/9	3	3	**4249604**	50
M 20 x 1.5/11	2	2.3	**4249610**	50
M 20 x 1.5/13	2	3	**4249611**	50
M 20 x 1.5/11	2	3.5	**4249612**	50
M 20 x 1.5/11	2	4	**4249613**	50
M 20 x 1.5/13	2	5	**4249614**	50
M 20 x 1.5/13	2	6	**4249615**	50
M 20 x 1.5/13	3	2	**4249616**	50
M 20 x 1.5/13	3	3	**4249617**	50
M 20 x 1.5/11	3	3.5	**4249618**	50
M 20 x 1.5/13	3	4	**4249619**	50
M 20 x 1.5/13	3	5.3	**4249620**	50
M 20 x 1.5/11	4	1.5	**4249621**	50
M 20 x 1.5/13	4	3	**4249622**	50
M 20 x 1.5/11	4	3.5	**4249623**	50
M 20 x 1.5/13	4	4	**4249624**	50
M 20 x 1.5/11	6	2	**4249625**	50
M 20 x 1.5/11	6	2.5	**4249626**	50
M 20 x 1.5/13	6	3.5	**4249627**	50
M 20 x 1.5/13	10	2	**4249628**	50
M 25 x 1.5/16	2	4	**4249640**	20
M 25 x 1.5/21	2	4.5	**4249641**	20
M 25 x 1.5/16	2	5	**4249642**	20
M 25 x 1.5/16	2	6	**4249643**	20
M 25 x 1.5/16	2	7	**4249644**	20
M 25 x 1.5/21	2	8	**4249645**	20
M 25 x 1.5/16	3	3	**4249646**	20
M 25 x 1.5/16	3	4	**4249647**	20
M 25 x 1.5/16	3	5	**4249648**	20
M 25 x 1.5/16	3	5.6	**4249649**	20
M 25 x 1.5/16	3	6	**4249650**	20
M 25 x 1.5/21	3	7	**4249651**	20
M 25 x 1.5/21	3	8	**4249652**	20
M 25 x 1.5/16	4	4	**4249653**	20
M 25 x 1.5/21	4	5	**4249654**	20
M 25 x 1.5/21	4	6	**4249655**	20
M 25 x 1.5/16	5	4	**4249656**	20
M 25 x 1.5/21	5	5	**4249657**	20
M 25 x 1.5/21	5	6	**4249658**	20
M 25 x 1.5/21	5	6.5	**4249659**	20
M 25 x 1.5/21	6	4	**4249660**	20
M 25 x 1.5/21	6	5	**4249661**	20
M 25 x 1.5/21	8	4	**4249662**	20
M 25 x 1.5/21	8	5	**4249663**	20
M 25 x 1.5/21	21	2	**4249664**	20
M 32 x 1.5/21	2	4.5	**4249670**	20
M 32 x 1.5/21	2	8	**4249671**	20
M 32 x 1.5/29	2	9	**4249672**	20
M 32 x 1.5/29	2	11	**4249673**	20
M 32 x 1.5/29	2	12	**4249674**	20
M 32 x 1.5/21	3	7	**4249675**	20
M 32 x 1.5/21	3	8	**4249676**	20

Outer thread	Hole Quantity	Hole diameter mm	Cat. No.	Std. Pk.
M 32 x 1.5/29	3	9	**4249677**	20
M 32 x 1.5/29	3	11	**4249678**	20
M 32 x 1.5/21	4	5	**4249679**	20
M 32 x 1.5/21	4	6	**4249680**	20
M 32 x 1.5/29	4	8	**4249681**	20
M 32 x 1.5/29	4	9	**4249682**	20
M 32 x 1.5/29	4	10	**4249683**	20
M 32 x 1.5/21	5	5	**4249684**	20
M 32 x 1.5/21	5	6	**4249685**	20
M 32 x 1.5/21	5	6.5	**4249686**	20
M 32 x 1.5/21	6	4	**4249687**	20
M 32 x 1.5/21	6	5	**4249688**	20
M 32 x 1.5/29	6	6	**4249689**	20
M 32 x 1.5/29	6	6.5	**4249690**	20
M 32 x 1.5/29	6	7	**4249691**	20
M 32 x 1.5/29	7	6	**4249692**	20
M 32 x 1.5/29	7	7	**4249693**	20
M 32 x 1.5/21	8	4	**4249694**	20
M 32 x 1.5/29	8	5	**4249695**	20
M 32 x 1.5/29	8	6	**4249696**	20
M 32 x 1.5/29	10	6	**4249697**	20
M 32 x 1.5/29	11	5	**4249698**	20
M 32 x 1.5/21	21	2	**4249699**	20
M 32 x 1.5/29	28	3	**4249701**	20

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9