

ROHS COMPLIANT		REVISION HISTORY			
		REV	DESCRIPTION	DATE	APPROVED
		-	NRN 34839	07/08	STW

PRODUCT DATA DRAWING

Technical drawing of a snap-in connector. The side view shows a component with a flange on the left and a cylindrical body on the right. Dimensions include a total length of (.278 [7.06]), a flange width of .080 [2.03], a body diameter of $\phi .156$ [3.96], and a mounting hole diameter of $\phi .146$ [3.71]. The cross-sectional view shows a 2X hole with a diameter of $\phi .178$ [4.52] and a wall thickness of .052±.001 [1.32±0.03]. A note indicates 'FOR .093 PANEL'.

MATERIAL:

BODY:

STAINLESS STEEL PER AMS-5640, UNS S30300 (TYPE 1)

SLEEVE, CONTACT & RETAINING RING:

BERYLLIUM COPPER PER ASTM B196, ALLOY No. UNS C17300, TD04

INSULATOR:

PTFE PER ASTM D1710, TYPE I, GRADE 1, CLASS B

FINISH:

BODY:

PASSIVATED PER AMS-QQ-P-35, TYPE II

SLEEVE, CONTACT & RETAINING RING:

GOLD PER ASTM B 488, TYPE II, CODE C, CLASS 1.27; OVER NICKEL PER AMS-QQ-N-290, CLASS 1, .00005" MIN.

PERFORMANCE:

IMPEDANCE:

50 OHMS

FREQ. RANGE:

DC TO 40.0 GHz

VSWR:

1.25:1 DC TO 26.5 GHz
1.35:1 DC TO 40.0 GHz

DWV:

325 VRMS

OPERATING TEMP.:

-55°C TO +125 °C

REMOVAL TOOL P/N 500-32-028

MATERIAL:

SEE NOTES

FINISH:

SEE NOTES

SURFACE AREA:

N/A

PROPRIETARY

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SV MICROWAVE, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SV MICROWAVE, INC IS PROHIBITED.

DIMENSIONS ARE IN INCHES TOLERANCES:

FRACTIONAL: $\pm 1/64$ ANGULAR: X° $\pm 1^{\circ}0'$
X°X' $\pm 15'$
DECIMAL: .X $\pm .030$
.XX $\pm .010$
.XXX $\pm .005$

INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M - 1994

THIRD ANGLE PROJECTION

UNLESS OTHERWISE SPECIFIED

1) ALL DIMENSIONS ARE IN INCHES (MILLIMETERS)
2) ALL DIMENSIONS ARE AFTER PLATING.
3) BREAK CORNERS & EDGES .005 R. MAX.
4) CHAM. 1ST & LAST THREADS.
5) SURFACE ROUGHNESS 63+MIL-STD-10.
6) DIA.'S ON COMMON CENTERS TO BE CONCENTRIC WITHIN .005 T.I.R.
7) REMOVE ALL BURRS

DRAWN: DAL 08/06/08

CHECKED: STW 08/06/08

APPROVED: STW 08/06/08

TITLE:

SMPM MALE SB SNAP-IN FOR .093 PANEL FOR $\phi .047$ S.R. CABLE

SIZE

B

CAGE CODE

95077

DWG. NO.

3211-40003

SCALE: 14:1

SHEET 1 OF 1

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9