

DRAWING MADE IN THIRD ANGLE PROJECTION

1426325

1426325

/home/us018246/edmod

PART NUMBER	REV	FIRST USED	TERMINATOR	FEED TYPE	DESCRIPTION
1426325-1	B	-	LEADMAKER	MECH POST FEED	CUTS CARRIER
1426325-2	B	-	BENCH	MECH PRE FEED	CUTS CARRIER
1426325-6	B	-	LEADMAKER	MECH POST FEED	CONTINUOUS CARRIER
7-1426325-1	B	-	LEADMAKER	MECH POST FEED	-1 AND SPARE PARTS
7-1426325-2	B	-	BENCH	MECH PRE FEED	-2 AND SPARE PARTS
7-1426325-6	B	-	LEADMAKER	MECH POST FEED	-6 AND SPARE PARTS
7-1426325-7	A	-	-	-	SPARE PARTS KIT

CRIMP DATA

AMP TERMINALAMP CRIMP SPECS

TERMINAL NAME: DYNAMIC CONNECTOR D-5 SERIES

CRIMP	SIZE	TYPE	RANGE
WIRE	4.57 [1.180 IN]	F	7.95mm ² - 8.92mm ²
INSUL	7.37 [1.290 IN]	F	4.90-7.80 [1.193-.307 IN]

WIRE STRIP LENGTH

6.50-7.50 [1.256-.295 IN]

APPL INSTRUCTION

408-8322

TERMINAL

-

FEED

24.50 [1.965 IN]

TERMINALS APPLIED

1318696-6	-	-	-	-
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-

WIRE SIZE	CRIMP HEIGHT	PIN PN AND LENGTH [IN]
8.92mm ²	3.33 ±0.08 [1.131 ±.003 IN]	9-354778-3 [1.2960]
7.95mm ²	3.21 ±0.08 [1.126 ±.003 IN]	354779-3 [1.3005]
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-

RECOMMENDED SPARE PARTS.

GREASE RAM, CAM, CAM FOLLOWER AND FEED ROD LIGHTLY.

LUBRICATE DAILY PER THE APPLICATOR INSTRUCTION SHEET SUPPLIED WITH THE APPLICATOR.

CUT TO LENGTH AT ASSY.

INSULATION RANGE SHOWN IS AS MEASURED AFTER CRIMPING.

VIEW B ROTATED 180°

POST FEED 40 mm STROKE	POST FEED 30 mm STROKE	PRE FEED 30 mm STROKE	PRE FEED 40 mm STROKE

LOC

A

DIST

66

-	1	1	1	1	1	1	1426325	PRINT, APPLICATOR LOG SHEET	73
-	1	1	1	1	1	1	1338705-1	DOCUMENTATION PACKAGE	72
-	-	-	-	-	-	-	-	-	70
-	-	-	-	-	-	-	-	-	69
-	-	-	-	-	-	-	-	-	68
-	1	1	1	1	1	1	461264-1	PLATE, IDENTIFICATION	67
-	2	2	2	2	2	2	21017-2	SCR,DRIVE(#2x.19) ID PLATE	66
-	-	-	-	-	-	-	-	-	65
-	1	1	1	1	1	1	986950-1	WASHER, FLAT PRECISION	64
-	1	1	1	1	1	1	3-18031-0	SCR,SKT SET (M6X6)RAM	63
-	1	1	1	1	1	1	18023-9	SCR,SHC (M4X6) INS DISC	62
-	2	2	2	2	2	2	1-18024-5	SCR,BHC (M5X25) DRAG	61
-	1	1	1	1	1	1	18024-7	SCR,BHC (M4X10) ANVIL	60
-	1	1	1	1	1	1	5-18022-2	SCR,HEX (M4X8) FEED FINGER	59
-	-	-	-	-	-	-	-	-	58
-	-	-	-	-	-	-	-	-	57
-	1	1	1	1	1	1	1338685-1	PAWL, FEED	56
-	-	-	-	-	-	-	-	-	55
-	4	4	4	4	4	4	18024-8	SCR,BHC (M4x12) SHEAR HOLDER	54
-	2	2	2	2	2	2	9-18023-6	SCR,SHC (M4x14) TERM HLD DWN	53
-	1	1	1	1	1	1	18030-1	NUT,HEX (M3) HOLD DOWN	52
-	1	1	1	1	1	1	811242-5	BUMPER, HOLDDOWN	51
-	1	1	1	1	1	1	690753-2	SPACER, TONKER	50
-	1	1	1	1	1	1	18024-3	SCR,BHC (M3X10) CAM	49
-	-	1	-	-	1	-	1338675-1	CAM, PRE FEED 30 & 40 mm ST	48
-	1	-	1	1	-	1	1338676-1	CAM, POST FEED 30 & 40 mm ST	47
-	1	1	1	1	1	1	1320999-4	APPLICATOR BASIC SUBASSY	46
-	1	1	1	1	1	1	690191-1	PLUG, NYLON	45
-	1	1	1	1	1	1	1338660-1	RAM	44
-	1	1	1	1	1	1	690125-1	WASHER, LAMINATED	43
-	1	1	1	1	1	1	690124-5	WASHER, RAM	42
-	1	1	1	1	1	1	992285-2	SCR,SHC LOW HD (M8X25)RAM	41
-	1	1	1	1	1	1	23241-1	BALL, STEEL	40
-	1	1	1	1	1	1	2-22278-7	SPRING, COMPRESSION	39
-	1	1	1	1	1	1	1320922-4	DISC, INSULATION	38
-	1	1	1	1	1	1	354777-1	WIRE DISC, PLASTIC	37
-	1	1	1	1	1	1	22480-5	WASHER, SPRING	36
-	1	1	1	1	1	1	690212-1	POST, RAM	35
-	1	1	1	1	1	1	1320934-1	SUPPORT, TERMINAL	34
-	2	2	2	2	2	2	1-18024-0	SCR,BHC (M4X20) STRIP GUIDE	33
-	1	1	1	1	1	1	18027-2	WASHER, FLAT (M4)	32
-	1	1	1	1	1	1	1-18023-2	SCR,SKT CAP (M4X12) MOUNT BLOCK	31
-	1	1	1	1	1	1	1-1320908-0	SPACER, STRIP GUIDE	30
-	1	1	1	1	1	1	1633073-1	STRIP GUIDE PLATE ASSY	29
-	1	1	1	1	1	1	455888-6	SPACER, FRONT SHEAR DEP	28
-	2	2	2	2	2	2	1-22284-0	SPRING, DRAG	27
-	1	1	1	1	1	1	356835-1	LEVER, DRAG RELEASE	26
-	1	1	1	1	1	1	240792-1	DRAG, TERMINAL	25
-	1	1	1	1	1	1	1320928-1	PLATE, STRIP GUIDE	24
-	1	1	1	1	1	1	980371-4	SCR,SHC SHLD	23
-	1	-	1	1	-	1	690472-2	STRIPPER	22
-	1	1	1	1	1	1	1-18023-1	SCR,SHC (M4X10) STRIPPER	21
-	4	4	4	4	4	4	18025-2	WASHER,LOCK (M4) STRIPPER	20
-	-	1	-	-	1	-	2-1338987-6	STRIPPER	19
-	-	-	-	-	-	-	-	-	18
-	1	-	-	1	-	-	1338684-2	HOLDER, SHEAR, FRONT (NO-CUT)	17
-	-	-	-	-	-	-	-	-	16
-	-	-	-	-	-	-	-	-	15
-	-	-	-	-	-	-	-	-	14
-	-	-	-	-	-	-	-	-	13
-	1	1	1	1	1	1	5-22280-0	SPRING, SHEAR	12
-	1	1	1	1	1	1	356885-5	STOP, SHEAR	11
-	-	1	1	-	1	1	1-1320921-0	HOLDER, SHEAR, FRONT (CUT)	10
-	1	1	1	1	1	1	2-454276-3	SHEAR, FLOAT (FRONT)	9
1	2	2	2	1	1	1	1333229-7	ANVIL	8
-	1	1	1	1	1	1	1-240641-7	SPACER, DEPRESSOR (REAR)	7
-	-	-	-	-	-	-	-	-	6
-	1	1	1	1	1	1	2-455889-4	DEPRESSOR, SHEAR (FRONT)	5
-	1	1	1	1	1	1	4-238011-0	SPACER, BLOCK CRIMPER	4
1	2	2	2	1	1	1	1-409282-1	CRIMPER, INSULATION	3
-	1	1	1	1	1	1	455888-7	SPACER, CRIMPER	2
1	2	2	2	1	1	1	1-409414-4	CRIMPER, WIRE	1
-77	-76	-72	-71	-6	-2	-1	PART NO	DESCRIPTION	ITEM NO
-	-	-	-	-	-	-	REVISION OF EACH ASSY NO (WHEN BLANK, USE DWG REVISION)	-	-
QTY. REQD PER ASSY									
PARTS LIST									
DIMENSIONS: mm [INCHES]							MATL	HT TR	FIN
DO NOT SCALE PRINT.							-	-	-
TOLERANCES UNLESS OTHERWISE SPECIFIED:							DR	OBMAY02	APP
1 PLC DEC ±-							L.L.OFTHOUSE	OBMAY02	F.BACKHURST
2 PLC DEC ±-							CHK	REL	26JUN02
3 PLC DEC ±-							-	L.L.OFTHOUSE	-
ANGLES ±-							NAME	SIDE FEED HD-I APPLICATOR	
SURF TEXTURE: ✓							SCALE	HD-I APPL	
REMOVE BURRS, BREAK SHARP EDGES RO.38 MAX							DWG NO	1426325	
CAGE CODE							00779	CUSTOMER AND ASSEMBLY DRAWING	
RESTRICTED TO							-	-	

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9