

FO patch cable - FL MM PATCH 1,0 LC-ST - 2989174

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Assembled FO cable, break out cable, multimode fiberglass 50/125 µm (OM2), connector: LC/B-FOC(ST®), degree of protection: IP20, for installation in cable ducts or control cabinets, length: 1 m



Product Features

- Multi-mode patch cable for indoor installation
- Ideal for use in distributor systems and for connecting termination devices
- 2.8 mm single elements made from halogen-free and flame-retardant material



Key Commercial Data

| | |
|--------------------------------------|----------------|
| Packing unit | 1 pc |
| Weight per Piece (excluding packing) | 40.0 g |
| Custom tariff number | 85444210 |
| Country of origin | Czech Republic |

Technical data

Cable type

| | |
|--------------------|----------------------|
| Cable abbreviation | I-V(ZN)H |
| Cable type | Multimode fiberglass |

Ambient conditions

| | |
|---|---|
| Ambient temperature (operation) | -5 °C ... 70 °C |
| Ambient temperature (storage/transport) | -25 °C ... 70 °C |
| Ambient temperature (installation) | -5 °C ... 50 °C |
| Resistance to oil | Not resistant to oil, gasoline, acids, and lyes |

External sheath

| | |
|---|-----------------------------|
| Outer sheath, material | FRNC |
| External sheath, color | orange |
| External sheath, strain relief elements | Non-metallic, aramide fiber |

FO patch cable - FL MM PATCH 1,0 LC-ST - 2989174

Technical data

External sheath

| | |
|------------------------|--------|
| External diameter max. | 5.7 mm |
| External diameter min. | 2.8 mm |

Single wire

| | |
|-------------------------------------|------------------------------|
| Individual wires per module | 2 |
| Individual wire, diameter | 900 µm |
| Single wire, strain relief elements | Non-metallic, aramide fibers |

Mechanical properties

| | |
|---------------------------------------|---------|
| Bending radius short term/long term | 30 mm |
| Bending radius, long-term | 60 mm |
| Lateral pressure, long-term | 60 N/cm |
| Tensile strength short-term/long-term | 600 N |
| Numerical aperture | 0.2 |

General

| | |
|---|------------|
| Conductor length | 1 m |
| Cable weight | 15.8 kg/km |
| Transmission characteristics (category) | OM2 |
| Transmission speed | 1 Gbps |

Behavior in fire

| | |
|------------------------|------------------------------|
| Flame resistance | According to DIN 60332-1-2 |
| | IEC 60332-3-22 (Cat. A) |
| Concentration of fumes | in accordance with IEC 61034 |
| Halogen-free | According to IEC 60754-2 |
| Behavior in fire | No corrosive or toxic fumes |
| | 0.36 MJ/m |

Attenuation

| | |
|--------------------|---|
| Cable, attenuation | 2.5 dB/km (at 850 nm), 0.7 dB/km (at 1300 nm) |
|--------------------|---|

Standards and Regulations

| | |
|------------------------|---|
| Concentration of fumes | in accordance with IEC 61034 |
| Resistance to oil | Not resistant to oil, gasoline, acids, and lyes |
| Halogen-free | According to IEC 60754-2 |
| Behavior in fire | No corrosive or toxic fumes |
| | 0.36 MJ/m |
| Flame resistance | According to DIN 60332-1-2 |
| | IEC 60332-3-22 (Cat. A) |

FO patch cable - FL MM PATCH 1,0 LC-ST - 2989174

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27061003 |
| eCl@ss 4.1 | 27061003 |
| eCl@ss 5.0 | 27061003 |
| eCl@ss 5.1 | 27061003 |
| eCl@ss 6.0 | 27259207 |
| eCl@ss 7.0 | 27259207 |
| eCl@ss 8.0 | 27061003 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC001263 |
| ETIM 3.0 | EC001263 |
| ETIM 4.0 | EC001263 |
| ETIM 5.0 | EC001263 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 26121607 |
| UNSPSC 7.0901 | 26121607 |
| UNSPSC 11 | 26121607 |
| UNSPSC 12.01 | 26121607 |
| UNSPSC 13.2 | 26121607 |

Accessories

Accessories

Adapter

Fiber optic coupling - PSM-SET-BFOC-LINK/2 - 2799429



Coupling; set consisting of 2 couplings for connecting B-FOC plugs

Fiber optic coupling - FL MM PATCH COUPLER LC-LC - 2700312



Coupling, LC/LC, can be used for multi-mode glass fibers

FO patch cable - FL MM PATCH 1,0 LC-ST - 2989174

Accessories

Fiber optic coupling - FL COUPLER SC-DUPLEX - 2901788



Coupling, SC duplex/SC duplex, compatible with multi-mode and single mode glass fibers, PCF, and polymer fibers

Data cable by the meter

FO cable - PSM-LWL-GDM-RUGGED- 50/125 - 2799322



Fiberglass cable, duplex 50/125 μm , by the meter, without connector, for indoor installation

FO cable - PSM-LWL-GDO- 50/125 - 2799432



Fiberglass cable, duplex 50/125 μm , by the meter, without connector, for outdoor installation

Data cable preassembled

FO patch cable - FOC-GDM-RUGGED-1016/IP20/... - 2901558



rugged GOF installation cable (IP20 heads only) for inner areas with highly tear-proof aramid strain-relief elements. Individual elements consist of highly flexible FRNC material. The cable is halogen-free, ozone and UV resistant and has a rugged polyurethane (PUR) outer sheath.

FO patch cable - FL MM PATCH 1,0 LC-ST - 2989174

Accessories

FO patch cable - FOC-GDM-RUGGED-1016/... - 1402193



rugged GOF installation cable for inner areas with highly tear-proof aramid strain-relief elements. Individual elements consist of highly flexible FRNC material. The cable is halogen-free, ozone and UV resistant and has a rugged polyurethane (PUR) outer sheath.

FO patch cable - FOC-GDO-1017/IP20/... - 2901559



Highly rugged GOF round cable (IP20 heads only) for assembly and for outdoor installation with integrated moisture barrier as well as rodent-proof scrim. Individual elements made from highly flexible FRNC material. The wire is ozone and UV resistant with a very rugged polyethylene outer sheath.

Fiber optics connector (device side)

SC-RJ female insert - VS-SCRJ-GOF-BU/BU - 1652978



SC-RJ socket insert, duplex, for VS-A-F-IP67 panel mounting frame, can be used for fiberglass (multi-mode and single mode), PCF, and polymer fibers

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9