THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION –,– .
© COPYRIGHT – By – ALL RIGHTS RESERVED.

LOC	DIST
AD	00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A6	REVISED PER ECO-14-014809	30SEP2014	NK	RH









1 1 DRAWING IS A GUIDE FOR NON-CRITICAL DIMENSIONS.

2 EACH SWITCH WITH THREDED BUSHINGS SUPPLIED WITH THE FOLLWING MOUNTING HARDWARE:
(2) HEX NUTS
(1) INTERNAL TOOTH LOCKWASHER
(1) LOCATING RING.

3 G CONTACT OPTION CAN BE USED FOR SIGNAL OR POWER LEVEL SWITCHING. IF SWITCH IS USED AT LEVELS EXCEEDING .4VA @ 20V AC/DC, SWITCH IS RENDERED FOR POWER SWITCHING ONLY DUE TO ARC REMOVAL OF GOLD PLATING. RATING MARKED ON FRAME IS 2A 250VAC, 5A 120VAC.

4 DATE CODE AND COUNTRY OF ORIGIN MAY APPEAR ON EITHER SIDE OF SWITCH.

5 LENGTH OF TOGGLE REDUCED BY .020 WITH A, AV2, V30 OR V40 VERTICAL SUPPORT BRACKET OPTIONS.

6 ALL LOGO, RATING, DATE CODE, AND FUNCTION MARKINGS TO BE LASER MARKED.

FUNCTION CHART

FUNCTION			
01	ON	NONE	ON
08	ON	NONE	(ON)
TERMINALS CONNECTED	2–3	– – –	1–2

None: No mechanical position
Off: Mechanical position with no electrical connection
(On): Momentary action

SPECIFICATIONS CHART

RATING, B CONTACTS	.4VA MAX @20V MAX. AC OR DC
RATING, G CONTACTS–SEE NOTE 3	.4VA MAX @20V MAX. AC OR DC OR 5A @120 VAC OR 28 VDC (RESISTIVE)
	2A @250 VAC (RESISTIVE)
RATING, Q CONTACTS	5A @120 VAC OR 28 VDC (RESISTIVE)
	2A @250 VAC (RESISTIVE)
ELECTRICAL LIFE	6,000 CYCLES AT RATED LOAD
CONTACT RESISTANCE	10 MILLIOHMS MAX INITIAL @ 2–4VDC, 100ma
INSULATION RESISTANCE	1,000 MEGOHMS MIN
DIELECTRIC WITHSTANDING VOLTAGE	1,000 V RMS AT SEA LEVEL
OPERATING TEMPRATURE	–30C TO 85C

PART NUMBER SEQUENCE CHART

MODEL	FUNCTION	TOGGLE	BUSHING	TERMINAL	CONTACT	RoHS
A1	01	K	CW	A	B	04
	08	K1	D	AV2	G	
		L	D9	C	Q	
		L1	H	V30		
		L2	Y	V40		
		M	Y9	W		
		P3		W4		
		S		Z		
		T		Z3		
		T1				

EXAMPLE: A101SYCQ04

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± –
1 PLC ± –
2 PLC ± –
3 PLC ± .010
4 PLC ± –
ANGLES ± 2°

MATERIAL –
FINISH –

DWN B.S.VISWESWARA 14APR05
CHK M.ZITTO –
APVD P.BROUILLETTE –
PRODUCT SPEC —
APPLICATION SPEC —
WEIGHT —

TE Connectivity

NAME
GEMINI A SERIES TOGGLE SWITCH, SINGLE POLE, 2 POSITION FUNCTIONS (01 & 08)

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A2	00779	C-1825136	—

CUSTOMER DRAWING | SCALE 3:1 | SHEET 1 OF 4 | REV A6

1825136

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION -,- .
© COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST
AD	00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	–	SEE SHEET 1	–	—	—

TOGGLES



M SHORT

DIM L	BUSHING TYPE
.200	Y, H
.270	D, D9



S STANDARD

DIM L	BUSHING TYPE
.410	Y, H
.480	D, D9



K

NO BUSHING OPTION NEEDED



K1

NO BUSHING OPTION NEEDED



L LEVER

DIM L	BUSHING TYPE
.840	Y, H
.910	D, D9



L1 LEVER

DIM L	BUSHING TYPE
.640	Y, H
.710	D, D9



L2 LEVER

DIM L	BUSHING TYPE
.550	Y, H
.620	D, D9



P3 NO BUSHING OPTION NEEDED



T NO BUSHING OPTION NEEDED



T1 NO BUSHING OPTION NEEDED

BUSHINGS



D THREADED

D9 UNTHREADED



Y THREADED

Y9 UNTHREADED

CONTAINS O–RING BETWEEN TOGGLE AND BUSHING AND BETWEEN BUSHING AND PANEL



CW THREADED SPLASHPROOF



H HIGH TORQUE

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± –
1 PLC ± –
2 PLC ± –
3 PLC ± .010
4 PLC ± –
ANGLES ± 2°

MATERIAL –

FINISH –

DWN	B.S.VISWESWARA 14APR05
CHK	M.ZITTO –
APVD	P.BROUILLETTE –
PRODUCT SPEC	—
APPLICATION SPEC	—
WEIGHT	—

TE Connectivity

NAME: GEMINI A SERIES TOGGLE SWITCH, SINGLE POLE, 2 POSITION FUNCTIONS (01 & 08)

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A2	00779	C-1825136	—

CUSTOMER DRAWING | SCALE 2:1 | SHEET 2 OF 4 | REV A6

1825136

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION –,– .
© COPYRIGHT – By – ALL RIGHTS RESERVED.

LOC	DIST
AD	00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	–	SEE SHEET 1	–	—	—

AV2 VERTICAL RIGHT ANGLE ⚠5





RECOMMENDED PCB LAYOUT

Z WIRE LUG



.030 THK.

Z3 QUICK CONNECT



.030 THK.

A RIGHT ANGLE ⚠5









RECOMMENDED PCB LAYOUT

W W4 WIRE WRAP



.030 THK.

OPTION	DIM A
W	.736
W4	1.062

V30 V40 ⚠5 VERTICAL SUPPORT BRACKET







OPTION	DIM A
V30	.460
V40	.630



RECOMMENDED PCB LAYOUT

C PRINTED CIRCUIT



.030 THK.



RECOMMENDED PCB LAYOUT

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± –
1 PLC ± –
2 PLC ± –
3 PLC ± .010
4 PLC ± –
ANGLES ± 2°

MATERIAL –
FINISH –

DWN B.S.VISWESWARA 14APR05
CHK M.ZITTO –
APVD P.BROUILLETTE –
PRODUCT SPEC —
APPLICATION SPEC —
WEIGHT —

TE Connectivity

NAME GEMINI A SERIES TOGGLE SWITCH, SINGLE POLE, 2 POSITION FUNCTIONS (01 & 08)

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A2	00779	C-1825136	—

CUSTOMER DRAWING | SCALE 2:1 | SHEET 3 OF 4 | REV A6

1825136

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION –,– .
© COPYRIGHT – By – ALL RIGHTS RESERVED.

LOC	DIST
AD	00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	–	SEE SHEET 1	–	—	—

Alco P/N	P/N
A101K1V30B04	1825136–1
A101KAB04	1825136–2
A101KAQ04	1825136–3
A101P3YV30B04	1825136–4
A101KCQ04	1825136–5
A101KD9AQ04	1825136–6
A101KZQ04	1825136–7
A101SYAV2B04	1825136–8
A101L1D9V30Q04	1825136–9
A101L1YZB04	1–1825136–0
A101LDZQ04	1–1825136–1
A101MD9AB04	1–1825136–2
A101MD9AG04	1–1825136–3
A101MD9AQ04	1–1825136–4
A101MD9AV2B04	1–1825136–5
A101MD9AV2G04	1–1825136–6
A101MD9AV2Q04	1–1825136–7
A101MD9V30B04	1–1825136–8
A101MDAQ04	1–1825136–9
A101MDAV2B04	2–1825136–0
A101MDCG04	2–1825136–1
A101MDZQ04	2–1825136–2
A101MYCQ04	2–1825136–3
A101MYZQ04	2–1825136–4
A103SYAV2B04	2–1825136–5
A101P3CB04	2–1825136–6
A101P3ZQ04	2–1825136–7
A101KAV2Q04	2–1825136–8
A101MDCQ04	2–1825136–9
A101SCWCQO04	3–1825136–0
A101SCWZQ04	3–1825136–1
A101SD9AB04	3–1825136–2
A101SD9AQ04	3–1825136–3
A101SD9AV2B04	3–1825136–4
A101SD9AV2Q04	3–1825136–5
A101SD9V30B04	3–1825136–6
A101SD9V30Q04	3–1825136–7
A101SDCQ04	3–1825136–8
A101SDZQ04	3–1825136–9
A101SHZQ04	4–1825136–0
A101SY9CQ04	4–1825136–1
A101SYAB04	4–1825136–2
A101SYAQ04	4–1825136–3
A101SYCB04	4–1825136–4
A101SYCQ04	4–1825136–5
not assigned	4–1825136–6
A101SYWQ04	4–1825136–7
A101SYZB04	4–1825136–8

Alco P/N	P/N
A101SYZQ04	4–1825136–9
not assigned	5–1825136–0
not assigned	5–1825136–1
A101T1ZB04	5–1825136–2
A101T1ZQ04	5–1825136–3
A101TCQ04	5–1825136–4
A101TZQ04	5–1825136–5
A108MD9AB04	5–1825136–6
not assigned	5–1825136–7
A108P3CQ04	5–1825136–8
A108P3ZQ04	5–1825136–9
A108SD9AQ04	6–1825136–0
A108SDZQ04	6–1825136–1
A108SYCB04	6–1825136–2
A108SYCQ04	6–1825136–3
A108SYZQ04	6–1825136–4
not assigned	6–1825136–5
A101SYAG04	6–1825136–6

RECOMMENDED PANEL CUT–OUTS

BUSHING SIZE	WITHOUT LOCKING RING		WITH STANDARD LOCKING RING
1/4			
15/32			

MATERIALS CHART

COMPONENT NAME	BASE MATERIAL	FINISH
CASE	DAP, RED, UL94 V–0	
FRAME	STAINLESS STEEL	
B TERMINALS & CONTACTS	COPPER	GOLD OVER NICKEL
G TERMINALS & CONTACTS	COPPER	GOLD OVER SILVER
Q TERMINALS & CONTACTS	COPPER	.000400 SILVER
ACTUATOR	PHENOLIC, BLACK, UL94 V–1	
LEVER	BRASS	CHROME
BUSHING	BRASS	NICKEL
SPRING	MUSIC WIRE	
SUPPORT BRACKET	BRASS	TIN
PIVOT PIN	STEEL	NICKEL
LOCK WASHER	STAINLESS STEEL	
LOCKING RING	STAINLESS STEEL	
NUTS	C3604BD BRASS	NICKEL
TERMINAL SEAL	EPOXY	

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± –
1 PLC ± –
2 PLC ± –
3 PLC ± .010
4 PLC ± –
ANGLES ± 2°

MATERIAL –
FINISH –

DWN B.S.VISWESWARA 14APR05
CHK M.ZITTO –
APVD P.BROUILLETTE –
PRODUCT SPEC —
APPLICATION SPEC —
WEIGHT —

TE Connectivity

NAME GEMINI A SERIES TOGGLE SWITCH, SINGLE POLE, 2 POSITION FUNCTIONS (01 & 08)

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A2	00779	C-1825136	—

CUSTOMER DRAWING | SCALE 3:1 | SHEET 4 OF 4 | REV A6

1825136

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9