

OxiCap[®] NOJ Series



Niobium Oxide Capacitor



- Non-burn safe technology
- Reliability level: 0.5%/1000 hrs.
- 6 case sizes available
- Environmentally friendly
- IBM global approval received in 2004
- Electra Award received in 2005
- CV range: 4.7-1000 μ F / 1.8-10V



Electra Award
2005



For part marking see page 130

CASE DIMENSIONS: millimeters (inches)

| Code | EIA Code | EIA Metric | L \pm 0.20 (0.008) | W \pm 0.20 (0.008) -0.10 (0.004) | H \pm 0.20 (0.008) -0.10 (0.004) | W \pm 0.20 (0.008) | A \pm 0.30 (0.012) -0.20 (0.008) | S Min. |
|------|----------|------------|----------------------|---------------------------------------|---------------------------------------|----------------------|---------------------------------------|--------------|
| A | 1206 | 3216-18 | 3.20 (0.126) | 1.60 (0.063) | 1.60 (0.063) | 1.20 (0.047) | 0.80 (0.031) | 1.10 (0.043) |
| B | 1210 | 3528-21 | 3.50 (0.138) | 2.80 (0.110) | 1.90 (0.075) | 2.20 (0.087) | 0.80 (0.031) | 1.40 (0.055) |
| C | 2312 | 6032-28 | 6.00 (0.236) | 3.20 (0.126) | 2.60 (0.102) | 2.20 (0.087) | 1.30 (0.051) | 2.90 (0.114) |
| D | 2917 | 7343-31 | 7.30 (0.287) | 4.30 (0.169) | 2.90 (0.114) | 2.40 (0.094) | 1.30 (0.051) | 4.40 (0.173) |
| E | 2917 | 7343-43 | 7.30 (0.287) | 4.30 (0.169) | 4.10 (0.162) | 2.40 (0.094) | 1.30 (0.051) | 4.40 (0.173) |
| V | 2924 | 7361-38 | 7.30 (0.287) | 6.10 (0.240) | 3.55 (0.140) | 3.10 (0.120) | 1.30 (0.051) | 4.40 (0.173) |

W₁ dimension applies to the termination width for A dimensional area only.

HOW TO ORDER

| | | | | | | | |
|-------------|-------------------------------------|--|----------------------------|--|---|---|---|
| NOJ | D | 107 | M | 006 | R | WJ | - |
| Type | Case Size See table above | Capacitance Code 1st two digits represent significant figures, 3rd digit represents multiplier in pF | Tolerance M=±20% | Rated DC Voltage 001 = 1.8Vdc 002 = 2.5Vdc 004 = 4Vdc 006 = 6.3Vdc 010 = 10Vdc | Packaging R = Pure Tin 7" Reel S = Pure Tin 13" Reel | Specification Suffix WJ = Standard Suffix | Additional characters may be added for special requirements V = Dry pack Option (selected codes only) with exception of D, E, V cases |

TECHNICAL SPECIFICATIONS

| | | | | | | | |
|------------------------------------|--|-----|-----|-----|-----|----|--|
| Technical Data: | All technical data relate to an ambient temperature of +25°C is not stated | | | | | | |
| Capacitance Range: | 4.7 μ F to 1000 μ F | | | | | | |
| Capacitance Tolerance: | ±20% | | | | | | |
| Leakage Current DCL: | 0.02CV | | | | | | |
| Rated Voltage DC (V _R) | ≤ +85°C: | 1.8 | 2.5 | 4 | 6.3 | 10 | |
| Category Voltage (V _C) | ≤ +105°C: | 1.2 | 1.7 | 2.7 | 4 | 7 | |
| Surge Voltage (V _S) | ≤ +85°C: | 2.3 | 3.3 | 5.2 | 8 | 13 | |
| Surge Voltage (V _S) | ≤ +105°C: | 1.6 | 2.2 | 3.4 | 5 | 8 | |
| Temperature Range: | -55°C to +105°C | | | | | | |
| Reliability: | 0.5% per 1000 hours at 85°C, V _R , 0.1 Ω /V series impedance, 60% confidence level Meets requirements of AEC-Q200 | | | | | | |

OxiCap® NOJ Series

Niobium Oxide Capacitor



CAPACITANCE AND RATED VOLTAGE RANGE (LETTER DENOTES CASE SIZE)

| Capacitance | | Rated Voltage DC (V _R) to 85°C / 0.66 DC to 105°C | | | | |
|-------------|------|---|----------|------------|--------------|------------|
| μF | Code | 1.8V (x) | 2.5V (e) | 4V (G) | 6.3V (J) | 10V (A) |
| 4.7 | 475 | | | | A | A |
| 6.8 | 685 | | | | A | A |
| 10 | 106 | | | | A | A/B |
| 15 | 156 | | | A | A/B | A/B |
| 22 | 226 | | A | A/B | A/B | B/C/B(700) |
| 33 | 336 | | A/B | A/B | B/C/B(700) | C |
| 47 | 476 | A | A/B | A/B/C | B/C | C |
| 68 | 686 | B | B/C | B/C | B/C | C |
| 100 | 107 | B/C | B/C | B/C/B(250) | B/C/D/B(400) | D/D(150) |
| 150 | 157 | C | C | C/D | C/D | |
| 220 | 227 | C | C | C/D | C/D/E | V |
| 330 | 337 | C | C/D | D | D/E | |
| 470 | 477 | | D/E | D/E | E/V | |
| 680 | 687 | | E | E/V | | |
| 1000 | 108 | | V | V | | |

Released codes

Engineering samples - please contact manufacturer

*Codes under development - subject to change

Note: Voltage ratings are minimum values. AVX reserves the right to supply higher ratings in the same case size, to the same reliability standards.



LEAD-FREE

LEAD-FREE COMPATIBLE
COMPONENT



RoHS
COMPLIANT



NON-BURN
NON-SMOKE

Niobium Oxide Capacitor

RATINGS & PART NUMBER REFERENCE

| AVX Part No. | Case Size | Capacitance (µF) | Rated Voltage (V) | DCL (µA) Max. | DF % Max. | ESR Max. (Ω) @100kHz | MSL | 100kHz RMS Current (A) | | | 100kHz RMS Voltage (V) | | |
|---|-----------|------------------|-------------------|---------------|-----------|----------------------|-----|------------------------|-------|-------|------------------------|-------|-------|
| | | | | | | | | 25°C | 85°C | 105°C | 25°C | 85°C | 105°C |
| 1.8 Volt @ 85°C (1.2 Volt @ 105°C) | | | | | | | | | | | | | |
| NOJA476M001#WJ | A | 47 | 1.8 | 1.7 | 8 | 1.6 | 1 | 0.237 | 0.213 | 0.095 | 0.379 | 0.342 | 0.152 |
| NOJB476M001#WJ | B | 47 | 1.8 | 1.7 | 6 | 1.6 | 1 | 0.252 | 0.227 | 0.101 | 0.404 | 0.364 | 0.162 |
| NOJB686M001#WJ | B | 68 | 1.8 | 2.5 | 6 | 1.5 | 1 | 0.261 | 0.235 | 0.104 | 0.391 | 0.352 | 0.156 |
| NOJB107M001#WJ | B | 100 | 1.8 | 3.6 | 6 | 1.4 | 1 | 0.270 | 0.243 | 0.108 | 0.378 | 0.340 | 0.151 |
| NOJC107M001#WJ | C | 100 | 1.8 | 3.6 | 6 | 0.4 | 1 | 0.574 | 0.517 | 0.230 | 0.230 | 0.207 | 0.092 |
| NOJC157M001#WJ | C | 150 | 1.8 | 5.4 | 8 | 0.4 | 1 | 0.574 | 0.517 | 0.230 | 0.230 | 0.207 | 0.092 |
| NOJC227M001#WJ | C | 220 | 1.8 | 8.0 | 8 | 0.4 | 1 | 0.574 | 0.517 | 0.230 | 0.230 | 0.207 | 0.092 |
| NOJC337M001#WJ | C | 330 | 1.8 | 11.9 | 8 | 0.3 | 1 | 0.663 | 0.597 | 0.265 | 0.199 | 0.179 | 0.080 |
| 2.5 Volt @ 85°C (1.7 Volt @ 105°C) | | | | | | | | | | | | | |
| NOJA226M002#WJ | A | 22 | 2.5 | 1.1 | 6 | 1.9 | 1 | 0.218 | 0.196 | 0.087 | 0.414 | 0.372 | 0.165 |
| NOJA336M002#WJ | A | 33 | 2.5 | 1.7 | 6 | 1.7 | 1 | 0.230 | 0.207 | 0.092 | 0.391 | 0.352 | 0.156 |
| NOJB336M002#WJ | B | 33 | 2.5 | 1.7 | 6 | 1.7 | 1 | 0.245 | 0.220 | 0.098 | 0.416 | 0.375 | 0.167 |
| NOJA476M002#WJ | A | 47 | 2.5 | 2.4 | 8 | 1.6 | 1 | 0.237 | 0.213 | 0.095 | 0.379 | 0.342 | 0.152 |
| NOJB476M002#WJ | B | 47 | 2.5 | 2.4 | 6 | 1.6 | 1 | 0.252 | 0.227 | 0.101 | 0.404 | 0.364 | 0.162 |
| NOJB686M002#WJ | B | 68 | 2.5 | 3.4 | 6 | 1.5 | 1 | 0.261 | 0.235 | 0.104 | 0.391 | 0.352 | 0.156 |
| NOJC686M002#WJ | C | 68 | 2.5 | 3.4 | 6 | 0.5 | 1 | 0.514 | 0.462 | 0.206 | 0.257 | 0.231 | 0.103 |
| NOJB107M002#WJ | B | 100 | 2.5 | 5.0 | 6 | 1.4 | 1 | 0.270 | 0.243 | 0.108 | 0.378 | 0.340 | 0.151 |
| NOJC107M002#WJ | C | 100 | 2.5 | 5.0 | 6 | 0.4 | 1 | 0.574 | 0.517 | 0.230 | 0.230 | 0.207 | 0.092 |
| NOJC157M002#WJ | C | 150 | 2.5 | 7.5 | 6 | 0.4 | 1 | 0.574 | 0.517 | 0.230 | 0.230 | 0.207 | 0.092 |
| NOJC227M002#WJ | C | 220 | 2.5 | 11.0 | 8 | 0.4 | 1 | 0.574 | 0.517 | 0.230 | 0.230 | 0.207 | 0.092 |
| NOJC337M002#WJ | C | 330 | 2.5 | 16.5 | 10 | 0.3 | 1 | 0.663 | 0.597 | 0.265 | 0.199 | 0.179 | 0.080 |
| NOJD337M002#WJ | D | 330 | 2.5 | 16.5 | 10 | 0.3 | 3 | 0.775 | 0.697 | 0.310 | 0.232 | 0.209 | 0.093 |
| NOJD477M002#WJ | D | 470 | 2.5 | 23.5 | 10 | 0.3 | 3 | 0.775 | 0.697 | 0.310 | 0.232 | 0.209 | 0.093 |
| NOJE477M002#WJ | E | 470 | 2.5 | 23.5 | 10 | 0.3 | 3 | 0.812 | 0.731 | 0.325 | 0.244 | 0.219 | 0.097 |
| NOJE687M002#WJ | E | 680 | 2.5 | 34.0 | 12 | 0.3 | 3 | 0.812 | 0.731 | 0.325 | 0.244 | 0.219 | 0.097 |
| NOJV108M002#WJ | V | 1000 | 2.5 | 50.0 | 18 | 0.3 | 3 | 1.000 | 0.900 | 0.400 | 0.300 | 0.270 | 0.120 |
| 4 Volt @ 85°C (2.7 Volt @ 105°C) | | | | | | | | | | | | | |
| NOJA156M004#WJ | A | 15 | 4 | 1.2 | 6 | 2 | 1 | 0.212 | 0.191 | 0.085 | 0.424 | 0.382 | 0.170 |
| NOJA226M004#WJ | A | 22 | 4 | 1.8 | 6 | 1.9 | 1 | 0.218 | 0.196 | 0.087 | 0.414 | 0.372 | 0.165 |
| NOJB226M004#WJ | B | 22 | 4 | 1.8 | 6 | 1.9 | 1 | 0.232 | 0.209 | 0.093 | 0.440 | 0.396 | 0.176 |
| NOJA336M004#WJ | A | 33 | 4 | 2.6 | 10 | 1.7 | 1 | 0.230 | 0.207 | 0.092 | 0.391 | 0.352 | 0.156 |
| NOJB336M004#WJ | B | 33 | 4 | 2.6 | 6 | 1.7 | 1 | 0.245 | 0.220 | 0.098 | 0.416 | 0.375 | 0.167 |
| NOJA476M004#WJ | A | 47 | 4 | 3.8 | 18 | 2.2 | 1 | 0.202 | 0.182 | 0.081 | 0.445 | 0.400 | 0.178 |
| NOJB476M004#WJ | B | 47 | 4 | 3.8 | 6 | 1.6 | 1 | 0.252 | 0.227 | 0.101 | 0.404 | 0.364 | 0.162 |
| NOJC476M004#WJ | C | 47 | 4 | 3.8 | 6 | 0.5 | 1 | 0.514 | 0.462 | 0.206 | 0.257 | 0.231 | 0.103 |
| NOJB686M004#WJ | B | 68 | 4 | 5.4 | 6 | 1.5 | 1 | 0.261 | 0.235 | 0.104 | 0.391 | 0.352 | 0.156 |
| NOJC686M004#WJ | C | 68 | 4 | 5.4 | 6 | 0.5 | 1 | 0.514 | 0.462 | 0.206 | 0.257 | 0.231 | 0.103 |
| NOJB107M004#WJ | B | 100 | 4 | 8.0 | 16 | 1.4 | 1 | 0.270 | 0.243 | 0.108 | 0.378 | 0.340 | 0.151 |
| NOJB107M004#WB | B | 100 | 4 | 8.0 | 16 | 0.25 | 1 | 0.639 | 0.575 | 0.255 | 0.160 | 0.144 | 0.064 |
| NOJC107M004#WJ | C | 100 | 4 | 8.0 | 6 | 0.4 | 1 | 0.574 | 0.517 | 0.230 | 0.230 | 0.207 | 0.092 |
| NOJC157M004#WJ | C | 150 | 4 | 12.0 | 6 | 0.4 | 1 | 0.574 | 0.517 | 0.230 | 0.230 | 0.207 | 0.092 |
| NOJD157M004#WJ | D | 150 | 4 | 12.0 | 6 | 0.3 | 3 | 0.775 | 0.697 | 0.310 | 0.232 | 0.209 | 0.093 |
| NOJC227M004#WJ | C | 220 | 4 | 17.6 | 8 | 0.4 | 1 | 0.574 | 0.517 | 0.230 | 0.230 | 0.207 | 0.092 |
| NOJD227M004#WJ | D | 220 | 4 | 17.6 | 8 | 0.4 | 3 | 0.671 | 0.604 | 0.268 | 0.268 | 0.241 | 0.107 |
| NOJD337M004#WJ | D | 330 | 4 | 26.4 | 8 | 0.3 | 3 | 0.775 | 0.697 | 0.310 | 0.232 | 0.209 | 0.093 |
| NOJD477M004#WJ | D | 470 | 4 | 37.6 | 12 | 0.3 | 3 | 0.775 | 0.697 | 0.310 | 0.232 | 0.209 | 0.093 |
| NOJE477M004#WJ | E | 470 | 4 | 37.6 | 12 | 0.3 | 3 | 0.812 | 0.731 | 0.325 | 0.244 | 0.219 | 0.097 |
| NOJE687M004#WJ | E | 680 | 4 | 54.4 | 14 | 0.3 | 3 | 0.812 | 0.731 | 0.325 | 0.244 | 0.219 | 0.097 |
| NOJV687M004#WJ | V | 680 | 4 | 54.4 | 14 | 0.3 | 3 | 1.000 | 0.900 | 0.400 | 0.300 | 0.270 | 0.120 |
| NOJV108M004#WJ | V | 1000 | 4 | 80.0 | 18 | 0.3 | 3 | 1.000 | 0.900 | 0.400 | 0.300 | 0.270 | 0.120 |
| 6.3 Volt @ 85°C (4 Volt @ 105°C) | | | | | | | | | | | | | |
| NOJA475M006#WJ | A | 4.7 | 6.3 | 1.1 | 6 | 3.2 | 1 | 0.168 | 0.151 | 0.067 | 0.537 | 0.483 | 0.215 |
| NOJA685M006#WJ | A | 6.8 | 6.3 | 1.1 | 6 | 2.6 | 1 | 0.186 | 0.167 | 0.074 | 0.484 | 0.435 | 0.193 |
| NOJA106M006#WJ | A | 10 | 6.3 | 1.2 | 6 | 2.2 | 1 | 0.202 | 0.182 | 0.081 | 0.445 | 0.400 | 0.178 |
| NOJB156M006#WJ | B | 15 | 6.3 | 1.8 | 6 | 2 | 1 | 0.226 | 0.203 | 0.090 | 0.452 | 0.406 | 0.181 |
| NOJA156M006#WJ | A | 15 | 6.3 | 1.8 | 8 | 2 | 1 | 0.212 | 0.191 | 0.085 | 0.424 | 0.382 | 0.170 |
| NOJB226M006#WJ | B | 22 | 6.3 | 2.6 | 6 | 1.9 | 1 | 0.232 | 0.209 | 0.093 | 0.440 | 0.396 | 0.176 |
| NOJA226M006#WJ | A | 22 | 6.3 | 2.6 | 8 | 1.8 | 1 | 0.224 | 0.201 | 0.089 | 0.402 | 0.362 | 0.161 |
| NOJB336M006#WJ | B | 33 | 6.3 | 4.0 | 6 | 1.7 | 1 | 0.245 | 0.220 | 0.098 | 0.416 | 0.375 | 0.167 |

Moisture Sensitivity Level (MSL) is defined according to J-STD-020.

All technical data relates to an ambient temperature of +25°C. Capacitance and DF are measured at 120Hz, 0.5V RMS with a maximum DC bias of 2.2 volts. DCL is measured at rated voltage after 5 minutes.

For typical weight and composition see page 123.

NOTE: AVX reserves the right to supply a higher voltage rating or tighter tolerance part in the same case size, to the same reliability standards.

OxiCap® NOJ Series



Niobium Oxide Capacitor

RATINGS & PART NUMBER REFERENCE

| AVX Part No. | Case Size | Capacitance (µF) | Rated Voltage (V) | DCL (µA) Max. | DF % Max. | ESR Max. (Ω) @100kHz | MSL | 100kHz RMS Current (A) | | | 100kHz RMS Voltage (V) | | |
|---|-----------|------------------|-------------------|---------------|-----------|----------------------|-----|------------------------|-------|-------|------------------------|-------|-------|
| | | | | | | | | 25°C | 85°C | 105°C | 25°C | 85°C | 105°C |
| 6.3 Volt @ 85°C (4 Volt @ 105°C) | | | | | | | | | | | | | |
| NOJB336M006#WB | B | 33 | 6.3 | 4.0 | 6 | 0.7 | 1 | 0.382 | 0.344 | 0.153 | 0.267 | 0.240 | 0.170 |
| NOJC336M006#WJ | C | 33 | 6.3 | 4.0 | 6 | 0.5 | 1 | 0.514 | 0.462 | 0.206 | 0.257 | 0.231 | 0.103 |
| NOJB476M006#WJ | B | 47 | 6.3 | 5.6 | 6 | 1.6 | 1 | 0.252 | 0.227 | 0.101 | 0.404 | 0.364 | 0.162 |
| NOJC476M006#WJ | C | 47 | 6.3 | 5.7 | 6 | 0.5 | 1 | 0.514 | 0.462 | 0.206 | 0.257 | 0.231 | 0.103 |
| NOJB686M006#WJ | B | 68 | 6.3 | 8.2 | 20 | 1.5 | 1 | 0.261 | 0.235 | 0.104 | 0.391 | 0.352 | 0.156 |
| NOJC686M006#WJ | C | 68 | 6.3 | 8.2 | 6 | 0.5 | 1 | 0.514 | 0.462 | 0.206 | 0.257 | 0.231 | 0.103 |
| NOJB107M006#WJ | B | 100 | 6.3 | 60.0 | 20 | 1.7 | 1 | 0.245 | 0.220 | 0.098 | 0.416 | 0.375 | 0.167 |
| NOJB107M006#WB | B | 100 | 6.3 | 60.0 | 20 | 0.4 | 1 | 0.505 | 0.454 | 0.202 | 0.202 | 0.182 | 0.081 |
| NOJC107M006#WJ | C | 100 | 6.3 | 12.0 | 8 | 0.4 | 1 | 0.574 | 0.517 | 0.230 | 0.230 | 0.207 | 0.092 |
| NOJD107M006#WJ | D | 100 | 6.3 | 12.0 | 6 | 0.4 | 3 | 0.671 | 0.604 | 0.268 | 0.268 | 0.241 | 0.107 |
| NOJC157M006#WJ | C | 150 | 6.3 | 18.0 | 6 | 0.4 | 1 | 0.574 | 0.517 | 0.230 | 0.230 | 0.207 | 0.092 |
| NOJD157M006#WJ | D | 150 | 6.3 | 18.0 | 6 | 0.4 | 3 | 0.671 | 0.604 | 0.268 | 0.268 | 0.241 | 0.107 |
| NOJC227M006#WJ | C | 220 | 6.3 | 26.4 | 14 | 0.4 | 1 | 0.574 | 0.517 | 0.230 | 0.230 | 0.207 | 0.092 |
| NOJD227M006#WJ | D | 220 | 6.3 | 26.4 | 8 | 0.4 | 3 | 0.671 | 0.604 | 0.268 | 0.268 | 0.241 | 0.107 |
| NOJE227M006#WJ | E | 220 | 6.3 | 26.4 | 12 | 0.4 | 3 | 0.704 | 0.633 | 0.281 | 0.281 | 0.253 | 0.113 |
| NOJD337M006#WJ | D | 330 | 6.3 | 39.6 | 10 | 0.3 | 3 | 0.775 | 0.697 | 0.310 | 0.232 | 0.209 | 0.093 |
| NOJE337M006#WJ | E | 330 | 6.3 | 39.6 | 12 | 0.3 | 3 | 0.812 | 0.731 | 0.325 | 0.244 | 0.219 | 0.097 |
| NOJE477M006#WJ | E | 470 | 6.3 | 56.4 | 16 | 0.3 | 3 | 0.812 | 0.731 | 0.325 | 0.244 | 0.219 | 0.097 |
| NOJV477M006#WJ | V | 470 | 6.3 | 56.4 | 12 | 0.3 | 3 | 1.000 | 0.900 | 0.400 | 0.300 | 0.270 | 0.120 |
| 10 Volt @ 85°C (7 Volt @ 105°C) | | | | | | | | | | | | | |
| NOJA475M010#WJ | A | 4.7 | 10 | 1.0 | 6 | 3.1 | 1 | 0.170 | 0.153 | 0.068 | 0.528 | 0.475 | 0.211 |
| NOJA685M010#WJ | A | 6.8 | 10 | 1.4 | 6 | 2.6 | 1 | 0.186 | 0.167 | 0.074 | 0.484 | 0.435 | 0.193 |
| NOJA106M010#WJ | A | 10 | 10 | 2.0 | 6 | 2.2 | 1 | 0.202 | 0.182 | 0.081 | 0.445 | 0.400 | 0.178 |
| NOJB106M010#WJ | B | 10 | 10 | 2.0 | 6 | 2.2 | 1 | 0.215 | 0.194 | 0.086 | 0.474 | 0.426 | 0.189 |
| NOJA156M010#WJ | A | 15 | 10 | 3.0 | 6 | 2 | 1 | 0.212 | 0.191 | 0.085 | 0.424 | 0.382 | 0.170 |
| NOJB156M010#WJ | B | 15 | 10 | 3.0 | 6 | 2 | 1 | 0.226 | 0.203 | 0.090 | 0.452 | 0.406 | 0.181 |
| NOJB226M010#WJ | B | 22 | 10 | 4.4 | 6 | 1.8 | 1 | 0.238 | 0.214 | 0.095 | 0.428 | 0.386 | 0.171 |
| NOJB226M010#WB | B | 22 | 10 | 4.4 | 6 | 0.7 | 1 | 0.382 | 0.344 | 0.153 | 0.267 | 0.240 | 0.107 |
| NOJC226M010#WJ | C | 22 | 10 | 4.4 | 6 | 0.5 | 1 | 0.514 | 0.462 | 0.206 | 0.257 | 0.231 | 0.103 |
| NOJC336M010#WJ | C | 33 | 10 | 6.6 | 6 | 0.5 | 1 | 0.514 | 0.462 | 0.206 | 0.257 | 0.231 | 0.103 |
| NOJC476M010#WJ | C | 47 | 10 | 9.4 | 6 | 0.4 | 1 | 0.574 | 0.517 | 0.230 | 0.230 | 0.207 | 0.092 |
| NOJC686M010#WJ | C | 68 | 10 | 13.6 | 12 | 0.5 | 1 | 0.514 | 0.462 | 0.206 | 0.257 | 0.231 | 0.103 |
| NOJD107M010#WJ | D | 100 | 10 | 20.0 | 12 | 0.4 | 3 | 0.671 | 0.604 | 0.268 | 0.268 | 0.241 | 0.107 |
| NOJD107M010#WB | D | 100 | 10 | 20.0 | 12 | 0.15 | 3 | 1.095 | 0.986 | 0.438 | 0.164 | 0.148 | 0.066 |
| NOJV227M010#WJ | V | 220 | 10 | 44.0 | 12 | 0.4 | 3 | 0.866 | 0.779 | 0.346 | 0.364 | 0.312 | 0.139 |

Moisture Sensitivity Level (MSL) is defined according to J-STD-020.

All technical data relates to an ambient temperature of +25°C. Capacitance and DF are measured at 120Hz, 0.5V RMS with a maximum DC bias of 2.2 volts. DCL is measured at rated voltage after 5 minutes.

The EIA & CECC standards for low ESR Solid Tantalum Capacitors allow an ESR movement to 1.25 times catalogue limit post mounting.

For typical weight and composition see page 123.

NOTE: AVX reserves the right to supply a higher voltage rating or tighter tolerance part in the same case size, to the same reliability standards.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9