



## Main

|                                        |                                                                                                                                                    |
|----------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| Range of product                       | Preventa Safety detection                                                                                                                          |
| Product or component type              | Safety switch                                                                                                                                      |
| Component name                         | XCSLF                                                                                                                                              |
| Design                                 | Slim                                                                                                                                               |
| Material                               | Metal                                                                                                                                              |
| Head type                              | Key operated turret head                                                                                                                           |
| Contacts type and composition          | 2 NC + 1 NO                                                                                                                                        |
| Contact operation                      | Slow-break, break before make                                                                                                                      |
| Solenoid contacts type and composition | 2 NC + 1 NO (slow-break, break before make)                                                                                                        |
| Cable entry                            | 3 entries tapped M20 x 1.5                                                                                                                         |
| Electromagnet interlocking             | Locking on de-energisation and unlocking on energisation of solenoid                                                                               |
| [Us] rated supply voltage              | 230 V (- 15...10 %)                                                                                                                                |
| Cable outer diameter                   | 0.28...0.51 in (7...13 mm)                                                                                                                         |
| Electrical connection                  | Spring terminal, 1 x 1.5 mm <sup>2</sup> flexible or solid cable<br>Spring terminal, 2 x 0.5 mm <sup>2</sup> flexible cables with 13 mm bared ends |
| Number of poles                        | 3                                                                                                                                                  |
| Locking options description            | With interlocking, locking by solenoid                                                                                                             |
| Local signalling                       | 1 LED orange (actuator withdrawn)<br>1 LED green (actuator inserted and locked)                                                                    |
| Signalling circuit voltage             | 230 V                                                                                                                                              |

## Complementary

|                                              |                                                                                                                                                                   |
|----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Positive opening                             | With NC contact                                                                                                                                                   |
| Supply voltage type                          | AC/DC                                                                                                                                                             |
| Supply frequency                             | 50/60 Hz                                                                                                                                                          |
| Load factor                                  | 1                                                                                                                                                                 |
| Signalling circuit type                      | AC                                                                                                                                                                |
| Mechanical durability                        | 1000000 cycles                                                                                                                                                    |
| Minimum actuation speed                      | 0.03 ft/s (0.01 m/s)                                                                                                                                              |
| Maximum actuation speed                      | 1.64 ft/s (0.5 m/s)                                                                                                                                               |
| [Ie] rated operational current               | 0.55 A at 24 V utilisation category DC-13, R300 conforming to EN/IEC 60947-5-1<br>0.75 A at 240 V utilisation category AC-15, C300 conforming to EN/IEC 60947-5-1 |
| [Ithe] conventional enclosed thermal current | 4 A                                                                                                                                                               |
| Maximum load current                         | <= 15 A                                                                                                                                                           |
| [Ui] rated insulation voltage                | 250 V (degree of pollution: 3) conforming to EN/IEC 60947-1<br>300 V conforming to UL 508<br>300 V conforming to CSA C22.2 No 14                                  |
| [Uimp] rated impulse withstand voltage       | 4 kV conforming to EN/IEC 60947-5-1                                                                                                                               |
| Minimum switching current                    | 10 mA at 20 °C                                                                                                                                                    |
| Minimum switching voltage                    | 17 V                                                                                                                                                              |
| Short-circuit protection                     | 4 A cartridge fuse type gG (gl)<br>6 A type fast blow                                                                                                             |
| Actuator forcible withdrawal rtc             | 3000 N                                                                                                                                                            |
| Actuator force for extraction                | >= 20 N                                                                                                                                                           |
| Resistance to mechanical impact              | 9.6 J against the partition<br>6.4 J without partition                                                                                                            |
| Operating rate                               | 10 cyc/mn for maximum durability                                                                                                                                  |
| Safety level                                 | Can reach category 4 with the appropriate monitoring system and correctly wired                                                                                   |

conforming to EN/ISO 13849-1  
 Can reach PL = e with the appropriate monitoring system and correctly wired  
 conforming to EN/ISO 13849-1  
 Can reach SIL 3 conforming to EN/IEC 61508

|                         |                                                                                                |
|-------------------------|------------------------------------------------------------------------------------------------|
| Safety reliability data | B10d = 5500000 (value given for a life time of 20 years limited by mechanical or contact wear) |
| Body material           | Zamak                                                                                          |
| Head material           | Zamak                                                                                          |
| Depth                   | 2.01 in (51 mm)                                                                                |
| Height                  | 8.07 in (205 mm)                                                                               |
| Width                   | 1.73 in (44 mm)                                                                                |
| Product weight          | 2.43 lb(US) (1.1 kg)                                                                           |

## Environment

|                                       |                                                                                                                        |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| standards                             | EN 1088/ISO 14119<br>EN/IEC 60204-1<br>EN/IEC 60947-5-1<br>EN/IEC 62061<br>EN/ISO 13849-1<br>UL 508<br>CSA C22.2 No 14 |
| product certifications                | CSA<br>TÜV<br>UL                                                                                                       |
| protective treatment                  | TC                                                                                                                     |
| ambient air temperature for operation | -13...140 °F (-25...60 °C)                                                                                             |
| ambient air temperature for storage   | -40...158 °F (-40...70 °C)                                                                                             |
| vibration resistance                  | 5 gn (f = 10...500 Hz) conforming to IEC 60068-2-6                                                                     |
| shock resistance                      | 10 gn 11 ms conforming to IEC 60068-2-27                                                                               |
| electrical shock protection class     | Class I conforming to EN/IEC 61140                                                                                     |
| IP degree of protection               | IP66 conforming to EN/IEC 60529 and EN/IEC 60947-5-1<br>IP67                                                           |

## Offer Sustainability

|                                                                                                                            |                                                                                                                            |
|----------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| Not Green Premium product                                                                                                  | Not Green Premium product                                                                                                  |
| Compliant - since 1045 - Schneider Electric declaration of conformity                                                      | Compliant - since 1045 - Schneider Electric declaration of conformity                                                      |
| Reference not containing SVHC above the threshold                                                                          | Reference not containing SVHC above the threshold                                                                          |
| Available                                                                                                                  | Available                                                                                                                  |
| WARNING: This product can expose you to chemicals including:                                                               | WARNING: This product can expose you to chemicals including:                                                               |
| Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and                                | Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and                                |
| Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. | Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. |
| For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                              | For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                              |

## Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9