# **Detailed Specifications & Technical Data**

### **ENGLISH MEASUREMENT VERSION**



# 8115 Multi-Conductor - Low Capacitance Computer Cable for EIA RS-232/422



For more Information please call

1-800-Belden1




### **General Description:**

24 AWG stranded (7x32) TC conductors, Datalene® insulation, twisted pairs, overall Beldfoil® (100% coverage) + TC braid shield (65% coverage), 24 AWG stranded TC drain wire, PVC jacket.

# **Physical Characteristics (Overall)**

# Conductor

AWG:



**Total Number of Conductors:** 

30

#### Insulation

### Insulation Material:

Insulation Trade Name	Insulation Material	Wall Thickness (in.)	
Datalene®	FPE - Foam Polyethylene	0.015	

#### **Outer Shield**

#### Outer Shield Material:

Layer # Outer Shield Trade Name		Type	Outer Shield Material	Coverage (%)
1	Beldfoil®	Таре	Aluminum Foil-Polyester Tape w/Shorting Fold	100
2		Braid	TC - Tinned Copper	65

### Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire Conductor Material
24	7x32	TC - Tinned Copper

### **Outer Jacket**

### Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (in.)
PVC - Polyvinyl Chloride	0.040

### **Overall Cable**

**Overall Nominal Diameter:** 

0.477 in.

### Pair

### Pair Color Code Chart:

Number	Color
1	White/Blue & Blue/White
2	White/Orange & Orange/White
3	White/Green & Green/White
4	White/Brown & Brown/White
5	White/Gray & Gray/White
6	Red/Blue & Blue/Red
7	Red/Orange & Orange/Red
8	Red/Green & Green/Red
9	Red/Brown & Brown/Red
10	Red/Gray & Gray/Red
11	Black/Blue & Blue/Black
12	Black/Orange & Orange/Black
13	Black/Green & Green/Black
14	Black/Brown & Brown/Black
15	Black/Gray & Gray/Black

# **Mechanical Characteristics (Overall)**

Operating Temperature Range:	-30°C To +80°C	
UL Temperature Rating:	80°C (UL AWM Style 2919)	
Bulk Cable Weight:	107 lbs/1000 ft.	
Max. Recommended Pulling Tension:	170.500 lbs.	

Page 1 of 3 09-11-2017

# **Detailed Specifications & Technical Data**

### **ENGLISH MEASUREMENT VERSION**



# 8115 Multi-Conductor - Low Capacitance Computer Cable for EIA RS-232/422

Min. Bend Radius/Minor Axis: Applicable Specifications and Agency Compliance (Overall) **Applicable Standards & Environmental Programs** NEC/(UL) Specification: CEC/C(UL) Specification: UL Style 2919 (30 V 80°C) **AWM Specification:** EU Directive 2011/65/EU (ROHS II): EU CE Mark: Yes EU Directive 2000/53/EC (ELV): Yes EU Directive 2002/95/EC (RoHS): Yes EU RoHS Compliance Date (mm/dd/yyyy): 01/01/2004 EU Directive 2002/96/EC (WEEE): Yes EU Directive 2003/11/EC (BFR): Yes CA Prop 65 (CJ for Wire & Cable): MII Order #39 (China RoHS): Yes Flame Test **UL Flame Test:** UL1685 UL Loading Plenum/Non-Plenum Plenum (Y/N): No

### **Electrical Characteristics (Overall)**

Nom. Characteristic Impedance:

Impedance (Ohm) 100

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/ft) 12.5

Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/ft)
22

Nominal Velocity of Propagation:

**VP (%)** 78

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft) 24

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft) 2.6

Max. Operating Voltage - UL:

 Voltage
 Description

 30 V RMS
 UL AWM Style 2919

 300 V RMS
 CM

Max. Recommended Current:

Current
.88 Amps per conductor @ 25°C

## Notes (Overall)

Notes: Datalene® insulation features include low dielectric constant and a dissipation factor for high-speed, low-distortion data handling. Physical properties include good crush resistance and light weight.

# **Put Ups and Colors:**

Item #	Putup	Ship Weight	Color	Notes	Item Desc
8115 0601000	1,000 FT	114.000 LB	CHROME	С	15 PR #24 FHDPE SH PVC
8115 060500	500 FT	62.500 LB	CHROME	C	15 PR #24 FHDPE SH PVC

### Notes:

C = CRATE REEL PUT-UP.

Page 2 of 3 09-11-2017

# **Detailed Specifications & Technical Data**

### **ENGLISH MEASUREMENT VERSION**



# 8115 Multi-Conductor - Low Capacitance Computer Cable for EIA RS-232/422

Revision Number: 3 Revision Date: 08-31-2012

© 2017 Belden, Inc All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product

product. ´ Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).

Page 3 of 3

# **ПОСТАВКА** ЭЛЕКТРОННЫХ КОМПОНЕНТОВ

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001 Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

# Данный компонент на территории Российской Федерации Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

# http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

# Офис по работе с юридическими лицами:

105318, г. Москва, ул. Щербаковская д. 3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru moschip.ru\_6 moschip.ru\_4 moschip.ru\_9