



# BAS40 THRU BAS70

## Surface Mount Schottky Barrier Diode 200 mWatt

### Features

- SOT-23 Package For surface mount application
- Protects from line to  $V_{CC}$  and line to ground
- Low forward voltage and reverse recovery characteristics
- Bidirectional-low-forward available with "-04" suffix (Figure 2)
- Tape & Reel EIA Standard 481.

### Mechanical Data

- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Halogen free available upon request by adding suffix "-HF"
- Mounting Position: Any
- Weight: .008 grams (approx.)

### MAXIMUM RATINGS


- Operating Temperature:  $-55^{\circ}\text{C}$  to  $+125^{\circ}\text{C}$
- Storage Temperature:  $-55^{\circ}\text{C}$  to  $+150^{\circ}\text{C}$
- Power Dissipation: 200 mWatts @  $T_{amb}=25^{\circ}\text{C}$
- Forward Continuous Current: BAS40  $I_{FM}=200\text{mA}$  @  $T_a=25^{\circ}\text{C}$   
BAS70  $I_{FM}=70\text{mA}$  @  $T_a=25^{\circ}\text{C}$
- Surge Forward Current:  $600\text{mA}$  @  $t_p<1\text{s}$ ,  $T_{amb}=25^{\circ}\text{C}$

### DESCRIPTION

Various configurations of Schottky barrier's diodes in SOT-23 package are provided for general-purpose use in high-speed switching, mixers and detector applications. They may also be used for signal integrity and counteract the transmission-line effects with (PC) board traces by clamping over/and undershoot from signal reflections with the schottky-low-threshold voltages.


This type of termination also does not depend on matching the transmission line characteristic impedance, making it particularly useful where line impedance is unknown or a variable. This method of termination can control distortions of clock, data, address, and control lines as well as provides a stabilizing effect on signal jitter. It can also significantly reduce power consumption compared to standard resistor-based termination methods.

### SOT-23



| DIM | INCHES |       | MM   |      | NOTE |
|-----|--------|-------|------|------|------|
|     | MIN    | MAX   | MIN  | MAX  |      |
| A   | .110   | .120  | 2.80 | 3.04 |      |
| B   | .083   | .104  | 2.10 | 2.64 |      |
| C   | .047   | .055  | 1.20 | 1.40 |      |
| D   | .035   | .041  | .89  | 1.03 |      |
| E   | .070   | .081  | 1.78 | 2.05 |      |
| F   | .018   | .024  | .45  | .60  |      |
| G   | .0005  | .0039 | .013 | .100 |      |
| H   | .035   | .044  | .89  | 1.12 |      |
| J   | .003   | .007  | .085 | .180 |      |
| K   | .015   | .020  | .37  | .51  |      |


### Suggested Solder Pad Layout







# BAS40 and BAS70

## ELECTRICAL CHARACTERISTICS PER DIODE @ 25°C Unless otherwise specified

| DEVICE TYPE | DEVICE MARKING | FIGURE | Repetitive Peak Reverse Voltage | Reverse Breakdown Voltage Tested with 10µA Pulse | Leakage Current Pulse test tp < 300µs @ |     | Forward Voltage Pulse Test tp < 300µs at I <sub>F</sub> = 1 mA at I <sub>F</sub> = 40 mA |                      |                      | Reverse Recovery Time from I <sub>F</sub> = 10 mA through I <sub>R</sub> =10mA to I <sub>R</sub> =1mA | Thermal Resistance Junction to Ambient Air | Capacitance At V <sub>R</sub> = 0V F = 1 MHz C <sub>tot</sub> |
|-------------|----------------|--------|---------------------------------|--------------------------------------------------|-----------------------------------------|-----|------------------------------------------------------------------------------------------|----------------------|----------------------|-------------------------------------------------------------------------------------------------------|--------------------------------------------|---------------------------------------------------------------|
|             |                |        | V <sub>RRM</sub> (VOLTS)        | V <sub>(BR)/R</sub> (VOLTS)                      | I <sub>R</sub> (nA)                     |     | V <sub>F</sub> (mV)                                                                      |                      |                      | t <sub>rr</sub> (ns)                                                                                  | R <sub>thJA</sub> (K/W)                    | pF                                                            |
|             |                |        | TYP                             | MIN                                              | TYP                                     | MAX | I <sub>F</sub> =1mA                                                                      | I <sub>F</sub> =15mA | I <sub>F</sub> =40mA | MAX                                                                                                   | MAX                                        | MAX                                                           |
| BAS40       | 43             | 1      | 40                              | 40                                               | 10                                      | 200 | 380                                                                                      |                      | 1000                 | 5                                                                                                     | 430                                        | 5                                                             |
| BAS40-04    | 44             | 2      | 40                              | 40                                               | 10                                      | 200 | 380                                                                                      |                      | 1000                 | 5                                                                                                     | 430                                        | 5                                                             |
| BAS40-05    | 45             | 3      | 40                              | 40                                               | 10                                      | 200 | 380                                                                                      |                      | 1000                 | 5                                                                                                     | 430                                        | 5                                                             |
| BAS40-06    | 46             | 4      | 40                              | 40                                               | 10                                      | 200 | 380                                                                                      |                      | 1000                 | 5                                                                                                     | 430                                        | 5                                                             |
| BAS70       | 73             | 1      | 70                              | 70                                               | 10                                      | 200 | 410                                                                                      | 1000                 |                      | 5                                                                                                     | 430                                        | 2                                                             |
| BAS70-04    | 74             | 2      | 70                              | 70                                               | 10                                      | 200 | 410                                                                                      | 1000                 |                      | 5                                                                                                     | 430                                        | 2                                                             |
| BAS70-05    | 75             | 3      | 70                              | 70                                               | 10                                      | 200 | 410                                                                                      | 1000                 |                      | 5                                                                                                     | 430                                        | 2                                                             |
| BAS70-06    | 76             | 4      | 70                              | 70                                               | 10                                      | 200 | 410                                                                                      | 1000                 |                      | 5                                                                                                     | 430                                        | 2                                                             |



## Typical Characteristics



## Ordering Information :

| Device         | Packing               |
|----------------|-----------------------|
| Part Number-TP | Tape&Reel: 3Kpcs/Reel |

Note : Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

### \*\*\*IMPORTANT NOTICE\*\*\*

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp .** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp .** and all the companies whose products are represented on our website, harmless against all damages.

### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9