

SCR/SCR and SCR/Diode (MAGN-A-PAK Power Modules), 230 A



MAGN-A-PAK

FEATURES

- High voltage
- Electrically isolated base plate
- 3500 V_{RMS} isolating voltage
- Industrial standard package
- Simplified mechanical designs, rapid assembly
- High surge capability
- Large creepage distances
- UL approved file E78996
- Designed and qualified for industrial level
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912


**RoHS
COMPLIANT**

PRODUCT SUMMARY

| | |
|-------------|-------------------------------|
| $I_{T(AV)}$ | 230 A |
| Type | Modules - Thyristor, Standard |
| Package | MAGN-A-PAK |
| Circuit | Two SCRs doubler circuit |

DESCRIPTION

This new VSK series of MAGN-A-PAK modules uses high voltage power thyristor/thyristor and thyristor/diode in seven basic configurations. The semiconductors are electrically isolated from the metal base, allowing common heatsinks and compact assemblies to be built. They can be interconnected to form single phase or three phase bridges or as AC-switches when modules are connected in anti-parallel mode. These modules are intended for general purpose applications such as battery chargers, welders, motor drives, UPS, etc.

MAJOR RATINGS AND CHARACTERISTICS

| SYMBOL | CHARACTERISTICS | VALUES | UNITS |
|-------------------|-----------------|-------------|--------------------|
| $I_{T(AV)}$ | 85 °C | 230 | A |
| $I_{T(RMS)}$ | | 510 | |
| I_{TSM} | 50 Hz | 7500 | |
| | 60 Hz | 7850 | |
| I^2t | 50 Hz | 280 | kA ² s |
| | 60 Hz | 260 | |
| $I^2\sqrt{t}$ | | 280 | kA ² √s |
| V_{DRM}/V_{RRM} | | 800 to 2000 | V |
| T_J | Range | -40 to 130 | °C |

ELECTRICAL SPECIFICATIONS

VOLTAGE RATINGS

| TYPE NUMBER | VOLTAGE CODE | V_{RRM}/V_{DRM} , MAXIMUM REPETITIVE PEAK REVERSE AND OFF-STATE BLOCKING VOLTAGE V | V_{RSM} , MAXIMUM NON-REPETITIVE PEAK REVERSE VOLTAGE V | I_{RRM}/I_{DRM} AT 130 °C MAXIMUM mA |
|-------------|--------------|---|--|---|
| VS-VSK.230- | 08 | 800 | 900 | 50 |
| | 12 | 1200 | 1300 | |
| | 16 | 1600 | 1700 | |
| | 18 | 1800 | 1900 | |
| | 20 | 2000 | 2100 | |



| ON-STATE CONDUCTION | | | | | |
|--|---------------|--|-----------------------|--------|--------------------|
| PARAMETER | SYMBOL | TEST CONDITIONS | | VALUES | UNITS |
| Maximum average on-state current at case temperature | $I_{T(AV)}$ | 180° conduction, half sine wave | | 230 | A |
| | | | | 85 | °C |
| Maximum RMS on-state current | $I_{T(RMS)}$ | As AC switch | | 510 | |
| Maximum peak, one-cycle on-state non-repetitive, surge current | I_{TSM} | t = 10 ms | No voltage reappplied | 7500 | A |
| | | t = 8.3 ms | reappplied | 7850 | |
| | | t = 10 ms | 100 % V_{RRM} | 6300 | |
| | | t = 8.3 ms | reappplied | 6600 | |
| Maximum I^2t for fusing | I^2t | t = 10 ms | No voltage reappplied | 280 | kA ² s |
| | | t = 8.3 ms | reappplied | 256 | |
| | | t = 10 ms | 100 % V_{RRM} | 198 | |
| | | t = 8.3 ms | reappplied | 181 | |
| Maximum $I^2\sqrt{t}$ for fusing | $I^2\sqrt{t}$ | t = 0.1 ms to 10 ms, no voltage reappplied | | 2800 | kA ² √s |
| Low level value or threshold voltage | $V_{T(TO)1}$ | $(16.7\% \times \pi \times I_{T(AV)} < I < \pi \times I_{T(AV)})$, $T_J = T_J$ maximum | | 1.03 | V |
| High level value of threshold voltage | $V_{T(TO)2}$ | $(I > \pi \times I_{T(AV)})$, $T_J = T_J$ maximum | | 1.07 | |
| Low level value on-state slope resistance | r_{t1} | $(16.7\% \times \pi \times I_{T(AV)} < I < \pi \times I_{T(AV)})$, $T_J = T_J$ maximum | | 0.77 | mΩ |
| High level value on-state slope resistance | r_{t2} | $(I > \pi \times I_{T(AV)})$, $T_J = T_J$ maximum | | 0.73 | |
| Maximum on-state voltage drop | V_{TM} | $I_{TM} = \pi \times I_{T(AV)}$, $T_J = T_J$ maximum, 180° conduction, average power = $V_{T(TO)} \times I_{T(AV)} + r_f \times (I_{T(RMS)})^2$ | | 1.59 | V |
| Maximum holding current | I_H | Anode supply = 12 V, initial $I_T = 30$ A, $T_J = 25$ °C | | 500 | mA |
| Maximum latching current | I_L | Anode supply = 12 V, resistive load = 1 Ω, gate pulse: 10 V, 100 μs, $T_J = 25$ °C | | 1000 | |

| SWITCHING | | | | | |
|-----------------------|--------|--|--|-----------|-------|
| PARAMETER | SYMBOL | TEST CONDITIONS | | VALUES | UNITS |
| Typical delay time | t_d | $T_J = 25$ °C, gate current = 1 A $dI_g/dt = 1$ A/μs | | 1.0 | μs |
| Typical rise time | t_r | $V_d = 0.67\% V_{DRM}$ | | 2.0 | |
| Typical turn-off time | t_q | $I_{TM} = 300$ A; $dI/dt = 15$ A/μs; $T_J = T_J$ maximum; $V_R = 50$ V; $dV/dt = 20$ V/μs; gate 0 V, 100 Ω | | 50 to 150 | |

| BLOCKING | | | | | |
|--|-----------------------|---|--|--------|-------|
| PARAMETER | SYMBOL | TEST CONDITIONS | | VALUES | UNITS |
| Maximum peak reverse and off-state leakage current | I_{RRM} , I_{DRM} | $T_J = T_J$ maximum | | 50 | mA |
| RMS insulation voltage | V_{INS} | 50 Hz, circuit to base, all terminals shorted, 25 °C, 1 s | | 3000 | V |
| Critical rate of rise of off-state voltage | dV/dt | $T_J = T_J$ maximum, exponential to 67 % rated V_{DRM} | | 1000 | V/μs |

| TRIGGERING | | | | | |
|---|-------------|--|--|--------|-------|
| PARAMETER | SYMBOL | TEST CONDITIONS | | VALUES | UNITS |
| Maximum peak gate power | P_{GM} | $t_p \leq 5$ ms, $T_J = T_J$ maximum | | 10.0 | W |
| Maximum average gate power | $P_{G(AV)}$ | f = 50 Hz, $T_J = T_J$ maximum | | 2.0 | |
| Maximum peak gate current | + I_{GM} | $t_p \leq 5$ ms, $T_J = T_J$ maximum | | 3.0 | A |
| Maximum peak negative gate voltage | - V_{GT} | $t_p \leq 5$ ms, $T_J = T_J$ maximum | | 5.0 | V |
| Maximum required DC gate voltage to trigger | V_{GT} | $T_J = -40$ °C | Anode supply = 12 V, resistive load; $R_a = 1$ Ω | 4.0 | |
| | | $T_J = 25$ °C | | 3.0 | |
| | | $T_J = T_J$ maximum | | 2.0 | |
| Maximum required DC gate current to trigger | I_{GT} | $T_J = -40$ °C | Anode supply = 12 V, resistive load; $R_a = 1$ Ω | 350 | |
| | | $T_J = 25$ °C | | 200 | |
| | | $T_J = T_J$ maximum | | 100 | |
| Maximum gate voltage that will not trigger | V_{GD} | $T_J = T_J$ maximum, rated V_{DRM} applied | | 0.25 | V |
| Maximum gate current that will not trigger | I_{GD} | $T_J = T_J$ maximum, rated V_{DRM} applied | | 10.0 | mA |
| Maximum rate of rise of turned-on current | dI/dt | $T_J = T_J$ maximum, $I_{TM} = 400$ A, rated V_{DRM} applied | | 500 | A/μs |



| THERMAL AND MECHANICAL SPECIFICATIONS | | | | |
|---|-----------------|--|------------|-------|
| PARAMETER | SYMBOL | TEST CONDITIONS | VALUES | UNITS |
| Junction operating temperature range | T_J | | -40 to 130 | °C |
| Storage temperature range | T_{Stg} | | -40 to 150 | |
| Maximum thermal resistance, junction to case per junction | R_{thJC} | DC operation | 0.125 | K/W |
| Typical thermal resistance, case to heatsink per module | R_{thCS} | Mounting surface flat, smooth and greased | 0.02 | |
| Mounting torque $\pm 10\%$ | MAP to heatsink | A mounting compound is recommended and the torque should be rechecked after a period of about 3 h to allow for the spread of the compound. | 4 to 6 | Nm |
| | busbar to MAP | | | |
| Approximate weight | | | 500 | g |
| | | | 17.8 | oz. |
| Case style | | | MAGN-A-PAK | |

| ΔR CONDUCTION PER JUNCTION | | | | | | | | | | | |
|----------------------------|--|-------|-------|-------|-------|---|-------|-------|-------|-------|-------|
| DEVICES | SINUSOIDAL CONDUCTION AT T_J MAXIMUM | | | | | RECTANGULAR CONDUCTION AT T_J MAXIMUM | | | | | UNITS |
| | 180° | 120° | 90° | 60° | 30° | 180° | 120° | 90° | 60° | 30° | |
| VSK.230- | 0.009 | 0.010 | 0.010 | 0.020 | 0.032 | 0.007 | 0.011 | 0.015 | 0.020 | 0.033 | K/W |

Note

- Table shows the increment of thermal resistance R_{thJC} when devices operate at different conduction angles than DC




Fig. 1 - Current Ratings Characteristics




Fig. 2 - Current Ratings Characteristics




Fig. 3 - On-State Power Loss Characteristics




Fig. 5 - Maximum Non-Repetitive Surge Current




Fig. 4 - On-State Power Loss Characteristics




Fig. 6 - Maximum Non-Repetitive Surge Current




Fig. 7 - On-State Power Loss Characteristics




Fig. 8 - On-State Power Loss Characteristics




Fig. 9 - On-State Power Loss Characteristics




Fig. 10 - On-State Voltage Drop Characteristics




Fig. 11 - Reverse Recovery Charge Characteristics




Fig. 12 - Gate Characteristics




Fig. 13 - Thermal Impedance Z_{thJC} Characteristics

ORDERING INFORMATION TABLE






| | | | | | | |
|-------------|--------------|-----------|------------|----------|-----------|------------|
| Device code | VS-VS | KT | 230 | - | 20 | PbF |
| | ① | ② | ③ | ④ | ⑤ | |

- 1** - Vishay Semiconductors product
- 2** - Circuit configuration (see dimensions - link at the end of datasheet)
- 3** - Current rating
- 4** - Voltage code x 100 = V_{RRM} (see voltage ratings table)
- 5** -
 - None = standard production
 - PbF = lead (Pb)-free

Note

- To order the optional hardware go to www.vishay.com/doc?95172




| CIRCUIT CONFIGURATION | | |
|---|----------------------------|---|
| CIRCUIT DESCRIPTION | CIRCUIT CONFIGURATION CODE | CIRCUIT DRAWING |
| Two SCRs doubler circuit | KT | <p>VSKT...</p>  <p>Available 800 V: contact factory for different requirements</p> |
| SCR/diode doubler circuit, positive control | KH | <p>VSKH...</p>  <p>Available 800 V: contact factory for different requirements</p> |
| SCR/diode doubler circuit, negative control | KL | <p>VSKL...</p>  <p>Available 800 V: contact factory for different requirements</p> |
| Two SCRs common cathodes | KK | <p>VSKK...</p>  <p>Available 800 V: contact factory for different requirements</p> |
| Two SCRs common anodes | KV | <p>VSKV...</p>  <p>Available 800 V: contact factory for different requirements</p> |

| LINKS TO RELATED DOCUMENTS | |
|----------------------------|--|
| Dimensions | www.vishay.com/doc?95086 |

MAGN-A-PAK

DIMENSIONS in millimeters (inches)



Notes

- Dimensions are nominal
- Full engineering drawings are available on request
- UL identification number for gate and cathode wire: UL 1385
- UL identification number for package: UL 94 V-0



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9