


8		7	
THIS DRAWING IS UNPUBLISHED.		RELEASED FOR PUBLICATION	
© COPYRIGHT 2011		2011	
BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.			
ATLANTIC VERSION TERMINATOR INTERFACE ADAPTER	PART NUMBER	REVISION	DESCRIPTION
	2150030-1	B	FINE CRIMP HEIGHT ADJUST
	2150030-2	B	FINE CRIMP HEIGHT ADJUST
	2150030-5	B	FINE CRIMP HEIGHT ADJUST
	2150030-6	B	NON-CRIMP HEIGHT ADJUST
	2150030-7	B	FINE CRIMP HEIGHT ADJUST
	7-2150030-7	A	CRIMP TOOLING KIT

APPLICATOR DATA		
CRIMP	SIZE	TYPE
WIRE	2.30 mm [.091]	F
INSUL	3.30 mm [.130]	F
APPL INSTRUCTIONS 408-10390		

TERMINAL DATA: TE TERMINAL		TE CRIMP SPECIFICATION	
TERMINAL NAME: .250 FASTON RECEPTACLE			
WIRE STRIP LENGTH 4.40-6.40 mm [.173-.252 IN]		INSULATION DIAMETER RANGE Ø2.30-3.30 mm [.091-.130 IN]	
TERMINAL APPLICATION SPECIFICATION		114-2036	
TERMINALS APPLIED			
TE TERMINAL	TE TERMINAL	TE TERMINAL	TE TERMINAL
160389-3	42510-2	63609-3	140760-3
160389-4	42510-5	63609-4	140760-4
41772	63127-1	63693-1	140760-5
41772-1	63609-1	140760-1	
42510-1	63609-2	140760-2	

WIRE SIZE	CRIMP HEIGHT mm [INCH]	CRIMP HEIGHT REFERENCE SETTING
18 AWG or 0.75mm ²	1.42+/-0.05 [.056+/- .002]	6.0
(2) 22 AWG	1.37+/-0.05 [.054+/- .002]	6.5
20 AWG or 0.50mm ²	1.30+/-0.05 [.051+/- .002]	7.3
0.40mm ²	1.27+/-0.05 [.050+/- .002]	7.6
22 AWG or 0.30mm ²	1.24+/-0.05 [.049+/- .002]	8.0



- 1 RECOMMENDED SPARE PARTS
- 2 GREASE BEARING SURFACES LIGHTLY
3. LUBRICATE DAILY PER THE APPLICATOR INSTRUCTION SHEET SUPPLIED WITH THE APPLICATOR.
- 4 APPLICATOR SPECIFIC DATA TO BE ENTERED INTO BLANK MEMORY CHIP AT ASSEMBLY. SEE BELOW FOR PART NUMBER:
MECHANICAL FEED WITH "SMART APPLICATOR" CONVERSION: 8-2150030-4
PNEUMATIC FEED WITH "SMART APPLICATOR" CONVERSION: 8-2150030-4
SERVO FEED WITH "FINE CRIMP HEIGHT ADJUST": 8-2150030-5
SERVO FEED WITH "NON-CRIMP HEIGHT ADJUST": 8-2150030-6
5. ADJUSTMENT OF THE STRIPPER MAY BE REQUIRED WHEN MOVING THE APPLICATOR BETWEEN BENCH AND LEADMAKER APPLICATIONS.
- 6 APPLY PART NUMBER 1-23419-5 LOCTITE TO THREADS OF ITEM 50. 62 & 242. FOR -6 ONLY APPLY PART NUMBER 1-23419-5 LOCTITE TO THREADS OF ITEM 37. 50 & 242.
- 7 GREASE THREADS, GROOVE AND O-RING ON ITEMS 35 & 252.
- 8 MAGNET, ITEM 166 MUST BE ORIENTED CORRECTLY IN ORDER TO PROPERLY ACTUATE THE COUNTER.
- 9 CRIMP HEIGHT REFERENCE SETTING WAS THE SETTING USED WHEN THE APPLICATOR WAS QUALIFIED AT THE FACTORY. ADJUSTMENT MAY BE NECESSARY WHEN RUNNING APPLICATOR IN THE FIELD.
- 10 SPARE FEED CAM STORAGE LOCATION REFER TO INSTRUCTION SHEET FOR ADDITIONAL INFORMATION.
- 11 THE RECOMMENDED SET-UP FOR END FEED APPLICATORS IS POST-FEED WITH ITEM 2119653-1. THE APPLICATOR CAN BE CONFIGURED FOR PRE-FEED WITH ITEM 2119652-1 BUT MAY ENCOUNTER PROBLEMS WITH SOME APPLICATIONS. FEED ISSUES OR TERMINAL JAMMING MAY OCCUR IN THE PRE-FEED CONFIGURATION.
- 12 WHEN ASSEMBLING -6 NON-CRIMP HEIGHT ADJUST APPLICATOR USE SHIM PACK 2119957-2 TO ALIGN APPLICATOR'S MAXIMUM WIRE CRIMP HEIGHT AT NORMAL TERMINATOR SHUT HEIGHT

TERMINAL DATA: TE TERMINAL		TE CRIMP SPERIFICATION	
TERMINAL NAME: .250 FASTON RECEPTACLE			
WIRE STRIP LENGTH 4.40-6.40 mm [.173-.252 IN]		INSULATION DIAMETER RANGE Ø2.30-3.30 mm [.091-.130 IN]	
TERMINAL APPLICATION SPECIFICATION		114-20023	
TERMINALS APPLIED			
TE TERMINAL	TE TERMINAL	TE TERMINAL	TE TERMINAL
280000-6	280000-7	41771	41771-1

WIRE SIZE	CRIMP HEIGHT WIRE CRIMP UNITS	CRIMP HEIGHT REFERENCE SETTING
0.80mm ²	1.30+/-0.03 [.051+/- .001]	7.8
0.75mm ²	1.30+/-0.03 [.051+/- .001]	7.8
0.65mm ²	1.27+/-0.03 [.050+/- .001]	7.6
0.50mm ²	1.22+/-0.03 [.048+/- .001]	7.8
0.30mm ²	1.14+/-0.03 [.045+/- .001]	8.4

*WARNING
ON INSTALLATION, SET WIRE DISC, ITEM 40 TO LARGEST WIRE SIZE SETTING. USE OF SETTINGS BELOW MINIMUM REQUIRED CRIMP HEIGHT SETTING WILL CAUSE DAMAGE TO CRIMP TOOLING.

-	-	1	-	-	-	2119957-2	APPLICATOR SHIM PACK	260
-	1	-	1	1	1	8-21084-0	O-RING, .676 ID, .070 DIA. MAT.	252
-	-	-	-	1	-	2119640-1	PUSH ROD, AIR FEED	250
-	-	-	-	1	-	2079988-1	BUSHING, LCH5-12, MISUMI	249
-	-	-	-	1	-	2119641-1	FEED CAM, AIR FEED	248
-	1	-	1	1	1	2119798-1	DETENT PIN	247
-	1	-	1	1	1	1-22279-3	SPRING, COMPRESSION	246
-	-	1	-	-	-	2119759-1	RAM, AMP STYLE, END FEED, NON-ADJUST	245
-77	-7	-6	-5	-2	-1	PART NO	DESCRIPTION	ITEM NO


ATLANTIC VERSION
Shown on sheets 1 of 4 & 2 of 4
(Pacific version shown on sheets 3 of 4 & 4 of 4)

SET UP GAUGE 2119599-2	LOC A	DIST 66	REVISIONS			
			P	LTR	DESCRIPTION	DATE
				I	ORIGINAL	09DEC2011
				A	RELEASED	27FEB2012
				A1	ECR-13-010523	01JUL2013
				B	ECR-13-012365	06AUG2013


-	1	1	1	1	1	2119082-9	CAM, SNAIL, INSULATION ADJUSTMENT	244
-	1	1	1	1	1	2079764-1	WASHER, WAVE SPRING, CREST-TO-CREST	243
-	1	1	1	1	1	2119083-1	RETAINER, INSULATION DIAL	242
-	-	2	2	-	-	2168400-7	SHCS, LOW HEAD, RoHS, M5 X 10	240
-	-	-	-	-	1	2119580-1	MECHANICAL FEED ASSEMBLY	239
-	-	-	-	1	-	2063440-1	AIR FEED MODULE	238
-	-	1	1	-	-	2119740-2	TAG, IDENTIFICATION	213
-	-	REF	REF	-	-	1901697-1	FEED FINGER ASSEMBLY, EF	183
-	1	1	1	1	1	6-993111-6	PIN, SLOTTED SPRING 3.0 X 14.0	177
-	1	1	1	1	1	8-22280-7	SPRING, COMPRESSION	176
-	1	1	1	1	1	1752353-2	GUIDE PIN, HOLDDOWN	175
-	1	1	1	1	1	1901680-2	GUIDE PIN, HOLDDOWN	174
-	-	-	-	2	-	21045-3	RING, RETAIN, EXTERN, 3/16 CRESCENT	172
-	1	1	1	1	1	994969-1	MAGNET, RARE EARTH HIGH ENERGY	166
-	REF	REF	REF	REF	REF	994970-2	COUNTER, MAGNETIC	164
-	-	-	-	1	-	240638-1	SPRING, FEED FINGER	163
-	-	-	-	1	-	3-23627-7	PIN, RETAIN, GRVD, 3/16 X .854	137
-	-	REF	REF	-	-	SEE NOTE 4	MEMORY CHIP, PROGRAMMED	135
-	-	1	1	-	-	1633743-1	SERVO FEED LATCH ASM	133
-	1	1	1	1	1	455888-5	SPACER, CRIMPER	82
-	1	1	1	1	1	2119956-2	DOCUMENTATION PACKAGE	71
-	2	2	2	2	2	2-18032-2	SCR, SET, FLT POINT M3 X 10.0	70
-	1	-	-	1	1	2119740-1	TAG, IDENTIFICATION	67
-	2	2	2	2	2	2168078-1	SCREW, DRIVE, RH, RoHS, 2 x .188	66
-	1	1	1	1	1	1901681-1	HOLDDOWN, TERMINAL	65
-	2	2	2	2	2	2168400-8	SHCS, LOW HEAD, RoHS, M4 X 16	64
-	1	-	-	1	1	2119793-1	LIMITER, ADJUSTMENT BOLT	63
-	3	-	3	3	3	992763-5	SCR, SET, SOC, CONE POINT, M3 x 4.0	62
-	1	1	1	1	1	2079383-4	SCR, BHSC, RoHS (M4 X 8)	60
-	-	-	-	-	1	5-18022-5	SCR, HEX HD CAP, M4 X 6.0	59
-	-	-	-	-	1	2063961-1	FEED FINGER	58
-	3	3	3	3	3	2168400-4	SHCS, LOW HEAD, RoHS, M4 X 8	57
-	2	2	2	2	2	2168083-3	SCR, SKT HD CAP, RoHS, M4 X 12.0	56
-	2	2	2	2	2	5018030-2	NUT, HEX, REG, RoHS, M4	55
-	2	2	2	2	2	5018030-1	NUT, HEX, REG, RoHS, M3	54
-	2	2	2	2	2	986965-8	NUT, LOCK, HEX, TORQUE (M4)	53
-	1	1	1	1	1	1-5018030-0	NUT, HEX, REG, RoHS, M3.5	52
-	-	-	-	1	-	2119792-2	PAWL, EF, AIR	51
-	1	1	1	1	1	1-1752354-3	STANDOFF, HOLD-DOWN	50
-	-	-	-	1	2	18023-9	SCR, SKT HD CAP M4 X 6.0	49
-	-	-	-	-	1	2119652-1	FEED CAM, PRE FEED	48
-	-	-	-	-	1	2119653-1	FEED CAM, POST FEED	47
-	1	1	1	1	1	2119655-5	APPLICATOR BASIC ASSEMBLY, EF	46
-	1	-	-	1	1	2119369-1	RAM, AMP STYLE, END FEED	44
-	1	1	1	1	1	2079383-7	SCR, BHSC, RoHS (M8 X 25)	41
-	1	-	1	1	1	2119645-1	DISC, NUMBERED FA WIRE ADJUSTMENT	40
-	1	-	1	1	1	2119957-1	APPLICATOR SHIM PACK	39
-	1	1	1	1	1	2119644-1	RAM WASHER, PRECISION	38
-	1	1	1	1	1	2119085-1	FA HEAD, ATLANTIC STYLE	37
-	1	-	1	1	1	2119092-1	BOLT, ADJUSTMENT	35
-	7	7	7	7	7	1-18028-2	WASHER, FLAT, REG M4	33
-	2	2	2	2	2	2168083-9	SCR, SKT HD CAP, RoHS, M4 X 20	31
-	2	2	2	2	2	1-2168083-0	SCR, SKT HD CAP, RoHS, M4 X 10	29
-	1	1	1	1	1	240639-1	STRIPPER (MACHINING)	27
-	2	2	2	2	2	1320906-1	STUD, THREADED	25
-	1	1	1	1	1	1752371-5	PLATE, STRIP GUIDE	24
-	1	1	1	1	1	240825-2	PLATE, STRIP HOLD DOWN	23
-	2	2	2	2	2	2-22281-3	SPRING, COMPRESSION	22
-	1	1	1	1	1	1752373-4	DRAG	20
-	2	2	2	2	2	1901259-4	GUIDE, LOWER STRIP	18
-	4	4	4	4	4	1-2079383-1	SCR, BHSC, RoHS (M6 X 12)	17
-	1	1	1	1	1	3-240641-3	SPACER	16
-	1	1	1	1	1	1752360-1	SPACER, HOLD-DOWN	13
-	1	1	1	1	1	240644-1	PLATE, REAR SHEAR	11
-	-	-	-	-	-	-	-	10
-	1	1	1	1	1	690495-4	PLATE, FRONT SHEAR	9
1	1	1	1	1	1	1338673-1	ANVIL, COMBINATION	8
-	1	1	1	1	1	1-2217206-3	BLADE, SLUG	7
-	1	1	1	1	1	240641-3	SPACER	5
-	1	1	1	1	1	238009-1	BLOCK, FL CRIMPER SPACER	4
1	1	1	1	1	1	2-1633961-6	CRIMPER, INSULATION F PREMIUM	3
-	1	1	1	1	1	1-455888-0	SPACER, CRIMPER	2
1	1	1	1	1	1	1-456406-2	CRIMPER, WIRE PREMIUM	1
-77	-7	-6	-5	-2	-1	PART NO	DESCRIPTION	ITEM NO

THIS IS SUBJECT TO CHANGE WITHOUT NOTICE. THE USER SHALL BE CONTACTED FOR THE LATEST REVISION.		DWN B. WEAVER	09DEC2011	TE Connectivity Harrisburg, PA 17105-3608	
DIMENSIONS:		CHK G. HOFENER	09DEC2011	NAME	
mm		APVD G. RAILLEY	09DEC2011	Ocean End Feed Applicator	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		PRODUCT SPEC		SIZE	
0 PLC ±.5		APPLICATION SPEC		CASE CODE	
1 PLC ±0.13		-		DRAWING NO	
2 PLC ±0.13		-		00779	
3 PLC ±0.013		-		©=2150030	
4 PLC ±0.0001		-		RESTRICTED TO	
ANGLES ±.5		WEIGHT		A1	
FINISH		-		Customer Accessible Production Drawing	
-		-		SCALE 1:1	
-		-		SHEET 1 OF 4	
-		-		REV B	


LOC		DIST		REVISIONS			
A	66	P	LTR	DESCRIPTION	DATE	DWN	APVD
		-	-	SEE SHEET 1	-	-	-




HOLDDOWN SET-UP




FEED TYPE
MECHANICAL




PNEUMATIC



SERVO
LATCH PLATE



CAM POSITIONS



ATLANTIC VERSION
Shown on sheets 1 of 4 & 2 of 4
(Pacific version shown on sheets 3 of 4 & 4 of 4)

100% PROPERTY OF TYCO ELECTRONICS CORPORATION IT IS SUBJECT TO CHANGE WITHOUT NOTICE AND WITHOUT WARRANTY TYCO ELECTRONICS CORPORATION TYCO ELECTRONICS CORPORATION TYCO ELECTRONICS CORPORATION		DWN B. WEAVER 09DEC2011	TE Connectivity Harrisburg, PA 17105-3608	
CHK G. HOFFNER 09DEC2011		NAME	Ocean End Feed Applicator	
APVD G. BAILEY 09DEC2011		PRODUCT SPEC	SIZE A1	
APPLICATION SPEC		WEIGHT	CAGE CODE 00779	
MATERIAL		FINISH	DRAWING NO C=2150030	
Customer Accessible Production Drawing		SCALE 1:1	SHEET 2 OF 4	
			REV B	

8

7

6

5

4

3

2

1

THIS DRAWING IS UNPUBLISHED.


RELEASED FOR PUBLICATION

2011

© COPYRIGHT 2011

BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

PACIFIC VERSION
TERMINATOR
INTERFACE ADAPTER



PART
NUMBER

2-2150030-1

REVISION

B

DESCRIPTION

FINE CRIMP HEIGHT ADJUST

FEED TYPE

MECHANICAL

CONVERT TO

PNEUMATIC FEED

PART NUMBERS REQUIRED

2119950-1

2119792-1

-

2119641-2

-

2063440-1

SERVO LATCH PLATE

2119951-1

1901697-1

8-2150030-5

-

2168400-7 (QUANTITY 2)

SMART APPLICATOR

2161326-1

-

8-2150030-4

-

-

MECHANICAL FEED

2119949-1

2063961-1

5-18022-5

2119653-2

-

-

SERVO LATCH PLATE

2119951-1

1901697-1

8-2150030-5

-

2168400-7 (QUANTITY 2)

SMART APPLICATOR

2161326-1

-

8-2150030-4

-

-

MECHANICAL FEED

2119949-1

2063961-1

5-18022-5

2119653-2

-

-

PNEUMATIC FEED

2119950-1

2119792-1

-

2119641-2

-

2063440-1

-

-

-

-

-

-

-

-

-

-

-

-

2-2150030-2

B

FINE CRIMP HEIGHT ADJUST

PNEUMATIC

2119949-1

2063961-1

5-18022-5

2119653-2

-

-

2168400-7 (QUANTITY 2)

-

-

2-2150030-5

B

FINE CRIMP HEIGHT ADJUST

SERVO LATCH PLATE

2119949-1

2063961-1

5-18022-5

2119653-2

-

-

-

-

-

2-2150030-7

B

FINE CRIMP HEIGHT ADJUST

NONE

-

-

-

-

-

-

-

7-2150030-7

A

CRIMP TOOLING KIT

-

-

-

-

-

-

-

-

APPLICATOR DATA

CRIMP

SIZE

TYPE

WIRE

2.30 mm [.091]

F

INSUL

3.30 mm [.130]

F

APPL INSTRUCTIONS

408-10390




TERMINAL DATA: TE TERMINAL

TE CRIMP SPECIFICATION

TERMINAL NAME: .250 FASTON RECEPTACLE

WIRE STRIP LENGTH

4.40-6.40 mm [.173-.252 IN]



INSULATION DIAMETER RANGE

Ø2.30-3.30 mm [.091-.130 IN]

TERMINAL APPLICATION SPECIFICATION

114-2036

-

-

-

-

TERMINALS APPLIED

TE TERMINAL

TE TERMINAL

TE TERMINAL

TE TERMINAL

160389-3

42510-2

63609-3

140760-3

160389-4

42510-5

63609-4

140760-4

41772

63127-1

63693-1

140760-5

41772-1

63609-1


140760-1

42510-1

63609-2


140760-2

WIRE SIZE



CRIMP HEIGHT

mm [INCH]



CRIMP HEIGHT REFERENCE SETTING



18 AWG or 0.75mm²

1.42+/-0.05 [.056+/- .002]

6.0

(2) 22 AWG

1.37+/-0.05 [.054+/- .002]

6.5

20 AWG or 0.50mm²

1.30+/-0.05 [.051+/- .002]

7.3

0.40mm²

1.27+/-0.05 [.050+/- .002]

7.6

22 AWG or 0.30mm²

1.24+/-0.05 [.049+/- .002]


8.0

WIRE SIZE



CRIMP HEIGHT

WI _ CRIMP _ UNIT



CRIMP HEIGHT REFERENCE SETTING



0.80mm²

1.30+/-0.03 [.051+/- .001]

7.8

0.75mm²

1.30+/-0.03 [.051+/- .001]

7.8

0.65mm²

1.27+/-0.03 [.050+/- .001]

7.6

0.50mm²

1.22+/-0.03 [.048+/- .001]


7.8

0.30mm²

1.14+/-0.03 [.045+/- .001]


8.4

WIRE SIZE



CRIMP HEIGHT

mm [INCH]



CRIMP HEIGHT REFERENCE SETTING



18 AWG or 0.75mm²

1.42+/-0.05 [.056+/- .002]

6.0

(2) 22 AWG

1.37+/-0.05 [.054+/- .002]

6.5

20 AWG or 0.50mm²

1.30+/-0.05 [.051+/- .002]

7.3

0.40mm²

1.27+/-0.05 [.050+/- .002]

7.6

22 AWG or 0.30mm²

1.24+/-0.05 [.049+/- .002]


8.0

WIRE SIZE



CRIMP HEIGHT

WI _ CRIMP _ UNIT



CRIMP HEIGHT REFERENCE SETTING



0.80mm²

1.30+/-0.03 [.051+/- .001]

7.8

0.75mm²

1.30+/-0.03 [.051+/- .001]

7.8

0.65mm²

1.27+/-0.03 [.050+/- .001]

7.6

0.50mm²

1.22+/-0.03 [.048+/- .001]


7.8

0.30mm²

1.14+/-0.03 [.045+/- .001]


8.4

WIRE SIZE



CRIMP HEIGHT

mm [INCH]



CRIMP HEIGHT REFERENCE SETTING



18 AWG or 0.75mm²

1.42+/-0.05 [.056+/- .002]

6.0

(2) 22 AWG

1.37+/-0.05 [.054+/- .002]

6.5

20 AWG or 0.50mm²

1.30+/-0.05 [.051+/- .002]

7.3

0.40mm²

1.27+/-0.05 [.050+/- .002]

7.6

22 AWG or 0.30mm²

1.24+/-0.05 [.049+/- .002]


8.0

WIRE SIZE



CRIMP HEIGHT

WI _ CRIMP _ UNIT



CRIMP HEIGHT REFERENCE SETTING



0.80mm²

1.30+/-0.03 [.051+/- .001]

7.8

0.75mm²

1.30+/-0.03 [.051+/- .001]

7.8

0.65mm²

1.27+/-0.03 [.050+/- .001]

7.6

0.50mm²

1.22+/-0.03 [.048+/- .001]


7.8

0.30mm²

1.14+/-0.03 [.045+/- .001]


8.4

WIRE SIZE



CRIMP HEIGHT

mm [INCH]



CRIMP HEIGHT REFERENCE SETTING



18 AWG or 0.75mm²

1.42+/-0.05 [.056+/- .002]

6.0

(2) 22 AWG

1.37+/-0.05 [.054+/- .002]

6.5

20 AWG or 0.50mm²

1.30+/-0.05 [.051+/- .002]

7.3

0.40mm²

1.27+/-0.05 [.050+/- .002]

7.6

22 AWG or 0.30mm²

1.24+/-0.05 [.049+/- .002]


8.0

WIRE SIZE



CRIMP HEIGHT

WI _ CRIMP _ UNIT



CRIMP HEIGHT REFERENCE SETTING



0.80mm²

1.30+/-0.03 [.051+/- .001]

7.8

0.75mm²

1.30+/-0.03 [.051+/- .001]

7.8

0.65mm²

1.27+/-0.03 [.050+/- .001]

7.6

0.50mm²

1.22+/-0.03 [.048+/- .001]


7.8

0.30mm²

1.14+/-0.03 [.045+/- .001]


8.4

WIRE SIZE



CRIMP HEIGHT

mm [INCH]



CRIMP HEIGHT REFERENCE SETTING



18 AWG or 0.75mm²

1.42+/-0.05 [.056+/- .002]

6.0

(2) 22 AWG

1.37+/-0.05 [.054+/- .002]

6.5

20 AWG or 0.50mm²

1.30+/-0.05 [.051+/- .002]

7.3

0.40mm²

1.27+/-0.05 [.050+/- .002]

7.6

22 AWG or 0.30mm²

1.24+/-0.05 [.049+/- .002]


8.0

WIRE SIZE



CRIMP HEIGHT

WI _ CRIMP _ UNIT



CRIMP HEIGHT REFERENCE SETTING



0.80mm²

1.30+/-0.03 [.051+/- .001]

7.8

0.75mm²

1.30+/-0.03 [.051+/- .001]

7.8

0.65mm²

1.27+/-0.03 [.050+/- .001]

7.6

0.50mm²

1.22+/-0.03 [.048+/- .001]


7.8

0.30mm²

1.14+/-0.03 [.045+/- .001]


8.4

WIRE SIZE



CRIMP HEIGHT

mm [INCH]



CRIMP HEIGHT REFERENCE SETTING



18 AWG or 0.75mm²

1.42+/-0.05 [.056+/- .002]

6.0

(2) 22 AWG

1.37+/-0.05 [.054+/- .002]

6.5

20 AWG or 0.50mm²

1.30+/-0.05 [.051+/- .002]

7.3

0.40mm²

1.27+/-0.05 [.050+/- .002]

7.6

22 AWG or 0.30mm²

1.24+/-0.05 [.049+/- .002]


8.0

WIRE SIZE



CRIMP HEIGHT

WI _ CRIMP _ UNIT



CRIMP HEIGHT REFERENCE SETTING



0.80mm²

1.30+/-0.03 [.051+/- .001]

7.8

0.75mm²

1.30+/-0.03 [.051+/- .001]

7.8

0.65mm²

1.27+/-0.03 [.050+/- .001]

7.6

0.50mm²

1.22+/-0.03 [.048+/- .001]


7.8

0.30mm²

1.14+/-0.03 [.045+/- .001]


8.4

WIRE SIZE



CRIMP HEIGHT

mm [INCH]



CRIMP HEIGHT REFERENCE SETTING



18 AWG or 0.75mm²

1.42+/-0.05 [.056+/- .002]

6.0

(2) 22 AWG

1.37+/-0.05 [.054+/- .002]

6.5

20 AWG or 0.50mm²

1.30+/-0.05 [.051+/- .002]

7.3

0.40mm²

1.27+/-0.05 [.050+/- .002]

7.6

22 AWG or 0.30mm²

1.24+/-0.05 [.049+/- .002]


8.0

WIRE SIZE



CRIMP HEIGHT

WI _ CRIMP _ UNIT



CRIMP HEIGHT REFERENCE SETTING



0.80mm²

1.30+/-0.03 [.051+/- .001]

7.8

0.75mm²

1.30+/-0.03 [.051+/- .001]

7.8

0.65mm²

1.27+/-0.03 [.050+/- .001]

7.6

0.50mm²

1.22+/-0.03 [.048+/- .001]


7.8

0.30mm²

1.14+/-0.03 [.045+/- .001]


8.4

WIRE SIZE



CRIMP HEIGHT

mm [INCH]



CRIMP HEIGHT REFERENCE SETTING



18 AWG or 0.75mm²

1.42+/-0.05 [.056+/- .002]

6.0

(2) 22 AWG

1.37+/-0.05 [.054+/- .002]

6.5

20 AWG or 0.50mm²

1.30+/-0.05 [.051+/- .002]

7.3

0.40mm²

1.27+/-0.05 [.050+/- .002]

7.6

22 AWG or 0.30mm²

1.24+/-0.05 [.049+/- .002]


8.0

WIRE SIZE



CRIMP HEIGHT

WI _ CRIMP _ UNIT



CRIMP HEIGHT REFERENCE SETTING



0.80mm²

1.30+/-0.03 [.051+/- .001]

7.8

0.75mm²

1.30+/-0.03 [.051+/- .001]

7.8

0.65mm²

1.27+/-0.03 [.050+/- .001]

7.6

0.50mm²

1.22+/-0.03 [.048+/- .001]


7.8

0.30mm²

1.14+/-0.03 [.045+/- .001]


8.4

WIRE SIZE



CRIMP HEIGHT

mm [INCH]



CRIMP HEIGHT REFERENCE SETTING



18 AWG or 0.75mm²

1.42+/-0.05 [.056+/- .002]

6.0

(2) 22 AWG

1.37+/-0.05 [.054+/- .002]

6.5

20 AWG or 0.50mm²

1.30+/-0.05 [.051+/- .002]

7.3

0.40mm²

1.27+/-0.05 [.050+/- .002]

7.6

22 AWG or 0.30mm²

1.24+/-0.05 [.049+/- .002]


8.0

WIRE SIZE



CRIMP HEIGHT

WI _ CRIMP _ UNIT



CRIMP HEIGHT REFERENCE SETTING



0.80mm²

1.30+/-0.03 [.051+/- .001]

7.8

0.75mm²

1.30+/-0.03 [.051+/- .001]

7.8

0.65mm²

1.27+/-0.03 [.050+/- .001]

7.6

0.50mm²

1.22+/-0.03 [.048+/- .001]


7.8

0.30mm²

1.14+/-0.03 [.045+/- .001]


8.4

WIRE SIZE



CRIMP HEIGHT

mm [INCH]



CRIMP HEIGHT REFERENCE SETTING



18 AWG or 0.75mm²

1.42+/-0.05 [.056+/- .002]

6.0

(2) 22 AWG

1.37+/-0.05 [.054+/- .002]

6.5

20 AWG or 0.50mm²

1.30+/-0.05 [.051+/- .002]

7.3

0.40mm²

1.27+/-0.05 [.050+/- .002]

7.6

22 AWG or 0.30mm²

1.24+/-0.05 [.049+/- .002]


8.0

WIRE SIZE



CRIMP HEIGHT

WI _ CRIMP _ UNIT



CRIMP HEIGHT REFERENCE SETTING



0.80mm²

1.30+/-0.03 [.051+/- .001]

7.8

0.75mm²

1.30+/-0.03 [.051+/- .001]

7.8

0.65mm²

1.27+/-0.03 [.050+/- .001]

7.6

0.50mm²

1.22+/-0.03 [.048+/- .001]


7.8

0.30mm²

1.14+/-0.03 [.045+/- .001]


8.4

WIRE SIZE



CRIMP HEIGHT

mm [INCH]



CRIMP HEIGHT REFERENCE SETTING



18 AWG or 0.75mm²

1.42+/-0.05 [.056+/- .002]

6.0

(2) 22 AWG

1.37+/-0.05 [.054+/- .002]

6.5

20 AWG or 0.50mm²

1.30+/-0.05 [.051+/- .002]

7.3

0.40mm²

1.27+/-0.05 [.050+/- .002]

7.6

22 AWG or 0.30mm²

1.24+/-0.05 [.049+/- .002]


8.0

WIRE SIZE



CRIMP HEIGHT

WI _ CRIMP _ UNIT



CRIMP HEIGHT REFERENCE SETTING



0.80mm²

1.30+/-0.03 [.051+/- .001]

7.8

0.75mm²

1.30+/-0.03 [.051+/- .001]

7.8

0.65mm²

1.27+/-0.03 [.050+/- .001]

7.6

0.50mm²

1.22+/-0.03 [.048+/- .001]


7.8

0.30mm²

1.14+/-0.03 [.045+/- .001]


8.4

WIRE SIZE



CRIMP HEIGHT

mm [INCH]



CRIMP HEIGHT REFERENCE SETTING



18 AWG or 0.75mm²

1.42+/-0.05 [.056+/- .002]

6.0

(2) 22 AWG

1.37+/-0.05 [.054+/- .002]

6.5

20 AWG or 0.50mm²

1.30+/-0.05 [.051+/- .002]

7.3

0.40mm²

1.27+/-0.05 [.050+/- .002]

7.6

22 AWG or 0.30mm²

1.24+/-0.05 [.049+/- .002]


8.0

WIRE SIZE



CRIMP HEIGHT

WI _ CRIMP _ UNIT



CRIMP HEIGHT REFERENCE SETTING



0.80mm²

1.30+/-0.03 [.051+/- .001]

7.8

0.75mm²

1.30+/-0.03 [.051+/- .001]

7.8

0.65mm²

1.27+/-0.03 [.050+/- .001]

7.6

0.50mm²

1.22+/-0.03 [.048+/- .001]


7.8

0.30mm²

1.14+/-0.03 [.045+/- .001]


8.4

WIRE SIZE



CRIMP HEIGHT

mm [INCH]



CRIMP HEIGHT REFERENCE SETTING



18 AWG or 0.75mm²

1.42+/-0.05 [.056+/- .002]

6.0

(2) 22 AWG

1.37+/-0.05 [.054+/- .002]

6.5

20 AWG or 0.50mm²

1.30+/-0.05 [.051+/- .002]

7.3

0.40mm²

1.27+/-0.05 [.050+/- .002]

7.6

22 AWG or 0.30mm²


1.24+/-0.05 [.049+/- .002]

8.0


WIRE SIZE




LOC	DIST	REVISIONS			
		P	LYR	DESCRIPTION	DATE
A	66	-	-	SEE SHEET 1	-




HOLDDOWN SET-UP




FEED TYPE
MECHANICAL




PNEUMATIC



SERVO
LATCH PLATE



CAM POSITIONS



PACIFIC VERSION
Shown on sheets 3 of 4 & 4 of 4
(Atlantic version shown on sheets 1 of 4 & 2 of 4)

DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		DWN B. WEAVER 09DEC2011		STE TE Connectivity	
mm		0 PLC ±0.5		CHK G. HOFNER 09DEC2011		Harrisburg, PA 17105-3608	
FINISH		1 PLC ±0.13		APVD G. RILEY 09DEC2011		NAME	
MATERIAL		2 PLC ±0.13		PRODUCT SPEC		Ocean End Feed	
		3 PLC ±0.013		APPLICATION SPEC		Applicator	
		4 PLC ±0.0001		WEIGHT		SIZE	
				Customer Accessible Production Drawing		CAGE CODE	
				SCALE 1:1		DRAWING NO	
				SHEET 4 OF 4		REV B	

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9