

## 8525 Hook-up/Lead - (Type MW) MIL-W-76C-PVC

 For more Information  
 please call

1-800-Belden1

**Description:**

Tinned copper, PVC insulation, medium wall. The extruded PVC insulation is flame and ozone resistant. Inert to most chemicals, oils, and solvents. Covers single cond., PVC insulated hook-up wire for internal wiring of electrical and electronic equipment.

**Physical Characteristics (Overall)****Conductor****AWG:**

| # Conductors | AWG | Stranding | Conductor Material |
|--------------|-----|-----------|--------------------|
| 1            | 24  | 7x32      | TC - Tinned Copper |

**Insulation****Insulation Material:**

| Insulation Material      | Wall Thickness (mm) |
|--------------------------|---------------------|
| PVC - Polyvinyl Chloride | 0.4318              |

**Overall Insulation****Overall Cabling**

Overall Nominal Diameter: 1.473 mm

**Applicable Specifications and Agency Compliance (Overall)****Applicable Standards & Environmental Programs**

|                                       |              |
|---------------------------------------|--------------|
| EU CE Mark:                           | Yes          |
| EU Directive 2000/53/EC (ELV):        | Yes          |
| EU Directive 2002/95/EC (RoHS):       | Yes          |
| EU RoHS Compliance Date (mm/dd/yyyy): | 10/01/2005   |
| EU Directive 2002/96/EC (WEEE):       | Yes          |
| EU Directive 2003/11/EC (BFR):        | Yes          |
| CA Prop 65 (CJ for Wire & Cable):     | Yes          |
| MII Order #39 (China RoHS):           | Yes          |
| Military Specification:               | MIL-W-76C    |
| MIL Spec Rating:                      | 1000 V, 80°C |

**Plenum/Non-Plenum**

Plenum (Y/N): No

**Related Documents:**

No related documents are available for this product

**Put Ups and Colors:**

| Item #       | Putup  | Ship Weight | Color | Notes | Item Desc      |
|--------------|--------|-------------|-------|-------|----------------|
| 8525 001100  | 30 MT  | 0.136 KG    | BROWN |       | 24 STR PVC BRN |
| 8525 0011000 | 305 MT | 1.361 KG    | BROWN | P     | 24 STR PVC BRN |
| 8525 002100  | 30 MT  | 0.136 KG    | RED   |       | 24 STR PVC RED |
| 8525 0021000 | 305 MT | 1.361 KG    | RED   | P     | 24 STR PVC RED |

## METRIC MEASUREMENT VERSION

## 8525 Hook-up/Lead - (Type MW) MIL-W-76C-PVC

|              |        |          |              |   |                    |
|--------------|--------|----------|--------------|---|--------------------|
| 8525 003100  | 30 MT  | 0.136 KG | ORANGE       |   | 24 STR PVC ORG     |
| 8525 0031000 | 305 MT | 1.361 KG | ORANGE       | P | 24 STR PVC ORG     |
| 8525 004100  | 30 MT  | 0.136 KG | YELLOW       |   | 24 STR PVC YEL     |
| 8525 0041000 | 305 MT | 1.361 KG | YELLOW       | P | 24 STR PVC YEL     |
| 8525 005100  | 30 MT  | 0.136 KG | GREEN, DARK  |   | 24 STR PVC GRN     |
| 8525 0051000 | 305 MT | 1.361 KG | GREEN, DARK  | P | 24 STR PVC GRN     |
| 8525 006100  | 30 MT  | 0.136 KG | BLUE, LIGHT  |   | 24 STR PVC LBLU    |
| 8525 0061000 | 305 MT | 1.361 KG | BLUE, LIGHT  | P | 24 STR PVC LBLU    |
| 8525 007100  | 30 MT  | 0.136 KG | VIOLET       |   | 24 STR PVC VIO     |
| 8525 0071000 | 305 MT | 1.361 KG | VIOLET       | P | 24 STR PVC VIO     |
| 8525 008100  | 30 MT  | 0.136 KG | GRAY         |   | 24 STR PVC GRY     |
| 8525 0081000 | 305 MT | 1.361 KG | GRAY         | P | 24 STR PVC GRY     |
| 8525 009100  | 30 MT  | 0.136 KG | WHITE        |   | 24 STR PVC WHT     |
| 8525 0091000 | 305 MT | 1.361 KG | WHITE        | P | 24 STR PVC WHT     |
| 8525 010100  | 30 MT  | 0.136 KG | BLACK        |   | 24 STR PVC BLK     |
| 8525 0101000 | 305 MT | 1.361 KG | BLACK        | P | 24 STR PVC BLK     |
| 8525 0131000 | 305 MT | 1.361 KG | BLUE, DARK   | P | 24 STR PVC DBLU    |
| 8525 0141000 | 305 MT | 1.361 KG | WHITE/BLACK  | A | 24 STR PVC WHT/BLK |
| 8525 0171000 | 305 MT | 1.361 KG | WHITE/YELLOW | A | 24 STR PVC WHT/YEL |
| 8525 0181000 | 305 MT | 1.361 KG | WHITE/BLUE   | A | 24 STR PVC WHT/BLU |
| 8525 0191000 | 305 MT | 1.361 KG | WHITE/BROWN  | A | 24 STR PVC WHT/BRN |

**Notes:**

A = STOCKED STRIPE COLORS.

P = STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M' FOR 1 OR 2 STRIPES. 10000' MINIMUM ORDER FOR COLOR COMBINATION. PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL

Revision Number: 1    Revision Date: 05-14-2007

© 2011 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9