



ZHD-SCE LOW FIRE HAZARD DIESEL RESISTANT HEAT SHRINK IDENTIFICATION SYSTEM

Technical Datasheet

TTDS-263 Revision 6 October 2015

ZHD-SCE Zero Halogen, Diesel Resistant, Heat Shrink Identification Marker Sleeves for the identification of wires and cables.

ZHD-SCE is presented as cut sleeves organised in ladder format.

Manufactured using a specially developed radiation cross-linked, zero halogen material. ZHD-SCE is designed specifically to bridge the gap for installations where the highest performance is demanded from an identification sleeve, without compromising on safety or capability.

ZHD-SCE Heat Shrink Identification Marker Sleeves are available as part of a complete identification system. The system comprises specific printers, thermal transfer ribbons and WINTOTAL software.

PAGE 1

ZHD-SCE, LOW FIRE HAZARD, DIESEL RESISTANT HEAT SHRINK CABLE IDENTIFICATION SYSTEM

Features

- Zero Halogen
- Low Toxic Fumes
- Non-flame propagating
- Resistant to key rail and industrial fluids including diesel (defined by RW-2536)
- Sleeve diameters from 2.4mm to 38.1mm
- Shrink ratio 2:1

Applications

- Pre-termination Cable Identification
- Suitable for locations where there is a fire risk to people or equipment
- Suitable for installations that require outstanding fluid resistance, especially from diesel, from a zero halogen identification sleeve
- Rail, Mass transit, Aerospace, Marine and Heavy Industrial

Temperature Rating

- Operating Temperature Range -55°C to 125°C (-67°F to 257°F)

Design For Environment

- No Halogens, Sulphur, Nitrogen, Phosphorus and Cadmium sources above trace level. The flame retardant used in this product does not contain melamine cyanurate
- Further information and a downloadable declaration covering RoHS and REACH compliance can be found at the 'TE Product Compliance Support Centre':

<http://www.te.com/usa-en/utilities/product-compliance.html>

Specifications / Approvals

TE Connectivity Standard **RW-2536**

Rail Standards

EN45545-2, Hazard Classifications 1 and 2, In accordance with requirement set R22/R23

BS 6853 Code of practice for fire precautions in the design and construction of passenger carrying trains.


Interior minor use of materials of mass 100g to 500g vehicle category II

EN 50343 Rolling stock applications - Rolling stock - Rules for installation of cabling - Appendix H

Where possible, TE has tested product as a finished item, including the print. Operational tests are followed by an assessment of mark adherence to validate fit form and function. Further details can be found in TE standard RW-2536.




PAGE 2



Options

| | | | | | |
|------------------------|---|---|-------|------|--------|
| Pre-scoring | Perforated score to produce multiple marker sleeves from each ZHD-SCE sleeve. | | | | |
| | Not scored | Code | Blank | | |
| | Side scored | Code | SS | | |
| | Sided scored with one pre-score | Code | SS1 | | |
| | 1 Pre-score | Code | S1 | | |
| | 2 Pre-scores | Code | S2 | | |
| Packaging sizes | <blank> | 250 piece packs available for all sizes | | | |
| | 1K | 1000 piece reels available for all sizes up to 25.4 | | | |
| | 2.5K | 2500 piece reels available for sizes 4.8 up to 25.4 | | | |
| | 5K | 5000 piece reels available for sizes 2.4 and 3.2 | | | |
| Colours | Code | Yellow | White | | |
| | Code | 4 | 9 | | |
| | Code | Red | Green | Blue | Orange |
| | Code | 2 | 5 | 6 | 3 |



Specify product name, pack size (leave blank for 250), sleeve size (in mm), sleeve length (always 50), pre-score (leave blank if not required) and colour

Dimensions in mm (inches)

Ordering Information

| Ordering description | Inside diameter | | | | Recommended cable diameter use range | |
|--|-----------------------|--------|--------------------------|--------|--------------------------------------|----------------|
| | As supplied (minimum) | | After recovery (Maximum) | | | |
| | mm | inches | mm | inches | mm | inches |
| ZHD-SCE - <pack size> - 2.4 - 50 - <score> - <colour> | 2.4 | 0.094 | 1.19 | 0.047 | 1.27 to 1.90 | 0.050 to 0.075 |
| ZHD-SCE - <pack size> - 3.2 - 50 - <score> - <colour> | 3.2 | 0.126 | 1.58 | 0.060 | 1.77 to 2.66 | 0.069 to 0.105 |
| ZHD-SCE - <pack size> - 4.8 - 50 - <score> - <colour> | 4.8 | 0.189 | 2.36 | 0.090 | 2.54 to 4.06 | 0.100 to 0.160 |
| ZHD-SCE - <pack size> - 6.4 - 50 - <score> - <colour> | 6.4 | 0.250 | 3.18 | 0.125 | 3.81 to 5.46 | 0.150 to 0.215 |
| ZHD-SCE - <pack size> - 9.5 - 50 - <score> - <colour> | 9.5 | 0.375 | 4.75 | 0.187 | 5.59 to 8.12 | 0.220 to 0.320 |
| ZHD-SCE - <pack size> - 12.7 - 50 - <score> - <colour> | 12.7 | 0.500 | 6.35 | 0.250 | 6.99 to 10.79 | 0.275 to 0.425 |
| ZHD-SCE - <pack size> - 19.0 - 50 - <score> - <colour> | 19.0 | 0.730 | 9.53 | 0.375 | 10.16 to 16.25 | 0.400 to 0.640 |
| ZHD-SCE - <pack size> - 25.4 - 50 - <score> - <colour> | 25.4 | 1.000 | 12.70 | 0.500 | 14.29 to 21.59 | 0.563 to 0.850 |
| ZHD-SCE - 38.1 - 50 - <score> - <colour> | 38.1 | 1.500 | 19.05 | 0.750 | 20.95 to 33.02 | 0.825 to 1.300 |




Printer Information

Print quality and print performance can only be guaranteed when specific TE printer and ribbons are used.

The current list of printers and ribbons can be found in TE document 411-121005 'Identification Printer Product Ribbon Matrix'. This document can be found in 'Access Our Tools':

<http://www.te.com/usa-en/utilities/access-product-tools-and-resources.html>



Software

WINTOTAL software, available to download for a 14 day evaluation period from the Identification Printer Software page:

<http://www.te.com/usa-en/products/identification-labeling/printers-software.html>

Contact a TE representative for further information



www.te.com/rail

TE Connectivity, TE Connectivity (logo) and Every Connection Counts are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

© 2015 TE Connectivity Ltd. family of companies All Rights Reserved.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9