
# **Detailed Specifications & Technical Data**

**ENGLISH MEASUREMENT VERSION** 



## 2L28026 Flat - Gray Ribbon 2L280XX Series



For more Information please call

1-800-Belden1



#### **Description:**

Belden's 1.00mm pitch gray ribbon cable was designed for the disk drive market where the 2.00mm IDC connector is widely used.

## **Physical Characteristics (Overall)**

#### Conductor

#### AWG:

# Conductors	AWG	Stranding	Conductor Material
26	28	7x36	TC - Tinned Copper

Total Number of Conductors: 26

Conductor Spacing Center to Center: .0394 +/- .002

Conductor Spacing Outside Center to Outside .984 +/- .008

Center:

#### Insulation

### Insulation Material:

Insulation Material	Wall Thickness (in.)
PVC - Polyvinyl Chloride	.010

Insulation Resistance: >10, 000 Megaohms

#### **Outer Shield**

## Outer Shield Material:

Outer Shield Material
Unshielded

#### **Overall Cable**

Overall Nominal Thickness: .0354 +/- .0031

Overall Nominal Width: 1.02 +/- .008

## **Mechanical Characteristics (Overall)**

Operating Temperature Range: -40°C To +105°C

## **Applicable Specifications and Agency Compliance (Overall)**

#### **Applicable Standards & Environmental Programs**

UL AWM Style:	2651
UL Rating:	105°C, 300 V RMS, VW-1
CSA Specification:	AWM I A 105°C 300 V FT1
CSA Rating:	105°C, 300 V RMS, FT1
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	07/01/2005
EU Directive 2002/96/EC (WEEE):	Yes

Page 1 of 3 09-04-2012

# **Detailed Specifications & Technical Data**

#### **ENGLISH MEASUREMENT VERSION**



## 2L28026 Flat - Gray Ribbon 2L280XX Series

EU Directive 2003/11/EC (BFR):	Yes	
CA Prop 65 (CJ for Wire & Cable):	Yes	
MII Order #39 (China RoHS):	Yes	
Flame Test		
UL Flame Test:	VW-1	
CSA Flame Test:	FT1	
Plenum/Non-Plenum		
Plenum (Y/N):	No	

## **Surface Printing (Overall)**

## **Electrical Characteristics (Overall)**

#### Nom. Characteristic Impedance:

Description	Impedance (Ohm)
(GS)	130
(GSG)	90

#### Nom. Inductance:

Description	Inductance (µH/ft)
@ 1 MHz (GS)	.24
@ 1 MHz (GSG)	.16

#### Nom. Capacitance Conductor to Conductor:

Description	Capacitance (pF/ft)
@ 1 kHz (GSG)	20
@ 1 MHz (GS)	9.5
@ 1 MHz (GSG)	16.5

## Nominal Velocity of Propagation:

Description	VP (%)
	69

#### **Nominal Delay:**

-
Delay (ns/ft)
Delay (115/11)
4.47 NO/ET (000)
1.47 NS/FT. (GSG)

#### Nom. Conductor DC Resistance:

#### DCR @ 20°C (Ohm/1000 ft) 68.2 OHMS/1000 FT. MAX.

## Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100 ft.)
10	3.3
20	5.1
30	7
40	8.3
50	9.8
60	11.6
70	13.1
80	14.2
90	16.4
100	17.6

## Max. Operating Voltage - Non-UL:

Voltage	
300 V RMS	

#### Max. Recommended Current:

Current
1 Amp per conductor @ 20°C

**Dielectric Withstand Voltage:** 2, 000 V RMS

Page 2 of 3 09-04-2012

## **Detailed Specifications & Technical Data**

#### **ENGLISH MEASUREMENT VERSION**



#### 2L28026 Flat - Gray Ribbon 2L280XX Series

#### Typical Unbalanced Crosstalk:

Description	Pulse Rise Time (NS) (MHz)	Near End % (MHz)	Far End % (MHz)
10 ft. sample length	3	4.3	6.7
10 ft. sample length	5	3.8	3.4
10 ft. sample length	7	3.6	2.5

#### **Notes (Overall)**

Notes: GSG=Ground-Signal-Ground Mode

#### **Polarity Identification (Overall)**

Polarity Identification:

**BLACK POLARITY STRIPE ON #1 CONDUCTOR** 

#### **Put Ups and Colors:**

Item #	Putup	Ship Weight	Color	Notes	Item Desc	
2L28026 008H100	100 FT	3.100 LB	GRAY		26 #28 STR PVC RIBBON	

Revision Date: 02-20-2009 Revision Number: 1

© 2012 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

# **ПОСТАВКА** ЭЛЕКТРОННЫХ КОМПОНЕНТОВ

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001 Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

# Данный компонент на территории Российской Федерации Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

## http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

## Офис по работе с юридическими лицами:

105318, г. Москва, ул. Щербаковская д. 3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru moschip.ru\_6 moschip.ru\_4 moschip.ru\_9