

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT

ALL RIGHTS RESERVED.

LOC

DIST

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD

D

C

B

A

REPLACED BY OCEAN STYLE APPLICATOR PART NUMBER

FOR REPLACEMENT PARTS FOR APPLICATOR REFER TO ADDITIONAL PAGE(S). SPARE PARTS KIT (IF LISTED) WILL REMAIN AVAILABLE.

THE REPLACEMENT OCEAN STYLE APPLICATOR HAS THE SAME TERMINATOR/PRESS INTERFACE AS APPLICATOR

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:



TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	±
1 PLC	±
2 PLC	±
3 PLC	±
4 PLC	±
ANGLES	±

MATERIAL

FINISH

DWN

CHK

APVD

PRODUCT SPEC

APPLICATION SPEC

WEIGHT

TE Connectivity

NAME

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A3

C-

SCALE

SHEET OF

REV

1470-19 (3/11)

Pro/ENGINEER DRAWING

THIS DRAWING IS A CONTROLLED DOCUMENT

LAYOUT
L1426112

SET UP GAGE
458637-3



2000

THIS DRAWING IS UNCLASSIFIED
BY AMP INCORPORATED. ALL RIGHTS RESERVED.

LOC
A
DIST
66

DRAWING MADE IN THIRD ANGLE PROJECTION



PART NUMBER	REV	FIRST USED	TERMINATOR	FEED TYPE	DESCRIPTION
1426112-1	E	-	LEADMAKER	MECH POST FEED	CUTS CARRIER
1426112-2	E	-	BENCH	MECH PRE FEED	CUTS CARRIER
1426112-6	E	-	LEADMAKER	MECH POST FEED	CONTINUOUS CARRIER
7-1426112-1	E	-	LEADMAKER	MECH POST FEED	-1 AND SPARE PARTS
7-1426112-2	E	-	BENCH	MECH PRE FEED	-2 AND SPARE PARTS
7-1426112-6	E	-	LEADMAKER	MECH POST FEED	-6 AND SPARE PARTS
7-1426112-7	A	-	-	-	SPARE PARTS KIT

CRIMP DATA AMP TERMINAL AMP CRIMP SPECS				
TERMINAL NAME: PC BOARD CONTACT (RECEPT SL-156)				
CRIMP	SIZE	TYPE	RANGE	
WIRE	1.78 [.070 IN]	F	24 - 18 AWG (0.2mm ² -0.9mm ²)	
INSUL	2.54 [.100 IN]	F	2.54 MAX [.100 IN]	
WIRE STRIP LENGTH 3.58-4.34 [.141-.171 IN]			APPL INSTRUCTION 408-8322 	
TERMINAL 114-1015 (B)		-		FEED
APPL SPEC 114-1021 (A)		-		8.90 [.350 IN]
TERMINALS APPLIED 				
640252 (A)	-	-	-	-
61668 (B)	-	-	-	-
350980 (A)	-	-	-	-
770476 (A)	-	-	-	-
737262 (A)	-	-	-	-
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-
WIRE SIZE mm ² AWG 		CRIMP HEIGHT 		PIN PN & LENGTH [IN]
18 AWG		1.30 ±0.05 [.051 ±.002 IN]		1-354779-9 [.3085]
20 AWG		1.14 ±0.05 [.045 ±.002 IN]		3-354779-2 [.3150]
22 AWG		1.07 ±0.05 [.042 ±.002 IN]		3-354779-9 [.3185]
24 AWG		1.02 ±0.05 [.040 ±.002 IN]		4-354779-4 [.3210]
.22mm		1.04 ±0.05 [.041 ±.002 IN]		4-354779-1 [.3195]
.38mm		1.07 ±0.05 [.042 ±.002 IN]		3-354779-9 [.3185]
.50mm		1.09 ±0.05 [.043 ±.002 IN]		3-354779-6 [.3170]
.75mm		1.24 ±0.05 [.049 ±.002 IN]		2-354779-3 [.3105]
-		-		-
-		-		-
-		-		-
-		-		-
-		-		-
-		-		-
-		-		-

1. RECOMMENDED SPARE PARTS.
2. GREASE RAM, CAM, CAM FOLLOWER AND FEED ROD LIGHTLY.
3. LUBRICATE DAILY PER THE APPLICATOR INSTRUCTION SHEET SUPPLIED WITH THE APPLICATOR.

VIEW B ROTATED 180°			
POST FEED 40 mm STROKE	POST FEED 30 mm STROKE	PRE FEED 30 mm STROKE	PRE FEED 40 mm STROKE

AMP 1756 REV 3-92 8 25-AUG-06 08:59:12 b8420 7 6 5 4 3



QTY REQD PER ASSY		PARTS LIST	
DO NOT SCALE PRINT.		MATERIAL	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		FIN	
1 PLC DEC ±0.5 (.02 IN)		DR L. LOFTHOUSE	
2 PLC DEC ±-		CHK 22JAN01	
3 PLC DEC ±-		REL 22JAN01	
ANGLES ±-		M. CLIFFORD	
SURF TEXTURE:		NAME	
REMOVE BURRS, BREAK SHARP EDGES RO.36 MAX		SIDE FEED HD-I APPLICATOR	
SCALE		DWG NO	
00779		1426112	
CUSTOMER AND ASSEMBLY DRAWING		SHEET 1 OF 1	
		REV E	

-	1	1	1	1	1	1	1426112	PRINT, APPLICATOR LOG SHEET	73
-	1	1	1	1	1	1	1338705-1	DOCUMENTATION PACKAGE	71
-	-	-	-	-	-	-	-	-	70
-	-	-	-	-	-	-	-	-	69
-	-	-	-	-	-	-	-	-	68
-	1	1	1	1	1	1	461264-1	PLATE, IDENTIFICATION	67
-	2	2	2	2	2	2	21017-2	SCR, DRIVE (#2x.19) ID PLATE	66
-	-	-	-	-	-	-	-	-	65
-	1	1	1	1	1	1	986950-1	WASHER, FLAT PRECISION	64
-	1	1	1	1	1	1	3-18031-0	SCR, SKT SET (M6X6) RAM	63
-	1	1	1	1	1	1	18023-9	SCR, SHC (M4X6) INS DISC	62
-	2	2	2	2	2	2	2-18032-5	SCR, SOC SET (M5X20) DRAG	61
-	1	1	1	1	1	1	18024-7	SCR, BHC (M4X10) ANVIL	60
-	1	1	1	1	1	1	5-18022-2	SCR, HEX (M4X8) FEED FINGER	59
-	-	-	-	-	-	-	-	-	58
-	-	-	-	-	-	-	-	-	57
-	1	1	1	1	1	1	1338685-1	PAWL, FEED	56
-	-	-	-	-	-	-	-	-	55
-	4	4	4	4	4	4	18024-8	SCR, BHC (M4x12) SHEAR HOLDER	54
-	-	-	-	-	-	-	-	-	53
-	1	1	1	1	1	1	18030-1	NUT, HEX (M3) HOLD DOWN	52
-	1	1	1	1	1	1	811242-5	BUMPER, HOLDDOWN	51
-	1	1	1	1	1	1	690753-2	SPACER, TONKER	50
-	1	1	1	1	1	1	18024-3	SCR, BHC (M3X10) CAM	49
-	-	-	-	-	-	-	-	-	48
-	1	-	1	-	-	-	1338675-1	CAM, PRE FEED 30 & 40 mm ST	47
-	1	-	1	-	-	-	1338676-1	CAM, POST FEED 30 & 40 mm ST	46
-	1	1	1	1	1	1	1320999-3	APPLICATOR BASIC SUBASSY	45
-	1	1	1	1	1	1	690191-1	PLUG, NYLON	44
-	1	1	1	1	1	1	1338660-1	RAM	43
-	1	1	1	1	1	1	690125-1	WASHER, LAMINATED	42
-	1	1	1	1	1	1	690124-1	WASHER, RAM	41
-	1	1	1	1	1	1	2-18024-6	SCR, BHC (M8X25) RAM	40
-	1	1	1	1	1	1	23241-1	BALL, STEEL	39
-	1	1	1	1	1	1	2-22278-7	SPRING, COMPRESSION	38
-	1	1	1	1	1	1	1320922-1	DISC, INSULATION	37
-	1	1	1	1	1	1	354777-1	WIRE DISC, PLASTIC	36
-	1	1	1	1	1	1	22480-5	WASHER, SPRING	35
-	1	1	1	1	1	1	690212-1	POST, RAM	34
-	1	1	1	1	1	1	1320934-1	SUPPORT, TERMINAL	33
-	2	2	2	2	2	2	1-18024-0	SCR, BHC (M4X20) STRIP GUIDE	32
-	1	1	1	1	1	1	18027-2	WASHER, FLAT (M4)	31
-	3	3	3	3	3	3	1-18023-2	SCR, SKT CAP (M4X12) MOUNT BLOCK	30
-	1	1	1	1	1	1	1320908-4	SPACER, STRIP GUIDE	29
-	1	1	1	1	1	1	1633073-1	STRIP GUIDE PLATE ASSY	28
-	1	1	1	1	1	1	1-455888-7	SPACER, FRONT SHEAR DEP	27
-	2	2	2	2	2	2	1-22284-0	SPRING, DRAG	26
-	1	1	1	1	1	1	356835-1	LEVER, DRAG RELEASE	25
-	1	1	1	1	1	1	240792-1	DRAG, TERMINAL	24
-	1	1	1	1	1	1	1320928-1	PLATE, STRIP GUIDE	23
-	1	1	1	1	1	1	980371-4	SCR, SHC SHLD	22
-	1	-	1	-	-	-	690472-2	STRIPPER	21
-	1	1	1	1	1	1	1-18023-1	SCR, SHC (M4X10) STRIPPER	20
-	4	4	4	4	4	4	18025-2	WASHER, LOCK (M4) STRIPPER	19
-	-	1	-	-	1	-	690472-1	STRIPPER	18
-	1	-	-	1	-	-	1338684-1	HOLDER, SHEAR, FRONT (NO-CUT)	17
-	-	-	-	-	-	-	-	-	16
-	-	-	-	-	-	-	-	-	15
-	-	-	-	-	-	-	-	-	14
-	-	-	-	-	-	-	-	-	13
-	1	1	1	1	1	1	3-22280-3	SPRING, SHEAR	12
-	1	1	1	1	1	1	356885-4	STOP, SHEAR	11
-	-	1	1	-	1	1	1320921-1	HOLDER, SHEAR, FRONT (CUT)	10
-	1	1	1	1	1	1	454276-1	SHEAR, FLOAT (FRONT)	9
-	1	2	2	2	1	1	1-1333203-0	ANVIL	8
-	-	-	-	-	-	-	-	-	7
-	-	-	-	-	-	-	-	-	6
-	1	1	1	1	1	1	1-455889-4	DEPRESSOR, SHEAR (FRONT)	5
-	1	1	1	1	1	1	2-238011-2	SPACER, BLOCK CRIMPER	4
-	1	2	2	2	1	1	4-456134-8	CRIMPER, INSULATION	3
-	1	1	1	1	1	1	455888-7	SPACER, CRIMPER	2
-	1	2	2	2	1	1	1-456404-6	CRIMPER, WIRE	1
-77	-76	-72	-71	-6	-2	-1	PART NO	DESCRIPTION	ITEM NO

REVISION OF EACH ASSY NO (WHEN BLANK, USE DWG REVISION)

1426112

D

C

B

A

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9