



Introducing Solar Identification Labels



KEY FEATURES

- Recommended for use in identification of DC Disconnects and Inverters.
- For use on painted smooth metal and textured metal surfaces.
- Excellent durability in extreme outdoor elements such as UV, rain, humidity, cold and salt spray.
- Multiple formats available
- RoHS Compliant
- Outdoor durability for this label is unmatched by other labels in its class.

DESCRIPTION

TE Connectivity introduces label solutions for Solar Panel Installation per the National Electric Code (NEC) specification. Labels are manufactured using ultraviolet (UV) resistant ink, permanent acrylic adhesive and base material designed to withstand environmental elements. A laminate is added to provide additional protection against prolonged UV exposure.

APPLICATIONS

Renewable Energy:

- Solar : DC Switches, Combiner Boxes
- Wind : DC Switches

TEMPERATURE RATINGS

Service Temperature:

- -51°C to 93.3°C (-60°F to 200°F)

STANDARDS AND SPECIFICATIONS

ASTM D 3652 : Physical Construction

ASTM D 3330 : Adhesion

ASTM D 2979 : Adhesion

ASTM D 1000 : Flammability

ASTM D 3759 : Tensile Strength and Elongation

MIL-STD 202G : Method 215

ASTM D 3424 : Method 4, UV Light exposure

ASTM G85 : Annex 5, Salt Spray - Prohesion

ASTM 81531 : Print Adherence

UL PGDQ2 MH17001

UL PGJ12 MH17292

MATERIALS

- High performance vinyl base material
- UV resistant ink
- UV resistant clear lamination

PRODUCT OFFERING


100 Quantity Per Roll

| TE Ordering Description | SAP Part Number | Label Description |
|-------------------------|-----------------|---------------------------------|
| SOL-SD-104076-4-0.1 | CN4616-000 | Solar Disconnect |
| SOL-DCD-104100-4-0.1 | CN4619-000 | DC Disconnect |
| SOL-DPS-104019-4-0.1 | CN4618-000 | Warning - Dual Power Sources |
| SOL-EHS-104019-4-0.1 | CN4617-000 | Warning - Electric Shock Hazard |

500 Quantity Per Roll

| TE Ordering Description | SAP Part Number | Label Description |
|-------------------------|-----------------|---------------------------------|
| SOL-SD-104076-4-0.5 | CL3803-000 | Solar Disconnect |
| SOL-DCD-104100-4-0.5 | CL3806-000 | DC Disconnect |
| SOL-DPS-104019-4-0.5 | CL3804-000 | Warning - Dual Power Sources |
| SOL-EHS-104019-4-0.5 | CL3805-000 | Warning - Electric Shock Hazard |

PRODUCT DIMENSIONS



PRODUCT OFFERING

100 Quantity Per Roll

| TE Ordering Description | SAP Part Number | Label Description |
|-------------------------|-----------------|---------------------------------|
| SOL-SRS-127508N-1-4 | CR0780-000 | System Inverter Rating |
| SOL-CP-127508N-1-X | CR0781-000 | Laminate for above label |
| SOL-SRS-127698N-1-4 | CR0782-000 | System Charge Controller Rating |
| SOL-CP-127698N-1-X | CR0783-000 | Laminate for above label |
| SOL-SRS-812120N-1-4 | CR0784-000 | Generic System Rating |
| SOL-CP-812120N-1-X | CR0785-000 | Laminate for above label |

500 Quantity Per Roll

| TE Ordering Description | SAP Part Number | Label Description |
|-------------------------|-----------------|---------------------------------|
| SOL-SRS-127508N-.5-4 | CR0786-000 | System Inverter Rating |
| SOL-CP-127508N-.5-X | CR0787-000 | Laminate for above label |
| SOL-SRS-127698N-.5-4 | CR0788-000 | System Charge Controller Rating |
| SOL-CP-127698N-.5-X | CR0789-000 | Laminate for above label |
| SOL-SRS-812120N-.5-4 | CR0791-000 | Generic System Rating |
| SOL-CP-812120N-.5-X | CR0792-000 | Laminate for above label |

NOTE : Solar labels SOL-SRS127508 and SOL-SRS127698 will be oriented on the roll so that they will be compatible with the thermal transfer printers. 1330-0607 is the recommended ribbon.

PRODUCT DIMENSIONS

SOL-SRS-127508N-1-4
5.00"W X 2.00"H

| | | |
|------------------------------|----------------------|---|
| RATED OPERATING CURRENT: | <input type="text"/> | A |
| RATED OPERATING VOLTAGE: | <input type="text"/> | V |
| MAXIMUM SYSTEM VOLTAGE: | <input type="text"/> | V |
| RATED SHORT-CIRCUIT CURRENT: | <input type="text"/> | A |

SOL-SRS-127698N-1-4
5.00"W X 2.75"H

| | | |
|---------------------------------|----------------------|---|
| RATED OPERATING CURRENT: | <input type="text"/> | A |
| RATED OPERATING VOLTAGE: | <input type="text"/> | V |
| MAXIMUM SYSTEM VOLTAGE: | <input type="text"/> | V |
| RATED SHORT-CIRCUIT CURRENT: | <input type="text"/> | A |
| POLARITY OF GROUNDED CONDUCTOR: | <input type="text"/> | |
| MAXIMUM VOLTAGE: | <input type="text"/> | V |

SOL-SRS-812120N-1-4
3.20"W X 4.72"H

| | |
|---------------------------|----------------------|
| Peak Power: | <input type="text"/> |
| Max Power Voltage: | <input type="text"/> |
| Max Power Current: | <input type="text"/> |
| Max Open Circuit Voltage: | <input type="text"/> |
| Short Circuit Current: | <input type="text"/> |



KEY FEATURES

- Reflectivity even in poor visibility and bad weather conditions.
- Its special impact and scratch resistant surface and flexibility make it suitable for identification in darkened areas, i.e, conduit raceways, enclosures, etc.
- Complies with international specifications for reflective materials including ASTM D4956.
- White reflective lettering jumps out from the red ink when hit with a light source like a flashlight.
- 7 – 10 year outdoor durability (longer for indoor or protected from weather).
- Highly flexible for uneven surfaces, painted, smooth metal or textured metal surfaces.
- Reflective properties are built in, not a 'charge time' film.
- Resistant to most oils and greases.

DESCRIPTION

Reflective solar labels are manufactured using retro reflective marking to provide emergency responders with appropriate warning and guidance relative to isolating the solar electric system. The label(s) were designed to be in accordance with the dimensional, functional and verbiage requirements established by the California Fire Marshall's April 2009, Solar Photovoltaic Installation Guideline.

APPLICATIONS

Use at the Main Service Disconnect, and DC conduit, raceways, enclosures, cable assemblies and junction boxes on solar photovoltaic installations.

MATERIALS

CAUTION SOLAR CIRCUIT : Permanent solvent based adhesive

5 mil retro-reflective cast PVC film

UV resistant over lam when applicable

STANDARDS AND SPECIFICATIONS

ASTM D 3652 : Physical Construction

ASTM D 3330 : Adhesion

ASTM D 2979 : Adhesion

ASTM D 1000 : Flammability

ASTM D 3759 : Tensile Strength and Elongation

MIL-STD 202G : Method 215

ASTM D 3424 : Method 4, UV Light exposure

ASTM G85 : Annex 5, Salt Spray - Prohesion

ASTM 81531 : Print Adherence

ASTM D4956 : Standard Specification for Retroreflective Sheeting for Traffic Control

PRODUCT OFFERING

Packs of 50 (10 labels/sheet, 5 sheets/pack)

| TE Ordering Description | SAP Part Number | Dimensions | Label Description |
|-------------------------|-----------------|--------------------------------|---------------------------------|
| SOL-SEC-305254-4-0.1 | CN6557-000 | 1 x 12" (25.4 x 304.8") | CAUTION SOLAR ELECTRICAL SYSTEM |
| SOL-CSC-159254-4-0.1 | CN4615-000 | 1 x 6.25" (25.4 x 158.75mm) | CAUTION SOLAR CIRCUIT |

FOR MORE INFORMATION

te.com/products/solarlabels

TE Technical Support Center

| | |
|-------------------|-----------------------|
| USA: | +1 (800) 522-6752 |
| Canada: | +1 (905) 475-6222 |
| Mexico | +52 (0) 55-1106-0800 |
| Latin/S. America: | +54 (0) 11-4733-2200 |
| Germany: | +49 (0) 6251-133-1999 |
| UK: | +44 (0) 800-267666 |
| France: | +33 (0) 1-3420-8686 |
| Netherlands: | +31 (0) 73-6246-999 |
| China: | +86 (0) 400-820-6015 |

Part numbers in this brochure are RoHS Compliant*, unless marked otherwise.

*as defined www.te.com/leadfree

te.com

© 2011 Tyco Electronics Corporation, a TE Connectivity Ltd. company. All Rights Reserved.

1-1773449-6 CIS 3M FP 03/2011

TE Connectivity, TE connectivity (logo) and TE (logo) are trademarks.

Other logos, product and/or company names might be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information in this brochure, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalog are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.



Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9