P993

Low Range Differential Pressure PCB Mount Sensor

Typical Applications

- Variable Air Volume Systems (VAV)
- Filter Pressure Monitoring
- Duct Air Flow
- Modulated Furnace Controls
- Combustion Air Flow
- Gaseous Leak Detection

Standard Full Scale Pressure Ranges

1, 2, 5, 10, ±1, ±2, and ±5 inches of H20

Features

- Rugged PCB Mount Package
- Amplified Temperature Compensated Linear Output
- No Position Sensitivity
- EMI/RFI & ESD Protected
- Superior Output Signal Stability

Description

The P993 series of pressure sensors incorporates a silicon capacitive sensing element in a compact package.

Using a 5 Vdc input, the sensors provide a 0.25 to 4.0 Vdc output proportional to pressure. Internal temperature compensation provides an accurate, easy to use device.

The innovative design eliminates mounting position effects found on other low pressure differential sensors currently available in the market.

Potsdamer Str. 14, 32423 Minden, Germany
Tel: +49 571 3859-0 - Fax: +49 571 3859-119
Email: info@kavlico.de

235 E. Main St., Suite 102A, Northville, MI 48167, USA
Tel: +1 (248) 465-0815 - Fax: +1 (248) 465-0810
Email: pressure.sensors@kavlico.com

www.kavlico.com

RoHS

A brand of CST
CUSTOM SENSORS & TECHNOLOGIES

Technical Specifications

Note: Performance Specifications with 5 Vdc supply at 25°C

Differential Pressure Ranges (inches of H_2O):	1, 2, 5, 10, ±1, ±2, and ±5
Proof Pressure:	1.0 PSI (either port)
Burst Pressure:	1.5 PSI (either port))
Supply Voltage:	5.0 ± 0.25 Vdc
Supply Current:	4mA Max.
Output Voltage (Ratiometric):	0.25 to 4.0 Vdc
Calibration Tolerance (at 5.0 Vdc supply and no load):	
Zero/Null Pressure:	0.25 Vdc ± 60 mV
Span:	3.75 Vdc ± 60 mV
Voltage Ratiometricity:	±1.5% of span Max. 4.75 to 5.25 Vdc supply
Total Error Band (10° to 40°C):	±2% of span Max. (±3% for 0-1" range)
Output Impedance:	100 Ω Max.
Service Life:	10,000,000 cycles Min.
Shock:	10 g's at 6ms duration
Vibration:	1 g from 20 Hz to 1200 Hz
Operating Temperature:	0°C to 60°C
Storage Temperature:	-40°C to +95°C
Humidity:	95% RH, non-condensing
Weight:	20 grams Max.
Electrical Termination:	3 solderable pins, tin plated
Preferred Mounting Position:	None
Pressure Connection:	1/8" diameter tube fitting with barb for 3/16 ID tubing
Recommended Interface Impedance:	25 kΩ Min. resistance between transducer output and ground, in parallel with 0.2 uF Max. capacitance
Over-Voltage Protection:	16 Vdc
Reverse Polarity Protection:	-6 Vdc

How to Order

Use this diagram, working top to bottom and left to right to construct your model number. An example is shown below. Custom OEM options are also available.

P993 Low Range Differential Pressure PCB Mount Sensor

	Pressure Range
1	0 - 1.0" H_2O
1B	±1" H_2O
2	0 - 2.0" H_2O
2B	±2" H_2O
5	0 - 5.0" H_2O
5B	±5" H_2O
10	0 - 10" H_2O

P993 - 5B
Example: P993 - 5B
Description: P993 Pressure Sensor, ±5" H_2O





Dimensions in: mm [inches]

Before installation and operation, ensure that the appropriate pressure sensor has been selected in terms of pressure range, design and specific measuring conditions.

Non-compliance can result in serious injury and/or damage to the equipment.

Don't see what you want?

Call us at +1 (619) 710-2068 to customize this product to meet your application-specific needs!

Warning: The product information contained in this catalogue is given purely as information and does not constitute a representation, warranty or any form of contractual commitment. Kavlico reserve the right to modify their products without notice. It is imperative that we should be consulted over any particular use or application of our products and it is the responsibility of the buyer to establish, particularly through all the appropriate tests, that the product is suitable for the use or application. Under no circumstances will our warranty apply, nor shall we be held responsible for any application (such as any modification, addition, deletion, use in conjunction with other electrical or electronic components, circuits or assemblies, or any other unsuitable material or substance) which has not been expressly agreed by us prior to the sale of our products.

© 2013 Kavlico. All rights reserved.

Potsdamer Str. 14, 32423 Minden, Germany
Tel: +49 571 3859-0 - Fax: +49 571 3859-119
Email: info@kavlico.de

235 E. Main St., Suite 102A, Northville, MI 48167, USA
Tel: +1 (248) 465-0815 - Fax: +1 (248) 465-0810
Email: pressure.sensors@kavlico.com

www.kavlico.com

RoHS

A brand of CST
CUSTOM SENSORS & TECHNOLOGIES

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9