# Direct Ring Lighting/Low Angle Ring Lighting FLV-DR Series/-DL Series

#### **Order Information**

					<b>Connectable Option</b>	Connectable Lig	nting Controller *	
	Model	Light Color	Electricity (W)	Weight (g)	Diffusion Plates	Camera-mount Lighting Controller FLV-TCC Series	Analog Lighting Controller FLV-ATC Series	Dimensions
Direct	FLV-DR3220W	White	1.2	60	FLV-DR3220DF	0	0	А
Ring	FLV-DR3220R	Red	1.2	60	FLV-DR3220DF	0	0	А
Lighting	FLV-DR3220B	Blue	1.2	60	FLV-DR3220DF	0	0	А
	FLV-DR5030W	White	2.4	60	FLV-DR5030DF	0	0	В
	FLV-DR5030R	Red	1.6	60	FLV-DR5030DF	0	0	В
	FLV-DR5030B	Blue	2.4	60	FLV-DR5030DF	0	0	В
	FLV-DR5030IR	Infrared Light	1.5	60	FLV-DR5030DF	0	0	В
	FLV-DR5030UV	Ultraviolet Light	2.9	60	FLV-DR5030DF	0	0	В
	FLV-DR6615W	White	3.4	120	FLV-DR6615DF	0	O	С
	FLV-DR6615R	Red	2.4	120	FLV-DR6615DF	0	0	С
	FLV-DR6615B	Blue	3.4	120	FLV-DR6615DF	0	O	С
	FLV-DR7000W	White	3.6	110	FLV-DR7000DF	0	O	D
	FLV-DR7000R	Red	2.4	110	FLV-DR7000DF	0	O	D
	FLV-DR7000B	Blue	3.6	110	FLV-DR7000DF	0	O	D
	FLV-DR7030W	White	3.6	120	FLV-DR7030DF	0	O	E
	FLV-DR7030R	Red	2.4	120	FLV-DR7030DF	0	O	E
	FLV-DR7030B	Blue	3.6	120	FLV-DR7030DF	0	O	E
	FLV-DR7030IR	Infrared Light	2.4	120	FLV-DR7030DF	0	O	E
	FLV-DR7030UV	Ultraviolet Light	5.3	120	FLV-DR7030DF	0	$\bigcirc$	E
	FLV-DR9000W	White	6.3	230	FLV-DR9000DF	0	O	F
	FLV-DR9000R	Red	4.4	230	FLV-DR9000DF	0	$\bigcirc$	F
	FLV-DR9000B	Blue	6.3	230	FLV-DR9000DF	0	O	F
	FLV-DR9030W	White	5.8	200	FLV-DR9030DF	0	$\bigcirc$	G
	FLV-DR9030R	Red	4.4	200	FLV-DR9030DF	0	O	G
	FLV-DR9030B	Blue	5.8	200	FLV-DR9030DF	O	0	G
	FLV-DR9030IR	Infrared Light	3.9	200	FLV-DR9030DF	0	0	G
	FLV-DR9030UV	Ultraviolet Light	6.8	200	FLV-DR9030DF	0	0	G
	FLV-DR9215W	White	5.3	200	FLV-DR9215DF	0	0	Н
	FLV-DR9215R	Red	4.6	200	FLV-DR9215DF	0	O	Н
	FLV-DR9215B	Blue	5.3	200	FLV-DR9215DF	0	O	Н
	FLV-DR12030W	White	8.7	360	FLV-DR12030DF	0	0	I
	FLV-DR12030R	Red	6.5	360	FLV-DR12030DF	0	O	I
	FLV-DR12030B	Blue	8.7	360	FLV-DR12030DF	0	0	I
Low	FLV-DL5890W	White	1.6	90	FLV-DL5890DF	0	0	J
Ring	FLV-DL5890R	Red	1.2	90	FLV-DL5890DF	0	0	J
Lighting	FLV-DL5890B	Blue	1.6	90	FLV-DL5890DF	0	0	J
	FLV-DL7260W	White	4.4	120	FLV-DL7260DF	0	0	K
	FLV-DL7260R	Red	3.5	120	FLV-DL7260DF	0	0	K
	FLV-DL7260B	Blue	4.4	120	FLV-DL7260DF	0	0	K
	FLV-DL9090W	White	2.4	100	-	0	0	L
	FLV-DL9090R	Red	1.6	100	-	0	0	L
	FLV-DL9090B	Blue	2.4	100	-	0	0	L
	FLV-DL12060W	White	11.6	310	FLV-DL12060DF	0	0	M
	FLV-DL12060R	Red	1.1	310		0	0	IVI
	FLV-DL12060B	Blue	11.6	310	FLV-DL12060DF	0	0	M
		vvnite	13.5	260		C	<u> </u>	N
	FLV-DL15060R	Red	10.1	260	FLV-DL15060DF	0	0	N
	FLV-DL15060B	Blue	13.5	260	FLV-DL15060DF	0	Ø	N

\*: The table shows whether each Lighting can be connected to Lighting Controllers. When multiple Lightings are connected to a Lighting Controller, make sure that the total electricity of all connected Lightings does not exceed the electricity of connectable lighting of each Lighting Controller. ©: Connectable. Light can be continuously emitted.

: Connectable. Light can be emitted only while the trigger is input.

X: Not connectable

#### Lightings



# Lightings Standard Models FLV Series

# Direct Ring Lighting/Low Angle Ring Lighting FLV-DR Series/-DL Series



# Lightings Standard Models FLV Series

# **Bar Lighting FLV-BR Series**

#### **Order Information**

				Connectable Option	Connectable Light	ting Controller *	
Model	Light Color	Electricity (W)	Weight (g)	Diffusion Plates	Camera-mount Lighting Controller FLV-TCC Series	Analog Lighting Controller FLV-ATC Series	Dimensions
FLV-BR6022W	White	1.2	60	FLV-BR6022DF	O	O	A
FLV-BR6022R	Red	1.2	60	FLV-BR6022DF	O	O	A
FLV-BR6022B	Blue	1.2	60	FLV-BR6022DF	O	O	A
FLV-BR6022IR	Infrared Light	0.9	60	FLV-BR6022DF	O	O	A
FLV-BR6022UV	Ultraviolet Light	1.7	60	FLV-BR6022DF	O	0	А
FLV-BR8532W	White	3.9	130	FLV-BR8532DF	O	O	В
FLV-BR8532R	Red	2.9	130	FLV-BR8532DF	0	0	В
FLV-BR8532B	Blue	3.9	130	FLV-BR8532DF	0	0	В
FLV-BR11222W	White	2.4	100	FLV-BR11222DF	0	0	С
FLV-BR11222R	Red	2	100	FLV-BR11222DF	0	0	С
FLV-BR11222B	Blue	2.4	100	FLV-BR11222DF	0	0	С
FLV-BR11222IR	Infrared Light	1.7	100	FLV-BR11222DF	0	0	С
FLV-BR11222UV	Ultraviolet Light	3.9	100	FLV-BR11222DF	0	0	С
FLV-BR14030W	White	6	140	FLV-BR14030DF	0	0	D
FLV-BR14030R	Red	4.1	140	FLV-BR14030DF	0	0	D
FLV-BR14030B	Blue	6	140	FLV-BR14030DF	0	0	D
FLV-BR15020W	White	2.9	120	FLV-BR15020DF	0	0	E
FLV-BR15020R	Red	2.4	120	FLV-BR15020DF	0	0	E
FLV-BR15020B	Blue	2.9	120	FLV-BR15020DF	0	0	E
FLV-BR21222W	White	6	140	FLV-BR21222DF	0	0	F
FLV-BR21222R	Red	4.4	140	FLV-BR21222DF	0	0	F
FLV-BR21222B	Blue	6	140	FLV-BR21222DF	0	0	F
FLV-BR21230W	White	8.4	220	FLV-BR21230DF	0	0	G
FLV-BR21230R	Red	6.8	220	FLV-BR21230DF	0	0	G
FLV-BR21230B	Blue	8.4	220	FLV-BR21230DF	0	0	G
FLV-BR21230IR	Infrared Light	6	220	FLV-BR21230DF	0	0	G
FLV-BR21230UV	Ultraviolet Light	13	220	FLV-BR21230DF	0	0	G
FLV-BR38037W	White	14.9	430	FLV-BR48031DF	0	0	Н
FLV-BR38037R	Red	11.6	430	FLV-BR48031DF	0	0	Н
FLV-BR38037B	Blue	14.9	430	FLV-BR48031DF	0	0	Н
FLV-BR48031W	White	17.6	460	FLV-BR48031DF	×	0	I
FLV-BR48031R	Red	15.9	460	FLV-BR48031DF	×	0	I
FLV-BR48031B	Blue	17.6	460	FLV-BR48031DF	×	0	I I

\*: The table shows whether each Lighting can be connected to Lighting Controllers. When multiple Lightings are connected to a Lighting Controller, make sure that the total electricity of all connected Lightings does not exceed the electricity of connectable lighting of each Lighting Controller. ©: Connectable. Light can be continuously emitted. : Connectable. Light can be emitted only while the trigger is input.

X: Not connectable







# Coaxial Lighting **FLV-CL Series**

#### **Order Information**

		Electricity	Waight	Connectable Lighting	g Controller *	
Model	Light Color	(W)	(g)	Camera-mount Lighting Controller FLV-TCC Series	Analog Lighting Controller FLV-ATC Series	Dimensions
FLV-CL30W	White	2	110	$\bigcirc$	0	A
FLV-CL30R	Red	1.1	110	$\bigcirc$	0	A
FLV-CL30B	Blue	2	110	0	0	A
FLV-CL40W	White	3.6	170	0	0	В
FLV-CL40R	Red	2.2	170	0	0	В
FLV-CL40B	Blue	3.6	170	0	0	В
FLV-CL60W	White	9.2	380	0	0	С
FLV-CL60R	Red	4.8	380	0	0	С
FLV-CL60B	Blue	9.2	380	0	0	С
FLV-CL60IR	Infrared Light	3.9	380	0	0	С
FLV-CL60UV	Ultraviolet Light	9.2	380	0	0	С
FLV-CL80W	White	14.4	580	0	0	D
FLV-CL80R	Red	9.6	580	0	0	D
FLV-CL80B	Blue	14.4	580	0	0	D
FLV-CL100W	White	21.2	820	×	0	E
FLV-CL100R	Red	14	820	0	0	E
FLV-CL100B	Blue	21.2	820	×	0	E

\*: The table shows whether each Lighting can be connected to Lighting Controllers. When multiple Lightings are connected to a Lighting Controller, make sure that the total electricity of all connected Lightings does not exceed the electricity of connectable lighting of each Lighting Controller. ©: Connectable. Light can be continuously emitted. C: Connectable. Light can be emitted only while the trigger is input. X: Not connectable



# Shadowless Lighting **FLV-FS Series**

#### **Order Information**

Model		Electricity (W)	Weight (g)	Connectable Lighting		
	Light Color			Camera-mount Lighting Controller FLV-TCC Series	Analog Lighting Controller FLV-ATC Series	Dimensions
FLV-FS74W	White	4.1	140	0	0	A
FLV-FS74R	Red	2.9	140	0	0	A
FLV-FS74B	Blue	4.1	140	0	0	A

\*: The table shows whether each Lighting can be connected to Lighting Controllers. When multiple Lightings are connected to a Lighting Controller, make sure that the total electricity of all connected Lightings does not exceed the electricity of connectable lighting of each Lighting Controller. O: Connectable. Light can be continuously emitted.

 $\bigcirc$  : Connectable. Light can be emitted only while the trigger is input. X: Not connectable



# Shadowless Lighting FLV-FR Series

### **Order Information**

Model	Light Color	Electricity (W)	Weight (g)	Connectable Lighting	J Controller *	Dimensions
				Camera-mount Lighting Controller FLV-TCC Series	Analog Lighting Controller FLV-ATC Series	
FLV-FR114W	White	3.2	270	0	0	A
FLV-FR114R	Red	2.4	270	0	0	A
FLV-FR114B	Blue	3.2	270	0	0	A
FLV-FR150W	White	4.8	500	0	0	В
FLV-FR150R	Red	2.9	500	0	0	В
FLV-FR150B	Blue	4.8	500	0	O	В

\*: The table shows whether each Lighting can be connected to Lighting Controllers. When multiple Lightings are connected to a Lighting Controller, make sure that the total electricity of all connected Lightings does not exceed the electricity of connectable lighting of each Lighting Controller. ○: Connectable. Light can be continuously emitted.

Connectable. Light can be emitted only while the trigger is input.
 X: Not connectable



# **Shadowless Lighting FLV-FP Series**

#### **Order Information**

Model	Light Color	Electricity (W)	Weight (g)	Connectable Lighting		
				Camera-mount Lighting Controller FLV-TCC Series	Analog Lighting Controller FLV-ATC Series	Dimensions
FLV-FP130W	White	6.8	320	0	0	A
FLV-FP130R	Red	6	320	0	0	A
FLV-FP130B	Blue	6.8	320	0	0	A

\*: The table shows whether each Lighting can be connected to Lighting Controllers. When multiple Lightings are connected to a Lighting Controller, make sure that the total electricity of all connected Lightings does not exceed the electricity of connectable lighting of each Lighting Controller. O: Connectable. Light can be continuously emitted.

 $\bigcirc$ : Connectable. Light can be emitted only while the trigger is input. X: Not connectable



# **Shadowless Lighting FLV-FQ Series**

#### **Order Information**

Model		Electricity	Weight (g)	Connectable Lighting		
	Light Color	(W)		Camera-mount Lighting Controller FLV-TCC Series	Analog Lighting Controller FLV-ATC Series	Dimensions
FLV-FQ48W	White	1.8	100	0	0	A
FLV-FQ48R	Red	1.1	100	0	0	A
FLV-FQ48B	Blue	1.8	100	0	O	А

\*: The table shows whether each Lighting can be connected to Lighting Controllers. When multiple Lightings are connected to a Lighting Controller, make sure that the total electricity of all connected Lightings does not exceed the electricity of connectable lighting of each Lighting Controller. O: Connectable. Light can be continuously emitted.

 $\bigcirc$ : Connectable. Light can be emitted only while the trigger is input. X: Not connectable



# Lightings FLV Series

# Direct Back Lighting FLV-DB Series

## **Order Information**

		Electricity (W)	Weight (g)	Connectable Lighting	g Controller *	
Model	Light Color			Camera-mount Lighting Controller FLV-TCC Series	Analog Lighting Controller FLV-ATC Series	Dimensions
FLV-DB3729W	White	0.9	50	0	0	A
FLV-DB3729R	Red	0.9	50	0	0	A
FLV-DB3729B	Blue	0.9	50	0	0	A
FLV-DB10181W	White	8	160	0	0	В
FLV-DB10181R	Red	4.8	160	0	0	В
FLV-DB10181B	Blue	8	160	0	0	В
FLV-DB130130W	White	15.2	270	×	O	С
FLV-DB130130R	Red	10.1	270	0	0	С
FLV-DB130130B	Blue	15.2	270	×	0	С
FLV-DB212152W	White	28.8	510	×	0	D
FLV-DB212152R	Red	17.3	510	×	O	D
FLV-DB212152B	Blue	28.8	510	×	0	D

\*: The table shows whether each Lighting can be connected to Lighting Controllers. When multiple Lightings are connected to a Lighting Controller, make sure that the total electricity of all connected Lightings does not exceed the electricity of connectable lighting of each Lighting Controller. ©: Connectable. Light can be continuously emitted.

: Connectable. Light can be emitted only while the trigger is input.

X: Not connectable



# Edge Type Lighting FLV-FB Series

### **Order Information**

		Electricity	Woight	Connectable Lighting	J Controller *	
Model	Light Color	(W)	(g)	Camera-mount Lighting Controller FLV-TCC Series	Analog Lighting Controller FLV-ATC Series	Dimensions
FLV-FB5050W	White	1.8	80	0	O	А
FLV-FB5050R	Red	0.9	80	$\bigcirc$	O	А
FLV-FB5050B	Blue	1.8	80	0	0	А
FLV-FB7070W	White	1.8	90	0	O	В
FLV-FB7070R	Red	1.8	90	$\bigcirc$	O	В
FLV-FB7070B	Blue	1.8	90	$\bigcirc$	O	В
FLV-FB9090W	White	3.4	160	$\bigcirc$	O	С
FLV-FB9090R	Red	1.8	160	$\bigcirc$	O	С
FLV-FB9090B	Blue	3.4	160	$\bigcirc$	O	С
FLV-FB130130W	White	5.3	230	0	0	D
FLV-FB130130R	Red	2.7	230	$\bigcirc$	O	D
FLV-FB130130B	Blue	5.3	230	0	0	D
FLV-FB200200W	White	6.8	710	$\bigcirc$	O	E
FLV-FB200200R	Red	5.1	710	0	O	E
FLV-FB200200B	Blue	6.8	710	0	0	E

\*: The table shows whether each Lighting can be connected to Lighting Controllers. When multiple Lightings are connected to a Lighting Controller, make sure that the total electricity of all connected Lightings does not exceed the electricity of connectable lighting of each Lighting Controller. ©: Connectable. Light can be continuously emitted. C: Connectable. Light can be emitted only while the trigger is input. X: Not connectable



# Lightings Standard Models FLV Series

# **Edge Type Coaxial Lighting FLV-FX** Series

## **Order Information**

	Light Color	Electricity (W)	Weight (g)	Connectable Lighting	g Controller *	Dimensions
Model				Camera-mount Lighting Controller FLV-TCC Series	Analog Lighting Controller FLV-ATC Series	
FLV-FX100W	White	3.9	180	0	0	A
FLV-FX100R	Red	2	180	0	0	A
FLV-FX100B	Blue	3.9	180	0	0	A
FLV-FX143W	White	5.3	240	0	0	В
FLV-FX143R	Red	3.9	240	0	0	В
FLV-FX143B	Blue	5.3	240	O	0	В

\*: The table shows whether each Lighting can be connected to Lighting Controllers. When multiple Lightings are connected to a Lighting Controller, make sure that the total electricity of all connected Lightings does not exceed the electricity of connectable lighting of each Lighting Controller. ○: Connectable. Light can be continuously emitted.

Connectable. Light can be emitted only while the trigger is input. X: Not connectable



# **Dome Lighting FLV-DD Series**

#### **Order Information**

	Light Color	Electricity (W)	Weight (g)	Connectable Lighting	J Controller *	
Model				Camera-mount Lighting Controller FLV-TCC Series	Analog Lighting Controller FLV-ATC Series	Dimensions
FLV-DD70W	White	2	130	0	0	A
FLV-DD70R	Red	2	130	0	0	A
FLV-DD70B	Blue	2	130	0	0	A
FLV-DD100W	White	14.4	210	0	0	В
FLV-DD100R	Red	9.6	210	0	0	В
FLV-DD100B	Blue	14.4	210	0	0	В
FLV-DD150W	White	14.4	490	0	0	С
FLV-DD150R	Red	9.6	490	0	0	С
FLV-DD150B	Blue	14.4	490	0	0	С

\*: The table shows whether each Lighting can be connected to Lighting Controllers. When multiple Lightings are connected to a Lighting Controller, make sure that the total electricity of all connected Lightings does not exceed the electricity of connectable lighting of each Lighting Controller.

O: Connectable. Light can be continuously emitted.

Connectable. Light can be emitted only while the trigger is input. X: Not connectable



# High-power Spot Lighting FLV-EP08 Series

#### **Order Information**

Model		Electricity	Waight	Connectable Lighting		
	Light Color	(W)	(g)	Camera-mount Lighting Controller FLV-TCC Series	Analog Lighting Controller FLV-ATC Series	Dimensions
FLV-EP0803W	White	2.3	80	×	0	A
FLV-EP0803R	Red	2.3	80	×	0	А
FLV-EP0803B	Blue	2.3	80	×	0	A

\*: The table shows whether each Lighting can be connected to Lighting Controllers. When multiple Lightings are connected to a Lighting Controller, make sure that the total electricity of all connected Lightings does not exceed the electricity of connectable lighting of each Lighting Controller. O: Connectable. Light can be continuously emitted.

 $\bigcirc$  : Connectable. Light can be emitted only while the trigger is input. X: Not connectable



# **Spot Lighting LV-EP50 Series**

#### **Order Information**

		Electricity Weigh		Connectable Lighting			
Model	Light Color	(W)	(g)	Camera-mount Lighting Controller FLV-TCC Series	Analog Lighting Controller FLV-ATC Series	Dimensions	
FLV-EP50W	White	2.3	200	×	0	A	
FLV-EP50R	Red	2.3	200	×	0	A	

\*: The table shows whether each Lighting can be connected to Lighting Controllers. When multiple Lightings are connected to a Lighting Controller, make sure that the total electricity of all connected Lightings does not exceed the electricity of connectable lighting of each Lighting Controller. O: Connectable. Light can be continuously emitted.

Connectable. Light can be emitted only while the trigger is input.
 X: Not connectable



Camera-mount Lighting Controller for FLV Series

Camera-mount Compact Lighting Controller to Perform Multistage Control with up to 4 Lightings



# **Product features**

- Compact design helps save space in the control panel.
- Lighting intensity can be maintained even with long wiring distances.
- No complicated wiring to the Vision Sensor is required.

#### <Standard Lighting System>



intensity does not decrease even if the Controller and Lighting are separated.

#### **Order Information**

	Number of Connectable	Applicable	Lighting	Power Supply Voltage	Electricity of	Luminance Control Method	
Model	Lightings	Standard Lighting FLV Series *1	Spot Lighting FLV-EP Series		Connectable Lighting		
FLV-TCC1	1ch	0	-	24 \/DC *2	15\W max	Digital #3	
FLV-TCC4	4ch	0	-	24 000 42	15 W IIIdX.	Digital 43	

\*1. Standard lighting is all FLV-series Lightings excluding the FLV-EP-series Spot Lightings.

\*2. If the total power consumption of Lightings is 7.5 W or less, an external power supply is not required because the power is supplied from the Camera.

**\*3**. Luminance can be controlled by setting from the Vision Sensor Controller.

Standard Models FLV Series

# Specification

Item		Model	FLV-TCC1	FLV-TCC4			
Number	of connectable	lightings	1	4			
Applicat	ole Lighting		FLV series (However, FLV-EP series is exclu	uded.)			
Applicat	ole Cameras		FH-S series, FZ-S series				
Applicat	ole Image Senso	or Controller	FH series, FZ5 series				
Input Vo	ltage		Supplied from applicable camera (13 V) or external power supply (24 V)				
External	power supply	voltage	24 VDC $\pm$ 10% (including ripple)				
		Recommended power supply	Model S8VS-06024 (manufactured by OMRON, 24 VDC, 2.5 A, 60 W)				
Connect	able lighting						
13 V	DC for camera s	supply					
C	Continuous ligh	ting	7.5 W max.	4ch total 7.5 W max.			
Т	Trigger lighting Simultaneous lighting		7.5 W max.	4ch total 7.5 W max.			
		Individual lighting		7.5 W max. for 1ch			
24 VDC for external supply		supply					
C	Continuous ligh	ting	7.5 W max.	4ch total 7.5 W max.			
Т	rigger lighting	Simultaneous lighting	No duty restriction: 7.5 W max. Duty by 50%: 15 W max.	No duty restriction: 4ch total 7.5 W max. Duty by 50%: 4ch total 15 W max.			
		Individual lighting		No duty restriction: 7.5 W max. for 1ch Duty by 50%: 15 W max. for 1ch			
Drive me	ethod		Contrast voltage method				
Lighting	method		Trigger lighting, Continuous lighting				
Luminar	nce Control Met	hod	Duty light adjustment or voltage light adjustment Duty light adjustment: PWM frequency of 100 kHz, light adjustment of 255 levels Voltage light adjustment: Light adjustment of 255 levels (all are set with image sensor controller)				
Trigger I	lighting		Lighting in synchronization with trigger input timing from the controller. (auto setting in accordance with shutter speed)				
	Trigger light	ing delay time	Ton: 30 μs max.				
	Lighting dur	ation setting	Synchronized with the shutter speed of the camera (when the trigger is illuminated)				
	Lighting time	e control	Set with image sensor controller, or synchron	nized with shutter speed			
External	Interface		Camera connection cable (directly connected with the main unit)				
Insulatio	on Resistance		0.5 MΩ (100 VDC)				
Ambient	Temperature		Operating: 0 to +50°C, Storage: -15 to +60°C	C (with no icing or condensation)			
Ambient	Humidity		Operating and storage: 35% to 85% (with no	condensation)			
Degree of	of Protection		IP20 (IEC60529)				
Vibratio	n Resistance (d	estructive)	10 to 150 Hz, (0.7 mm double amplitude) 80 min each in X, Y, and Z directions				
Shock Resistance (destructive)			150 m/s <sup>2</sup> 3 times each in 6 directions (up/do	wn, left/right, forward/backward)			
Materials			Case: Aluminum, Cable: PVC				
Weight			Approx: 120 g (including the camera mount plate)	Approx. 130 g (including the camera mount plate)			
Accesso	ories		Instruction manual, Camera Mount plate, mounting screws (M2 set screw $\times$ 4, M2 flat head screw $\times$ 4, M4 flat head screw $\times$ 4)				

#### **Part Names and Functions**



No.	Name	Description
1	Lighting connecting connector	Connects the LED lighting.
2	Camera connecting cable	Connects to the extension connector of the camera.
3	24 V external power supply input terminal block	Connects the 24 VDC power supply.
4	Mounting hole for fixing screw	Holes to mount the screws to secure the Lighting Controller to a mounting plate or device.

## Mounting the Controller to the Camera

The Lighting Controller can be mounted to the Camera using the provided Camera Mount plate. Mounting directions are: (1) Upper mount, (2) Right side mount, (3) Left side mount.

(1) Top/Bottom mount (2) Right side mount (3) Left side mount



#### Dimensions •Lighting Controller



#### •Camera mount plate (provided)



Standard Models FLV Series

# **Analog Lighting Controller for FLV Series FLV-ATC** Series

# **Stationary Lighting Controller**



# **Product features**

- Suitable for small installation space near the Camera
- Light emission trigger can be input directly even without Omron's Vision Sensor.

#### **Order Information**

Applicable Lighting Model *2		Number of Connectable Lightings	Power Supply Voltage	Electricity of Connectable Lighting	Luminance Control Method	
Standard Lighting *1	FLV-ATC21024	2ch		40W/max		
Stanuaru Lighting 🗛 I	FLV-ATC41024	4ch	100 to 240 VAC	4000 max.	Analog	
For Spot Lighting	FLV-ATC10405	1ch	100 10 240 VAC	3W max.	Analog	
For Spot Lighting	FLV-ATC40405	4ch	1	12W max.		

\*1. Standard lighting is all FLV-series Lightings excluding the FLV-EP-series Spot Lightings. \*2. The standard plug is A type. C, B, B3, SE, BF, and O types are also available. (The suffix "-C", "-B", "-B3", "-SE", "-BF", or "-O" is added to the model name.)

# Standard Lighting FLV-ATC21024/-ATC41024

#### **Parts Names and Functions**



No.	Name	Description
1	Main power supply	Starts up the Controller when it is turned ON.
2	Lighting adjustment volume	Rotating the volume clockwise increases the emission intensity or counterclockwise decreases it.
3	AC power supply input connector	A terminal to supply AC power. Connect the provided AC input cable.
4	Lighting connector	Connects an LED lighting.
5	Terminal block for trigger input	A terminal block for lighting illumination trigger input from outside to each lighting.
6	Lighting mode switching button	Illumination mode switch button is ON (The button is pushed.): Short-circuiting (+) and (-) of TR1 to TR4 respectively makes the trigger input status ON, turning the light ON. Releasing (+) and (-) makes the status OFF, turning the light OFF.
		Illumination mode switch button is OFF (The button is not pushed.): Short-circuit (+) and (-) of TR1 to TR4 respectively makes the trigger input status OFF, turning the light OFF. Releasing (+) and (-) makes the status OFF, turning the light ON.
7	Frame ground terminal	A terminal for frame ground. Connect the ground line.

## Analog Lighting Controller for FLV Series FLV-ATC Series

#### **Specifications**

Item Model	FLV-ATC21024-	FLV-ATC41024-			
Number of connectable lightings	1	4			
Applicable lighting	FLV series (However, FLV-EP series is excluded.)				
Power supply voltage	100 to 240 VAC				
Electricity of connectable lighting	2ch total 40 W max. 30 W max. for 1ch	4ch total 40 W max. 30 W max. for 1ch			
Drive method	Constant voltage method				
Lighting method	Trigger lighting, Continuous lighting				
Luminance control method	Voltage light adjustment: 14.0 to 24.0 V				
Trigger lighting	Lighting in synchronization with input from the trigger input terminal				
Trigger lighting delay time	Ton: 100 μs max.				
External interface	Trigger input terminal block				
Dielectric strength	AC 1500 V 50/60 Hz 1 min				
Insulation resistance	20 MΩ (500 VDC)				
Ambient temperature	Operating: 0 to +50°C, Storage: -15 to +60°	C (with no icing or condensation)			
Ambient humidity	Operating/storage: 35% to 85% (with no cor	ndensation)			
Degree of protection	IP20 (IEC60529)				
Vibration resistance (destructive)	10 to 150 Hz, (0.2 mm double amplitude) 80	) min each in X, Y, and Z directions			
Shock resistance (destructive)	150 m/s <sup>2</sup> 3 times each in 6 directions (up/down, left/right, forward/backward)				
Materials	Case: Aluminum				
Weight	Approx. 800 g				
Accessories	Instruction manual, AC input cable *1				

\*1: The suffixed symbol of the model name means the plug shape of the accessory cable. A model name with no suffix means type A.

#### Connection with external trigger input terminal block

• Connection of this terminal block is not required if external lighting issuance trigger is not used.

#### <Connection of trigger input terminal block>



\* Current flowing through the short circuit is less than 2 mA.

#### ●FLV-ATC21024-□



# • FLV-ATC41024-



Illumination mode switch button is ON (The button is pushed.)

Short-circuiting (+) and (-) of TR1 to	TR4	respectively	makes	the	trigger
input status ON, turning the light ON.					

Releasing (+) and (-) makes the status OFF, turning the light OFF.

Illumination mode switch button is OFF (The button is not pushed.)

Short-circuit (+) and (-) of TR1 to TR4 respectively makes the trigger input status OFF, turning the light OFF.

Releasing (+) and (-) makes the status ON, turning the light ON.

#### [Important]

- Make sure that excessive force is not imposed on the wire and terminal block.
- Do not install the product in which loads are constantly applied to the terminal block such as the wire being under tension.
- When wiring the terminal block, use an applicable cable (AWG 14 to 24, tip processing length: 7 mm).

Standard Models FLV Series

# Dimensions (Unit: mm)

#### ●FLV-ATC21024-□



●FLV-ATC41024-□

# •For Spot Lighting FLV-ATC10405/-ATC40405

## **Parts Names and Functions**



No.	Name	Description
1	Main power supply	Starts up the Controller when it is turned ON.
2	Lighting adjustment volume	Rotating the volume clockwise increases the emission intensity or counterclockwise decreases it.
3	AC power supply input connector	A terminal to supply AC power. Connect the provided AC input cable.
4	Lighting connector	Connects an LED lighting.
5	Terminal block for trigger input	A terminal block for lighting illumination trigger input from outside to each lighting.
6	Frame ground terminal	A terminal for frame ground. Connect the ground line.

# **Specifications**

ItemModel	FLV-ATC10405-	FLV-ATC40405-			
Number of connectable lightings	1	4			
Applicable lighting	FLV-EP series				
Power supply voltage	100 to 240 VAC				
Electricity of connectable lighting	3 W max. 4ch total 12 W max. 3 W max. for 1ch				
Drive method	Constant current method				
Lighting method	Trigger lighting, Continuous lighting				
Luminance control method	uminance control method Current light adjustment ~0.4 A				
Trigger lighting	Turning the light off in synchronization with input from the trigger input terminal				
Trigger lighting delay time	Ton: 100 μs max.				
External interface	Trigger input terminal block				
Dielectric strength	AC 1500 V 50/60 Hz 1 min				
Insulation resistance	20 MΩ (500 VDC)				
Ambient temperature	Operating: 0 to +50°C, Storage: -15 to +60°C (w	ith no icing or condensation)			
Ambient humidity	Operating/storage: 35% to 85% (with no condens	sation)			
Degree of protection	IP20 (IEC60529)				
Vibration resistance (destructive)	10 to 150 Hz, (0.2 mm double amplitude) 80 min each in X, Y, and Z directions				
Shock resistance (destructive)	150 m/s <sup>2</sup> 3 times each in 6 directions (up/down, left/right, forward/backward)				
Materials	Case: Aluminum				
Weight	Approx. 800 g				
Accessories	Instruction manual, AC input cable *1				

\*1: The suffixed symbol of the model name means the plug shape of the accessory cable. A model name with no suffix means type A.

#### Connections with external trigger input terminal block

• Connection of this terminal block is not required if external lighting issuance trigger is not used.

#### <Connection of trigger input terminal block>



\* Current flowing through the short circuit is less than 1 mA.

#### ●FLV-ATC10405-□





Trigger input terminal block CH1 to CH4

Short-circuiting (+) and (-) of TR1 to TR4 respectively makes the trigger input status OFF, turning the light OFF. Releasing (+) and (-) makes the status ON, turning the light ON.

#### [Important]

- Make sure that excessive force is not imposed on the wire and terminal block.
- Do not install the product in which loads are constantly applied to the terminal block such as the wire being under tension.
- When wiring the terminal block, use an applicable cable (AWG 14 to 24, tip processing length: 7 mm).

## Dimensions (Unit: mm)



# Bar Lighting FL-BR Series

# The highest level of brightness in the industry. These Bar Lighting are structured for adaptable wiring and mounting.



# Illumination Structure



# **Lighting Intensity Distribution Characteristics**





#### Wide Area Model (FL-BR9120W)

X axis (long axis)







## Application

Standard Lighitng



It is difficult to read characters with low contrast.

(TRACE)

ABCDE

**FL Series** 

Sharp images are created of both two-dimensional codes and characters.

# Order Information

Standard Models	Model	Light color
Wide Area Model	FL-BR5020W	
High-brightness Models	FL-BR5020W-H	
Wide Area Model	FL-BR9120W	
High-brightness Models	FL-BR9120W-H	WINE LEDS
Wide Area Model	FL-BR13120W	
High-brightness Models	FL-BR13120W-H	

#### **Ratings and Specifications**

Model	Wide Area Model	High-brightness Models	Wide Area Model	High-brightness Models	Wide Area Model	High-brightness Models
	FL-BR5020W	FL-BR5020W-H	FL-BR9120W	FL-BR9120W-H	FL-BR13120W	FL-BR13120W-H
Light source			White	LEDs		
Vibration resistance		10 to 150 Hz (Doub	le amplitude: 0.7 mn	n), 80 min each in X	, Y, and Z directions	
Shock resistance			150 m/s <sup>2</sup> 3 times e	ach in 6 directions		
Ambient temperature		Operation: 0 to 4	0°C, Storage: -15 to	$60^{\circ}\text{C}$ (with no icing	or condensation)	
Ambient humidity		Operatio	n or storage: 35% to	85% (with no conde	ensation)	
Ambient atmosphere			No corros	ive gases.		
Degree of protection			IEC602	59 IP20		
Weight	Appro	x. 40g	Appro	x. 70g	Approx	. 100g
Materials	Light: Case: Aluminum; Cover, side parts, and lens: Heat resistant polyvinyl chloride; Connector: Thermoplastic resin with glass					
LED Class	Class2 (JIS C 6802:2005)					
Accessories			Instructio	n manual		
The color of white LEDs can vary due to intrinsic characteristics						

Confirm suitability for the application in advance.

## Dimensions (Unit: mm)



# Direct Ring Lighting FL-DR Series

# Clear Images WITH Industry's Top Level of Brightness and a Illumination over a Wide Field of View

Lighting High-brightness Models



#### Illumination Structure



## Lighting Intensity Distribution Characteristics

High-brightness Models (FL-DR50W-H)



Wide Area Model (FL-DR50W)



# Application

Standard Lighitng



Faster lines make it necessary to increase shutter speeds, but then the clarity of workpiece images decreases.

FL series



More than sufficient brightness is provided for high-speed lines.

# **Order Information**

Standard Models	Model	Light color
Wide Area Model	FL-DR32W	
High-brightness Models	FL-DR32W-H	
Wide Area Model	FL-DR50W	
High-brightness Models FL-DR50W-H		
Wide Area Model	FL-DR90W	
High-brightness Models	FL-DR90W-H	

#### **Ratings and Specifications**

Model	Wide Area Model	High-brightness Models	Wide Area Model	High-brightness Models	Wide Area Model	High-brightness Models
	FL-DR32W	FL-DR32W-H	FL-DR50W	FL-DR50W-H	FL-DR90W	FL-DR90W-H
Light source		White LEDs				
Vibration resistance		10 to 150 Hz (Doub	le amplitude: 0.7 mn	n), 80 min each in X	, Y, and Z directions	
Shock resistance	150 m/s <sup>2</sup> 3 times each in 6 directions					
Ambient temperature	Operation: 0 to 40°C, Storage: -15 to 60°C (with no icing or condensation)					
Ambient humidity	Operation or storage: 35% to 85% (with no condensation)					
Ambient atmosphere	No corrosive gases.					
Degree of protection		IEC60259 IP20				
Weight	Approx. 25g Approx. 30g Approx. 70g Approx. 80g				Approx. 80g	
Materials	Light: Case: Aluminum; Cover, side parts, and lens: Heat resistant polyvinyl chloride; Connector: Thermoplastic resin with glass					
LED Class	Class2 (JIS C 6802:2005)					
Accessories	Instruction manual					
The color of white LEDs can vary due to intrinsic characteristic				insic characteristics		

The color of white LEDs can vary due to intrinsic characteristic Confirm suitability for the application in advance.

# Dimensions (Unit: mm)





# Stationary Lighting Controller FL-STC Series

The smallest body in the industry is combined with the industry's longest cable at 25 m. Install in essentially any location.

Two-channel models



One-channel models

## **Product features**

#### • Easy Control and Adjustment of the Lighting

With a compact design small enough to fit in the palm of your hand, the Controller can be built into the control panel or in the gap between production lines.

By using the longest lighting cable in the industry (25 m), the Controller can be installed along with the image processing monitor in a variety of locations. It is possible to adjust the lighting while looking at the screen.

#### Connect to a Remote Control Panel

# Mount to a DIN Rail underneath the Line or in the Gap between Tables





#### Lighting Control without Programming

This enables light emission synchronized with the camera using essentially any trigger, such as a photoelectric sensor. The Controller be connected to an image processing device to control lighting without any programming on a PLC.

#### [ Control Output ]

- PNP/NPN compatible
- Power source: 24 V
- [Lighting Emission Controls]
- Lighting triggers can be used individually for each channel.
- Lighting delay and lighting time can be controlled.

#### Intuitive Digital Light Controls

Digital adjustment of light emission makes it easy to reproduce the lighting environment after line switchovers.



28

#### **Order Information**

Standard Models	Model	I/O specifications	Input voltage
One channel models	FL-STC10	NPN	
One-channel models	FL-STC15	PNP	
Two-channel models	FL-STC20	NPN	24 VDC
	FL-STC25	PNP	

#### **Ratings and Specifications**

Product name		One-channel models Two-channel models		nel models	
I/O type		NPN	PNP	NPN	PNP
Model		FL-STC10	FL-STC15	FL-STC20	FL-STC25
Power supply volt	age	24 VDC±10% (including ripple)			
Power consumption		36 W, 1.5 A max. (including the lighting section)		72 W, 3 A max. (including the lighting section)	
Number of output	channels		1		2
Applicable lights			FL- Se	eries *1	
Light control modes	Continuous light emission mode	While the St P	robe Controller power sou WM frequency: 100 kHz, I	rce is ON, light is continuo _ight adjustment: 400 leve	usly emitted. Is
	Triggered light emission mode	Light emission is synchronized with an external trigger input. Light emission: Continuous while the trigger is input, or 0.1 to 99.9 ms (set in 0.1-ms increments) PWM frequency: 100 kHz, Light adjustment: 400 levels			nput. : in 0.1-ms increments) Is
	Strobe light emission mode	Light emission is synchronized with the external trigger input, but twice the amount of light is emitted in comparison with the trigger light emission mode. Light emission pulse width: 0.01 to 5 ms (light adjustment: 500 levels equivalent)			nount of light is emitted in els equivalent)
Light adjustment setting	Operation on the light	Light adjustment mode settings and light adjustment value input: slide switch and directional pad			tch and directional pad
	Remote operation	Light adjustment value input: 9-bit binary input			
External interface		Parallel I/O connector (	D-sub 15-pin), Terminal bl source voltage inp	ock (external trigger input ut with 2 terminals)	with 2 terminals, power
Ambient temperat	ure	Operation:	0 to 40°C, Storage: -15 to	60°C (with no icing or cor	ndensation)
Ambient humidity		Op	peration or storage: 35% to	85% (with no condensati	on)
Vibration resistan	се	10 to 150 Hz	(Double amplitude: 0.7mm	n), 80 min each in X, Y, an	d Z directions
Shock resistance	Shock resistance         150 m/s² 3 times each in 6 direction (up-down, left-right, front-back)			nt-back)	
Materials	Materials Case: PC				
Degree of protecti	ion	IEC60529 IP20			
Weight		Approx. 100 g			
Accessories			Instruction manual, Ter	minal block Connector	

(\*1) Ask your OMRON representative for details on applicable models.

#### **Dimensions (Unit: mm)**



h-brightness Models

eries

#### **I/O Circuit Diagrams**



Terminal block	NPN type (FL-STC20/10)				
→ 1 TRIG1 2 TRIG2 (*2) 3 24VDC	Terminal block				
4 0V	ļ				
	V				
Load					
DI11 SEL					
DI12 SAVE					
DI13 TRIG1					
DI14 TRIG2					

(\*2) no use for FL-STC10

#### •Electrical Specifications

Output circuit	Input circuit
NPN Open-collector 30VDC	ON: Connected to 0 V or 1.5 V
50mA max.	max.
ON: residual voltage 1.2V max.	OFF: Open
OFF: leakage current 0.1mA	(Leakage current: 0.1 mA max.)
max.	· - /



(\*2) no use for FL-STC15

#### •Electrical Specifications

Output circuit	Input circuit
PNP Open-collector 50mA max. ON: residual voltage 1.2V max. OFF: leakage current 0.1mA max.	ON: Connected to power supply voltage or power supply voltage -1.5 V max. OFF: Open (Leakage current: 0.1 mA max.)

#### Wiring diagram

Pin Arrangement	Pin No.	Signal	Signal direction	Function	
	DI1	D1	Input         Bit 1 of light control data (least significant bit)         (1)CONT/TRIG Mode Light control data is specified using 9 bits of	(1)CONT/TRIG Mode Light control data is specified using 9 bits of binary	
	DI2	D2	Input	Bit 2 of light control data	data from D1 to D9.
DI6 DI7 DI8 DI9 DI10 DI1 DI2 DI3 DI4 DI5	DI3	D3	Input	Bit 3 of light control data	400 (binary 000000001 to 110010000).
	DI4	D4	Input	Bit 4 of light control data	(2)STB Mode
	DI5	D5	Input	Bit 5 of light control data	Strobe light emission data is specified in 9 bits of
	DI6	D6	Input	Bit 6 of light control data	the 500 values from 0.01 to 5.00 ms (binary
	DI7	D7	Input	Bit 7 of light control data	000000001 to 111110100).
	DI8	D8	Input	Bit 8 of light control data	Each bit is 1 for ON and 0 for OFF (open).
	DI9	D9	Input	Bit 9 of light control data (most significant bit)	
	DI10	CLR	Input	Error reset input. Errors are (open) to ON.	e reset when the error reset input changes from OFF
	DI11	SEL	Input	Lighting control channel se OFF (open) specifies chan	lection input. nel 1, ON specifies channel 2.
	DI12	SAVE	Input	The light control data (D1 to changes from OFF (open)	b D9) is saved in the built-in memory when the input to ON.
	DI13	TRIG1	Input	Inputs the light emission tri	gger signal for channel 1.
	DI14	TRIG2	Input	nput Inputs the light emission trigger signal for channel 2. (*)	
	DO1	ERR	output	Turns ON when an error or	ccurs.

\* An input with the same function as the lighting emission trigger input is also available on the terminal block (pins 1 and 2). When using the trigger input, connect the input line only to the parallel connector or only to the terminal block. It is not possible to use both input lines at the same time.

30

Camera-mount Lighting Controller for FL Series

# Camera-mount Compact Lighting Controller Which Requires No Power Supply Nor Lighting Control



lodels

# **Product features**

- No separate power supply is required because the power is supplied from the Camera.
- Light is emitted when a trigger signal is received from the Camera.
- Simple connection between the Camera and the Lighting with a single cable



#### **Order Information**

Item	Model	Weight
Lighting Controller	FL-TCC1	Approx. 110 g
Camera Mounting Spacer	FL-TCC1-XSP	Approx. 10 g
Camera Mounting Attachment	FL-TCC1-XAT	Approx. 20 g

## **Ratings and Specifications**

#### Lighting Controller

Model		Lighting Controller
Model Name		FL-TCC1
Input Voltage	•	Supplied from compatible camera.
Compatible	Cameras	FH-S/SC/S02/SC02/S04/SC04, FZ-S/SC/S2M/SC2M/S5M2/SC5M2/SH/SHC/SF/SFC/SP/SPC and others. (*)
Compatible Controllers		FH Series, FZ5 Series, FZ4 Series, FZ3 Series (H900, H950, H700, H750, H300, H350, L350) and others. (*)
Currant Con	sumption	MAX 10W, 0.9A (Lighting Included)
Lighting Cha	nnel	1
Applicable L	ighting	FL-□ series
Luminance	Functions	PWM frequency: 100 KHz, Control step: 255 steps (configurable from the Controller)
Control Method	Trigger lighting	Lighting ON synchronized with trigger input timing from the Controller. (Auto setting in accordance with the shutter speed.)
Trigger lighting delay time		Ton: 30 μs max. (Trigger ready μs) Toff: 10 μs max.
External Inte	rface	Dedicated communication connector
Ambient Ten	nperature	Operating: 0 to +50°C, Storage: -15 to +60°C (with no icing or condensation)
Ambient Hur	nidity	Operating and storage: 35% to 85% (with no condensation)
Vibration res	istance	10 to 55 Hz, (0.7mm double amplitude) 80 min each in X, Y, and Z directions
Shock resist	ance	150 m/s <sup>2</sup> 3 times each in 6 directions (up/down, left/right, forward/backward)
Materials		Case: SECC, Cable: PVC
Degree of Pr	otection	IP20 (IEC60529)
Weight		Approx. 110 g
Accessories		Instruction sheet, Insulation Sheet, Mounting screw (M2 $ imes$ 6 mm) $ imes$ 4

\* Contact your OMRON sales representative for more information on model compatibility.



w III w

# Cable

#### For FL series

#### **Order Information**



Model	Cable Length	Weight
FL-XC1	1m	Approx. 50 g
FL-XC2	2m	Approx. 80 g
FL-XC3	3m	Approx. 120 g
FL-XC5	5m	Approx. 190 g

10m

25m

Extension Cable, Standard Cables

#### •Extension Cables, Flexible Cables

Model	Cable Length	Weight
FL-XC1R	1m	Approx. 60 g
FL-XC2R	2m	Approx. 100 g
FL-XC3R	3m	Approx. 150 g
FL-XC5R	5m	Approx. 240 g
FL-XC10R	10m	Approx. 500 g
FL-XC25R	25m	Approx. 1200 g

#### Parallel Cable

FL-XC10

FL-XC25

Model	Cable Length	Weight
FL-XCP2	2m	Approx. 180 g

#### Dimensions (Unit: mm) • Extension Cable



Parallel Cable

Approx. 400 g

Approx. 1000 g



Note 1. Depends on the cable length.

#### For FLV series

#### **Order Information**

Туре	Model	Cable Length	Dimensions
Extension Cable for Standard Lighting *1	FLV-XC1	1m	
	FLV-XC2	2m	^
	FLV-XC3	3m	
	FLV-XC5	5m	
Extension Cable for Spot Lighting	FLV-XC1EP	1m	
	FLV-XC2EP	2m	P
	FLV-XC3EP	3m	
	FLV-XC5EP	5m	
Branch Cable for Standard Lighting *1	FLV-XC1S2	1m	
	FLV-XC2S2	2m	C
	FLV-XC3S2	3m	
	FLV-XC5S2	5m	

\*1. Standard lighting is all FLV-series Lightings excluding the FLV-EP-series Spot Lightings.

### Dimensions (Unit: mm)



# **Diffusion Plates and Polarization Plates**

#### For FL series

#### **Order Information**



Diffusion Plates									
Standard Models	Model	Outer diameter (mm)	Weight						
	FL-BR5020DF	49.8×18×4	Approx. 5 g						
Bar Lighting	FL-BR9120DF	90.6×18×4	Approx. 10 g						
	FL-BR13120DF	131.4×18×4	Approx. 15 g						
Standard Models	Model	Outer diameter/Inner diameter/Thickness (mm)	Weight						
	FL-DR32DF	32/10/4	Approx. 5 g						
<b>Direct Ring Lighting</b>	FL-DR50DF	50/28/4	Approx. 10 g						
	FL-DR90DF	90/50/4	Approx. 15 g						

#### Polarization Plates

Standard Models	Model	Outer diameter/Inner diameter/Thickness (mm)	Weight
	FL-DR32PL	32/10/2	Approx. 3 g
Direct Ring Lighting	FL-DR50PL	50/28/2	Approx. 5 g
	FL-DR90PL	90/50/2	Approx. 15 g

#### For FLV series

## **Order Information**

#### Diffusion Plates

Standard Models	Model	Connectable Lighting
	FLV-DR12030DF	Direct Ring Lighting FLV-DR12030
	FLV-DR9215DF	Direct Ring Lighting FLV-DR9215
	FLV-DR9030DF	Direct Ring Lighting FLV-DR9030
	FLV-DR9000DF	Direct Ring Lighting FLV-DR9000
Direct Ring Lighting	FLV-DR7000DF	Direct Ring Lighting FLV-DR7000
	FLV-DR7030DF	Direct Ring Lighting FLV-DR7030
	FLV-DR6615DF	Direct Ring Lighting FLV-DR6615
	FLV-DR5030DF	Direct Ring Lighting FLV-DR5030
	FLV-DR3220DF	Direct Ring Lighting FLV-DR3220

#### Diffusion Plates

Standard Models	Model	Connectable Lighting
	FLV-BR48031DF	Bar Lighting FLV-BR48031
	FLV-BR38037DF	Bar Lighting FLV-BR38037
	FLV-BR21230DF	Bar Lighting FLV-BR21230
	FLV-BR21222DF	Bar Lighting FLV-BR21222
Bar Lighting	FLV-BR15020DF	Bar Lighting FLV-BR15020
	FLV-BR14030DF	Bar Lighting FLV-BR14030
	FLV-BR11222DF	Bar Lighting FLV-BR11222
	FLV-BR8532DF	Bar Lighting FLV-BR8532
	FLV-BR6022DF	Bar Lighting FLV-BR6022

#### Diffusion Plates

Standard Models	Model	Connectable Lighting
	FLV-DL15060DF	Low Angle Ring Lighting FLV-DL15060
Low Angle Ring Lighting	FLV-DL12060DF	Low Angle Ring Lighting FLV-DL12060
	FLV-DL7260DF	Low Angle Ring Lighting FLV-DL7260
	FLV-DL5890DF	Low Angle Ring Lighting FLV-DL5890

# **Mounting Brackets**

For	COLIDE
	361163

### **Order Information**

Standard Models	Model
Bar Lighting	FL-XBK1

# Dimensions (Unit: mm)



# Standard Lens SV-V Series

- Standard CCTV lens.
- Lineup of 9 models with focal lengths ranging from 6 to 100 mm.
- Locking set screws for focus and iris.
- More robust structure designed for machine vision.
- Lower distortion and higher resolution than previous CCTV lenses.



#### **Order Information**

Series	Model	Dimension	Focal distance (mm)	Focus (F No)	Field of view (V $\times$ H)	Closest distance (mm)	Filter size	Weight (g)	Total length (mm)	Maximum compatible CCD
	3Z4S-LE SV-0614V	A	6	1.4	42.3°× 54.6°	200	M27.0 P0.5	49	30	1/3 inch
C-mount	3Z4S-LE SV-0813V	В	8	1.3	44.6°× 57.3°	200	M25.5 P0.5	55	34	1/3 inch
Lens for	3Z4S-LE SV-1214V	С	12	1.4	21.9°× 38.9°	300	M27.0 P0.5	44	29.5	1/3 inch
image	3Z4S-LE SV-1614V	D	16	1.4	22.8°× 30.1°	400	M27.0 P0.5	34	24.5	1/3 inch
sensor	3Z4S-LE SV-2514V	E	25	1.4	14.9°× 19.8°	500	M27.0 P0.5	36	24	1/3 inch
(Recommend:	3Z4S-LE SV-3518V	F	35	1.8	10.8°X 14.4°	300	M27.0 P0.5	47	33.5	1/3 inch
FZ-S⊟/	3Z4S-LE SV-5018V	G	50	1.8	7.9°× 10.5°	300	M30.5 P0.5	67	37	1/3 inch
FH-S□)	3Z4S-LE SV-7527V	Н	75	2.7	4.9°×6.6°	1200	M30.5 P0.5	76	42	1/3 inch
	3Z4S-LE SV-10035V	I	100	3.5	4.0°× 5.3°	2000	M30.5 P0.5	79	43.9	1/3 inch

#### Dimensions

1-32 UNF (C -mount)



37

# High-resolution, Low-distortion Lens SV-H/VS-H1 Series

- High-resolution lens for megapixel camera.
- Lineup of 9 models for 2/3-inch cameras, with focal lengths ranging from 6 to 100 mm, and 5 models for 1-inch Cameras.
- Locking set screws for focus and iris.
- Bright F number of 1.4 for high-speed CMOS camera.
- Compact design but minimized decrease in distortion and brightness.



for 2/3-inch image sensor SV-H series



for 1-inch image sensor VS-H1 series

#### **Order Information**

Series	Model	Dimension	Focal distance (mm)	Focus (F No)	Field of view (V $\times$ H)	Closest distance (mm)	Filter size	Weight (g)	Total length (mm)	Maximum compatible CCD
	3Z4S-LE SV-0614H	A	6	1.4	56.8°× 71.5°	100	M40.5 P0.5	145	57.5	2/3 inch
	3Z4S-LE SV-0814H	В	8	1.4	44.9°× 57.6°	100	M35.5 P0.5	125	52.5	2/3 inch
C-mount	3Z4S-LE SV-1214H	С	12	1.4	30.2°× 39.6°	100	M27 P0.5	85	51	2/3 inch
2/3-inch	3Z4S-LE SV-1614H	D	16	1.4	23.1°× 30.6°	100	M27 P0.5	85	47.5	2/3 inch
image sensor	3Z4S-LE SV-2514H	E	25	1.4	15.0°× 20.0°	150	M27 P0.5	65	36	2/3 inch
	3Z4S-LE SV-3514H	F	35	1.4	10.8°× 14.3°	200	M35.5 P0.5	150	45.5	2/3 inch
FZ-S□2M/	3Z4S-LE SV-5014H	G	50	1.4	7.5°× 10.0°	300	M40.5 P0.5	170	57.7	2/3 inch
FZ-S□5M/ FH-S□02)	3Z4S-LE SV-7525H	Н	75	2.5	2/3"= 5.0° × 6.7° 1"= 7.3° × 9.7°	1200	M34.0 P0.5	85	49.5	1 inch
	3Z4S-LE SV-10028H	I	100	2.8	2/3"= 3.9° × 5.1° 1"= 5.6° × 7.5°	2000	M37.5 P0.5	105	66.5	1 inch
C-mount	3Z4S-LE VS-1214H1	J	12	1.4	44.0°× 56.9°	300	M35.5 P0.5	140	48	1 inch
Lens for	3Z4S-LE VS-1614H1	K	16	1.4	33.7°× 44.3°	300	M30.5 P0.5	110	42.5	1 inch
1-inch image	3Z4S-LE VS-2514H1	L	25	1.4	21.5°× 28.5°	300	M30.5 P0.5	90	33.5	1 inch
(Recommend:	3Z4S-LE VS-3514H1	М	35	1.4	15.6°× 20.7°	300	M30.5 P0.5	100	35	1 inch
FH-S□04)	3Z4S-LE VS-5018H1	N	50	1.8	11.0°X 14.6°	500	M40.5 P0.5	135	44.5	1 inch

# Dimensions













38

Lenses

# Vibrations and shocks resistant C-mount Lens

- Lineup of 7 models with focal lengths ranging from 15 to 75 mm.
- A fixation ring is used to fasten to the surface.
- Internal structure of the lens is designed to strengthen against vibration to achieve higher resistance to vibration than previous lenses, which allows the lens to be moved or to be used in a place subject to vibration.
- Install in narrow space without a locking set screw.

#### **Order Information**





#### Vibrations and shocks resistant C-mount Lens VS-MC Series

Series	Model	Dimension	Focal distance (mm)	Focus (F No.)	Maximum outer diameter: (mm)	Total length (mm)	Filter size	WD (mm)	Depth of field (mm)	Maximum compatible CCD
				Maximum				625.8	33.8	
	3Z4S-LE VS-MC50			aperture	31dia.	63.9	M27.0 P0.5	262.4	6.0	
		-						121.1	1.3	
\/ib.setie.se								625.8	75.6	
vibrations	3Z4S-LE VS-MC50-FNO56	F	50	5.6	31dia.	63.9	M27.0 P0.5	262.4	13.4	2/3 inch
resistant C-								121.1	2.9	
mount Lens	3Z4S-LE VS-MC50-FNO80			8	31dia.	63.9	M27.0 P0.5	625.8	108.0	
for 2/3-inch								262.4	19.2	
image sensor								121.1	4.1	
(Recommend:	3Z4S-LE VS-MC75			Maximum aperture	31dia.	105.5	M27.0 P0.5	563.0	17.7	
FZ-SL/FZ-								404.4	9.1	
S□2IVI/FZ- S□5M2/E7								153.8	1.3	
SHD/FH-SD/								563.0	26.1	
FH-S[02)	3Z4S-LE VS-MC75-FNO56	G	75	5.6	31dia.	105.5	M27.0 P0.5	404.4	13.4	2/3 inch
, , ,		-						153.8	1.9	
				8	31dia.	105.5	M27.0 P0.5	563.0	37.2	
	3Z4S-LE VS-MC75-FNO80							404.4	19.2	]
								153.8	2.7	











# Lens for small camera of Vision Sensor FZ series FZ-LES Series

• Lenses for small cameras: 12 x 12 mm pen-shaped camera and 17 mm thick flat camera.



#### **Order Information**

Model	Focal length	Brightness
FZ-LES3	3mm	F2.0
FZ-LES6	6mm	F2.0
FZ-LES16	16mm	F3.4
FZ-LES30	30mm	F3.4



# Non-telecentric Macro Lens **VS-MC Series**

- Lineup of 4 models with magnifications ranging from 1.0 to 0.1 and WD ranging from 325.5 to 82.4 mm.
- 16-mm-dia. simple mechanism with high resistance to vibration.



#### **Order Information**

Model	Dimension	Magnification	Field of vision *1 (V $\times$ H) mm	Dimension Effective FNO	O/I (mm)	WD (mm)	Depth of field *2	Resolution *3	TV distortion
3Z4S-LE VS-MC01-330	А	0.1	$66.0 \times 88.0$	4.43	364.5	325.5	35.4mm	30.5µm	0.01% max.
3Z4S-LE VS-MC03-180	В	0.3	$22.0 \times 29.3$	5.29	248.5	184.8	4.7mm	11.6µm	0.00% max.
3Z4S-LE VS-MC05-130	С	0.5	13.2 × 17.6	6.10	198.8	126.3	2.0mm	8.2µm	0.00% max.
3Z4S-LE VS-MC1-80	D	1.0	$6.6 \times 8.8$	8.14	176.8	82.4	0.7mm	5.5µm	0.00% max.

\*1 Calculated using the size of an image element (2/3 inch =  $6.6 \times 8.8$  mm).

\*2 Calculated using a permissible circle of confusion diameter of 0.04 mm.

\*3 Calculated using a wavelength of 550 nm.



# **Lens Option**

#### **Order Information**

#### **Polarizing Filter**

Model
3Z4S-LE SV-PL255
3Z4S-LE SV-PL270
3Z4S-LE SV-PL305



#### **Extension Tubes**

Model	Length (mm)
3Z4S-LE SV-EXR	7-piece set (40, 20, 10, 5, 2.0, 1.0, 0.5 mm)
* These Extension Tubes are also available	individually. Order using the following model

★ These Extension Tubes are also available individually. Order using the following model number, replacing the box with the desired length: 3Z4S-LE SV-EXR□. (0.5, 1, 2, 5, 10, 15, 20, 25, 30, 40, 50 mm)



#### **Extension Tubes for Small Digital CCD Cameras**

Model	Contents
FZ-LESR	Set of 3 tubes (15 mm, 10 mm, 5 mm) Maximum outer diameter: 12 mm dia.

#### **Rear Converter Lens**

Model	
3Z4S-LE SV-1.5X *1	
3Z4S-LE SV-2.0X *2	

- \*1 In the following lenses, it is necessary to use it together with the extension tubes of 5mm or more. SV-0614H, SV-0814H, SV-1214H, SV-
- SV-0614H, SV-0814H, SV-1214H, SV-2514H, SV-0614V, SV-0813V \*2 In the following lenses, it is necessary to
- use it together with the extension tubes of 5mm or more.

SV-0614H, SV-0814H, SV-1214H, SV-2514H, SV-0813V

#### Configuration





# Terms and Conditions of Sale

- 1. Offer; Acceptance. These terms and conditions (these "Terms") are deemed part of all quotes, agreements, purchase orders, acknowledgments, price lists, catalogs, manuals, brochures and other documents, whether electronic or in catalogs, manuals, brochures and other documents, whether electronic or in writing, relating to the sale of products or services (collectively, the "Products") by Omron Electronics LLC and its subsidiary companies ("Omron"). Omron objects to any terms or conditions proposed in Buyer's purchase order or other documents which are inconsistent with, or in addition to, these Terms. Prices: Payment Terms, All prices stated are current, subject to change without notice by Omron. Omron reserves the right to increase or decrease prices on any unshipped portions of outstanding orders. Payments for Products are due net 30 days unless otherwise stated in the invoice. Discounts, Cash discounts, if any, will apply only on the net amount of invoices sent to Buyer after deducting transportation charges, taxes and duties, and will be allowed only if (i) the invoice is paid according to Omron's payment terms and (ii) Buyer has no past due amounts.
- 2
- 3.
- and (ii) Buyer has no past due amounts. Interest. Omron, at its option, may charge Buyer 1-1/2% interest per month or the maximum legal rate, whichever is less, on any balance not paid within the stated terms.
- Orders. Omron will accept no order less than \$200 net billing. Governmental Approvals. Buyer shall be responsible for, and shall bear all 6 costs involved in, obtaining any government approvals required for the impor-tation or sale of the Products.
- Taxes. All taxes, duties and other governmental charges (other than general real property and income taxes), including any interest or penalties thereon, imposed directly or indirectly on Omron or required to be collected directly or 7. indirectly by Omron for the manufacture, production, sale, delivery, importa-tion, consumption or use of the Products sold hereunder (including customs duties and sales, excise, use, turnover and license taxes) shall be charged to and remitted by Buyer to Omron. <u>Financial.</u> If the financial position of Buyer at any time becomes unsatisfactory
- 8. <u>Einancial</u> If the financial position of Buyer at any time becomes unsatisfactory to Omron, Omron reserves the right to stop shipments or require satisfactory security or payment in advance. If Buyer fails to make payment or otherwise comply with these Terms or any related agreement, Omron may (without liabil-ity and in addition to other remedies) cancel any unshipped portion of Prod-ucts sold hereunder and stop any Products in transit until Buyer pays all amounts, including amounts payable hereunder, whether or not then due, which are owing to it by Buyer. Buyer shall in any event remain liable for all unpaid accounts unpaid accounts.
- <u>Cancellation</u>, <u>Etc.</u> Orders are not subject to rescheduling or cancellation unless Buyer indemnifies Omron against all related costs or expenses.
   <u>Force Majeure</u>. Omron shall not be liable for any delay or failure in delivery
- Force majeure. Other shall not be lable for any delay or lating in delivery resulting from causes beyond its control, including earthquakes, fires, floods, strikes or other labor disputes, shortage of labor or materials, accidents to machinery, acts of sabotage, riots, delay in or lack of transportation or the requirements of any government authority.
   Shipping: Delivery. Unless otherwise expressly agreed in writing by Omron: a. Shipments shall be by a carrier selected by Omron; Omron will not drop ship expert in "break down" situations.
- except in "break down" situations. b. Such carrier shall act as the agent of Buyer and delivery to such carrier shall
  - constitute delivery to Buyer; c. All sales and shipments of Products shall be FOB shipping point (unless oth-
- c. All sales and shipments of Products shall be FOB shipping point (unless otherwise stated in writing by Omron), at which point title and risk of loss shall pass from Omron to Buyer; provided that Omron shall retain a security interest in the Products until the full purchase price is paid;
  d. Delivery and shipping dates are estimates only; and
  e. Omron will package Products as it deems proper for protection against normal handling and extra charges apply to special conditions.
  12. Claims. Any claim by Buyer against Omron for shortage or damage to the Products occurring before delivery to the carrier must be presented in writing to Omron within 30 days of receipt of shipment and include the original transportation bill signed by the carrier received the Products
- portation bill signed by the carrier noting that the carrier received the Products from Omron in the condition claimed.
- <u>Warranties</u>. (a) <u>Exclusive Warranty</u>. Omron's exclusive warranty is that the Products will be free from defects in materials and workmanship for a period of twelve months from the date of sale by Omron (or such other period expressed 13 (b) <u>Limitations</u>. OMRON MAKES NO WARRANTY OR REPRESENTATION, EXPRESS OR IMPLIED, ABOUT NON-INFRINGEMENT, MERCHANTABIL-

# Certain Precautions on Specifications and Use

- Suitability of Use. Omron Companies shall not be responsible for conformity 1. with any standards, codes or regulations which apply to the combination of the Product in the Buyer's application or use of the Product. At Buyer's request. Omron will provide application of use of the Froduct. At Buyer's application of use of the product applicable third party certification documents identifying ratings and limitations of use which apply to the Product. This information by itself is not sufficient for a complete determination of the suitability of the Prod-uct in combination with the end product, machine, system, or other application or use. Buyer shall be solely responsible for determining appropriateness of the particular Product with respect to Buyer's application, product or system. the particular Product with respect to Buyers application, product or system. Buyer shall take application responsibility in all cases but the following is a non-exhaustive list of applications for which particular attention must be given: (i) Outdoor use, uses involving potential chemical contamination or electrical interference, or conditions or uses not described in this document. (ii) Use in consumer products or any use in significant quantities. (iii) Energy control systems, combustion systems, railroad systems, aviation systems, medical equipment, amusement machines, vehicles, safety equip-ment and installicitors cubications of the consumer to construct the construction.

inent, and installations subject to separate industry or government regulations. (iv) Systems, machines and equipment that could present a risk to life or prop erty. Please know and observe all prohibitions of use applicable to this Prod-

NEVER USE THE PRODUCT FOR AN APPLICATION INVOLVING SERIOUS RISK TO LIFE OR PROPERTY OR IN LARGE QUANTITIES WITHOUT ENSURING THAT THE SYSTEM AS A WHOLE HAS BEEN DESIGNED TO

ITY OR FITNESS FOR A PARTICULAR PURPOSE OF THE PRODUCTS. BUYER ACKNOWLEDGES THAT IT ALONE HAS DETERMINED THAT THE PRODUCTS WILL SUITABLY MEET THE REQUIREMENTS OF THEIR INTENDED USE. Omron further disclaims all warranties and responsibility of any type for claims or expenses based on infringement by the Products or oth-erwise of any intellectual property right. (c) <u>Buyer Remedy</u>. Omron's sole obli-gation hereunder shall be, at Omron's election, to (i) replace (in the form originally shipped with Buyer responsible for labor charges for removal or replacement thereof) the non-complying Product, (ii) repair the non-complying Product, or (iii) repay or credit Buyer an amount equal to the purchase price of the non-complying Product; provided that in no event shall Omron be responsi-ble for warranty, repair, indemnity or any other claims or expenses regarding the Products unless Omron's analysis confirms that the Products were prop-erly handled, stored, installed and maintained and not subject to contamina-tion, abuse, misuse or inappropriate modification. Return of any Products by tion, abuse, misuse or inappropriate modification. Return of any Products by Buyer must be approved in writing by Omron before shipment. Omron Compa-nies shall not be liable for the suitability or unsuitability or the results from the use of Products in combination with any electrical or electronic components, circuits, system assemblies or any other materials or substances or environments. Any advice, recommendations or information given orally or in writing, are not to be construed as an amendment or addition to the above warranty. See http://www.omron247.com or contact your Omron representative for published information.

- Iished information.
  Limitation on Liability: Etc. OMRON COMPANIES SHALL NOT BE LIABLE FOR SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, LOSS OF PROFITS OR PRODUCTION OR COMMERCIAL LOSS IN ANY WAY CONNECTED WITH THE PRODUCTS, WHETHER SUCH CLAIM IS BASED IN CONTRACT, WARRANTY, NEGLIGENCE OR STRICT LIABILITY. Further, in no event shall liability of Omron Companies exceed the individual price of the Product on which liability is asserted. 14
- Indemnities. Buyer shall indemnify and hold harmless Omron Companies and their employees from and against all liabilities, losses, claims, costs and expenses (including attorney's fees and expenses) related to any claim, inves-tigation, litigation or proceeding (whether or not Omron is a party) which arises 15 or is alleged to arise from Buyer's acts or omissions under these Terms or in any way with respect to the Products. Without limiting the foregoing, Buyer (at its own expense) shall indemnify and hold harmless Omron and defend or set-tle any action brought against such Companies to the extent based on a claim that any Product made to Buyer specifications infringed intellectual property rights of another party.
- rights of another party. <u>Property: Confidentiality.</u> Any intellectual property in the Products is the exclu-sive property of Omron Companies and Buyer shall not attempt to duplicate it in any way without the written permission of Omron. Notwithstanding any charges to Buyer for engineering or tooling, all engineering and tooling shall remain the exclusive property of Omron. All information and materials supplied by Omron to Buyer relating to the Products are confidential and proprietary, and Buyer shall limit distribution thereof to its trusted employees and strictly provent disclosure to any third party. 16
- prevent disclosure to any third party. <u>Export Controls.</u> Buyer shall comply with all applicable laws, regulations and licenses regarding (i) export of products or information; (iii) sale of products to "forbidden" or other proscribed persons; and (ii) disclosure to non-citizens of 17
- "forbidden" or other proscribed persons; and (ii) disclosure to non-citizens of regulated technology or information. <u>Miscellaneous</u>. (a) <u>Waiver</u>. No failure or delay by Omron in exercising any right and no course of dealing between Buyer and Omron shall operate as a waiver of rights by Omron. (b) <u>Assignment</u>. Buyer may not assign its rights hereunder without Omron's written consent. (c) <u>Law</u>. These Terms are governed by the law of the jurisdiction of the home office of the Omron company from which Buyer is purchasing the Products (without regard to conflict of law principles). (d) <u>Amendment</u>. These Terms constitute the entire agreement between Buyer and Omron relating to the Products, and no provision may be changed or waived unless in writing singed by the parties. (e) Severability. If any provi-18 or waived unless in writing signed by the parties. (e) <u>Severability</u>. If any provi-sion hereof is rendered ineffective or invalid, such provision shall not invalidate any other provision. (f) Setoff, Buyer shall have no right to set off any amounts against the amount owing in respect of this invoice. (g) <u>Definitions</u>. As used herein, "<u>including</u>" means "including without limitation"; and "<u>Omron Compa-</u> nies" (or similar words) mean Omron Corporation and any direct or indirect subsidiary or affiliate thereof.

ADDRESS THE RISKS, AND THAT THE OMRON'S PRODUCT IS PROP-ERLY RATED AND INSTALLED FOR THE INTENDED USE WITHIN THE OVERALL EQUIPMENT OR SYSTEM.

- Programmable Products. Omron Companies shall not be responsible for the user's programming of a programmable Product, or any consequence thereof. <u>Performance Data</u>. Data presented in Omron Company websites, catalogs and other materials is provided as a guide for the user in determining suitabil-ity and does not constitute a warranty. It may represent the result of Omron's test conditions, and the user must correlate it to actual application require-2 3 ments. Actual performance is subject to the Omron's Warranty and Limitations of Liability.
- Change in Specifications. Product specifications and accessories may be 4 Change in specifications. Product specifications and accessions may be changed at any time based on improvements and other reasons. It is our prac-tice to change part numbers when published ratings or features are changed, or when significant construction changes are made. However, some specifica-tions of the Product may be changed without any notice. When in doubt, spe-cial part numbers may be assigned to fix or establish key specifications for your application. Please consult with your Omron's representative at any time to confirm actual creating of purphased Product to confirm actual specifications of purchased Product. Errors and Omissions. Information presented by Omron Companies has been
- 5 checked and is believed to be accurate; however, no responsibility is assumed for clerical, typographical or proofreading errors or omissions.



#### OMRON INDUSTRIAL AUTOMATION • THE AMERICAS HEADQUARTERS

Schaumburg, IL USA • 847.843.7900 • 800.556.6766 • www.omron247.com

OMRON CANADA, INC. • HEAD OFFICE Toronto, ON, Canada • 416.286.6465 • 866.986.6766 • www.omron247.com

OMRON ELECTRONICS DE MEXICO • HEAD OFFICE México DF • 52.55.59.01.43.00 • 001.800.556.6766 • mela@omron.com

OMRON ELECTRONICS DE MEXICO • SALES OFFICE Apodaca, N.L. • 52.81.11.56.99.20 • 001.800.556.6766 • mela@omron.com

OMRON ELETRÔNICA DO BRASIL LTDA • HEAD OFFICE São Paulo, SP, Brasil • 55.11.2101.6300 • www.omron.com.br OMRON ARGENTINA • SALES OFFICE Cono Sur • 54.11.4783.5300

OMRON CHILE • SALES OFFICE Santiago • 56.9.9917.3920

OTHER OMRON LATIN AMERICA SALES 54.11.4783.5300

**OMRON EUROPE B.V.** • Wegalaan 67-69, NL-2132 JD, Hoofddorp, The Netherlands. • Tel: +31 (0) 23 568 13 00 Fax: +31 (0) 23 568 13 88 • www.industrial.omron.eu





Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001 Адрес: 105318, г.Москва, ул.Щербаковская д.З, офис 1107

#### Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

#### http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

#### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.З, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж: moschip.ru moschip.ru\_4

moschip.ru\_6 moschip.ru\_9