



## Main

|                                    |                                                                                               |
|------------------------------------|-----------------------------------------------------------------------------------------------|
| Range of product                   | OsiSense XS                                                                                   |
| Series name                        | General purpose                                                                               |
| Sensor type                        | Inductive proximity sensor                                                                    |
| Device application                 | -                                                                                             |
| Sensor name                        | XS8                                                                                           |
| Sensor design                      | Form 40 x 40 x 117                                                                            |
| Size                               | 117 mm                                                                                        |
| Body type                          | Fixed                                                                                         |
| Detector flush mounting acceptance | Flush mountable                                                                               |
| Material                           | Plastic                                                                                       |
| Enclosure material                 | PBT                                                                                           |
| Type of output signal              | Discrete                                                                                      |
| Wiring technique                   | 2-wire                                                                                        |
| [Sn] nominal sensing distance      | 0.79 in (20 mm)                                                                               |
| Discrete output function           | 1 NO or 1 NC programmable                                                                     |
| Output circuit type                | AC/DC                                                                                         |
| Electrical connection              | Screw-clamp terminals, clamping capacity: 4 x 1.5 mm <sup>2</sup>                             |
| [Us] rated supply voltage          | 24...240 V DC<br>24...240 V AC 50/60 Hz                                                       |
| Switching capacity in mA           | 5...200 mA DC<br>5...300 mA AC                                                                |
| IP degree of protection            | IP65 conforming to IEC 60529<br>IP67 conforming to IEC 60529<br>IP69K conforming to DIN 40050 |

## Complementary

|                       |                                                         |
|-----------------------|---------------------------------------------------------|
| Detection face        | 5 positions turret head                                 |
| Front material        | PBT                                                     |
| Operating zone        | 0...0.63 in (0...16 mm)                                 |
| Differential travel   | 3...15% of Sr                                           |
| Repeat accuracy       | <= 3% of Sr                                             |
| Cable entry number    | 1 tapped entry 1/2" NPT cable gland                     |
| Status LED            | 1 LED green supply on<br>1 LED yellow output state      |
| Supply voltage limits | 20...264 V AC/DC                                        |
| Residual current      | <= 1.5 mA open state 120 V<br><= 0.6 mA open state 24 V |
| Switching frequency   | <= 25 Hz AC<br><= 50 Hz DC                              |
| Voltage drop          | <= 5.5 V at closed state                                |
| Delay first up        | <= 7.5 ms                                               |
| Delay response        | <= 1.2 ms                                               |
| Delay recovery        | <= 1.8 ms                                               |
| Marking               | CE                                                      |
| Height                | 1.57 in (40 mm)                                         |
| Length                | 1.57 in (40 mm)                                         |
| Width                 | 4.61 in (117 mm)                                        |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

|                |                        |
|----------------|------------------------|
| Product weight | 0.54 lb(US) (0.244 kg) |
|----------------|------------------------|

## Environment

|                                       |                                                                         |
|---------------------------------------|-------------------------------------------------------------------------|
| product certifications                | CCC<br>CSA<br>UL                                                        |
| ambient air temperature for operation | -13...158 °F (-25...70 °C)                                              |
| ambient air temperature for storage   | -40...185 °F (-40...85 °C)                                              |
| vibration resistance                  | 25 gn amplitude = +/- 2 mm (f = 10...55 Hz) conforming to IEC 60068-2-6 |
| shock resistance                      | 50 gn 11 ms conforming to EN 60068-2-27                                 |


## Offer Sustainability

|                                                                                                                            |                                                                                                                            |
|----------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| Green Premium product                                                                                                      | Green Premium product                                                                                                      |
| Compliant - since 1213 - Schneider Electric declaration of conformity                                                      | Compliant - since 1213 - Schneider Electric declaration of conformity                                                      |
| Reference not containing SVHC above the threshold                                                                          | Reference not containing SVHC above the threshold                                                                          |
| Available                                                                                                                  | Available                                                                                                                  |
| Need no specific recycling operations                                                                                      | Need no specific recycling operations                                                                                      |
| WARNING: This product can expose you to chemicals including:                                                               | WARNING: This product can expose you to chemicals including:                                                               |
| Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and                                | Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and                                |
| Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. | Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. |
| For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                              | For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                              |

## Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|


## Dimensions



- (1) 2 holes Ø 5,45 mm / Ø 0.21 in. (Tightening torque: < 1,5 Nm / < 13.3 lb-in.)
- (2) 3 screws M3,5. (Tightening torque: < 1,2 Nm / < 10.6 lb-in.)
- (3) 2 elongated holes 5,4 x 7,4 mm / 0.21 x 0.29 in. (Tightening torque: < 1,5 Nm / < 13.3 lb-in.)

## Mounting

### Head Positions



## Setting-up Precautions

### Minimum Mounting Distances (mm)


#### Side by Side



e (1) 80

≥


#### Face to Face



e (2) 160

≥

#### Facing a Metal Object




e (3) 60

≥

## Wiring Schemes

### 2-Wire AC or DC (Programmable)



## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9